

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Report No.: SZEM180100056203

Fax: +86 (0) 755 2671 0594 Page: 1 of 7
Email: ee.shenzhen@sqs.com

1 Cover Page

RF MPE REPORT

Application No.:	SZEM1801000562CR (SHEM1712008883CR)	
Applicant:	pplicant: Hangzhou Hikvision Digital Technology Co., Ltd	
FCC ID:	2ADTD-AEC4	
Equipment Under Test	t (EUT):	
NOTE: The following sa	imple(s) was/were submitted and identified by the client as	
EUT Name:	Dashcam	
Model No.:	AE-DN2312-C4, AE-DN2312-C4A, AE-DN2312-C4B, AE-DN2312-C4C, AE-DN2312-C4D ¤	
a	Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.	
Standards:	FCC Rules 47 CFR §2.1091 KDB447498 D01 General RF Exposure Guidance v06	
Date of Receipt:	2017-12-27	
Date of Test:	2017-12-27	
Date of Issue:	2018-01-25	
Test Result:	Pass*	

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Condi



Report No.: SZEM180100056203

Page: 2 of 7

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	1	2018-01-25	/	Original

Authorized for issue by:		
	Forychan	
	Foray Chen /Project Engineer	
	Eric Fu	



Report No.: SZEM180100056203

Page: 3 of 7

2 Contents

		Pa	ıge
1	C	OVER PAGE	1
2	C	CONTENTS	3
3	G	ENERAL INFORMATION	4
	3.1	CLIENT INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	TECHNICAL SPECIFICATIONS	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	T	EST STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	N	IEASUREMENT AND CALCULATION	6
	5.1	MAXIMUM TRANSMIT POWER	6
	5.2	MPE CALCULATION	7



Report No.: SZEM180100056203

Page: 4 of 7

3 General Information

3.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.	
Address of Applicant:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China	
Manufacturer:	Hangzhou Hikvision Digital Technology Co.	
Address of Manufacturer:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China	
Factory:	Hangzhou Hikvision Technology Co., Ltd.	
	2. Hangzhou Hikvision Electronics Co., Ltd.	
Address of Factory:	1. No.700, Dongliu Road, Binjiang District, Hangzhou Ctiy,Zhejiang, 310052, China	
	2. No.299, Qiushi Road,Tonglu Economic Development Zone,Tonglu County, Hangzhou,Zhejiang,310052,China.	

3.1 General Description of E.U.T.

Brand Name:	HIKVISION
Product Description:	Mobile product with 2.4G WiFi function
Power supply:	DC 5V by Car adapter USB port
	Car adapter:
	model:TC16A-0503100D
	INPUT:DC 12V-24V
	OUTPUT:DC5.0V 3.1A(1A Port& 2.1A Port)
Test voltage:	DC 12V and 2.1A output port
Cable:	DC Cable 400cm

3.2 Technical Specifications

Operation Frequency:	802.11 b/g/n(HT20): 2412MHz-2462MHz
Modulation Technique:	802.11 b DSSS(CCK, DQPSK, DBPSK) 802.11 g/n(OFDM(64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	802.11 b/g/n(HT20): 11
Data Rate:	802.11b: 1/2/5.5/11Mbps, 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: 13/26/39/52/78/104/117/135Mbps
Antenna Type:	PIFA Antenna
Antenna Gain:	-3.15 dBi



Report No.: SZEM180100056203

Page: 5 of 7

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM180100056203

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SZEM180100056202.

Test Mode	Test Channel	Power[dBm]	Power (mW)
11B	2412	12.42	17.46
11B	2437	12.46	17.62
11B	2462	12.51	17.82
11G	2412	11.15	13.03
11G	2437	11.26	13.37
11G	2462	11.45	13.96
11N20SISO	2412	10.59	11.46
11N20SISO	2437	10.78	11.97
11N20SISO	2462	10.8	12.02



Report No.: SZEM180100056203

Page: 7 of 7

5.2 MPE Calculation

The best case gain of the antenna is -3.15 dBi. -3.15dB logarithmic terms convert to numeric result is nearly 0.48.

The Max Conducted Average Output Power is 17.82mW);

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

- inote: 1) P (Watts) =Power Input to antenna = $10^{\frac{dBm}{10}}$ / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

WiFi: S=
$$\frac{PG}{4R^2\pi} = \frac{17.82 \times 0.48}{4 \times 400 \times 3.14} = 0.002 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

-- End of the Report--