

# TEST REPORT

**Application No.:** SHEM2006004622CR  
**FCC ID:** 2ADTD-IOP2100  
**IC:** 20199-IOP2100  
**Applicant:** Hangzhou Hikvision Digital Technology Co., Ltd.  
**Address of Applicant:** No.555 Qianmo Road,Binjiang District Hangzhou 310052,China  
**Manufacturer:** Hangzhou Hikvision Digital Technology Co., Ltd.  
**Address of Manufacturer:** No.555 Qianmo Road,Binjiang District Hangzhou 310052,China  
**Factory:**  
 1.Hangzhou Hikvision Technology Co., Ltd.  
 2.Hangzhou Hikvision Electronics Co.,Ltd.  
 3. Chongqing Hikvision technology Co., Ltd.  
**Address of Factory:**  
 1.No.700,Dongliu Road,Binjiang District,Hangzhou Ctiy,Zhejiang,310052,China  
 2.No.299,Qiushi Road,Tonglu Economic Development Zone,Tonglu County,Hangzhou,Zhejiang,310052,China.  
 3. No. 118, Haikang Road, Area C, Jianqiao Industrial Park, Dadukou District, Chongqing, 401325,China

**Equipment Under Test (EUT):**

**EUT Name:** NETWORK CAMERA  
**Model No.:** DS-2CV2126G0-IDW  
**Trade mark:** HIKVISION  
**Standard(s) :**  
 47 CFR Part 15, Subpart C 15.247  
 RSS-247 Issue 2, February 2017  
 RSS-Gen Issue 5, March 2019 Amendment 1  
**Date of Receipt:** 2020-06-16  
**Date of Test:** 2020-06-17 to 2020-07-03  
**Date of Issue:** 2020-07-05

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

*Parlan Zhan*

Parlan Zhan  
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**



**SGS-CSTC Standards Technical Services  
(Shanghai) Co., Ltd.**

Report No.: SHEM200600462201  
Page: 2 of 78

Revision Record			
Version	Description	Date	Remark
00	Original	2020-07-05	/

Authorized for issue by:			
			
		<hr/> Micheal Niu / Project Engineer	
			
		<hr/> Parlam Zhan / Reviewer	



## 2 Test Summary

Test Item	FCC Requirement	IC Requirement	Test method	Result
Antenna Requirement	FCC Part 15, Subpart C Section 15.203/15.247 (c)	RSS-Gen Clause 8.3	---	PASS
AC Power Line Conducted Emission	FCC Part 15, Subpart C Section 15.207	RSS-Gen Clause 8.8	ANSI C63.10 (2013) Section 6.2	N/A
Minimum 6dB Bandwidth	FCC Part 15, Subpart C Section 15.247 (a)(2)	RSS-247 Clause 5.2(a)	ANSI C63.10 (2013) Section 11.8.1	PASS
Conducted Peak Output Power	FCC Part 15, Subpart C Section 15.247 (b)(3)(4)	RSS-247 Clause 5.4(d)	ANSI C63.10 (2013) Section 11.9.1.2	PASS
Power Spectrum Density	FCC Part 15, Subpart C Section 15.247 (e)	RSS-247 Clause 5.2(b)	ANSI C63.10 (2013) Section 11.10.2	PASS
RF Conducted Spurious Emissions and Band-edge	FCC Part 15, Subpart C Section 15.247(d)	RSS-247 Clause 5.5	ANSI C63.10 (2013) Section 11.11&11.13.3.2	PASS
Radiated Spurious Emissions and Band-edge	FCC Part 15, Subpart C Section 15.205&15.209&15.247(d)	RSS-247 Clause 5.5	ANSI C63.10 (2013) Section 6.4&6.5&6.6&6.10	PASS
99% Occupied bandwidth	---	RSS-Gen Section 6.7	ANSI C63.10 Section 6.9.3	PASS



### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS.....</b>	<b>4</b>
<b>4 GENERAL INFORMATION.....</b>	<b>5</b>
4.1 DETAILS OF E.U.T. ....	5
4.2 POWER LEVEL SETTING USING IN TEST.....	5
4.3 DESCRIPTION OF SUPPORT UNITS .....	5
4.4 MEASUREMENT UNCERTAINTY.....	6
4.5 TEST LOCATION.....	7
4.6 TEST FACILITY.....	7
4.7 DEVIATION FROM STANDARDS.....	7
4.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
<b>5 EQUIPMENT LIST.....</b>	<b>8</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....</b>	<b>9</b>
6.1 ANTENNA REQUIREMENT .....	9
<b>7 RADIO SPECTRUM MATTER TEST RESULTS.....</b>	<b>10</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz).....	10
7.2 MINIMUM 6dB BANDWIDTH.....	14
7.3 CONDUCTED PEAK OUTPUT POWER .....	15
7.4 POWER SPECTRUM DENSITY.....	17
7.5 CONDUCTED BAND EDGES MEASUREMENT.....	18
7.6 CONDUCTED SPURIOUS EMISSIONS .....	20
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	22
7.8 RADIATED SPURIOUS EMISSIONS.....	48
7.9 99% BANDWIDTH.....	77
<b>8 TEST SETUP PHOTOGRAPHS .....</b>	<b>78</b>
<b>9 EUT CONSTRUCTIONAL DETAILS.....</b>	<b>78</b>



## 4 General Information

### 4.1 Details of E.U.T.

Power supply: DC 12V by adapter  
 Serial Number: E38304014  
 Firmware Version: V5.5.1\_10\_200414  
 Test voltage: AC 120V/60Hz  
 Antenna Gain: Antenna 1:2dBi  
 Antenna 2: 2dBi  
 Directional gain:5.01dBi  
 Antenna Type: Antenna 1: Dipole Antenna  
 Antenna 2: Dipole Antenna  
 Channel Spacing: 5MHz  
 Modulation Type: 802.11b: DSSS (CCK, DQPSK, DBPSK)  
 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)  
 Number of Channels: 802.11b/g/n(HT20):11  
 802.11n(HT40):7  
 Operation Frequency: 802.11b/g/n(HT20): 2412MHz to 2462MHz  
 802.11n(HT40): 2422MHz to 2452MHz

### 4.2 Power level setting using in test

Channel	802.11b	802.11g	802.11n (HT20)
1	32	28	28
6	32	28	28
11	32	28	28
Channel	802.11n (HT40)		
3	28		
6	28		
9	28		

### 4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	/
SecureCRT	VanDyke	V 6.2.0	/
AC Adapter	MOSO	AMSA-C1500IC	/



#### 4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4 x 10 <sup>-8</sup>
2	Timeout	2s
3	Duty Cycle	0.4%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.1dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-6GHz)
		5.4dB (6GHz-18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



#### **4.5 Test Location**

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

#### **4.6 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED (CAB identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

#### **4.7 Deviation from Standards**

None

#### **4.8 Abnormalities from Standard Conditions**

None



## 5 Equipment List

Item	Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal. Due Date
<b>Conducted Emission at Mains Terminals (150kHz-30MHz)</b>						
1	EMI Test Receive	R&S	ESCI	100781	02/24/2020	02/23/2021
2	LISN	R&S	ENV216	101604	10/24/2019	10/23/2020
3	LISN	Schwarzbeck	NNLK 8129	8129-143	10/24/2019	10/23/2020
4	Pulse Limiter	R&S	ESH3-Z2	100609	02/24/2020	02/23/2021
5	CE test Cable	Thermax	/	14	02/24/2020	02/23/2021
<b>RF Conducted Test</b>						
1	Spectrum Analyzer	Agilent	E4446A	MY44020154	04/22/2020	04/21/2021
2	Spectrum Analyzer	Keysight	N9020A	MY55370209	12/19/2019	12/18/2020
3	Signal Generator	Agilent	E8257C	MY43321570	10/24/2019	10/23/2020
4	Vector Signal Generator	R&S	SMU 200A	102744	02/24/2020	02/23/2021
5	Universal Radio Communication Tester	R&S	CMU200	109525	12/19/2019	12/18/2020
6	Universal Radio Communication Tester	R&S	CMW500	159275	12/19/2019	12/18/2020
7	Power Meter	Anritsu	ML2495A	1445010	04/21/2020	04/20/2021
8	Switcher	CCSRF	FY562	KS301219	12/20/2019	12/19/2020
9	AC Power Source	EXTECH	6605	1570106	N.C.R	N.C.R
10	DC Power Supply	Agilent	E3632A	MY50340053	N.C.R	N.C.R
11	6dB Attenuator	Mini-Circuits	NAT-6-2W	15542-1	N.C.R	N.C.R
12	Power Divider	AISI	IOWOPE2068	PE2068	N.C.R	N.C.R
13	Filter	MICRO-TRONICS	BRM50701	5	N.C.R	N.C.R
14	Conducted test cable	/	RF01-RF04	/	04/21/2020	04/22/2021
15	Temp. / Humidity Chamber	TERCHY	MHK-120AK	X30109	04/21/2020	04/20/2021
<b>RF Radiated Test</b>						
1	Spectrum Analyzer	R&S	FSV40	101493	01/08/2020	01/07/2021
2	Signal Generator	Agilent	E8257C	MY43321570	10/24/2019	10/23/2020
3	Loop Antenna	Schwarzbeck	HXYZ9170	9170-108	02/24/2020	02/23/2021
4	Bilog Antenna	TESEQ	CBL 6112D	35403	06/22/2019	06/21/2021
5	Bilog Antenna	SCHWARZBECK	VULB9160	9160-3342	04/29/2019	04/28/2021
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	267	11/04/2018	11/03/2020
7	Horn-antenna(1-18GHz)	ETS-LINDGREN	3117	00143290	02/25/2019	02/24/2021
8	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	BBHA9170171	02/27/2018	02/26/2021
9	Pre-Amplifier(30MHz~18GHz)	CCSRF	AMP1277	1	12/19/2019	12/18/2020
10	Pre-Amplifier(0.1~26.5GHz)	EMCI	EMC012645	980060	04/21/2020	04/20/2021
11	Low Pass Filter	MICRO-TRONICS	VLFX-950	RV142900829	N.C.R	N.C.R
12	High Pass Filter	Mini-Circuits	VHF-1200	15542	N.C.R	N.C.R
13	Filter (5450MHz~5770 MHz)	MICRO-TRONICS	BRC50704-01	2	N.C.R	N.C.R
14	Filter (5690 MHz~5930 MHz)	MICRO-TRONICS	BRC50705-01	4	N.C.R	N.C.R
15	Filter (5150 MHz~5350 MHz)	MICRO-TRONICS	BRC50703-01	2	N.C.R	N.C.R
16	Filter (885 MHz~915 MHz)	MICRO-TRONICS	BRM14698	1	N.C.R	N.C.R
17	Filter (815 MHz~860 MHz)	MICRO-TRONICS	BRM14697	1	N.C.R	N.C.R
18	Filter (1745 MHz~1910 MHz)	MICRO-TRONICS	BRM14700	1	N.C.R	N.C.R
19	Filter (1922 MHz~1977 MHz)	MICRO-TRONICS	BRM50715	1	N.C.R	N.C.R
20	Filter (2550 MHz)	MICRO-TRONICS	HPM13362	5	N.C.R	N.C.R
21	Filter (1532 MHz~1845 MHz)	MICRO-TRONICS	BRM50713	1	N.C.R	N.C.R
22	Filter (2.4GHz)	MICRO-TRONICS	BRM50701	5	N.C.R	N.C.R
23	RE test cable	/	RE01-RE04	/	04/21/2020	04/22/2021





## **6 Radio Spectrum Technical Requirement**

### **6.1 Antenna Requirement**

#### **6.1.1 Test Requirement:**

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### **6.1.2 Conclusion**

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna 1 and antenna 2 is Dipole antenna, and a no consideration of replacement. The best case gain of the antenna 1 and antenna 2 is 2dBi.

Antenna location: Refer to Appendix (External Photos).



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207  
Test Method: ANSI C63.10 (2013) Section 6.2  
Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 48 % RH Atmospheric Pressure: 1010 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram



### 7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark:

1.LISN=Read Level+ Cable Loss+ LISN Factor

2.This test item was investigated while operating in each channel mode, however, it was determined that channel 11 operation for b modulation produced the worst conducted emissions. So the conducted emissions produced from other operation are not report.




Mode:a; Line:Live Line



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.4055	16.69	6.91	19.43	36.12	26.34	57.74	47.74	-21.62	-21.40	Pass
2*	0.4826	19.98	11.18	19.46	39.44	30.64	56.29	46.29	-16.85	-15.65	Pass
3	0.6016	9.98	2.65	19.48	29.46	22.13	56.00	46.00	-26.54	-23.87	Pass
4	0.9187	8.68	1.99	19.55	28.23	21.54	56.00	46.00	-27.77	-24.46	Pass
5	1.6007	6.41	0.06	19.63	26.04	19.69	56.00	46.00	-29.96	-26.31	Pass
6	11.0616	10.54	3.29	19.99	30.53	23.28	60.00	50.00	-29.47	-26.72	Pass



Mode:a; Line:Neutral Line



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.3820	21.94	13.79	19.38	41.32	33.17	58.24	48.24	-16.92	-15.07	Pass
2	0.3973	21.67	14.15	19.38	41.05	33.53	57.91	47.91	-16.86	-14.38	Pass
3*	0.4869	24.66	18.23	19.39	44.05	37.62	56.22	46.22	-12.17	-8.60	Pass
4	0.6091	15.51	8.20	19.43	34.94	27.63	56.00	46.00	-21.06	-18.37	Pass
5	0.8839	14.35	7.53	19.52	33.87	27.05	56.00	46.00	-22.13	-18.95	Pass
6	1.2413	11.47	5.64	19.58	31.05	25.22	56.00	46.00	-24.95	-20.78	Pass

## 7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM200600462201



### 7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)  
Test Method: ANSI C63.10 (2013) Section 11.9.1  
Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


**7.3.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.3.2 Test Setup Diagram**



**7.3.3 Measurement Procedure and Data**

The detailed test data see: Appendix A for SHEM200600462201




### 7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
 Test Method: ANSI C63.10 (2013) Section 11.10.2  
 Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission

#### 7.4.1 E.U.T. Operation

Operating Environment:  
 Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar  
 Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

#### 7.4.2 Test Setup Diagram



#### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix A for SHEM200600462201



## 7.5 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.13.3.2
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


**7.5.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C      Humidity: 50 % RH      Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.5.2 Test Setup Diagram**



**7.5.3 Measurement Procedure and Data**

The detailed test data see: Appendix A for SHEM200600462201



## 7.6 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247(d)
Test Method:	ANSI C63.10 (2013) Section 11.11
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))


**7.6.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.6.2 Test Setup Diagram**



**7.6.3 Measurement Procedure and Data**

The detailed test data see: Appendix A for SHEM200600462201



### 7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 6.10.5  
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


**7.7.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C      Humidity: 50 % RH      Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.7.2 Test Setup Diagram**





### 7.7.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1:  $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamplifier\ Factor$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: This test item was investigated while operating in SISO and MIMO mode, however, it was determined that SISO antenna 1 operation for b/g modulation and MIMO antenna operation for n modulation produced the worst emissions. So the emissions produced from other operation are not recorded in report.






Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2357.600	55.25	-4.33	50.92	74.00	-23.08	peak
2	2390.000	53.86	-4.24	49.62	74.00	-24.38	peak
3	2413.740	104.99	-4.18	100.81	74.00	26.81	peak




Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBm)	Correction factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	2363.480	56.25	-4.31	51.94	74.00	-22.06	peak
2	2390.000	56.80	-4.24	52.56	74.00	-21.44	peak
3	2410.940	111.72	-4.19	107.53	74.00	33.53	peak




Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2465.750	104.59	-4.05	100.54	74.00	26.54	peak
2	2483.500	53.95	-4.00	49.95	74.00	-24.05	peak
3	2500.000	52.90	-3.96	48.94	74.00	-25.06	peak




Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2463.650	111.81	-4.05	107.76	74.00	33.76	peak
2	2483.500	59.47	-4.00	55.47	74.00	-18.53	peak
3	2494.550	58.13	-3.97	54.16	74.00	-19.84	peak
4	2500.000	55.22	-3.96	51.26	74.00	-22.74	peak




Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2464.700	108.47	-4.05	104.42	54.00	50.42	AVG
2	2483.500	50.15	-4.00	46.15	54.00	-7.85	AVG
3	2487.650	52.18	-3.99	48.19	54.00	-5.81	AVG
4	2500.000	45.10	-3.96	41.14	54.00	-12.86	AVG




Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2343.180	55.32	-4.36	50.96	74.00	-23.04	peak
2	2390.000	52.98	-4.24	48.74	74.00	-25.26	peak
3	2409.680	104.28	-4.19	100.09	74.00	26.09	peak




Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dBm)	Correction factor (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	2371.460	57.05	-4.29	52.76	74.00	-21.24	peak
2	2390.000	66.08	-4.24	61.84	74.00	-12.16	peak
3	2416.820	109.74	-4.17	105.57	74.00	31.57	peak



Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low




No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2331.980	46.59	-4.39	42.20	54.00	-11.80	AVG
2	2390.000	46.86	-4.24	42.62	54.00	-11.38	AVG
3	2416.400	100.43	-4.18	96.25	54.00	42.25	AVG






Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2464.550	104.42	-4.05	100.37	74.00	26.37	peak
2	2483.500	53.37	-4.00	49.37	74.00	-24.63	peak
3	2488.250	54.76	-3.99	50.77	74.00	-23.23	peak
4	2500.000	52.45	-3.96	48.49	74.00	-25.51	peak




Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2465.150	110.16	-4.05	106.11	74.00	32.11	peak
2	2483.500	64.43	-4.00	60.43	74.00	-13.57	peak
3	2484.200	68.16	-4.00	64.16	74.00	-9.84	peak
4	2500.000	54.89	-3.96	50.93	74.00	-23.07	peak




Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2465.150	100.96	-4.05	96.91	54.00	42.91	AVG
2	2483.500	49.42	-4.00	45.42	54.00	-8.58	AVG
3	2485.700	45.80	-4.00	41.80	54.00	-12.20	AVG
4	2500.000	43.21	-3.96	39.25	54.00	-14.75	AVG




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2349.060	54.97	-4.35	50.62	74.00	-23.38	peak
2	2390.000	54.50	-4.24	50.26	74.00	-23.74	peak
3	2418.640	104.86	-4.17	100.69	74.00	26.69	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2369.640	57.33	-4.30	53.03	74.00	-20.97	peak
2	2390.000	72.31	-4.24	68.07	74.00	-5.93	peak
3	2418.220	108.66	-4.17	104.49	74.00	30.49	peak


Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2331.980	46.30	-4.39	41.91	54.00	-12.09	AVG
2	2390.000	52.55	-4.24	48.31	54.00	-5.69	AVG
3	2417.380	99.38	-4.17	95.21	54.00	41.21	AVG




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2466.200	99.26	-4.05	95.21	74.00	21.21	peak
2	2483.500	53.59	-4.00	49.59	74.00	-24.41	peak
3	2489.750	53.89	-3.99	49.90	74.00	-24.10	peak
4	2500.000	52.95	-3.96	48.99	74.00	-25.01	peak



Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2466.200	108.60	-4.05	104.55	74.00	30.55	peak
2	2483.500	71.35	-4.00	67.35	74.00	-6.65	peak
3	2494.100	58.66	-3.98	54.68	74.00	-19.32	peak
4	2500.000	54.25	-3.96	50.29	74.00	-23.71	peak






Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2467.100	99.35	-4.04	95.31	54.00	41.31	AVG
2	2483.500	52.29	-4.00	48.29	54.00	-5.71	AVG
3	2489.300	44.15	-3.99	40.16	54.00	-13.84	AVG
4	2500.000	43.24	-3.96	39.28	54.00	-14.72	AVG




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2362.500	55.68	-4.31	51.37	74.00	-22.63	peak
2	2390.000	53.68	-4.24	49.44	74.00	-24.56	peak
3	2429.420	96.45	-4.14	92.31	74.00	18.31	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency (MHz)	Reading ( )	Correction factor( )	Result ( )	Limit ( )	Margin (dB)	Remark
1	2388.260	64.83	-4.25	60.58	74.00	-13.42	peak
2	2390.000	63.41	-4.24	59.17	74.00	-14.83	peak
3	2407.160	103.29	-4.20	99.09	74.00	25.09	peak


Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2342.060	48.00	-4.37	43.63	54.00	-10.37	AVG
2	2390.000	45.97	-4.24	41.73	54.00	-12.27	AVG
3	2407.160	93.44	-4.20	89.24	54.00	35.24	AVG




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2438.670	95.60	-4.12	91.48	74.00	17.48	peak
2	2483.500	52.63	-4.00	48.63	74.00	-25.37	peak
3	2492.730	54.79	-3.98	50.81	74.00	-23.19	peak
4	2500.000	53.51	-3.96	49.55	74.00	-24.45	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	2467.910	104.26	-4.04	100.22	74.00	26.22	peak
2	2483.500	67.03	-4.00	63.03	74.00	-10.97	peak
3	2487.290	68.14	-3.99	64.15	74.00	-9.85	peak
4	2500.000	58.80	-3.96	54.84	74.00	-19.16	peak



Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor( )	Result ( )	Limit ( )	Margin (dB)	Remark
1	2466.890	94.67	-4.05	90.62	54.00	36.62	AVG
2	2483.500	51.39	-4.00	47.39	54.00	-6.61	AVG
3	2488.140	49.39	-3.99	45.40	54.00	-8.60	AVG
4	2500.000	44.45	-3.96	40.49	54.00	-13.51	AVG



### 7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6  
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.




**7.8.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.8.2 Test Setup Diagram**





### 7.8.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

#### Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 5) This test item was investigated while operating in SISO and MIMO mode, however, it was determined that SISO antenna 1 operation for b/g modulation and MIMO antenna operation for n modulation produced the worst emissions. So the emissions produced from other operation are not recorded in report.




Below 1GHz:  
Mode:a; Polarization:Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	93.0500	22.39	12.16	34.55	43.50	-8.95	100	360	QP
2	106.6300	24.58	14.27	38.85	43.50	-4.65	100	360	QP
3	268.6200	22.68	17.57	40.25	46.00	-5.75	100	145	QP
4	285.1100	23.37	17.81	41.18	46.00	-4.82	100	158	QP
5	350.1000	19.14	19.33	38.47	46.00	-7.53	300	220	QP
6	877.7800	9.67	25.56	35.23	46.00	-10.77	200	116	QP



Mode:a; Polarization:Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	38.7300	12.94	21.91	34.85	40.00	-5.15	100	113	QP
2	60.0700	23.60	11.54	35.14	40.00	-4.86	300	165	QP
3	93.0500	25.58	12.16	37.74	43.50	-5.76	200	67	QP
4	106.6300	22.69	14.27	36.96	43.50	-6.54	300	325	QP
5	163.8600	22.55	16.19	38.74	43.50	-4.76	100	199	QP
6	749.7400	13.73	24.52	38.25	46.00	-7.75	100	217	QP



Above 1GHz


Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4824.000	57.54	-10.21	47.33	74.00	-26.67	peak
2	7236.000	55.82	-7.05	48.77	74.00	-25.23	peak
3	9648.000	54.22	-4.77	49.45	74.00	-24.55	peak




Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dB)	Correction factor(dB)	Result (dB)	Limit (dB)	Margin (dB)	Remark
1	4824.000	58.86	-10.21	48.65	74.00	-25.35	peak
2	7236.000	54.70	-7.05	47.65	74.00	-26.35	peak
3	9648.000	54.45	-4.77	49.68	74.00	-24.32	peak




Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	56.56	-10.01	46.55	74.00	-27.45	peak
2	7311.000	56.11	-6.93	49.18	74.00	-24.82	peak
3	9748.000	50.89	-4.30	46.59	74.00	-27.41	peak



Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:middle




No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	58.60	-10.01	48.59	74.00	-25.41	peak
2	7311.000	54.46	-6.93	47.53	74.00	-26.47	peak
3	9748.000	51.51	-4.30	47.21	74.00	-26.79	peak






Mode:a; Polarization:Horizontal; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	60.30	-9.82	50.48	74.00	-23.52	peak
2	7386.000	53.58	-6.80	46.78	74.00	-27.22	peak
3	9848.000	54.37	-3.84	50.53	74.00	-23.47	peak




Mode:a; Polarization:Vertical; Modulation:b; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	55.79	-9.82	45.97	74.00	-28.03	peak
2	7386.000	53.00	-6.80	46.20	74.00	-27.80	peak
3	9848.000	52.02	-3.84	48.18	74.00	-25.82	peak




Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4824.000	58.82	-10.21	48.61	74.00	-25.39	peak
2	7236.000	57.59	-7.05	50.54	74.00	-23.46	peak
3	9648.000	51.94	-4.77	47.17	74.00	-26.83	peak



Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4824.000	56.19	-10.21	45.98	74.00	-28.02	peak
2	7236.000	53.71	-7.05	46.66	74.00	-27.34	peak
3	9648.000	55.11	-4.77	50.34	74.00	-23.66	peak




Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	59.46	-10.01	49.45	74.00	-24.55	peak
2	7311.000	53.03	-6.93	46.10	74.00	-27.90	peak
3	9748.000	52.19	-4.30	47.89	74.00	-26.11	peak




Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	60.50	-10.01	50.49	74.00	-23.51	peak
2	7311.000	54.97	-6.93	48.04	74.00	-25.96	peak
3	9748.000	50.56	-4.30	46.26	74.00	-27.74	peak




Mode:a; Polarization:Horizontal; Modulation:g; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	58.52	-9.82	48.70	74.00	-25.30	peak
2	7386.000	52.48	-6.80	45.68	74.00	-28.32	peak
3	9848.000	50.83	-3.84	46.99	74.00	-27.01	peak



Mode:a; Polarization:Vertical; Modulation:g; bandwidth:20MHz; Channel:High




No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	59.50	-9.82	49.68	74.00	-24.32	peak
2	7386.000	55.82	-6.80	49.02	74.00	-24.98	peak
3	9848.000	53.58	-3.84	49.74	74.00	-24.26	peak






Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading (dB)	Correction factor(dB)	Result (dB)	Limit (dB)	Margin (dB)	Remark
1	4824.000	56.10	-10.21	45.89	74.00	-28.11	peak
2	7236.000	56.99	-7.05	49.94	74.00	-24.06	peak
3	9648.000	51.98	-4.77	47.21	74.00	-26.79	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4824.000	59.34	-10.21	49.13	74.00	-24.87	peak
2	7236.000	58.35	-7.05	51.30	74.00	-22.70	peak
3	9648.000	55.63	-4.77	50.86	74.00	-23.14	peak




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	58.48	-10.01	48.47	74.00	-25.53	peak
2	7311.000	56.86	-6.93	49.93	74.00	-24.07	peak
3	9748.000	52.67	-4.30	48.37	74.00	-25.63	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	58.52	-10.01	48.51	74.00	-25.49	peak
2	7311.000	55.59	-6.93	48.66	74.00	-25.34	peak
3	9748.000	54.14	-4.30	49.84	74.00	-24.16	peak




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	55.65	-9.82	45.83	74.00	-28.17	peak
2	7386.000	55.90	-6.80	49.10	74.00	-24.90	peak
3	9848.000	54.24	-3.84	50.40	74.00	-23.60	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4924.000	56.10	-9.82	46.28	74.00	-27.72	peak
2	7386.000	55.54	-6.80	48.74	74.00	-25.26	peak
3	9848.000	53.19	-3.84	49.35	74.00	-24.65	peak




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low



No.	Frequency (MHz)	Reading (dB)	Correction factor(dB)	Result (dB)	Limit (dB)	Margin (dB)	Remark
1	4844.000	55.42	-10.13	45.29	74.00	-28.71	peak
2	7366.000	52.49	-6.84	45.65	74.00	-28.35	peak
3	9688.000	51.41	-4.58	46.83	74.00	-27.17	peak



Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low




No.	Frequency (MHz)	Reading (dB)	Correction factor(dB)	Result (dB)	Limit (dB)	Margin (dB)	Remark
1	4844.000	54.84	-10.13	44.71	74.00	-29.29	peak
2	7266.000	55.79	-7.00	48.79	74.00	-25.21	peak
3	9688.000	54.61	-4.58	50.03	74.00	-23.97	peak






Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:middle



No.	Frequency (MHz)	Reading (dB)	Correction factor(dB)	Result (dB)	Limit (dB)	Margin (dB)	Remark
1	4874.000	59.82	-10.01	49.81	74.00	-24.19	peak
2	7311.000	53.12	-6.93	46.19	74.00	-27.81	peak
3	9748.000	52.62	-4.30	48.32	74.00	-25.68	peak




Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:middle



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4874.000	58.86	-10.01	48.85	74.00	-25.15	peak
2	7311.000	52.13	-6.93	45.20	74.00	-28.80	peak
3	9748.000	52.73	-4.30	48.43	74.00	-25.57	peak




Mode:a; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4904.000	57.59	-9.89	47.70	74.00	-26.30	peak
2	7356.000	57.67	-6.85	50.82	74.00	-23.18	peak
3	9808.000	52.44	-4.02	48.42	74.00	-25.58	peak



Mode:a; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High



No.	Frequency (MHz)	Reading ()	Correction factor()	Result ()	Limit ()	Margin (dB)	Remark
1	4904.000	58.15	-9.89	48.26	74.00	-25.74	peak
2	7356.000	53.96	-6.85	47.11	74.00	-26.89	peak
3	9808.000	53.82	-4.02	49.80	74.00	-24.20	peak

**7.9 99% Bandwidth**

Test Requirement RSS-Gen Section 6.7  
Test Method: ANSI C63.10 Section 6.9.3


**7.9.1 E.U.T. Operation**

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

**7.9.2 Test Setup Diagram**



**7.9.3 Measurement Procedure and Data**

The detailed test data see: Appendix A for SHEM200600462201



## **8 Test Setup Photographs**

Refer to the < Test Setup photos-FCC>.

## **9 EUT Constructional Details**

Refer to the < External Photos > & < Internal Photos >.

**- End of the Report -**