

588 West Jindu Road, Xinqiao, S<sup>I</sup>ongjiang, 201612 Shanghai, China Telephone: +86 (0) 21 6191 5666 Fax: +86 (0) 21 6191 5678 ee.shanghai@sgs.com

Report No.: SZEM170800857304 Page: 1 of 8

## 1 Cover Page

# FCC MPE REPORT

Application No.:	SZEM1708008573CR		
Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd		
FCC ID:	2ADTD-K1T803MF		
Equipment Under Test	t (EUT):		
NOTE: The following sa	imple(s) was/were submitted and identified by the client as		
Product Name:	Fingerprint Access Control Terminal		
Model No.(EUT):	DS-K1T803MF		
Add Model No.:	DS-K1T803MF-1, DS-K2M060, DS-K1T804MF, DS-K1T804MF-1,		
	DS-K1T804MF-E, DS-K1T803XYZ-UVW, DS-K1T804XYZ-UVW		
Standards:	FCC Rules 47 CFR §2.1091		
	KDB447498 D01 General RF Exposure Guidance v06		
Date of Receipt:	2017-06-22		
Date of Test: 2017-06-22 to 2017-07-06			
Date of Issue:	2017-08-18		
Test Result:	Pass*		

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above.



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Report No.: SZEM170800857304 Page: 2 of 8

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	2017-08-18	/	Original

Authorized for issue by:			
Engineer	Eddy Zong	2017-07-06	
	Eddy Zong /Project Engineer	Date	
Reviewer	Parlam zhan	2017-07-12	
	Parlam Zhan /Reviewer	Date	



Report No.: SZEM170800857304 Page: 3 of 8

## 2 Contents

1		OVER PAGE		
2	CONTENTS			
3	G	ENERAL INFORMATION	.4	
	3.1	CLIENT INFORMATION	.4	
	3.1	GENERAL DESCRIPTION OF E.U.T.		
	3.2	TECHNICAL SPECIFICATIONS	.4	
	3.3	TEST LOCATION	. 5	
	3.4	Test Facility	. 5	
4	Т	EST STANDARDS AND LIMITS	. 6	
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	. 6	
5	Ν	IEASUREMENT AND CALCULATION	.7	
	5.1	MAXIMUM TRANSMIT POWER	.7	
	5.2	MPE CALCULATION	. 8	
6	Е	UT CONSTRUCTIONAL DETAILS	. 8	



Report No.: SZEM170800857304 Page: 4 of 8

## **3** General Information

#### 3.1 Client Information

Applicant:	Hangzhou Hikvision Digital Technology Co., Ltd.
Address of Applicant:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China
Manufacturer:	Hangzhou Hikvision Digital Technology Co.
Address of Manufacturer:	No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China
Footon <i>i</i> :	1. Hangzhou Hikvision Technology Co., Ltd.
Factory:	2. Hangzhou Hikvision Electronics Co., Ltd.
Address of Fastery	1. No.700, Dongliu Road, Binjiang District, Hangzhou Ctiy,Zhejiang, 310052, China
Address of Factory:	2. No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu County, Hangzhou, Zhejiang, 310052, China.

#### 3.1 General Description of E.U.T.

Brand Name:	HIKVISION
Product Description:	Fixed product with 2.4G WiFi function
Rated Input:	DC 12V 1A
Test Voltage:	AC 120V 60Hz for adapter

#### 3.2 Technical Specifications

802.11 b/g/n(HT20): 2412MHz~2462MHz
802.11 n(HT40): 2422MHz~2452MHz
802.11 b: DSSS(CCK, DQPSK, DBPSK)
802.11 g/n(HT20/n(HT40): OFDM(64QAM, 16QAM, QPSK, BPSK)
802.11b: 1/2/5.5/11Mbps,
802.11g: 6/9/12/18/24/36/48/54Mbps
802.11n: MCS0-7
802.11 b/g/n(HT20): 11
802.11 n(HT40): 7
Integral
2.4 dBi



Report No.: SZEM170800857304 Page: 5 of 8

#### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053

Fax: +86 755 2671 0594

#### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration

Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM170800857304 Page: 6 of 8

## 4 Test Standards and Limits

#### 4.1 FCC Radiofrequency radiation exposure limits:

According to§1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm2)	Averaging time (minutes)
Limits for General I	Limits for General Population/Uncontrolled Exposure			
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note:Limit for 13.56MHz is 60.77 V/m



Report No.: SZEM170800857304 Page: 7 of 8

### 5 Measurement and Calculation

#### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SZEM170800857302 & SZEM170800857303

Test Mode	Test Channel	Power[dBm]	Power[mW]
11B	2412	20.77	119.40
11B	2437	21.37	137.09
11B	2462	21.46	139.96
11G	2412	20.8	120.23
11G	2437	21.45	139.64
11G	2462	21.22	132.43
11N20SISO	2412	20.61	115.08
11N20SISO	2437	21.38	137.40
11N20SISO	2462	21.01	126.18
11N40SISO	2422	21.64	145.88
11N40SISO	2437	21.55	142.89
11N40SISO	2452	21.61	144.88

13.56MHz: 51.79dBuV/m



#### 5.2 MPE Calculation

The Max Conducted Peak Output Power is 21.64dBm (145.88mW); The best case gain of the antenna is 2.4dBi. 2.4dB logarithmic terms convert to numeric result is nearly 1.74

For FCC:

According to the formula  $S = \frac{PG}{4R^2\pi}$ , we can calculate S which is MPE.

Note:

 $\frac{dBm}{10}$ 

- 1) P (Watts) =Power Input to antenna = $10^{10}$  / 1000
- 2) G (Antenna gain in numeric) = 10<sup>^</sup> (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit =  $1 \text{mW/cm}^2$

For WiFi: S=  $\frac{PG}{4R^2\pi} = \frac{145.88 \times 1.74}{4 \times 400 \times 3.14} = 0.05 \text{ mW/cm}^2$ 

For 13.56MHz: 51.79dBuV/m=0.00039 V/m< 60.77 V/m.

13.56MHz and WiFi modules can simultaneous transmitting, so the maximum rate of MPE is  $\frac{0.00039}{60.77} + \frac{0.05}{1}$  =0.05<=1.0. according to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

6 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

--End of the Report--