

Report No.: SHEM200700531603

Page: 1 of 8

Cover Page

RF Exposure Evaluation Report

Application No.: SHEM2007005316CR

FCC ID: 2ADTD-K5032

Applicant: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Applicant: No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Hangzhou Hikvision Digital Technology Co., Ltd. Manufacturer:

Address of Manufacturer: No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Factory: 1, Hangzhou Hikvision Technology Co., Ltd. 2, Hangzhou Hikvision Electronics Co., Ltd.

3, Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Factory: 1, No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang,

310052. China

2, No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu

County, Hangzhou, Zhejiang, 310052, China.

3, No.555 Qianmo Road, Binjiang District Hangzhou 310052, China

Equipment Under Test (EUT):

EUT Name: Visitor Terminal DS-K5032 Model No.:

DS-K5032UHK, DS-K5032CKV, DS-K5032UVS, DS-K5032KVO, Add Model No.:

DS-K5032HUN

FCC Rules 47 CFR §2.1091 Standard(s):

KDB447498 D01 General RF Exposure Guidance v06

2020-07-01 **Date of Receipt:**

2020-07-06 to 2020-07-23 **Date of Test:**

2020-07-24 Date of Issue:

Pass* **Test Result:**

Parlam Zhan **E&E Section Manager**

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

检验检测专用章

pprovals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn

NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 中国・上海・松江区金都西路588号 邮编: 201612

t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM200700531603

Page: 2 of 8

Revision Record							
Version Description Date Remark							
00	Original	2020-07-24	/				

Authorized for issue by:			
	Michael Mil		
	Micheal Niu /Project Engineer	-	
	Parlam Zhan		
	Parlam Zhan /Reviewer	_	



Report No.: SHEM200700531603

Page: 3 of 8

2 Contents

		Pa	age
1	С	COVER PAGE	1
2	С	CONTENTS	3
3	G	SENERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T	∠
	3.2	TECHNICAL SPECIFICATIONS	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	Т	EST STANDARDS AND LIMITS	(
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	(
5	N	MEASUREMENT AND CALCULATION	7
	5.1	MAXIMUM TRANSMIT POWER	7
	5.2	MDE CALCULATION	Ç



Report No.: SHEM200700531603

Page: 4 of 8

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 12V by Adapter

3.2 Technical Specifications

2.4G WiFi

Antenna Gain:	3.73dBi
Antenna Type:	PIFA Antenna
Channel Spacing:	5MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK)
	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz

13.56MHz

Antenna Type	Loop Antenna
Modulation Type	ASK
Number of Channels	1
Operation Frequency	13.56MHz



Report No.: SHEM200700531603

Page: 5 of 8

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch 588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (LAB CODE: 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

• FCC (Designation Number: CN5033)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

• ISED (CAB Identifier: CN0020)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM200700531603

Page: 6 of 8

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
Limits for General I	Population/Uncontrolled	Exposure		
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note:Limit for 2.4GHz is 1.0 mW/cm² Limit for 13.56MHz is 60.77 V/m



Report No.: SHEM200700531603

Page: 7 of 8

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200700531601, SHEM200700531602,

2.4G WiFi

Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]
11B	2412	Ant1	12.11	16.26
11B	2437	Ant1	12.32	17.06
11B	2462	Ant1	12.13	16.33
11G	2412	Ant1	11.82	15.21
11G	2437	Ant1	12.08	16.14
11G	2462	Ant1	11.82	15.21
11N20SISO	2412	Ant1	11.23	13.27
11N20SISO	2437	Ant1	11.52	14.19
11N20SISO	2462	Ant1	11.24	13.30

13.56MHz: 64.98 dBuV/m@3m, @20cm=@3m+40log(3/0.2)=112.02dBuV/m



Report No.: SHEM200700531603

Page: 8 of 8

5.2 MPE Calculation

For WiFi:

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

For WIFI

The max. antenna gain is 3.73 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm²)	Result
17.06	2.360	20	0.00801	1	Pass

For 13.56MHz: 112.02dBuV/m=0.4V/m< 60.77 V/m.

The 2.4G band and 13.56MHz function can simultaneous transmitting.But the maximum rate of MPE is 0.008/1.0+0.4/60.77=0.01<=1.0. according to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

-- End of the Report--