

Report No.: SHEM200700534502

Page: 1 of 8

#### 1 Cover Page

### RF Exposure REPORT

**Application No.**: SHEM2007005345CR **FCC ID:** 2ADTD-TCP440-DB

Applicant: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Applicant: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.

Address of Manufacturer: No. 555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Factory: Hangzhou Hikvision Technology Co., Ltd.

Address of Factory:

No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang, 310052,

China

**Equipment Under Test (EUT):** 

EUT Name: Parking Camera
Model No.: DS-TCP440-DB
Add Model No.: Refer to page 2
Trade mark: HIKVISION

FCC Rules 47 CFR §2.1093

Standard(s): KDB447498 D01 General RF Exposure Guidance v06

**Date of Receipt:** 2020-07-01

**Date of Test:** 2020-07-02 to 2020-07-14

**Date of Issue:** 2020-07-14

Test Result: Pass\*

arian zhan

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

pprovals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: To Chocket the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: To Chocket the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: To Chocket the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: To Chocket the authen

or email: CN.Doccheck@sgs.com
NO.588 West Jindu Road, Songjiang District, Shanghai, China 201612 t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn
中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM200700534502

Page: 2 of 8

#### Add Model No.:

DS-TCP400-DB,DS-TCP100-DB,DS-TCP100-D,DS-TCP140,DS-TCP140-B,DS-TCP100,DS-TCP140,DS-TCP200-D,DS-TCP200-DB,DS-TCP240-B,DS-TCP240-DB,DS-TCP200,DS-TCP240,DS-TCP300-B,DS-TCP300-D,DS-TCP300-DB,DS-TCP330-B,DS-TCP330-D,DS-TCP330-DB,DS-TCP340-B,DS-TCP340-DB,DS-TCP300,DS-TCP340,DS-TCP300-BH,DS-TCP300-DH,DS-TCP300-DBH,DS-TCP300-DH,DS-TCP300-DH,DS-TCP300-DH,DS-TCP300-DH,DS-TCP340-DH,DS-TCP340-DH,DS-TCP340-DH,DS-TCP340-DH,DS-TCP340-DH,DS-TCP440-BH,DS-TCP440-DH,DS-TCP400-DH,DS-TCP400-DH,DS-TCP400-DH,DS-TCP400-DH,DS-TCP440-DH,DS-TCP440-DH,DS-TCP400-DH,DS-TCP400-DH,DS-TCP440-DH,DS-TCP440-DH,DS-TCP440-DH,DS-TCP440-DH,DS-TCP400-D,DS-TCP400-D,DS-TCP440-DH,DS-TCP440-



Report No.: SHEM200700534502

Page: 3 of 8

Revision Record				
Version	Description	Date	Remark	
00	Original	2020-07-14	/	

Authorized for issue by:		
	hidral Mil	
	Micheal Niu / Project Engineer	
	parlan 2han	
	Parlam Zhan / Reviewer	



Report No.: SHEM200700534502

Page: 4 of 8

#### 2 Contents

			Page
1	COV	/ER PAGE	1
2	CON	NTENTS	4
3	GEN	IERAL INFORMATION	5
	3.1	GENERAL DESCRIPTION OF E.U.T.	5
	3.2	DETAILS OF E.U.T.	5
	3.3	TEST LOCATION	6
	3.4	TEST FACILITY	6
4	TES	T STANDARDS AND LIMITS	7
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	7
5	MEA	ASUREMENT AND CALCULATION	8
	5.1	MAXIMUM TRANSMIT POWER	8
	5.2	RE EXPOSURE CALCULATION	8



Report No.: SHEM200700534502

Page: 5 of 8

#### 3 General Information

#### 3.1 General Description of E.U.T.

Power supply:	DC 12V by Adapter

#### 3.2 Details of E.U.T.

Antenna Gain:	2.64dBi
Antenna Type:	PCB Antenna
Bluetooth Version:	V4.2 LE
Channel Spacing:	2MHz
Modulation Type:	GFSK
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz



Report No.: SHEM200700534502

Page: 6 of 8

#### 3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

#### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### • NVLAP (LAB CODE: 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

#### • FCC (Designation Number: CN5033)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

#### ISED (CAB Identifier: CN0020)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory

#### VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM200700534502

Page: 7 of 8

#### 4 Test Standards and Limits

#### 4.1 FCC Radiofrequency radiation exposure limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max power of channel)/(min test separation distance)]\*[ $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion. For 2.4G band device, the limit of worse case is

 $P_{\text{max}} \le 3.0^{+} D_{\text{min}} / \sqrt{f} = 3.0^{+} 5 / \sqrt{2.480} = 9.525 \text{mW}$ 



Report No.: SHEM200700534502

Page: 8 of 8

#### 5 Measurement and Calculation

#### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200700534501.

#### Test Data:

Test Mode	Test Channel	Power[dBm]	Peak Power (mW)
BLE	2402	1.35	1.36
BLE	2440	1.75	1.50
BLE	2480	0.52	1.13

#### 5.2 RF Exposure Calculation

The Max Conducted Peak Output Power is 1.5mW. The best case gain of the antenna is 2.64dBi.

2.64dBi logarithmic terms convert to numeric result is nearly 1.84.

According to the formula. calculate the EIRP test result:

EIRP= P x G = 1.5 mW x 1.84= 2.76mW < 9.525mW

So the SAR report is not required.

--End of the Report--