


TEST REPORT

Part 15.247 & RSS-247 (Issue 2)

Equipment under test CAR Dash CAM
Model name F70 PRO
FCC ID 2ADTG-F70PRO
IC number 12594A-F70PRO
Applicant THINKWARE CORPORATION
Manufacturer THINKWARE CORPORATION
Date of test(s) 2023.05.30 ~ 2023.06.05
Date of issue 2023.06.07

Issued to
THINKWARE CORPORATION
A, 9FL., Samwhan Hipex, 240, Pangyoyeok-ro, Bundang-gu,
Seongnam-si, Gyeonggi-do, South Korea
Tel: +82-2-589-9425 / Fax: +82-2-589-9600

Issued by
KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	Report approval by :
	
Bong-Seok, Kim Test engineer	Yeong-Jun Cho Technical manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (2) of (53)

Revision history

Revision	Date of issue	Test report No.	Description
-	2023.06.07	KES-RF-23T0085	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (3) of (53)

TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	5
1.3.	Derivative Model Information.....	5
1.4.	Accessory information.....	5
1.5.	Sample calculation	5
1.6.	Maximum average output power.....	5
1.7.	Measurement Uncertainty	5
1.8.	Frequency/channel operations.....	6
2.	Summary of tests	7
3.	Test results.....	8
3.1.	Output power.....	8
3.2.	Radiated restricted band and emissions.....	10
3.3.	Antenna Requirement.....	51
Appendix A.	Measurement equipment	52
Appendix B.	Test setup photos	53

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (4) of (53)

1. General information

Applicant: THINKWARE CORPORATION
Applicant address: A, 9FL., Samwhan Hipex, 240, Pangyoyeok-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea
Test site: KES Co., Ltd.
Test site address: ☐ 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
☒ 473-29, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea
Test Facility: FCC Accreditation Designation No.: KR0100, Registration No.: 444148
ISED Registration No.: 23298
FCC rule part(s): 15.247
IC rule part(s): RSS-247
FCC ID: 2ADTG-F70PRO
IC Number : 12594A-F70PRO
Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test: CAR Dash CAM
Frequency range: 2 402 MHz ~ 2 480 MHz (LE 1 Mbps)
2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20)
2 422 MHz ~ 2 452 MHz (802.11n_HT40)
Model: F70 PRO
Modulation technique: GFSK, DSSS, OFDM
Number of channels: 2 402 MHz ~ 2 480 MHz (LE 1 Mbps) : 40 ch
2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20) : 11 ch
2 422 MHz ~ 2 452 MHz (802.11n_HT40) : 7 ch
Antenna specification: PCB Antenna // Peak gain: 1.78 dBi
Power source: DC 12~24 V
H/W version: V0.00.05-PVT2
S/W version: 3.1

1.2. Test configuration

The **THINKWARE CORPORATION // CAR Dash CAM // F70 PRO // FCC ID: 2ADTG-F70PRO // IC : 12594A-F70PRO** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
ISED RSS-247 Issue 2 and RSS-Gen Issue 5
KDB 558074 D01 v05 r02
ANSI C63.10-2013

1.3. Derivative Model Information

N/A

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	--	-	-	-

1.5. Sample calculation

Where relevant, the following sample calculation is provided

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.74 + 10 = 10.74 \text{ (dB)}\end{aligned}$$

For Radiation test :

$$\text{Field strength level (dB}\mu\text{V/m)} = \text{Measured level (dB}\mu\text{V)} + \text{Antenna factor (dB)} + \text{Cable loss (dB)} - \text{Amplifier gain (dB)}$$

1.6. Maximum average output power

Refer to the average output power

Note.

- Radiated emission were performed with the EUT set to transmit at the channel with highest output Power as worst-case scenario.
- Worst-case data rates as provided by the client were:
802.11b : **1Mbps** / 802.11g : **6Mbps** / 802.11n_HT20/40 : **MCS0**

1.7. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.38 dB (SHIELD ROOM #6)
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1GHz	4.50 dB (SAC #6)
	Above 1GHz	4.90 dB (SAC #5)
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

1.8. Frequency/channel operations

Ch.	Frequency (MHz)	Mode
00	2 402	LE 1 Mbps
.	.	.
20	2 442	LE 1 Mbps
.	.	.
39	2 480	LE 1 Mbps

Ch.	Frequency (MHz)	Mode
01	2 412	802.11b/g/n_HT20
.	.	.
06	2 437	802.11b/g/n_HT20
.	.	.
11	2 462	802.11b/g/n_HT20

Ch.	Frequency (MHz)	Mode
03	2 422	802.11n_HT40
.	.	.
06	2 437	802.11n_HT40
.	.	.
09	2 452	802.11n_HT40

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (7) of (53)

2. Summary of tests

Section in FCC Part 15	Section in RSS-247 & Gen	Parameter	Test results
-	RSS-Gen 6.7	99% Occupied bandwidth	N/T ⁽¹⁾
15.247(a)(2)	RSS-247 5.2(a)	6 dB bandwidth	N/T ⁽¹⁾
15.247(b)(3)	RSS-247 5.4(d)	Output power	Pass
15.247(e)	RSS-247 5.2(b)	Power spectral density	N/T ⁽¹⁾
15.205, 15.209	RSS-247 5.5, RSS-Gen 8.9, 8.10	Radiated restricted band and emission	Pass ⁽²⁾
15.247(d)	RSS-247 5.5	Conducted spurious emission and band edge	N/T ⁽¹⁾
15.207	RSS-Gen 8.8	AC Conducted emissions	N/T ⁽³⁾
15.203	-	Antenna Requirement	Pass

* N/T is **Not Tested**.

Note :

1. This product is equipped with an approved module, please refer to Module Report below for details.

Report No. :

FCC : BLA-EMC-202203-A9202, BLA-EMC-202203-A9201

IC : A2303382-C02-R07, A2303382-C02-R08

2. Tested in Worst Case mode.

3. This EUT is a product that operates using only DC power.


3. Test results

3.1. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to RSS-247 5.4 (d), For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in Section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (9) of (53)

Test results**DC 12 V**

Measured output power (dBm)						
Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average	Peak	Average	Peak	Average	Peak
LE 1 Mbps	1.64	1.95	1.41	1.72	1.06	1.37

Measured output power (dBm)						
Mode	2 412 MHz		2 437 MHz		2 462 MHz	
	Average	Peak	Average	Peak	Average	Peak
802.11b	10.03	11.75	10.02	11.76	10.01	11.73
802.11g	8.36	18.22	8.29	18.16	8.24	18.11
802.11n_HT20	8.33	18.33	8.29	18.31	8.25	18.26

Measured output power (dBm)						
Mode	2 422 MHz		2 437 MHz		2 452 MHz	
	Average	Peak	Average	Peak	Average	Peak
802.11n_HT40	8.67	18.51	8.70	17.66	8.66	18.50

DC 24 V

Measured output power (dBm)						
Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average	Peak	Average	Peak	Average	Peak
LE 1 Mbps	2.04	2.41	2.42	2.74	2.68	3.07

Measured output power (dBm)						
Mode	2 412 MHz		2 437 MHz		2 462 MHz	
	Average	Peak	Average	Peak	Average	Peak
802.11b	10.73	12.43	10.72	12.41	10.70	12.43
802.11g	9.02	18.46	9.02	18.58	8.99	18.80
802.11n_HT20	9.02	18.35	9.05	19.15	8.99	18.44


Measured output power (dBm)						
Mode	2 422 MHz		2 437 MHz		2 452 MHz	
	Average	Peak	Average	Peak	Average	Peak
802.11n_HT40	9.45	18.24	9.47	18.53	9.44	18.35

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr


3.2. Radiated restricted band and emissions

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
5. Spectrum analyzer settings for $f < 1$ GHz:
 - ① Span = wide enough to fully capture the emission being measured
 - ② RBW = 100 kHz
 - ③ VBW $\geq$ RBW
 - ④ Detector = quasi peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
6. Spectrum analyzer settings for $f \geq 1$ GHz: Peak
 - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
 - ② RBW = 1 MHz
 - ③ VBW $\geq$ 3 MHz
 - ④ Detector = peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
 - ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1$ GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if span/(# of points in sweep) $\leq$ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Note.

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
8. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
9. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu\text{V}/\text{m}$)
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

According to RSS-Gen, Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits :

Frequency (MHz)	Distance (Meters)	Radiated ($\mu\text{V}/\text{m}$)
0.009 ~ 0.490	300	2 400 / F(kHz)
0.490 ~ 1.705	30	24 000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960*	3	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (16) of (53)

Duty cycle


Regarding to KDB 558074 D01_v04, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below.

Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100.

Test mode	T _{on} time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1 Mbps	0.39	0.63	0.62	62.40	2.05
802.11b	30	30	1	100	0

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (17) of (53)


Test results (Below 30 MHz)

Mode: DC 12 V_LE 1 Mbps

Channel: 00 (Worst case)

Distance of measurement: 3 meter

Horizontal



Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (18) of (53)

Mode: DC 12 V_802.11b(Worst Case)
Channel: 01 (Worst Case)
Distance of measurement: 3 meter

Horizontal



Spectrum Selection

No.	Range	Frequency	Reading	c.f	Result	Limit	Angle	Remark
		[MHz]	PK [dB (μV)]	[dB (1/m)]	PK [dB (μV/m)]	PK [dB (μV/m)]	[deg]	
1	Range1	0.523	29.0	19.7	48.7	-----	7.1	
2	Range1	0.609	24.8	19.8	44.6	-----	160.0	
3	Range1	1.017	17.3	20.3	37.6	-----	181.3	

Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-RF-23T0085
Page (19) of (53)

Mode: DC 24 V_LE 1 Mbps

Channel: 00 (Worst case)

Distance of measurement: 3 meter

Horizontal



Spectrum Selection

No.	Range	Frequency [MHz]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Limit PK [dB (μV/m)]	Angle [deg]	Remark
1	Range1	0.523	29.3	19.7	49.0	-----	177.2	
2	Range1	1.239	32.8	20.3	53.1	-----	359.9	
3	Range1	1.793	24.3	20.2	44.5	-----	155.4	
4	Range1	3.604	19.4	19.3	38.7	-----	359.9	

Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (20) of (53)

Mode: DC 24 V_802.11b(Worst Case)
Channel: 01 (Worst Case)
Distance of measurement: 3 meter

Horizontal



Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (21) of (53)


Test results (Below 1 000 MHz)

Mode: DC 12 V_LE 1 Mbps

Channel: 00 (Worst case)

Distance of measurement: 3 meter

Horizontal // Vertical



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	31.940	V	51.4	-14.9	36.5	40.0	3.5	100.0	178.0	
2	47.460	H	35.6	-12.0	23.6	40.0	16.4	187.0	250.8	
3	50.855	H	35.1	-11.8	23.3	40.0	16.7	188.0	332.5	
4	59.343	V	33.7	-12.7	21.0	40.0	19.0	100.0	333.4	
5	59.949	H	38.7	-12.8	25.9	40.0	14.1	179.0	93.4	
6	179.986	V	41.6	-14.1	27.5	43.5	16.0	121.0	111.5	
7	179.986	H	42.0	-14.1	27.9	43.5	15.6	200.0	286.5	
8	219.999	V	34.1	-12.1	22.0	46.0	24.0	100.0	333.4	
9	333.125	V	30.1	-8.6	21.5	46.0	24.5	131.0	0.0	
10	359.921	V	32.0	-7.8	24.2	46.0	21.8	100.0	159.7	
11	360.043	H	33.6	-7.8	25.8	46.0	20.2	187.0	0.1	
12	481.535	H	30.4	-5.7	24.7	46.0	21.3	200.0	308.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (22) of (53)

Mode: DC 12 V_802.11b(Worst Case)
Channel: 01 (Worst Case)
Distance of measurement: 3 meter

Horizontal // Vertical



Final Result

No.	Frequency	Pol	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP		QP	QP	QP			
			[dB (μV)]	[dB (1/m)]	[dB (μV/m)]	[dB (μV/m)]	[dB]	[cm]	[deg]	
1	31.455	H	36.1	-15.0	21.1	40.0	18.9	200.0	243.2	
2	31.455	V	51.4	-15.0	36.4	40.0	3.6	100.0	337.3	
3	31.698	V	50.6	-14.9	35.7	40.0	4.3	100.0	337.3	
4	59.949	H	34.1	-12.8	21.3	40.0	18.7	188.0	292.2	
5	86.624	H	33.1	-16.3	16.8	40.0	23.2	200.0	27.4	
6	179.986	H	42.1	-14.1	28.0	43.5	15.5	200.0	68.6	
7	179.986	V	41.6	-14.1	27.5	43.5	16.0	100.0	160.0	
8	333.125	V	32.7	-8.6	24.1	46.0	21.9	121.0	112.1	
9	360.043	H	32.6	-7.8	24.8	46.0	21.2	197.0	359.9	
10	498.753	V	28.1	-5.4	22.7	46.0	23.3	100.0	71.8	
11	500.329	H	31.4	-5.4	26.0	46.0	20.0	200.0	68.5	
12	882.509	V	30.0	-0.2	29.8	46.0	16.2	100.0	248.3	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-RF-23T0085
Page (23) of (53)

Mode: DC 24 V_LE 1 Mbps

Channel: 00 (Worst case)

Distance of measurement: 3 meter

Horizontal // Vertical



Final Result

No.	Frequency	Pol	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP		QP	QP	QP			
			[dB (μV)]	[dB (1/m)]	[dB (μV/m)]	[dB (μV/m)]	[dB]	[cm]	[deg]	
1	31.698	V	50.3	-14.9	35.4	40.0	4.6	100.0	200.8	
2	31.940	V	51.6	-14.9	36.7	40.0	3.3	100.0	178.0	
3	32.304	V	51.1	-14.8	36.3	40.0	3.7	100.0	178.0	
4	47.460	H	35.1	-12.0	23.1	40.0	16.9	194.0	250.8	
5	50.855	H	36.0	-11.8	24.2	40.0	15.8	178.0	332.5	
6	59.949	H	37.6	-12.8	24.8	40.0	15.2	200.0	93.4	
7	179.986	V	41.1	-14.1	27.0	43.5	16.5	100.0	111.5	
8	179.986	H	42.6	-14.1	28.5	43.5	15.0	200.0	286.5	
9	219.999	V	32.6	-12.1	20.5	46.0	25.5	100.0	333.4	
10	332.155	H	33.6	-8.6	25.0	46.0	21.0	177.0	28.2	
11	359.921	V	33.4	-7.8	25.6	46.0	20.4	132.0	159.7	
12	360.043	H	33.1	-7.8	25.3	46.0	20.7	187.0	0.1	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (24) of (53)

Mode: DC 24 V_802.11b(Worst Case)
Channel: 01 (Worst Case)
Distance of measurement: 3 meter

Horizontal // Vertical



Final Result

No.	Frequency	Pol	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP [dB (μV)]	[dB (1/m)]	QP [dB (μV/m)]	QP [dB (μV/m)]	QP [dB]	[cm]	[deg]	
1	31.455	V	50.4	-15.0	35.4	40.0	4.6	100.0	337.3	
2	31.819	V	49.7	-14.9	34.8	40.0	5.2	100.0	271.6	
3	59.949	V	34.6	-12.8	21.8	40.0	18.2	100.0	332.5	
4	86.624	H	34.6	-16.3	18.3	40.0	21.7	200.0	27.4	
5	99.961	H	30.4	-13.5	16.9	43.5	26.6	200.0	155.2	
6	179.986	H	41.6	-14.1	27.5	43.5	16.0	200.0	68.6	
7	179.986	V	40.8	-14.1	26.7	43.5	16.8	144.0	160.0	
8	331.791	H	32.9	-8.7	24.2	46.0	21.8	189.0	112.2	
9	333.125	V	31.1	-8.6	22.5	46.0	23.5	100.0	112.1	
10	360.043	H	32.9	-7.8	25.1	46.0	20.9	198.0	359.9	
11	500.329	H	35.6	-5.4	30.2	46.0	15.8	200.0	68.5	
12	882.509	V	30.0	-0.2	29.8	46.0	16.2	100.0	248.3	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (25) of (53)

Test results (Above 1 000 MHz)

DC 12V


Mode: LE 1 Mbps
Channel: 00
Distance of measurement: 3 meter

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 126.09	45.48	Peak	H	-8.26	-	37.22	74.00	36.78
1 327.27	47.73	Peak	V	-6.73	-	41.00	74.00	33.00

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 388.07	42.53	Peak	V	-1.22	-	41.31	74.00	32.69
2 389.46	42.56	Peak	H	-1.21	-	41.35	74.00	32.65



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (27) of (53)

Mode: LE 1 Mbps
Channel: 20
Distance of measurement: 3 meter

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 216.48	45.98	Peak	H	-7.64	-	38.34	74.00	35.66
1 331.47	48.07	Peak	V	-6.69	-	41.38	74.00	32.62



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (28) of (53)

Mode: LE 1 Mbps
Channel: 39
Distance of measurement: 3 meter

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 201.48	44.84	Peak	H	-7.77	-	37.07	74.00	36.93
1 328.07	48.53	Peak	V	-6.72	-	41.81	74.00	32.19

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.50	56.57	Peak	H	-0.88	-	55.69	74.00	18.31
2 483.50	28.92	Average	H	-0.88	2.05	28.04	54.00	23.91
2 483.50	56.57	Peak	V	-0.88	-	56.36	74.00	17.64
2 483.50	28.08	Average	V	-0.88	2.05	27.20	54.00	24.75

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-RF-23T0085
Page (29) of (53)

Restricted band // Horizontal // Peak




H(AV)
Date: 31.MAY.2023 10:04:19

Restricted band // Vertical // Peak




H(AV)
Date: 31.MAY.2023 10:00:09

Restricted band // Horizontal // Average




H(AV)
Date: 31.MAY.2023 10:04:48

Restricted band // Vertical // Average



H(AV)
Date: 31.MAY.2023 10:02:34

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF-23T0085
Page (31) of (53)

Test results (18 GHz to 30 GHz)

Mode: LE 1 Mbps
Channel: 00 (Worst case)
Distance of measurement: 3 meter



Note.

1. No spurious emission were detected above 18 GHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr