



# TEST REPORT



Report No. : RF-230787

Page 1 / 89

**KES Co., Ltd.**

#3002, #3503, #3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea  
Tel : +82-31-425-6200, Fax : +82-31-425-6200

## ■ FCC&IC TEST REPORT

### 1. Client

- Name : THINKWARE CORPORATION
- Address : A, 9FL., Samwhan Hipex, 240, Pangyoyeok-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea

### 2. Sample Description

- Product item : CAR BLACK BOX
- Model name : Q200
- Manufacturer etc. : THINKWARE CORPORATION

### 3. Date of test : 2023.12.20 ~ 2024.01.08

### 4. Location of Test : Permanent Testing Lab On Site Testing

- Adress : 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

### 5. Test method used : Part 15.247 & RSS-247 (Issue 3)

### 6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This laboratory is not accredited for the test results marked\*.

**This test report is not related to KOLAS accreditation.**

Affirmation	Tested by	Technical Manager
	Name : Bong-Seok Kim (Signature)	Name : Yeong-Jun Cho (Signature)

2024 . 01. 16.

## KES Co., Ltd.

### Accredited by KOLAS, Republic of KOREA



## REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2024.01.16	RF-230787	Initial

*This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.*

### Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").

Other (to be specified, for example when required by the standard or client)



## TABLE OF CONTENTS

1.	General information .....	4
1.1.	EUT description .....	4
1.2.	Test configuration.....	5
1.3.	Information about derivative model .....	5
1.4.	Accessory information .....	5
1.5.	Sample calculation .....	5
1.6.	Measurement Uncertainty .....	5
1.7.	Frequency/channel operations .....	6
2.	Summary of tests .....	7
3.	Test results .....	8
3.1.	Output power .....	8
3.2.	Radiated restricted band and emissions .....	10
3.3.	Antenna Requirement.....	88
Appendix A.	Measurement equipment.....	89





Report No. : RF-230787

## 1. General information

Applicant: THINKWARE CORPORATION  
Applicant address: A, 9FL., Samwhan Hipex, 240, Pangyoeyeok-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea  
Test site: KES Co., Ltd.  
Test site address:  #3002, #3503, #3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea  
 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea  
Test Facility: FCC Accreditation Designation No.: KR0100, Registration No.: 444148  
ISED Registration No.: 23298  
FCC rule part(s): FCC: 15.247  
IC rule part(s): IC : RSS-247  
FCC ID: 2ADTG-Q200  
IC ID: 12594A-Q200  
Test device serial No.:  Production  Pre-production  Engineering

### 1.1. EUT description

Equipment under test: CAR BLACK BOX  
Frequency range: 2 402 MHz ~ 2 480 MHz (LE 1 Mbps)  
2 412 MHz ~ 2 462 MHz (802.11b,g,n\_HT20)  
2 422 MHz ~ 2 452 MHz (802.11n\_HT40)  
Model: Q200  
Variant Model: -  
Modulation technique: GFSK, DSSS, OFDM  
Number of channels: 2 402 MHz ~ 2 480 MHz (LE 1 Mbps) : 40 ch  
2 412 MHz ~ 2 462 MHz (802.11b,g,n\_HT20) : 11 ch  
2 422 MHz ~ 2 452 MHz (802.11n\_HT40) : 7 ch  
Antenna specification: Chip Antenna // Peak gain: 1.99 dBi  
Power source: DC 12 V / 24 V  
H/W Version: V4.0  
S/W Version: V1.00.00  
S/N: PEP\_PVT\_\_\_53

**1.2. Test configuration**

The **THINKWARE CORPORATION // CAR BLACK BOX // Q200 // FCC ID: 2ADTG-Q200 //**

**IC ID: 12594A-Q200** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247  
ISED RSS-247 Issue 3 and RSS-Gen Issue 5  
KDB 558074 D01 v05 r02  
ANSI C63.10-2013

**1.3. Information about derivative model**

N/A

**1.4. Accessory information**

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

**1.5. Sample calculation**

Where relevant, the following sample calculation is provided  
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.70 + 10 = 10.70 \text{ (dB)} \end{aligned}$$

For Radiation test :

$$\text{Field strength level (dB}\mu\text{V/m)} = \text{Measured level (dB}\mu\text{V)} + \text{Antenna factor (dB)} + \text{Cable loss (dB)} - \text{Amplifier gain (dB)}$$

**1.6. Measurement Uncertainty**

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.22 dB ( SHIELD ROOM #6 )
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1GHz	4.04 dB ( SAC #6 )
	Above 1GHz	5.32 dB ( SAC #5 )
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		



### 1.7. Frequency/channel operations

Ch.	Frequency (MHz)	Rate(Mbps)
00	2 402	LE 1 Mbps
.	.	.
20	2 442	LE 1 Mbps
.	.	.
39	2 480	LE 1 Mbps

Ch.	Frequency (MHz)	Rate(Mbps)
01	2 412	802.11b,g,n_HT20
.	.	.
06	2 437	802.11b,g,n_HT20
.	.	.
11	2 462	802.11b,g,n_HT20

Ch.	Frequency (MHz)	Rate(Mbps)
03	2 422	802.11n_HT40
.	.	.
06	2 437	802.11n_HT40
.	.	.
09	2 452	802.11n_HT40



## 2. Summary of tests

Section in FCC Part 15	Section in RSS-247 & Gen	Test description	Test results
-	RSS-Gen 6.7	99% Occupied bandwidth	N/T <sup>note1</sup>
15.247(a)(2)	RSS-247 5.2(a)	6 dB bandwidth	N/T <sup>note1</sup>
15.247(b)(3)	RSS-247 5.4(d)	Output power	Pass
15.247(e)	RSS-247 5.2(b)	Power spectral density	N/T <sup>note1</sup>
15.205 15.209	RSS-247 5.5 RSS-Gen 8.9,8,10	Radiated restricted band and emission	Pass
15.247(d)	RSS-247 5.5	Conducted spurious emission and band edge	N/T <sup>note1</sup>
15.207(a)	RSS-Gen 8.8	AC Conducted emissions	N/T <sup>note2</sup>
15.203	-	Antenna Requirement	Pass <sup>note3</sup>

**N/T: Not Tested**

### Note

1. This product is equipped with an approved module, please refer to Module Report below for details.  
Report No.  
FCC : BLA-EMC-202203-A9202, BLA-EMC-202203-A9201  
IC : A2303382-C02-R07, A2303382-C02-R08
2. This EUT is a product that operates using only DC power.
3. Please check the antenna spec. for the Antenna Requirement.




### 3. Test results

#### 3.1. Output power

##### Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

##### Test setup



##### ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

##### ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

##### Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

##### Limit

According to RSS-247 5.4 (d), For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.



**Test results****DC 12 V**

Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	1.58	1.89	1.26	1.55	0.81	1.13

Mode	2 412 MHz		2 437 MHz		2 462 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11b	9.76	13.22	9.70	13.14	9.58	13.03
802.11g	6.37	16.43	6.39	16.72	6.43	16.42
802.11n_HT20	6.36	15.37	6.37	16.11	6.38	16.29

Mode	2 422 MHz		2 437 MHz		2 452 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11n_HT40	7.02	15.98	7.01	16.35	6.98	15.86

**DC 24 V**

Mode	2 402 MHz		2 442 MHz		2 480 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	1.29	1.69	1.11	1.43	0.72	1.07

Mode	2 412 MHz		2 437 MHz		2 462 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11b	10.74	14.16	10.64	14.07	10.57	13.98
802.11g	7.12	16.82	7.17	17.25	7.10	16.77
802.11n_HT20	6.86	16.58	6.91	16.49	6.80	16.72


Mode	2 422 MHz		2 437 MHz		2 452 MHz	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
802.11n_HT40	7.24	16.22	7.22	16.44	7.27	15.97




### 3.2. Radiated restricted band and emissions

#### Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



### Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

#### Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel**.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

#### Test procedure above 30 MHz ~ 1 000 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



**Test procedure above 1 000 MHz**

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  
5. Spectrum analyzer settings for  $f < 1$  GHz:
  - ① Span = wide enough to fully capture the emission being measured
  - ② RBW = 100 kHz
  - ③ VBW  $\geq$  RBW
  - ④ Detector = quasi peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
6. Spectrum analyzer settings for  $f \geq 1$  GHz: Peak
  - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
  - ② RBW = 1 MHz
  - ③ VBW  $\geq$  3 MHz
  - ④ Detector = peak
  - ⑤ Sweep time = auto
  - ⑥ Trace = max hold
  - ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for  $f \geq 1$  GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW  $\geq 3 \times$  RBW
- ④ Detector = RMS, if span/(# of points in sweep)  $\leq$  (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
  - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
  - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is  $10 \log(1/x)$ , where x is the duty cycle.
  - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is  $20 \log(1/x)$ , where x is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq 98$  percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1.  $f < 30$  MHz, extrapolation factor of 40 dB/decade of distance.  $F_d = 40\log(D_m/D_s)$   
 $f \geq 30$  MHz, extrapolation factor of 20 dB/decade of distance.  $F_d = 20\log(D_m/D_s)$   
 Where:  
 $F_d$  = Distance factor in dB  
 $D_m$  = Measurement distance in meters  
 $D_s$  = Specification distance in meters
2. Field strength(dB $\mu$ V/m) = Level(dB $\mu$ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB $\mu$ V/m) - Field strength(dB $\mu$ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

**Limit**

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated ( $\mu$ V/m)
0.009 ~ 0.490	300	2 400/F(kHz)
0.490 ~ 1.705	30	24 000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.



Report No. : RF-230787

**Limit**

According to RSS-Gen, Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits :

Frequency (MHz)	Distance (Meters)	Radiated ( $\mu\text{V/m}$ )
0.009 ~ 0.490	300	2 400 / F(kHz)
0.490 ~ 1.705	30	24 000 / F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960*	3	500

\* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

**Note:** Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.



Report No. : RF-230787

**Duty cycle**

Regarding to KDB 558074 D01\_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode	T <sub>on</sub> time (ms)	Period (ms)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (dB)
LE 1 Mbps	0.39	0.63	0.62	61.90	2.08
802.11b	30	30	1.00	100.00	0.00
802.11g	30	30	1.00	100.00	0.00
802.11n_HT20	30	30	1.00	100.00	0.00
802.11n_HT40	30	30	1.00	100.00	0.00

Duty cycle (Linear) = T<sub>on</sub> time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)








Report No. : RF-230787

Test results (Below 30 MHz)

Mode: LE 1 Mbps\_DC 12V  
 Distance of measurement: 3 meter  
 Channel: 00 (Worst case)




Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.



Report No. : RF-230787

Mode: LE 1 Mbps\_DC 24V  
 Distance of measurement: 3 meter  
 Channel: 00 (Worst case)



Spectrum Selection

No.	Range	Frequency [MHz]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Angle [deg]	Remark
1	Range1	1.220	29.3	18.9	48.2	0.1	
2	Range1	2.442	21.8	19.1	40.9	52.8	
3	Range1	4.706	23.6	19.3	42.9	336.6	


Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.



Report No. : RF-230787

Mode: 802.11b(Worst Case)\_DC 12V  
 Distance of measurement: 3 meter  
 Channel: 01 (Worst case)



Spectrum Selection

No.	Range	Frequency [MHz]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Angle [deg]	Remark
1	Range1	1.385	19.1	18.9	38.0	23.4	
2	Range1	3.477	21.6	19.2	40.8	156.2	
3	Range1	4.763	23.5	19.3	42.8	23.4	

Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.




Report No. : RF-230787

Mode: 802.11b(Worst Case)\_DC 24V

Distance of measurement: 3 meter

Channel: 01 (Worst case)



Spectrum Selection

No.	Range	Frequency [MHz]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Angle [deg]	Remark
1	Range1	0.526	25.5	18.7	44.2	336.6	
2	Range1	3.477	20.7	19.2	39.9	203.7	
3	Range1	4.890	24.1	19.3	43.4	0.0	

Note.

1. No spurious emission were detected under 30 MHz, the above test result is the peak result.




Report No. : RF-230787

Test results (Below 1 000 MHz)

Mode: LE 1 Mbps\_DC 12V

Distance of measurement: 3 meter

Channel: 00 (Worst case)



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB (μV)]	c.f [dB (1/m)]	Result QP [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	30.000	V	45.2	-15.5	29.7	40.0	10.3	150.0	272.8	
2	43.095	V	42.3	-12.6	29.7	40.0	10.3	123.0	252.1	
3	66.618	V	44.6	-14.6	30.0	40.0	10.0	133.0	117.9	
4	143.975	H	50.0	-16.1	33.9	43.5	9.6	200.0	118.6	
5	155.979	H	48.6	-15.8	32.8	43.5	10.7	224.0	118.6	
6	197.568	V	43.1	-12.7	30.4	43.5	13.1	120.0	294.6	
7	213.088	H	44.8	-12.0	32.8	43.5	10.7	200.0	314.0	
8	227.031	H	45.6	-11.5	34.1	46.0	11.9	244.0	285.8	
9	252.251	V	41.3	-10.7	30.6	46.0	15.4	100.0	0.0	
10	360.043	H	42.6	-7.6	35.0	46.0	11.0	301.0	198.3	
11	479.959	H	40.3	-5.6	34.7	46.0	11.3	254.0	337.2	
12	479.959	V	38.9	-5.6	33.3	46.0	12.7	100.0	7.4	




Report No. : RF-230787

Mode: LE 1 Mbps\_DC 24V

Distance of measurement: 3 meter

Channel: 00 (Worst case)




Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB (μV)]	c.f [dB (1/m)]	Result QP [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	30.000	V	48.0	-15.5	32.5	40.0	7.5	150.0	333.2	
2	42.731	V	44.2	-12.7	31.5	40.0	8.5	133.0	333.2	
3	66.496	V	41.6	-14.5	27.1	40.0	12.9	177.0	22.6	
4	143.975	H	50.1	-16.1	34.0	43.5	9.5	200.0	90.2	
5	155.979	H	48.8	-15.8	33.0	43.5	10.5	189.0	68.8	
6	166.164	V	46.3	-15.0	31.3	43.5	12.2	100.0	359.9	
7	210.056	H	46.8	-12.1	34.7	43.5	8.8	203.0	314.2	
8	225.698	H	47.1	-11.6	35.5	46.0	10.5	308.0	337.3	
9	242.430	V	41.8	-11.0	30.8	46.0	15.2	131.0	27.3	
10	360.043	H	42.0	-7.6	34.4	46.0	11.6	208.0	225.9	
11	479.959	V	39.7	-5.6	34.1	46.0	11.9	124.0	359.9	
12	760.046	H	37.2	-2.3	34.9	46.0	11.1	200.0	161.8	



Report No. : RF-230787

Mode: 802.11b(Worst Case)\_DC 12V  
 Distance of measurement: 3 meter  
 Channel: 01 (Worst case)



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	30.000	V	48.7	-15.5	33.2	40.0	6.8	130.0	152.5	
2	42.974	V	43.6	-12.7	30.9	40.0	9.1	122.0	241.2	
3	66.618	V	42.6	-14.6	28.0	40.0	12.0	158.0	27.6	
4	155.979	H	48.9	-15.8	33.1	43.5	10.4	208.0	66.8	
5	166.043	V	45.8	-15.0	30.8	43.5	12.7	141.0	284.6	
6	217.089	H	45.9	-11.9	34.0	46.0	12.0	254.0	117.1	
7	218.665	V	43.6	-11.8	31.8	46.0	14.2	187.0	27.6	
8	221.090	H	48.7	-11.7	37.0	46.0	9.0	233.0	332.5	
9	228.850	V	45.6	-11.5	34.1	46.0	11.9	133.0	248.4	
10	239.278	H	45.1	-11.1	34.0	46.0	12.0	207.0	294.2	
11	360.043	H	41.6	-7.6	34.0	46.0	12.0	179.0	229.3	
12	479.959	H	37.8	-5.6	32.2	46.0	13.8	254.0	311.4	






Report No. : RF-230787

Mode: 802.11b(Worst Case)\_DC 24V

Distance of measurement: 3 meter

Channel: 01 (Worst case)



Final Result

No.	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	30.000	V	48.2	-15.5	32.7	40.0	7.3	137.0	292.9	
2	42.731	V	44.3	-12.7	31.6	40.0	8.4	126.0	332.4	
3	66.618	V	42.6	-14.6	28.0	40.0	12.0	100.0	50.2	
4	143.975	H	48.9	-16.1	32.8	43.5	10.7	208.0	118.7	
5	155.979	H	48.6	-15.8	32.8	43.5	10.7	223.0	118.7	
6	209.086	H	49.7	-12.2	37.5	43.5	6.0	241.0	111.4	
7	219.878	H	49.6	-11.8	37.8	46.0	8.2	200.0	222.4	
8	222.303	V	42.2	-11.7	30.5	46.0	15.5	133.0	271.0	
9	264.013	H	42.6	-10.5	32.1	46.0	13.9	223.0	288.6	
10	359.921	H	43.7	-7.6	36.1	46.0	9.9	209.0	199.6	
11	479.959	V	38.1	-5.6	32.5	46.0	13.5	120.0	332.4	
12	760.046	V	35.0	-2.3	32.7	46.0	13.3	100.0	292.9	



Report No. : RF-230787

Test results (Above 1 000 MHz)

Mode: LE 1 Mbps\_ DC 12V

Distance of measurement: 3 meter


Channel: 00

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	48.67	Peak	H	-9.59	-	39.08	74.00	34.92
1 661.40	43.74	Peak	V	-4.65	-	39.09	74.00	34.91


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 383.16	42.72	Peak	H	-0.74	-	41.98	74.00	32.02
2 390.00	45.34	Peak	V	-0.73	-	44.61	74.00	29.39





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: LE 1 Mbps\_ DC 12V

Distance of measurement: 3 meter

Channel: 20

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 007.20	44.60	Peak	V	-9.55	-	35.05	74.00	38.95
1 042.00	43.66	Peak	H	-9.31	-	34.35	74.00	39.65



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

Mode: LE 1 Mbps\_ DC 12V  
Distance of measurement: 3 meter  
Channel: 39

**- Spurious**


Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 015.90	43.76	Peak	V	-9.49	-	34.27	74.00	39.73
1 056.40	44.32	Peak	H	-9.21	-	35.11	74.00	38.89

**- Band edge**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 483.50	67.80	Peak	H	-0.57	-	67.23	74.00	6.77
2 483.50	33.71	Average	H	-0.57	2.08	33.81	54.00	18.11
2 483.50	62.60	Peak	V	-0.57	-	62.03	74.00	11.97
2 483.50	30.18	Average	V	-0.57	2.08	29.61	54.00	22.31




Report No. : RF-230787





Report No. : RF-230787



Note.


1. No spurious emission were detected above 3 GHz.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: LE 1 Mbps\_ DC 12V  
Distance of measurement: 3 meter  
Channel: 00 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.





Report No. : RF-230787


Mode: 802.11b\_ DC 12V  
 Distance of measurement: 3 meter  
 Channel: 01

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 015.90	43.93	Peak	V	-9.49	-	34.44	74.00	39.56
1 068.00	43.64	Peak	H	-9.13	-	34.51	74.00	39.49


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 387.41	46.49	Peak	H	-0.73	-	45.76	74.00	28.24
2 389.35	48.41	Peak	V	-0.73	-	47.68	74.00	26.32





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Report No. : RF-230787

Mode: 802.11b\_ DC 12V  
 Distance of measurement: 3 meter  
 Channel: 06

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	46.88	Peak	H	-9.59	-	37.29	74.00	36.71
1 015.90	43.85	Peak	V	-9.49	-	34.36	74.00	39.64



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11b\_ DC 12V  
 Distance of measurement: 3 meter  
 Channel: 11

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	44.62	Peak	H	-9.59	-	35.03	74.00	38.97
1 024.60	43.53	Peak	V	-9.43	-	34.10	74.00	39.90


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 483.50	47.62	Peak	H	-0.57	-	47.05	74.00	26.95
2 483.78	48.33	Peak	V	-0.57	-	47.76	74.00	26.24





Report No. : RF-230787



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11b\_ DC 12V  
Distance of measurement: 3 meter  
Channel: 01 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787

Mode: 802.11g\_ DC 12V

Distance of measurement: 3 meter


Channel: 01


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 001.40	43.95	Peak	H	-9.59	-	34.36	74.00	39.64
1 027.50	44.02	Peak	V	-9.41	-	34.61	74.00	39.39

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 387.08	48.42	Peak	V	-0.73	-	47.69	74.00	26.31
2 390.00	46.49	Peak	H	-0.73	-	45.76	74.00	28.24





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.





Report No. : RF-230787


Mode: 802.11g\_ DC 12V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 004.30	43.55	Peak	V	-9.57	-	33.98	74.00	40.02
1 079.60	44.28	Peak	H	-9.05	-	35.23	74.00	38.77



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11g\_ DC 12V  
 Distance of measurement: 3 meter  
 Channel: 11


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 001.40	44.77	Peak	H	-9.59	-	35.18	74.00	38.82
1 256.20	43.40	Peak	V	-7.83	-	35.57	74.00	38.43

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 486.49	47.32	Peak	V	-0.57	-	46.75	74.00	27.25
2 489.75	49.13	Peak	H	-0.56	-	49.24	74.00	24.76





Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11g\_ DC 12V  
Distance of measurement: 3 meter  
Channel: 11 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787

Mode: 802.11n\_HT20\_DC 12V

Distance of measurement: 3 meter


Channel: 01


- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	44.72	Peak	V	-9.59	-	35.13	74.00	38.87
1 013.00	44.15	Peak	H	-9.51	-	34.64	74.00	39.36

- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 386.60	47.87	Peak	V	-0.73	-	47.14	74.00	26.86
2 389.03	45.76	Peak	H	-0.73	-	45.03	74.00	28.97





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11n\_HT20\_DC 12V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 001.40	44.28	Peak	H	-9.59	-	34.69	74.00	39.31
1 085.40	44.20	Peak	V	-9.01	-	35.19	74.00	38.81



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

Mode: 802.11n\_HT20\_DC 12V

Distance of measurement: 3 meter


Channel: 11

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 013.00	43.99	Peak	H	-9.51	-	34.48	74.00	39.52
1 033.30	43.44	Peak	V	-9.37	-	34.07	74.00	39.93

- Band edge


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.50	47.50	Peak	V	-0.57	-	46.93	74.00	27.07
2 484.13	49.93	Peak	H	-0.57	-	49.36	74.00	24.64







Report No. : RF-230787



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11n\_HT20\_DC 12V  
Distance of measurement: 3 meter  
Channel: 11 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787


Mode: 802.11n\_HT40\_DC 12V  
 Distance of measurement: 3 meter  
 Channel: 03

**- Spurious**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 068.00	44.06	Peak	H	-9.13	-	34.93	74.00	39.07
1 606.40	44.18	Peak	V	-5.17	-	39.01	74.00	34.99


**- Band edge**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 388.37	50.98	Peak	H	-0.73	-	50.25	74.00	23.75
2 390.00	48.36	Peak	V	-0.73	-	47.63	74.00	26.37





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11n\_HT40\_DC 12V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 010.10	44.59	Peak	H	-9.53	-	35.06	74.00	38.94
1 018.80	43.61	Peak	V	-9.47	-	34.14	74.00	39.86



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

Mode: 802.11n\_HT40\_DC 12V

Distance of measurement: 3 meter


Channel: 9

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 024.60	43.87	Peak	H	-9.43	-	34.44	74.00	39.56
1 030.40	43.79	Peak	V	-9.39	-	34.40	74.00	39.60


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 483.50	48.39	Peak	H	-0.57	-	47.82	74.00	26.18
2 484.09	52.55	Peak	V	-0.57	-	51.98	74.00	22.02





Report No. : RF-230787



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11n\_HT40\_DC 12V  
Distance of measurement: 3 meter  
Channel: 03 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.





Report No. : RF-230787

Mode: LE 1 Mbps\_ DC 24V

Distance of measurement: 3 meter


Channel: 00

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 015.90	43.92	Peak	V	-9.49	-	34.43	74.00	39.57
1 661.40	44.96	Peak	H	-4.65	-	40.31	74.00	33.69


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 366.45	43.17	Peak	H	-0.77	-	42.40	74.00	31.60
2 390.00	44.12	Peak	V	-0.73	-	43.39	74.00	30.61





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: LE 1 Mbps\_ DC 24V

Distance of measurement: 3 meter

Channel: 20

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	44.39	Peak	V	-9.59	-	34.80	74.00	39.20
1 062.20	44.74	Peak	H	-9.17	-	35.57	74.00	38.43



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: LE 1 Mbps\_ DC 24V  
 Distance of measurement: 3 meter  
 Channel: 39


**- Spurious**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	46.56	Peak	H	-9.59	-	36.97	74.00	37.03
1 661.40	45.61	Peak	V	-4.65	-	40.96	74.00	33.04

**- Band edge**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 483.50	67.34	Peak	H	-0.57	-	66.77	74.00	7.23
2 483.50	32.04	Average	H	-0.57	2.08	32.14	54.00	19.78
2 483.50	61.87	Peak	V	-0.57	-	61.30	74.00	12.70
2 483.50	30.76	Average	V	-0.57	2.08	30.19	54.00	21.73





Note.


1. No spurious emission were detected above 3 GHz.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: LE 1 Mbps\_ DC 24V  
Distance of measurement: 3 meter  
Channel: 00 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787


Mode: 802.11b\_ DC 24V  
 Distance of measurement: 3 meter  
 Channel: 01

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	43.74	Peak	H	-9.59	-	34.15	74.00	39.85
1 036.20	43.82	Peak	V	-9.35	-	34.47	74.00	39.53

- Band edge


Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 388.22	48.44	Peak	H	-0.73	-	47.71	74.00	26.29
2 390.00	48.32	Peak	V	-0.73	-	47.59	74.00	26.41







Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11b\_ DC 24V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 030.40	43.50	Peak	V	-9.39	-	34.11	74.00	39.89
1 082.50	44.21	Peak	H	-9.03	-	35.18	74.00	38.82



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11b\_ DC 24V  
 Distance of measurement: 3 meter  
 Channel: 11

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 013.00	44.46	Peak	V	-9.51	-	34.95	74.00	39.05
1 021.70	44.18	Peak	H	-9.45	-	34.73	74.00	39.27


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 483.50	48.51	Peak	V	-0.57	-	47.94	74.00	26.06
2 489.27	47.69	Peak	H	-0.56	-	47.13	74.00	26.87





Report No. : RF-230787



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11b\_ DC 24V  
Distance of measurement: 3 meter  
Channel: 01 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787

Mode: 802.11g\_ DC 24V

Distance of measurement: 3 meter


Channel: 01

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 001.40	43.75	Peak	H	-9.59	-	34.16	74.00	39.84
1 027.50	43.96	Peak	V	-9.41	-	34.55	74.00	39.45


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 389.03	48.70	Peak	V	-0.73	-	47.97	74.00	26.03
2 389.51	45.89	Peak	H	-0.73	-	45.16	74.00	28.84





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Report No. : RF-230787

Mode: 802.11g\_ DC 24V  
 Distance of measurement: 3 meter  
 Channel: 06

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 004.30	44.47	Peak	H	-9.57	-	34.90	74.00	39.10
1 082.50	44.22	Peak	V	-9.03	-	35.19	74.00	38.81



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.





Report No. : RF-230787


Mode: 802.11g\_ DC 24V  
 Distance of measurement: 3 meter  
 Channel: 11


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 010.10	43.27	Peak	V	-9.53	-	33.74	74.00	40.26
1 027.50	45.39	Peak	H	-9.41	-	35.98	74.00	38.02

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.54	47.69	Peak	V	-0.57	-	47.12	74.00	26.88
2 492.04	49.51	Peak	H	-0.56	-	49.62	74.00	24.38





Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11g\_ DC 24V  
Distance of measurement: 3 meter  
Channel: 06 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787


Mode: 802.11n\_HT20\_DC 24V  
 Distance of measurement: 3 meter  
 Channel: 00


**- Spurious**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 039.10	44.10	Peak	V	-9.33	-	34.77	74.00	39.23
1 042.00	43.75	Peak	H	-9.31	-	34.44	74.00	39.56

**- Band edge**

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 386.92	46.71	Peak	H	-0.73	-	45.98	74.00	28.02
2 388.70	49.25	Peak	V	-0.73	-	48.53	74.00	25.47





Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11n\_HT20\_DC 24V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 030.40	43.58	Peak	H	-9.39	-	34.19	74.00	39.81
1 033.30	43.74	Peak	V	-9.37	-	34.37	74.00	39.63



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

Mode: 802.11n\_HT20\_DC 24V

Distance of measurement: 3 meter


Channel: 11

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 013.00	43.81	Peak	H	-9.51	-	34.30	74.00	39.70
1 070.90	43.98	Peak	V	-9.11	-	34.87	74.00	39.13


- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.13	48.02	Peak	V	-0.57	-	47.45	74.00	26.55
2 486.97	49.59	Peak	H	-0.57	-	49.02	74.00	24.98





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.






Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11n\_HT20\_DC 24V  
Distance of measurement: 3 meter  
Channel: 06 (Worst case)



Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787


Mode: 802.11n\_HT40\_DC 24V  
 Distance of measurement: 3 meter  
 Channel: 03

- Spurious

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1 010.10	43.94	Peak	V	-9.53	-	34.41	74.00	39.59
1 070.90	43.63	Peak	H	-9.11	-	34.52	74.00	39.48


- Band edge

Frequency (MHz)	Level (dB $\mu$ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
2 389.82	45.16	Peak	H	-0.73	-	44.43	74.00	29.57
2 390.00	49.50	Peak	V	-0.73	-	48.77	74.00	25.23





Report No. : RF-230787



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787


Mode: 802.11n\_HT40\_DC 24V

Distance of measurement: 3 meter

Channel: 06

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 010.10	43.73	Peak	V	-9.53	-	34.20	74.00	39.80
1 015.90	44.05	Peak	H	-9.49	-	34.56	74.00	39.44



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

Mode: 802.11n\_HT40\_DC 24V

Distance of measurement: 3 meter


Channel: 9


- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 013.00	43.96	Peak	H	-9.51	-	34.45	74.00	39.55
1 108.50	43.89	Peak	V	-8.85	-	35.04	74.00	38.96

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.00	47.88	Peak	H	-0.57	-	47.31	74.00	26.69
2 485.28	51.92	Peak	V	-0.57	-	51.35	74.00	22.65





Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Report No. : RF-230787

**Test results (18 GHz to 30 GHz)**

Mode: 802.11n\_HT40\_DC 24V  
Distance of measurement: 3 meter  
Channel: 09 (Worst case)




Note.  
No spurious emission were detected above 18 GHz.



Report No. : RF-230787

### 3.3. Antenna Requirement

According to 15.207(a), An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.





**Appendix A. Measurement equipment**

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
SPECTRUM ANALYZER	R&S	FSV3044	101272	1 year	2024.03.16
SPECTRUM ANALYZER	R&S	FSV40	101725	1 year	2024.06.15
SIGNAL GENERATOR	KEYSIGHT	N5182B	MY59100115	1 year	2024.04.19
SIGNAL GENERATOR	Anritsu	68369B	002118	1 year	2024.05.12
Power Meter	Anritsu	ML2495A	2010001	1 year	2024.04.19
Pulse Power Sensor	Anritsu	MA2411B	1911111	1 year	2024.04.18
ATTENUATOR	Mini-Circuits	BW-S10-2W263+	1	1 year	2024.01.13 2025.01.16
BAND REJECT FILTER	MICRO-TRONICS	BRM50702	G272	1 year	2024.01.12 2025.01.12
EMI TEST RECEIVER	R&S	ESU26	100517	1 year	2024.07.31
LOOP ANTENNA	Schwarzbeck	FMZB1513	1513-257	2 years	2024.11.16
BILOG ANTENNA	Schwarzbeck	VULB 9163	714	2 years	2024.04.19
DC POWER SUPPLY	SORENSEN	DCS40-75E	1408A02745	1 year	2024.01.12 2025.01.12
Attenuator	HUBER+SHHNER	6806.17.A	NONE	1 year	2024.03.21
Horn Antenna	A.H.	SAS-571	414	1 year	2024.01.16 2025.01.16
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA 9170550	1 year	2024.01.16 2025.01.16
Amplifier	SONOMA INSTRUMENT	310N	186549	1 year	2024.03.21
PREAMPLIFIER	HP	8449B	3008A00538	1 year	2024.05.31
BROADBAND AMPLIFIER	SCHWARZBECK	BBV9721	PS9721-003	1 year	2024.01.16 2025.01.15

\* Statement of Traceability: KES Co., Ltd. attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Peripheral devices**

Device	Manufacturer	Model No.	Serial No.
Notebook computer	LG Electronics Inc.,	LGS53	306QCZP560949

**The end of test report**