

Standalone SAR test exclusion considerations

RF feature	Mode	Transmitting Frequency(MHz)	Test separation distance (mm)	ANT Gain (dBi)	Max. power with tune-up tolerance (dBm) ^{Note1}	Max. power with tune-up tolerance (mW)	Power thresholds	SAR test exclusion thresholds
BLE	GFSK(1Mbps)	2 402.00 ~ 2 480.00	5.0	1.68	0.50	1.122 0	0.35	3.00
Zigbee	O-QPSK (250 kbps)	2 480.00 ~ 2 480.00	5.0	0.90	-8.00	0.158 5	0.05	3.00

Note1. Please refer to the operation description for Max Tune-up power.

KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm

$\left[\left(\text{max. power of channel, including tune-up tolerance, mW} \right) / \left(\text{min. test separation distance, mm} \right) \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0$ for 1g SAR and ≤ 7.5 for 10g extremity SAR

Sample Calculation

$$= \left[\left(1.122\text{mW} / 5\text{mm} \right) \right] \times \left[\sqrt{2.48\text{GHz}} \right] = 0.35$$

Note. The calculation result was rounded to two decimal place for comparison.

Conclusion : SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required