

FCC RADIO TEST REPORT

Applicant..... : Airboxlab S.A.

Address..... : 3 av du blues, 4368 Sanem, Luxembourg

Manufacturer..... : VTech Communications Ltd.

Address..... : 23rd Floor, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, New Territories, Hong Kong.

Factory..... : VTech Communications Ltd.

Address..... : 23rd Floor, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, New Territories, Hong Kong.

Product Name.....: FoobotSAT

Brand Name..... : Foobot

Model No. : SAT0001100

FCC ID..... : 2ADTK-SAT0001100

Measurement Standard.....: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Receipt Date of Samples.... : July 30, 2020

Date of Tested..... : July 30, 2020 to February 03, 2021

Date of Report..... : March 11, 2021

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.

Prepared by

Rose Hu / Project Engineer



Table of Contents

1. Summary of Test Result.....	4
2. General Description of EUT	5
3. Test Channels and Modes Detail.....	8
4. Configuration of EUT.....	8
5. Modification of EUT.....	9
6. Description of Support Device.....	9
7. Test Facility and Location	10
8. Applicable Standards and References.....	10
9. Deviations and Abnormalities from Standard Conditions	11
10. Test Conditions	11
11. Measurement Uncertainty	11
12. Sample Calculations	12
13. Duty Cycle of Test Signal.....	12
14. Test Items and Results	13
14.1 Conducted Emissions Measurement.....	13
14.2 Maximum Conducted Output Power Measurement.....	23
14.3 6dB Bandwidth Measurement	25
14.4 Power Spectral Density Measurement	30
14.5 Band Edge and Conducted Spurious Emissions Measurement	35
14.6 Radiated Spurious Emissions and Restricted Bands.....	42
14.7 Antenna Requirement.....	56
15. Test Equipment List.....	57

Revision History

1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Conducted Emission	PASS	---
§15.247(b)(3)	Maximum Conducted Output Power	PASS	---
§15.247(a)(2)	6dB Bandwidth	PASS	---
§15.247(e)	Power Spectral Density	PASS	---
§15.247(d)	Band Edge and Conducted Spurious Emissions	PASS	---
§15.247(d),§15.209, §15.205	Radiated Spurious Emissions and Restricted Bands	PASS	---
§15.203	Antenna Requirement	PASS	---

2. General Description of EUT

Product Information	
Product Name:	FoobotSAT
Main Model Name:	SAT0001100
Additional Model Name:	N/A
Model Difference:	N/A
S/N:	2007-2305
Brand Name:	Foobot
Hardware Version:	V00
Software Version:	V00
Rating:	DC 12V come from Adapter
Typical arrangement:	Table-top
I/O Port:	DC Port*1, Ethernet Port*1
Accessories Information	
Adapter 1:	M/N: SK03T1-1200150W2 Input: AC100-240V 50/60Hz, 0.6A Max Output: DC 12.0V 1.5A 18.0W
Adapter 2:	M/N: GQ24-120150-E2 Input: AC100-240V 50/60Hz, 1.0A Max Output: DC 12.0V 1.5A
Cable:	AC mains: 1.00m unshielded DC line: 1.51m unshielded
Other:	N/A
Additional Information	
Note:	N/A
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification (2.4GHz WLAN)	
Frequency Range:	2412-2472MHz for IEEE 802.11b/g/n(HT20) 2422-2462MHz for IEEE 802.11n(HT40)
Modulation Technology:	DSSS, OFDM
Modulation Type:	CCK, DQPSK, DBPSK, 64-QAM, 16-QAM, QPSK, BPSK
Number of Channel:	13 for IEEE 802.11b/g/n(HT20) 9 for IEEE 802.11n(HT40)
Channel Space:	5MHz
Antenna Type:	PCB antenna
Antenna Gain:	0 dBi (Declared by manufacturer)
Technical Specification (BLE)	
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK
Number of Channel:	40
Channel Space:	2MHz
Antenna Type:	PCB antenna
Antenna Gain:	0 dBi (Declared by manufacturer)

Channel List			
IEEE 802.11b/ g/ n(HT20)		IEEE 802.11 n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	---	---
2	2417	---	---
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	---	---
11	2462	---	---
---	---	---	---

BLE Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	2	2404	3	2406
--	---	---	---	---	---
20	2440	---	---	40	2480

3. Test Channels and Modes Detail

For WIFI

Mode		Channel	Frequency (MHz)	Remark
1	TX	1	2412	IEEE 802.11b/ g/ n(HT20)
		3	2422	IEEE 802.11n(HT40)
		6	2437	IEEE 802.11b/ g/ n(HT20)/ n(HT40)
		9	2452	IEEE 802.11n(HT40)
		11	2462	IEEE 802.11b/ g/ n(HT20)
2.	Normal Mode	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

For BLE

Mode		Channel	Frequency (MHz)	Remark
1	TX	1	2412	---
		20	2440	---
		40	2480	---
2.	Normal Mode	---	---	---



Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

4. Configuration of EUT

TX Mode



Normal Mode



5. Modification of EUT

No modifications are made to the EUT during all test items.

6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
1.	Laptop	Lenovo	02213DC	0A33012	Power cord, 1.8m, unshielded	---
2.	Power supply (Laptop)	Delta	92P1154	N/A		---
3.	Test fixture	---	---	---	---	Provided by the laboratory
4.	iPAD	APPLE	MUUL2CH/A	DMPZV340 LMPG	---	---
5.	Router	HUAWEI	WS7200	L5KEQ2051 8024454	DC Line: 1.25m unshielded.	Adapter: Manufacturer: HONOTO M/N: HW-120200C01 I/P: AC 100-240V 50-60Hz, 0.8A O/P: DC 12V 2A

Software	Power Setting
ESP-RF-TEST-TOOL V2.5	Default

7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	<p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2024</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2021</p> <p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number is 907417</p> <p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number is 46405-9743A</p>
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2013

References Test Guidance:

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	2	AC 120V 60Hz	Ray Ding	See note 1
2.	Max. Conducted Output Power	1	AC 120V 60Hz	Ray Ding	See note 1
3.	6dB Bandwidth	1	AC 120V 60Hz	Ray Ding	See note 1
4.	Power Spectral Density	1	AC 120V 60Hz	Ray Ding	See note 1
5.	Band Edge and Conducted Spurious Emissions	1	AC 120V 60Hz	Ray Ding	See note 1
6.	Radiated Spurious Emissions and Restricted Bands	1, 2	AC 120V 60Hz	Ray Ding	See note 1
7..	Antenna Requirement	---	---	---	See note 1

Note:

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35°C, 30~70%, 86~106kPa.

11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.52 dB	---
2.	Radiated Emission Test	9kHz ~ 30MHz	±2.60 dB	---
		30MHz ~ 1GHz	±4.68 dB	---
		1GHz ~ 18GHz	±5.14 dB	---
		18GHz ~ 40GHz	±5.14 dB	---

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.1900	30.10	10.60	40.70	79.00	-38.30	QP

Where,

Freq. = Emission frequency in MHz
 Reading Level = Uncorrected Analyzer/Receiver reading
 Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation
 Measurement = Reading + Corrector Factor
 Limit = Limit stated in standard
 Margin = Measurement - Limit
 Detector = Reading for Quasi-Peak / Average / Peak

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Measurement (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
60.0700	45.88	-18.38	27.50	49.00	-21.50	QP

Where,

Freq. = Emission frequency in MHz
 Reading Level = Uncorrected Analyzer/Receiver reading
 Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier
 Measurement = Reading + Corrector Factor
 Limit = Limit stated in standard
 Over = Margin, which calculated by Measurement - Limit
 Detector = Reading for Quasi-Peak / Average / Peak

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

13. Duty Cycle of Test Signal

Note: Duty Cycle of test signal is $\geq 98\%$, Duty cycle factor is not required.

14. Test Items and Results

14.1 Conducted Emissions Measurement


LIMIT

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

Note: 1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

TEST RESULTS

PASS

Please refer to the following pages of the worst case.


For WIFI

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: GQ24-120150-E2	Detector: QP & AVG
Test Mode: 2	Phase: L1

Conducted Emission Measurement

Date: 2021/1/29

Time: 15:28:39




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.1580	39.30	10.60	49.90	65.57	-15.67	QP	
2	0.1580	21.40	10.60	32.00	55.57	-23.57	AVG	
3	0.2020	36.20	10.60	46.80	63.53	-16.73	QP	
4	0.2020	15.00	10.60	25.60	53.53	-27.93	AVG	
5	0.2420	32.70	10.60	43.30	62.03	-18.73	QP	
6	0.2420	16.90	10.60	27.50	52.03	-24.53	AVG	
7	0.3020	25.70	10.60	36.30	60.19	-23.89	QP	
8	0.3020	6.40	10.60	17.00	50.19	-33.19	AVG	
9	0.4780	16.37	10.63	27.00	56.37	-29.37	QP	
10	0.4780	5.97	10.63	16.60	46.37	-29.77	AVG	
11	0.5740	12.96	10.64	23.60	56.00	-32.40	QP	
12	0.5740	-0.44	10.64	10.20	46.00	-35.80	AVG	

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: GQ24-120150-E2	Detector: QP & AVG
Test Mode: 2	Phase: N

Conducted Emission Measurement

Date: 2021/1/29

Time: 15:35:32




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1700	38.00	10.60	48.60	64.96	-16.36	QP	
2	0.1700	15.60	10.60	26.20	54.96	-28.76	AVG	
3	0.2380	29.10	10.60	39.70	62.17	-22.47	QP	
4	0.2380	9.30	10.60	19.90	52.17	-32.27	AVG	
5	0.3100	26.10	10.60	36.70	59.97	-23.27	QP	
6	0.3100	9.70	10.60	20.30	49.97	-29.67	AVG	
7	0.4660	18.28	10.62	28.90	56.58	-27.68	QP	
8	0.4660	4.48	10.62	15.10	46.58	-31.48	AVG	
9	0.6540	10.75	10.65	21.40	56.00	-34.60	QP	
10	0.6540	-0.55	10.65	10.10	46.00	-35.90	AVG	
11	1.1300	8.50	10.70	19.20	56.00	-36.80	QP	
12	1.1300	-1.40	10.70	9.30	46.00	-36.70	AVG	

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP & AVG
Test Mode: 2	Phase: L1

Conducted Emission Measurement

Date: 2021/1/29

Time: 16:10:29




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
MHz	dBuV	dB	dBuV	dBuV	dB			
1 *	0.1500	37.50	10.60	48.10	66.00	-17.90	QP	
2	0.1500	18.30	10.60	28.90	56.00	-27.10	AVG	
3	0.2060	30.40	10.60	41.00	63.37	-22.37	QP	
4	0.2060	14.10	10.60	24.70	53.37	-28.67	AVG	
5	0.3140	23.70	10.60	34.30	59.86	-25.56	QP	
6	0.3140	10.60	10.60	21.20	49.86	-28.66	AVG	
7	0.5820	17.76	10.64	28.40	56.00	-27.60	QP	
8	0.5820	10.06	10.64	20.70	46.00	-25.30	AVG	
9	4.5819	13.29	10.71	24.00	56.00	-32.00	QP	
10	4.5819	3.99	10.71	14.70	46.00	-31.30	AVG	
11	15.4500	18.85	10.75	29.60	60.00	-30.40	QP	
12	15.4500	11.65	10.75	22.40	50.00	-27.60	AVG	

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP & AVG
Test Mode: 2	Phase: N

Conducted Emission Measurement

Date: 2021/1/29

Time: 16:17:37



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Comment						
							MHz	dBuV	dB	dBuV	dB	Detector	Comment
1 *	0.1539	37.40	10.60	48.00	65.79	-17.79	QP						
2	0.1539	19.80	10.60	30.40	55.79	-25.39	AVG						
3	0.1700	35.40	10.60	46.00	64.96	-18.96	QP						
4	0.1700	18.40	10.60	29.00	54.96	-25.96	AVG						
5	0.2380	28.90	10.60	39.50	62.17	-22.67	QP						
6	0.2380	11.00	10.60	21.60	52.17	-30.57	AVG						
7	0.5580	13.66	10.64	24.30	56.00	-31.70	QP						
8	0.5580	3.36	10.64	14.00	46.00	-32.00	AVG						
9	4.5059	10.19	10.71	20.90	56.00	-35.10	QP						
10	4.5059	1.69	10.71	12.40	46.00	-33.60	AVG						
11	15.3139	19.65	10.75	30.40	60.00	-29.60	QP						
12	15.3139	12.85	10.75	23.60	50.00	-26.40	AVG						


For BLE

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: GQ24-120150-E2	Detector: QP & AVG
Test Mode: 2	Phase: L1

Conducted Emission Measurement

Date: 2021/2/3

Time: 8:55:48




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.1620	37.50	10.60	48.10	65.36	-17.26	QP	
2	0.1620	16.10	10.60	26.70	55.36	-28.66	AVG	
3	0.1900	32.80	10.60	43.40	64.04	-20.64	QP	
4	0.1900	15.20	10.60	25.80	54.04	-28.24	AVG	
5	0.2220	28.90	10.60	39.50	62.74	-23.24	QP	
6	0.2220	13.80	10.60	24.40	52.74	-28.34	AVG	
7	0.5980	17.26	10.64	27.90	56.00	-28.10	QP	
8	0.5980	8.36	10.64	19.00	46.00	-27.00	AVG	
9	4.6179	12.89	10.71	23.60	56.00	-32.40	QP	
10	4.6179	4.49	10.71	15.20	46.00	-30.80	AVG	
11	15.1819	18.85	10.75	29.60	60.00	-30.40	QP	
12	15.1819	11.55	10.75	22.30	50.00	-27.70	AVG	

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: GQ24-120150-E2	Detector: QP & AVG
Test Mode: 2	Phase: N

Conducted Emission Measurement

Date: 2021/2/3

Time: 9:02:32




No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1539	37.50	10.60	48.10	65.79	-17.69	QP	
2	0.1539	19.20	10.60	29.80	55.79	-25.99	AVG	
3	0.2060	32.80	10.60	43.40	63.37	-19.97	QP	
4	0.2060	15.00	10.60	25.60	53.37	-27.77	AVG	
5	0.2580	28.10	10.60	38.70	61.50	-22.80	QP	
6	0.2580	9.90	10.60	20.50	51.50	-31.00	AVG	
7	0.6060	14.36	10.64	25.00	56.00	-31.00	QP	
8	0.6060	6.16	10.64	16.80	46.00	-29.20	AVG	
9	4.5339	9.49	10.71	20.20	56.00	-35.80	QP	
10	4.5339	0.49	10.71	11.20	46.00	-34.80	AVG	
11	15.3059	19.75	10.75	30.50	60.00	-29.50	QP	
12	15.3059	12.15	10.75	22.90	50.00	-27.10	AVG	

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP & AVG
Test Mode: 2	Phase: L1

Conducted Emission Measurement

Date: 2021/2/3

Time: 9:23:16




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1 *	0.1580	40.60	10.60	51.20	65.57	-14.37	QP
2	0.1580	18.10	10.60	28.70	55.57	-26.87	AVG
3	0.2100	34.90	10.60	45.50	63.21	-17.71	QP
4	0.2100	14.70	10.60	25.30	53.21	-27.91	AVG
5	0.2500	29.20	10.60	39.80	61.76	-21.96	QP
6	0.2500	10.40	10.60	21.00	51.76	-30.76	AVG
7	0.4739	20.58	10.62	31.20	56.45	-25.25	QP
8	0.4739	12.78	10.62	23.40	46.45	-23.05	AVG
9	6.5138	8.48	10.72	19.20	60.00	-40.80	QP
10	6.5138	-0.22	10.72	10.50	50.00	-39.50	AVG
11	20.3939	10.73	10.77	21.50	60.00	-38.50	QP
12	20.3939	0.43	10.77	11.20	50.00	-38.80	AVG

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP & AVG
Test Mode: 2	Phase: N

Conducted Emission Measurement

Date: 2021/2/3

Time: 9:30:36



No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1580	39.10	10.60	49.70	65.57	-15.87	QP	
2	0.1580	17.50	10.60	28.10	55.57	-27.47	AVG	
3	0.1779	35.80	10.60	46.40	64.58	-18.18	QP	
4	0.1779	15.20	10.60	25.80	54.58	-28.78	AVG	
5	0.2540	28.10	10.60	38.70	61.63	-22.93	QP	
6	0.2540	10.70	10.60	21.30	51.63	-30.33	AVG	
7	0.4460	19.58	10.62	30.20	56.95	-26.75	QP	
8	0.4460	3.68	10.62	14.30	46.95	-32.65	AVG	
9	1.4259	7.80	10.70	18.50	56.00	-37.50	QP	
10	1.4259	-2.60	10.70	8.10	46.00	-37.90	AVG	
11	20.2220	9.23	10.77	20.00	60.00	-40.00	QP	
12	20.2220	-1.77	10.77	9.00	50.00	-41.00	AVG	

14.2 Maximum Conducted Output Power Measurement


LIMIT

For system using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1 Watt.

If the transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi.

In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of Antenna exceeds 6dBi.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

ANSI C63.10 - 2013, Section 11.9.1.3

ANSI C63.10 - 2013, Section 11.9.2.3.2

TEST RESULTS

PASS

Please refer to the following table.

Temperature: 24°C			Humidity: 48%		Test Date: 2020-9-14		
Channel	Frequency (MHz)	Data Rate (Mbps)	Reading Level (dBm)	Duty Cycle Factor	Peak Output Power (dBm)	Limit (dBm)	Result
IEEE 802.11b							
1	2412	1	15.44	-	15.44	≤30	PASS
6	2437	1	15.37	-	15.37	≤30	PASS
11	2462	1	15.51	-	15.51	≤30	PASS
IEEE 802.11g							
1	2412	6	14.36	-	14.36	≤30	PASS
6	2437	6	14.40	-	14.40	≤30	PASS
11	2462	6	14.59	-	14.59	≤30	PASS
IEEE 802.11n(HT20)							
1	2412	MCS0	14.34	-	14.34	≤30	PASS
6	2437	MCS0	14.32	-	14.32	≤30	PASS
11	2462	MCS0	14.51	-	14.51	≤30	PASS
IEEE 802.11n(HT40)							
3	2422	MCS0	12.09	-	12.09	≤30	PASS
6	2437	MCS0	12.11	-	12.11	≤30	PASS
9	2452	MCS0	11.95	-	11.95	≤30	PASS
GFSK							
1	2402	1	3.78	-	3.78	≤30	PASS
20	2440	1	4.63	-	4.63	≤30	PASS
40	2480	1	4.45	-	4.45	≤30	PASS


Note: Peak Output Power = Reading Level + Duty Cycle Factor

14.3 6dB Bandwidth Measurement

LIMIT

The minimum 6dB bandwidth shall be at least 500 kHz

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to DTS KDB 558074 D01 15.247 Meas Guidance v05r02:


- a. Set the RBW = 100KHz.
- b. Set the VBW $\geq 3 \times$ RBW
- c. Set the Detector = peak.
- d. Set the Sweep time = auto couple.
- e. Set the Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


TEST RESULTS


PASS

Please refer to the following tables.

Temperature: 24°C			Humidity: 48%	Test Date: 2020-09-14		
Channel	Frequency (MHz)	Data Rate (Mbps)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
IEEE 802.11b						
1	2412	1	10.07	---	>0.5	PASS
6	2437	1	10.06	---	>0.5	PASS
11	2462	1	10.06	---	>0.5	PASS
IEEE 802.11g						
1	2412	6	16.42	---	>0.5	PASS
6	2437	6	16.42	---	>0.5	PASS
11	2462	6	16.42	---	>0.5	PASS
IEEE 802.11n(HT20)						
1	2412	MCS0	17.33	---	>0.5	PASS
6	2437	MCS0	17.33	---	>0.5	PASS
11	2462	MCS0	17.53	---	>0.5	PASS
IEEE 802.11n(HT40)						
3	2422	MCS0	36.33	---	>0.5	PASS
6	2437	MCS0	36.35	---	>0.5	PASS
9	2452	MCS0	36.33	---	>0.5	PASS
GFSK						
1	2402	1	0.6464	---	>0.5	PASS
20	2440	1	0.6471	---	>0.5	PASS
40	2480	1	0.6443	---	>0.5	PASS








14.4 Power Spectral Density Measurement

LIMIT

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC DTS KDB 558074 D01 15.247 Meas Guidance v05r02:


- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100\text{KHz}$
- d. Set the VBW $\geq 3 \times \text{RBW}$.
- e. Set the Detector = peak.
- f. Set the Sweep time = auto couple.
- g. Set the Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.
- j. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

PASS


Please refer to the following table.

Temperature: 24°C			Humidity: 48%	Test Date: 2020-09-14	
Channel	Frequency (MHz)	Data Rate (Mbps)	PSD dBm / 3kHz	Limit dBm / 3kHz	Result
IEEE 802.11b					
1	2412	1	-8.082	8	PASS
6	2437	1	-7.399	8	PASS
11	2462	1	-7.751	8	PASS
IEEE 802.11g					
1	2412	6	-12.921	8	PASS
6	2437	6	-12.515	8	PASS
11	2462	6	-12.465	8	PASS
IEEE 802.11n(HT20)					
1	2412	MCS0	-13.007	8	PASS
6	2437	MCS0	-12.502	8	PASS
11	2462	MCS0	-12.732	8	PASS
IEEE 802.11n(HT40)					
3	2422	MCS0	-15.236	8	PASS
6	2437	MCS0	-15.438	8	PASS
9	2452	MCS0	-17.024	8	PASS
GFSK					
1	2402	1	-11.521	8	PASS
20	2440	1	-10.515	8	PASS
40	2480	1	-10.585	8	PASS




Test Plots of Power Spectral Density


IEEE 802.11n(HT20) - 2412MHz




IEEE 802.11n(HT20) - 2437MHz




IEEE 802.11n(HT20) - 2462MHz




IEEE 802.11n(HT40) - 2422MHz



IEEE 802.11n(HT40) - 2437MHz




IEEE 802.11n(HT40) - 2452MHz



Test Plots of Power Spectral Density


GFSK- 2402MHz



GFSK- 2440MHz



GFSK- 2480MHz



14.5 Band Edge and Conducted Spurious Emissions Measurement

LIMIT

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to ANSI C63.10-2013, Section 11.11

Measurement Procedure REF

- a. Set the RBW = 100 kHz.
- b. Set the VBW \geq 300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep time = auto couple.
- e. Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


Measurement Procedure OOB

- a. Set RBW = 100 kHz.
- b. Set VBW \geq 300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep = auto couple.
- e. Set the Trace Mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum amplitude level.

TEST RESULTS

PASS

Please refer to the following test plots.




Band Edge

IEEE 802.11n(HT20)

Low Channel




High Channel




IEEE 802.11n(HT40)

Low Channel




High Channel





Conducted Spurious Emissions – IEEE 802.11b (The Worst Case)

Low Channel / 30MHz~1GHz



Low Channel / 1GHz~25GHz




Middle Channel / 30MHz~1GHz



Middle Channel / 1GHz~25GHz



High Channel / 30MHz~1GHz




High Channel / 1GHz~25GHz




Conducted Spurious Emissions -GFSK


Low Channel / 30MHz~1GHz




Low Channel / 1GHz~25GHz




Middle Channel / 30MHz~1GHz




Middle Channel / 1GHz~25GHz



High Channel / 30MHz~1GHz



High Channel / 1GHz~25GHz



14.6 Radiated Spurious Emissions and Restricted Bands Measurement


LIMIT

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500


Remark: (1) Emission level (dB) μV = 20 log Emission level $\mu\text{V/m}$
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
(5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



TEST PROCEDURES

a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.

b. For the radiated emission test above 1GHz:

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.

f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

TEST RESULTS

PASS

Please refer to the following pages.


For WIFI

M/N: SAT0001100	Testing Voltage: AC 120V/60Hz
Adapter: GQ24-120150-E2	Detector: QP
Test Mode: 1(IEEE 802.11b High channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 13:58:38



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		350.1000	33.75	-4.15	29.60	46.00	-16.40	QP
2		750.7100	28.26	3.04	31.30	46.00	-14.70	QP
3		800.1800	29.64	3.96	33.60	46.00	-12.40	QP
4	*	850.6200	35.50	4.80	40.30	46.00	-5.70	QP
5		900.0900	27.30	6.20	33.50	46.00	-12.50	QP
6		950.5300	25.33	6.27	31.60	46.00	-14.40	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V/60Hz
Adapter: GQ24-120150-E2	Detector: QP
Test Mode: 1(IEEE 802.11b High channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 14:05:42



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		46.4900	34.26	-7.46	26.80	40.00	-13.20	QP	
2		63.9500	36.66	-9.06	27.60	40.00	-12.40	QP	
3		125.0600	39.43	-11.23	28.20	43.50	-15.30	QP	
4	*	850.6200	31.60	4.80	36.40	46.00	-9.60	QP	
5		900.0900	26.44	4.96	31.40	46.00	-14.60	QP	
6		950.5300	28.23	5.07	33.30	46.00	-12.70	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP
Test Mode: 1(IEEE 802.11b High channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 15:17:29



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment	dBuV/m	dB	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		250.1900	35.56	-6.36	29.20	46.00	-16.80	QP
2		750.7100	29.06	3.04	32.10	46.00	-13.90	QP
3		800.1800	30.54	3.96	34.50	46.00	-11.50	QP
4	*	850.6200	33.70	4.80	38.50	46.00	-7.50	QP
5		900.0900	25.70	6.20	31.90	46.00	-14.10	QP
6		950.5300	26.23	6.27	32.50	46.00	-13.50	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V/60Hz
Adapter: SK03T1-1200150W2	Detector: QP
Test Mode: 1(IEEE 802.11b High channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 15:24:26



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		43.5800	32.56	-7.66	24.90	40.00	-15.10	QP	
2		63.9500	34.46	-9.06	25.40	40.00	-14.60	QP	
3		750.7100	26.36	3.04	29.40	46.00	-16.60	QP	
4	*	850.6200	30.70	4.80	35.50	46.00	-10.50	QP	
5		900.0900	26.54	4.96	31.50	46.00	-14.50	QP	
6		950.5300	27.03	5.07	32.10	46.00	-13.90	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


For BLE

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: GQ24-120150-E2	Detector: QP
Test Mode: 1(GFSK Middle channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 13:44:52



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		350.1000	33.65	-4.15	29.50	46.00	-16.50	QP
2		750.7100	27.76	3.04	30.80	46.00	-15.20	QP
3		800.1800	30.64	3.96	34.60	46.00	-11.40	QP
4	*	850.6200	35.80	4.80	40.60	46.00	-5.40	QP
5		900.0900	28.50	6.20	34.70	46.00	-11.30	QP
6		950.5300	27.63	6.27	33.90	46.00	-12.10	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V/60Hz
Adapter: GQ24-120150-E2	Detector: QP
Test Mode: 1(GFSK Middle channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 13:51:57



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment	dBuV/m	dB	
1		46.4900	34.86	-7.46	27.40	40.00	-12.60	QP
2		63.9500	36.56	-9.06	27.50	40.00	-12.50	QP
3		800.1800	26.54	3.96	30.50	46.00	-15.50	QP
4	*	850.6200	32.80	4.80	37.60	46.00	-8.40	QP
5		900.0900	27.84	4.96	32.80	46.00	-13.20	QP
6		950.5300	27.73	5.07	32.80	46.00	-13.20	QP


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP
Test Mode: 1(GFSK Middle channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 15:03:24



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	399.5700	32.64	-3.34	29.30	46.00	46.00	-16.70	QP	
2	750.7100	28.46	3.04	31.50	46.00	46.00	-14.50	QP	
3	800.1800	29.64	3.96	33.60	46.00	46.00	-12.40	QP	
4	* 850.6200	34.30	4.80	39.10	46.00	46.00	-6.90	QP	
5	900.0900	27.90	6.20	34.10	46.00	46.00	-11.90	QP	
6	950.5300	26.63	6.27	32.90	46.00	46.00	-13.10	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SAT0001100	Testing Voltage: AC 120V 60Hz
Adapter: SK03T1-1200150W2	Detector: QP
Test Mode: 1(GFSK Middle channel, the worst case)	Distance: 3m

Radiated Emission Measurement

Date: 2021/1/28

Time: 15:10:25



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment		Limit	Over				
					MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		44.5500	32.61	-7.61	25.00	40.00	-15.00	40.00	40.00	-15.00	QP	
2		63.9500	34.26	-9.06	25.20	40.00	-14.80	40.00	40.00	-14.80	QP	
3		250.1900	36.46	-7.36	29.10	46.00	-16.90	46.00	46.00	-16.90	QP	
4	*	850.6200	30.60	4.80	35.40	46.00	-10.60	46.00	46.00	-10.60	QP	
5		900.0900	26.74	4.96	31.70	46.00	-14.30	46.00	46.00	-14.30	QP	
6		950.5300	26.23	5.07	31.30	46.00	-14.70	46.00	46.00	-14.70	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Modulation: TX (IEEE 802.11b the worst case)			Test Result: PASS				Test frequency range: 1-25GHz				
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)		
		PK	AV		PK	AV	PK	AV	PK	AV	
Operation Mode: TX Mode (Low)											
4824	V	56.93	33.44	6.38	63.31	39.82	74.00	54.00	-10.69	-14.18	
7236	V	46.47	31.16	10.48	56.95	41.64	74.00	54.00	-17.05	-12.36	

4824	H	56.62	33.45	6.38	63.00	39.83	74.00	54.00	-11.00	-14.17	
7236	H	47.30	31.24	10.48	57.78	41.72	74.00	54.00	-16.22	-12.28	

Operation Mode: TX Mode (Mid)											
4874	V	56.59	33.42	6.56	63.15	39.98	74.00	54.00	-10.85	-14.02	
7311	V	47.60	31.25	10.53	58.13	41.78	74.00	54.00	-15.87	-12.22	

4874	H	56.48	33.38	6.56	63.04	39.94	74.00	54.00	-10.96	-14.06	
7311	H	46.81	31.30	10.53	57.34	41.83	74.00	54.00	-16.66	-12.17	

Operation Mode: TX Mode (High)											
4924	V	54.16	32.78	6.76	60.92	39.54	74.00	54.00	-13.08	-14.46	
7386	V	47.34	31.25	10.57	57.91	41.82	74.00	54.00	-16.09	-12.18	

4924	H	56.26	32.98	6.76	63.02	39.74	74.00	54.00	-10.98	-14.26	
7386	H	47.23	31.23	10.57	57.80	41.80	74.00	54.00	-16.20	-12.20	

Spurious Emission in restricted band:											
2390.000	H	47.61	32.50	0.09	47.70	32.59	74.00	54.00	-26.30	-21.41	
2390.000	V	47.77	32.79	0.09	47.86	32.88	74.00	54.00	-26.14	-21.12	
2483.500	H	48.37	32.69	0.35	48.72	33.04	74.00	54.00	-25.28	-20.96	
2483.500	V	47.03	32.66	0.35	47.38	33.01	74.00	54.00	-26.62	-20.99	
Remark: Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.											

Modulation: TX (GFSK)			Test Result: PASS				Test frequency range: 1-25GHz				
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)		
		PK	AV		PK	AV	PK	AV	PK	AV	
Operation Mode: TX Mode (Low)											
4804	V	46.12	31.12	6.30	52.42	37.42	74.00	54.00	-21.58	-16.58	
7206	V	45.39	30.37	10.44	55.83	40.81	74.00	54.00	-18.17	-13.19	

4804	H	46.64	31.29	6.30	52.94	37.59	74.00	54.00	-21.06	-16.41	
7206	H	45.73	30.51	10.44	56.17	40.95	74.00	54.00	-17.83	-13.05	

Operation Mode: TX Mode (Mid)											
4880	V	45.93	30.95	6.60	52.53	37.55	74.00	54.00	-21.47	-16.45	
7320	V	45.37	30.34	10.55	55.92	40.89	74.00	54.00	-18.08	-13.11	

4880	H	46.42	31.05	6.60	53.02	37.65	74.00	54.00	-20.98	-16.35	
7320	H	45.73	30.55	10.55	56.28	41.10	74.00	54.00	-17.72	-12.90	

Operation Mode: TX Mode (High)											
4960	V	45.34	30.89	6.89	52.23	37.75	74.00	54.00	-21.77	-16.25	
7440	V	45.73	30.85	10.60	56.33	41.45	74.00	54.00	-17.67	-12.55	

4960	H	45.71	30.73	6.89	52.60	37.62	74.00	54.00	-21.40	-16.38	
7440	H	46.51	31.04	10.60	57.11	41.64	74.00	54.00	-16.89	-12.36	

Spurious Emission in restricted band:											
2390.000	H	48.30	32.87	0.09	48.39	32.96	74.00	54.00	-25.61	-21.04	
2390.000	V	48.93	33.29	0.09	49.02	33.38	74.00	54.00	-24.98	-20.62	
2483.500	H	47.68	32.92	0.35	48.03	33.27	74.00	54.00	-25.97	-20.73	
2483.500	V	48.23	33.04	0.35	48.58	33.39	74.00	54.00	-25.42	-20.61	
<p>Remark: Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.</p>											

14.7 Antenna Requirement

STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.247:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

ANTENNA CONNECTED CONSTRUCTION

The antenna is PCB antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 0dBi, Therefore, the antenna is consider meet the requirement.

15. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Mar. 13, 2020	1 Year
2.	Antenna	Schwarzbeck	VULB9162	9162-010	Mar. 23, 2020	1 Year
3.	Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	Mar. 13, 2020	1 Year
4.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Mar. 13, 2020	1 Year
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	101094	Mar. 13, 2020	1 Year
6.	Horn Antenna	Schwarzbeck	BBHA9170	9170-172	Mar. 22, 2019	2 Year
7.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Mar. 13, 2020	1 Year
8.	Horn Antenna	COM-Power	AH-118	071078	Mar. 23, 2020	1 Year
9.	Pre-Amplifier	HP	HP 8449B	3008A00964	Mar. 13, 2020	1 Year
10.	Pre-Amplifier	HP	HP 8447D	1145A00203	Mar. 13, 2020	1 Year
11.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Mar. 23, 2020	1 Year
12.	Test Receiver	Rohde & Schwarz	ESCI	101152	Mar. 14, 2020	1 Year
13.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Mar. 13, 2020	1 Year
14.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Mar. 13, 2020	1 Year
15.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
16.	Chamber	SAEMC	9*7*7m	N/A	Jun. 20, 2019	2 Year
17.	Test Software	EZ	EZ_EMCA	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---