

# FCC PART 15.247

## TEST REPORT

For

### **INMOTION TECHNOLOGIES CO., LTD.**

18F, B1, Nanshan i Park, No.1001 Xueyuan Ave., Nanshan District, Shenzhen, China

**FCC ID: 2ADUSV8**

<b>Report Type:</b> Original Report	<b>Product Type:</b> INMOTION SCV
<b>Test Engineer:</b> Dean Liu	<i>Dean Liu</i>
<b>Report Number:</b> RDG160727003-00A	
<b>Report Date:</b> 2016-08-26	
<b>Reviewed By:</b> Jerry Zhang EMC Manager	<i>Jerry Zhang</i>
<b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY.....	4
TEST FACILITY.....	5
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION.....	6
EQUIPMENT MODIFICATIONS.....	6
EUT EXERCISE SOFTWARE.....	6
BLOCK DIAGRAM OF TEST SETUP.....	6
<b>SUMMARY OF TEST RESULTS</b> .....	<b>7</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1093- RF EXPOSURE</b> .....	<b>8</b>
APPLICABLE STANDARD.....	8
<b>FCC §15.203 - ANTENNA REQUIREMENT</b> .....	<b>9</b>
APPLICABLE STANDARD.....	9
ANTENNA CONNECTOR CONSTRUCTION.....	9
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS</b> .....	<b>10</b>
APPLICABLE STANDARD.....	10
MEASUREMENT UNCERTAINTY.....	10
EUT SETUP.....	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE.....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY.....	12
TEST DATA.....	12
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS</b> .....	<b>15</b>
APPLICABLE STANDARD.....	15
MEASUREMENT UNCERTAINTY.....	15
EUT SETUP.....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP.....	16
TEST PROCEDURE.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY.....	17
TEST DATA.....	17
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH</b> .....	<b>21</b>
APPLICABLE STANDARD.....	21
TEST PROCEDURE.....	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA.....	21
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER</b> .....	<b>24</b>
APPLICABLE STANDARD.....	24

TEST PROCEDURE .....24  
TEST EQUIPMENT LIST AND DETAILS.....24  
TEST DATA .....24

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....27**

APPLICABLE STANDARD .....27  
TEST PROCEDURE .....27  
TEST EQUIPMENT LIST AND DETAILS.....27  
TEST DATA .....27

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....29**

APPLICABLE STANDARD .....29  
TEST PROCEDURE .....29  
TEST EQUIPMENT LIST AND DETAILS.....29  
TEST DATA .....29

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *INMOTION TECHNOLOGIES CO., LTD*'s product, model number: *INMOTION SCV V8 (FCC ID: 2ADUSV8)* (the "EUT") in this report was a *INMOTION SCV*, which was measured approximately: 54 cm (L) x 48 cm (W) x 40 cm (H), rated input voltage: DC74V from rechargeable Lithium-ion battery or DC84V charging from adapter. The highest operation frequency is 2480 MHz.

Adapter Information :

Model: XVE-8400150

Input: 100-240V/AC, 50/60Hz, 2.5A

Output: DC 84V, 1.5A

*Note: The series product, model INMOTION SCV V8, INMOTION SCV V8+, INMOTION SCV V8A, INMOTION SCV V8B, INMOTION SCV V8C, INMOTION SCV V8D, INMOTION SCV V8E, INMOTION SCV V8F, INMOTION SCV V8S are electrically identical, the difference between them is the model name, we selected INMOTION SCV V8 for fully testing, the details was explained in the declaration letter.*

*All measurement and test data in this report was gathered from production sample serial number: 160727003 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-29.*

### Objective

This report is prepared on behalf of *INMOTION TECHNOLOGIES CO., LTD.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

N/A

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

### Equipment Modifications


No modification was made to the EUT tested.

### EUT Exercise Software

Test Software Version	SmartRF Studio 7		
Test Frequency	2402 MHz	2440 MHz	2480 MHz
Power Level	N/A	N/A	N/A

### Block Diagram of Test Setup

AC power line conducted Emissions test:



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

## **FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**

### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### **Measurement Result**

The tune-up power is 2.0 dBm (1.58 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$   
 $= 1.58/50 \cdot (\sqrt{2.480}) = 0.05 < 7.5$

**Note: The minimum distance between antenna and enclosure is 50 mm.**

**So the stand-alone SAR evaluation is not necessary.**



## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has one PCB antenna arrangement and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207

**Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cispr}$

Measurement	$U_{cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

**EUT Setup**



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2016-07-16	2017-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2016-05-06	2017-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**3.1 dB at 0.378019 MHz in the Line conducted mode**

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	27.2 °C
<b>Relative Humidity:</b>	51 %
<b>ATM Pressure:</b>	99.4 kPa

*The testing was performed by Dean Liu on 2016-08-08.*

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.157346	57.2	9.000	L1	10.2	8.4	65.6	Compliance
0.238124	52.7	9.000	L1	10.2	9.5	62.2	Compliance
0.330129	47.6	9.000	L1	10.3	11.8	59.4	Compliance
0.567545	44.9	9.000	L1	10.1	11.1	56.0	Compliance
0.614619	44.7	9.000	L1	10.3	11.3	56.0	Compliance
1.374420	43.3	9.000	L1	10.4	12.7	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.188994	50.1	9.000	L1	10.2	4.0	54.1	Compliance
0.330129	46.0	9.000	L1	10.3	3.4	49.4	Compliance
0.378019	45.2	9.000	L1	10.2	3.1	48.3	Compliance
0.567545	42.8	9.000	L1	10.1	3.2	46.0	Compliance
0.614619	42.7	9.000	L1	10.3	3.3	46.0	Compliance
14.305924	46.2	9.000	L1	10.7	3.8	50.0	Compliance

**AC120 V, 60 Hz, Neutral:**



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.153629	58.7	9.000	N	10.2	7.1	65.8	Compliance
0.188994	52.8	9.000	N	10.2	11.3	64.1	Compliance
0.238124	53.0	9.000	N	10.2	9.2	62.2	Compliance
0.332770	49.6	9.000	N	10.3	9.8	59.4	Compliance
0.567545	45.5	9.000	N	10.1	10.5	56.0	Compliance
0.614619	44.8	9.000	N	10.3	11.2	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.188994	50.5	9.000	N	10.2	3.6	54.1	Compliance
0.332770	46.0	9.000	N	10.3	3.4	49.4	Compliance
0.378019	45.0	9.000	N	10.2	3.3	48.3	Compliance
0.567545	42.6	9.000	N	10.1	3.4	46.0	Compliance
0.614619	42.5	9.000	N	10.3	3.5	46.0	Compliance
14.305924	46.3	9.000	N	10.7	3.7	50.0	Compliance

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

**Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.


Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB.

Table 2 – Values of  $U_{cispr}$


Measurement	$U_{cispr}$
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

**EUT Setup**

**Below 1GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.



## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2016-08-03	2017-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**5.20 dB at 30.0000 MHz in the Vertical polarization**

## Test Data

### Environmental Conditions


<b>Temperature:</b>	26.4 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	99.7 kPa

\* The testing was performed by Dean Liu on 2016-08-22.

Test Mode: Transmitting- (Middle channel) is worst case


1) Below 1GHz

Horizontal



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
30.0000	29.65	QP	0.95	30.60	40.00	9.40
170.6500	39.36	QP	-7.96	31.40	43.50	12.10
203.6300	41.94	QP	-7.74	34.20	43.50	9.30
259.8900	37.71	QP	-7.11	30.60	46.00	15.40
288.0200	34.30	QP	-5.90	28.40	46.00	17.60
323.9100	34.71	QP	-5.41	29.30	46.00	16.70

**Vertical**



Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.0000	33.85	QP	0.95	34.80	40.00	5.20
115.3600	40.86	QP	-6.16	34.70	43.50	8.80
174.5300	39.47	QP	-8.17	31.30	43.50	12.20
288.0200	42.80	QP	-5.90	36.90	46.00	9.10
324.8800	38.49	QP	-5.39	33.10	46.00	12.90
432.5500	32.36	QP	-2.96	29.40	46.00	16.60

2) 1-25GHz:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	60.28	PK	H	25.65	3.66	0.00	89.59	N/A	N/A
2402	59.42	AV	H	25.65	3.66	0.00	88.73	N/A	N/A
2402	63.78	PK	V	25.65	3.66	0.00	93.09	N/A	N/A
2402	62.97	AV	V	25.65	3.66	0.00	92.28	N/A	N/A
2390	24.42	PK	V	25.61	3.63	0.00	53.66	74.00	20.34
2390	13.05	AV	V	25.61	3.63	0.00	42.29	54.00	11.71
4804	36.32	PK	V	30.59	5.06	27.41	44.56	74.00	29.44
4804	32.84	AV	V	30.59	5.06	27.41	41.08	54.00	12.92
7206	32.15	PK	V	34.09	6.61	25.91	46.94	74.00	27.06
7206	27.91	AV	V	34.09	6.61	25.91	42.70	54.00	11.30
3250	36.02	PK	V	28.00	6.31	27.33	43.00	74.00	31.00
3250	23.81	AV	V	28.00	6.31	27.33	30.79	54.00	23.21
Middle Channel: 2440 MHz									
2440	61.68	PK	H	25.74	3.76	0.00	91.18	N/A	N/A
2440	60.93	AV	H	25.74	3.76	0.00	90.43	N/A	N/A
2440	64.99	PK	V	25.74	3.76	0.00	94.49	N/A	N/A
2440	64.39	AV	V	25.74	3.76	0.00	93.89	N/A	N/A
4880	36.82	PK	V	30.79	5.18	27.42	45.37	74.00	28.63
4880	33.46	AV	V	30.79	5.18	27.42	42.01	54.00	11.99
7320	32.65	PK	V	34.37	6.75	25.88	47.89	74.00	26.11
7320	28.45	AV	V	34.37	6.75	25.88	43.69	54.00	10.31
3156	36.68	PK	V	27.70	6.87	27.41	43.84	74.00	30.16
3156	24.38	AV	V	27.70	6.87	27.41	31.54	54.00	22.46
3590	36.33	PK	V	29.00	4.60	27.27	42.66	74.00	31.34
3590	25.57	AV	V	29.00	4.60	27.27	31.90	54.00	22.10
High Channel: 2480 MHz									
2480	62.76	PK	H	25.85	3.68	0.00	92.29	N/A	N/A
2480	62.05	AV	H	25.85	3.68	0.00	91.58	N/A	N/A
2480	65.47	PK	V	25.85	3.68	0.00	95.00	N/A	N/A
2480	64.87	AV	V	25.85	3.68	0.00	94.40	N/A	N/A
2483.5	28.69	PK	V	25.86	3.67	0.00	58.22	74.00	15.78
2483.5	19.15	AV	V	25.86	3.67	0.00	48.68	54.00	5.32
4960	37.14	PK	V	31.00	5.34	27.43	46.05	74.00	27.95
4960	33.78	AV	V	31.00	5.34	27.43	42.69	54.00	11.31
7440	32.93	PK	V	34.66	6.89	25.97	48.51	74.00	25.49
7440	28.71	AV	V	34.66	6.89	25.97	44.29	54.00	9.71
3325	34.85	PK	V	28.24	4.97	27.26	40.80	74.00	33.20
3325	23.89	AV	V	28.24	4.97	27.26	29.84	54.00	24.16


## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	27.2 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	100 kPa


\* The testing was performed by Dean Liu on 2016-08-12.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
Low	2402	0.688	≥0.5
Middle	2440	0.680	≥0.5
High	2480	0.680	≥0.5

BLE Low Channel




Date: 12.AUG.2016 00:16:27

### BLE Middle Channel



Date: 12.AUG.2016 00:18:24

### BLE High Channel



Date: 12.AUG.2016 00:19:58


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	27.2 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	100 kPa

\* The testing was performed by Dean Liu on 2016-08-12.




Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.


Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
Low	2402	1.84	30
Middle	2440	1.90	30
High	2480	1.66	30

Low Channel




Date: 12.AUG.2016 00:17:03

### Middle Channel



Date: 12.AUG.2016 00:18:58

### High Channel



Date: 12.AUG.2016 00:20:34

## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	27.2 °C
<b>Relative Humidity:</b>	49 %
<b>ATM Pressure:</b>	100 kPa

\* *The testing was performed by Dean Liu on 2016-08-12.*

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

### BLE Band Edge, Left Side



Date: 12.AUG.2016 00:17:38

### BLE Band Edge, Right Side



Date: 12.AUG.2016 00:21:09

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	831259/019	2016-07-28	2017-07-27
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-06	2017-05-06

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	27.2 °C
Relative Humidity:	49 %
ATM Pressure:	100 kPa


\* The testing was performed by Dean Liu on 2016-08-12.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-11.05	≤ 8
Middle	2440	-10.53	≤ 8
High	2480	-11.15	≤ 8

Low Channel




Date: 12.AUG.2016 00:17:17

### Middle Channel



Date: 12.AUG.2016 00:19:10

### High Channel



Date: 12.AUG.2016 00:20:47

\*\*\*\*\* END OF REPORT \*\*\*\*\*