



TEST REPORT

Report No. : HST201412-4609-SAR
Product description: Wireless Transmitter
Model/Type : AWX6070B
Applicant's name: H&F TECHNOLOGIES,IN
CORPORATED




RF Exposure Evaluation REPORT

FCCID: 2ADV7AWX6070B

Report Reference No.: HST201412-4609-SAR

Tested by (+ signature):  Yanbin Xing

Review by (+ signature):  Sandy Yu

Approved by (+ signature):  Robin Peng

Date of issue: Jan. 10, 2015

Total number of pages: 8 Pages

Testing Laboratory.....: Guangdong Environment Radiation Monitoring Center.
(Accredited by CNAS, Accredited Number: L5539)
FCC- Registration No: 667318 on on Sep. 29, 2009

Address: No.91, Dongguan Zhuang Road, Guangzhou City, Guangdong Province, China

Applicant's name: H&F TECHNOLOGIES,IN CORPORATED

Address: 650 FLINN AVENUE MOORPARK,CA 93021 USA

Manufacturer's name: Enping Karsect Electronics Co., Ltd

Address: No. F45-1, District F, Foreign and Private Capital Industrial Zone, Enping, Guangdong, China

Test specification.....: Entrusted testing

Standard.....: FCC Part 1.1307, 2.1091, and 2.1093: 2014

Non-standard test method.....: N/A

Test Report Form No.: N/A

Test Report Form(s) Originator ..: N/A

Test item description.....: Wireless Transmitter

Trade Mark.....: Audio 2000's

Model/Type reference: AWX6070B

Ratings: 3.0Vdc 2*AA Batteries

TABLE OF CONTENT

1	Test Summary	3
2	General Information.....	4
2.1	Client Information	4
2.2	General Description of E.U.T.	4
2.3	Details of E.U.T.	4
2.4	Description of Support Units.....	4
2.5	Standards Applicable for Testing	4
2.6	Test Location	5
2.7	Deviation from Standards.....	5
2.8	Abnormalities from Standard Conditions.....	5
3	RF Exposure Evaluation	6
4	Equipments Used during Test.....	8

1 TEST SUMMARY

Test	Test Requirement	Standard Paragraph	Result
Carrier Radiated Power	FCC Part 2.1046	74.861 e) 1) 54–72, 76–88 & 174–216 MHz bands, 50 mW 470–608 and 614–806 MHz bands, 250 mW	PASS*
RF Exposure Evaluation	FCC Part 1.1307, 2.1091, and 2.1093	447498 D01 General RF Exposure Guidance v05r02	PASS

Remark:

♣The EUT has one channel, which is located in the range 614.200 MHz to 697.800MHz.

Only test result of sample of in channels 614.2 MHz, 696.1 MHz and 697.8 MHz were recorded in this report.

2 GENERAL INFORMATION

2.1 Client Information

Applicant: H&F TECHNOLOGIES,IN CORPORATED
 Address of Applicant: 650 FLINN AVENUE MOORPARK,CA 93021 USA

2.2 General Description of E.U.T.

EUT Name: Wireless Transmitter
 Item No.: Listed on the 3rd page
 Serial No.: Not supplied by client

2.3 Details of E.U.T.

Power Supply: 3.0Vdc 2*AA Batteries
 Main Function: Wireless microphone system with an associated receiver for transmitting voice.
 Transmitting Power: Low 614.2MHz: 11.0dBm(i.e.12.59 mW) \pm 1.0 dBm
 Mid. 696.1MHz: 10.8dBm(i.e.12.02 mW) \pm 1.0 dBm
 High 697.8MHz: 10.8dBm(i.e 12.02 mW) \pm 1.0 dBm

The final amplifier Collector Voltage and Collector Current are 0.3V & 3.5mA respectively.

Necessary Bandwidth: $2M+2DK= 2 \times 40 \text{ kHz} + 2 \times 20\text{kHz} \times 1.0 = 120 \text{ kHz}$

16 channels for each microphone; Modulation: F3E; Antenna Type: Fixed; Gained: 0 dBi

2.4 Description of Support Units

Connect the EUT to mains power, and then test the EUT with signal generator.

2.5 Standards Applicable for Testing

The standard used was FCC Part 1.1307, 2.1091, and 2.1093: 2014

The EUT belongs to licensed low power auxiliary devices.

2.6 Test Location

ERP & Spurious Emission tests were subcontracted to the laboratory following-

Guangdong Environment Radiation Monitoring Center.

860, South Guangzhou Avenue, Guangzhou, P.R. China

Tel: 86-20-84281721 Fax: N/A Email: Kevin.ma@nemko.com

FCC- Registration No: 667318 on on Sep. 29, 2009

CNAS- Accreditation No: L5539.

2.7 Deviation from Standards

None.

2.8 Abnormalities from Standard Conditions

None.

3 RF EXPOSURE EVALUATION

Test Requirement: FCC CFR 47 RF Exposure Evaluation

Test Method: 447498 D01 General RF Exposure Guidance v05r02

Test Date: Jan. 13, 2015

Test Procedure:

SAR Test In 447498 D01 General RF Exposure Guidance v05r02 Section
Guidance 4.3.1

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f_{(\text{GHz})}} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{25} \text{ where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁶
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Note:

Max. power of channel, including tune-up tolerance:

Low 614.2MHz: 12.0dBm(i.e.15.85 mW)

Mid. 696.1MHz: 11.8dBm(i.e.15.14 mW)

High 697.8MHz: 11.8dBm(i.e.15.14 mW)

Distance from the antenna to the outer skin = 5 mm

Min. test separation =5 mm

Low channel $F_{(\text{GHz})}=0.6142$ GHz

Mid channel $F_{(\text{GHz})}= 0.6961$ GHz

High channel $F_{(\text{GHz})}=0.6978$ GHz

In low channel: 614.2MHz:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f_{(\text{GHz})}} \right] \cdot$$

$$\begin{aligned} \left[\sqrt{f_{(\text{GHz})}} \right] &= \left[(15.85 / 5) \cdot \sqrt{0.6142} \right] \\ &= 2.484 \\ &\leq 3 \end{aligned}$$

In mid channel: 696.1MHz:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f_{(\text{GHz})}} \right] \cdot$$

$$\begin{aligned} \left[\sqrt{f_{(\text{GHz})}} \right] &= \left[(15.14 / 5) \cdot \sqrt{0.6961} \right] \\ &= 2.526 \\ &\leq 3 \end{aligned}$$

In high channel: 697.8MHz:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \cdot \sqrt{f_{(\text{GHz})}} \right] \cdot$$

$$\begin{aligned} [\sqrt{f_{(GHz)}}] &= [(15.14) / 5]^* (\sqrt{0.6978}) \\ &= 2.529 \\ &\leq 3 \end{aligned}$$

Result: The EUT's SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required.

4 EQUIPMENTS USED DURING TEST

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date	Cal. Due date
1	RF Generator	Rohde & Schwarz	SMB100A-B106	1.031	2014-5-10	2015-5-10
2	Spectrum Analyzer	Rohde & Schwarz	FSP30	EMC0001	2014-1-17	2015-1-17
3	EMI Test Receiver	Rohde & Schwarz	ESCI	EMC1002	2014-2-17	2015-2-17
4	2-Channel Power Meter	Rohde & Schwarz	NRP2	1.033	2014-5-10	2015-5-10
5	Audio Analyzer	Hewlett Packard	8903B	EMC0011	2014-11-5	2015-11-5
6	Power Sensor	Rohde & Schwarz	NRP-Z91	1.034	2014-5-10	2015-5-10
7	Power Sensor	Rohde & Schwarz	NRP-Z91	1.035	2014-5-10	2015-5-10
8	Temperature Chamber	Gongwen	GDS-250	SFT0009	2014-11-5	2015-11-5
9	D.C. Power Supply	KIKUSUI	PAN35-10A	SFT0319	2014-11-5	2015-11-5
10	Temperature Chamber	Gongwen	GDS-250	SFT0009	2014-11-5	2015-11-5
11	D.C. Power Supply	KIKUSUI	PAN35-10A	SFT0319	2014-11-5	2015-11-5
12	Humidity/ Temperature Meter	Anymetre	TH101B	SFT0063	2014-11-5	2015-11-5
13	Barometer	ChangChun	DYM3	SEL0088	2014-6-8	2015-6-8
14	Multimeter	UNI-T	UT70A	EMC0017	2014-11-5	2015-11-5
15	Monopole Antenna	HST	N/A	EMC0089	2014-11-5	2015-11-5
16	Low loss coaxial cable	HST	2 m	EMC1008	2014-11-5	2015-11-5
17	Monopole Antenna	HST	N/A	N/A	2014-11-5	2015-11-5
18	Noise Generator	Ningbo Zhongce	DF1681	EMC0009	2014-11-5	2015-11-5
19	1-18 GHz Antenna	R & S	HF906	1.01	2014-5-10	2015-5-10
20	3m Semi-anechoic Chamber	ABLATROSS	SAC-3	1.001	2014-5-10	2015-5-10
21	EMI Receiver	R & S	ESCI-3	1.002	2014-5-10	2015-5-10
22	Spectrum Analyzer	R & S	FSP30	1.003	2014-5-10	2015-5-10
23	BiConiLog Antenna	SCHWARZBECK	SWB-VULB 9163	1.042	2014-5-10	2015-5-10
24	Pre-amplifier	B & Z TECHNOLOGIES	SCA-SCU18	1.01.1	2014-5-10	2015-5-10
25	Biconical Antenna	SCHWARZBECK	VULB9163	1.011	2014-5-10	2015-5-10

End of report