

FCC Test Report

Report No.: RF161205C08

FCC ID: 2ADWC-AI7697H

Test Model: AI7697H

Received Date: Dec. 05, 2016

Test Date: Jan. 11, 2017 ~ Jan. 24, 2017

Issued Date: Feb. 08, 2017

Applicant: AcSiP Technology Corporation

Address: 3F.-1, No.207, Fusing Rd., Taoyuan Dist., Taoyuan County 330, Taiwan
(R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results.....	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes.....	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	12
3.4.1 Configuration of System under Test	12
3.5 General Description of Applied Standards.....	12
4 Test Types and Results	13
4.1 Radiated Emission and Bandedge Measurement	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement	13
4.1.2 Test Instruments	14
4.1.3 Test Procedures.....	15
4.1.4 Deviation from Test Standard	15
4.1.5 Test Set Up	16
4.1.6 EUT Operating Conditions.....	16
4.1.7 Test Results	17
4.2 Conducted Emission Measurement.....	30
4.2.1 Limits of Conducted Emission Measurement	30
4.2.2 Test Instruments	30
4.2.3 Test Procedures.....	31
4.2.4 Deviation from Test Standard	31
4.2.5 Test Setup.....	31
4.2.6 EUT Operating Conditions.....	31
4.2.7 Test Results	32
4.3 6 dB Bandwidth Measurement.....	34
4.3.1 Limits of 6 dB Bandwidth Measurement.....	34
4.3.2 Test Setup.....	34
4.3.3 Test Instruments	34
4.3.4 Test Procedure	34
4.3.5 Deviation from Test Standard	34
4.3.6 EUT Operating Conditions.....	34
4.3.7 Test Result	35
4.4 Conducted Output Power Measurement	37
4.4.1 Limits of Conducted Output Power Measurement.....	37
4.4.2 Test Setup.....	37
4.4.3 Test Instruments	37
4.4.4 Test Procedures.....	37
4.4.5 Deviation from Test Standard	37
4.4.6 EUT Operating Conditions.....	37
4.4.7 Test Results	38
4.5 Power Spectral Density Measurement	39
4.5.1 Limits of Power Spectral Density Measurement.....	39
4.5.2 Test Setup.....	39
4.5.3 Test Instruments	39
4.5.4 Test Procedure	39
4.5.5 Deviation from Test Standard	39
4.5.6 EUT Operating Condition	39

4.5.7 Test Results	40
4.6 Conducted Out of Band Emission Measurement	42
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	42
4.6.2 Test Setup.....	42
4.6.3 Test Instruments	42
4.6.4 Test Procedure	42
4.6.5 Deviation from Test Standard	42
4.6.6 EUT Operating Condition	42
4.6.7 Test Results	43
5 Pictures of Test Arrangements.....	51
Appendix – Information on the Testing Laboratories	52

Release Control Record

Issue No.	Description	Date Issued
RF161205C08	Original Release	Feb. 08, 2017

1 Certificate of Conformity

Product: 802.11b/g/n IoT Module

Brand: AcSiP

Test Model: AI7697H

Sample Status: Production Unit

Applicant: AcSiP Technology Corporation


Test Date: Jan. 11, 2017 ~ Jan. 24, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




, Date:

Feb. 08, 2017

Rona Chen / Specialist

Approved by :



, Date:

Feb. 08, 2017

Stanley Wu / Assistant Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)

FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -8.95 dB at 0.15391 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.03 dB at 2389.92 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (\pm)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	802.11b/g/n IoT Module
Brand	AcSiP
Test Model	AI7697H
Status of EUT	Production Unit
Power Supply Rating	3.3 Vdc (Host equipment)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
Operating Frequency	2412 ~ 2462 MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	353.997 mW
Antenna Type	PIFA antenna with 2.12 dBi gain
Antenna Connector	N/A
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

1. The PIFA antenna which provided by client is a support unit for test only.
2. Physically, the EUT provides 1 completed transmitter and 1 receiver.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (HT20)	1TX
802.11n (HT40)	1TX

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where	RE\geq1G: Radiated Emission above 1 GHz PLC: Power Line Conducted Emission	RE$<$1G: Radiated Emission below 1 GHz APCM: Antenna Port Conducted Measurement
-------	--	--

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 - Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 - Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11n (HT20)	1 to 11	1	OFDM	BPSK	MCS0

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 - Following channel(s) was (were) selected for the final test as listed below.

The following channel(s) was (were) selected for the final test as listed below:						
EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11n (HT20)	1 to 11	1	OFDM	BPSK	MCS0

Bandedge Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
 - Following channel(s) was (were) selected for the final test as listed below.

The following channel(s) was (were) selected for the final test as listed below:						
EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 11	OFDM	BPSK	MCS0
-	802.11n (HT40)	3 to 9	3, 9	OFDM	BPSK	MCS0

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
-	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Toby Tian
APCM	25 deg. C, 65 % RH	3.3 Vdc	Taylor Liu


3.3 Duty Cycle of Test Signal

802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

802.11g: Duty cycle of test signal is 100 %, duty factor is not required.

802.11n (HT20): Duty cycle of test signal is 100 %, duty factor is not required.


802.11n (HT40): Duty cycle of test signal is 100 %, duty factor is not required.



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).
The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Jun. 21, 2016	Jun. 20, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 16, 2016	Dec. 15, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Dec. 29, 2016	Dec. 28, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Loop Antenna	EM-6879	269	Aug. 11, 2016	Aug. 10, 2017
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 24, 2016	Jun. 23, 2017
Preamplifier Agilent	83017A	MY39501357	Jun. 24, 2016	Jun. 23, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 08, 2016	Sep. 07, 2017
Power Sensor Anritsu	MA2411B	1207325	Sep. 08, 2016	Sep. 07, 2017
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 24, 2016	Jun. 23, 2017
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 24, 2016	Jun. 23, 2017
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The FCC Site Registration No. is 149147.
 5. The IC Site Registration No. is IC7450I-1.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 KHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for RMS Average (Duty cycle < 98 %) for Peak detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

<Frequency Range below 1 GHz>



<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1 GHz Data :

802.11b

EUT Test Condition		Measurement Detail					
Channel	Channel 1	Frequency Range				1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function				Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By				Karl Lee	

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.05	52.25	50.54	54	-1.75	31.8	5.4	35.49	163	357	Average
2386.68	58.72	57.01	74	-15.28	31.8	5.4	35.49	163	357	Peak
2412	112.15	110.38			31.81	5.43	35.47	163	357	Average
2412	114.7	112.93			31.81	5.43	35.47	163	357	Peak
4824	48.39	40.26	54	-5.61	33.97	8.26	34.1	101	70	Average
4824	53.81	45.68	74	-20.19	33.97	8.26	34.1	101	70	Peak

Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.05	46.69	44.98	54	-7.31	31.8	5.4	35.49	201	268	Average
2386.23	54.85	53.14	74	-19.15	31.8	5.4	35.49	201	268	Peak
2412	104.57	102.8			31.81	5.43	35.47	201	268	Average
2412	107.07	105.3			31.81	5.43	35.47	201	268	Peak
4824	47.81	39.68	54	-6.19	33.97	8.26	34.1	102	204	Average
4824	53.61	45.48	74	-20.39	33.97	8.26	34.1	102	204	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail					
Channel		Channel 6			Frequency Range		1 GHz ~ 25 GHz	
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)	
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee	

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.29	54.78	53.07	74	-19.22	31.8	5.4	35.49	160	358	Peak
2399.37	47.99	46.26	54	-6.01	31.8	5.4	35.47	160	358	Average
2437	111.64	109.79			31.85	5.46	35.46	160	358	Average
2437	114.01	112.16			31.85	5.46	35.46	160	358	Peak
2483.56	46.41	44.45	54	-7.59	31.88	5.5	35.42	160	358	Average
2485.28	55.81	53.82	74	-18.19	31.88	5.53	35.42	160	358	Peak
4874	49.67	41.48	54	-4.33	33.98	8.27	34.06	100	69	Average
4874	54.66	46.47	74	-19.34	33.98	8.27	34.06	100	69	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2374.26	53.41	51.75	74	-20.59	31.78	5.37	35.49	197	268	Peak
2388.66	42.45	40.74	54	-11.55	31.8	5.4	35.49	197	268	Average
2437	104.4	102.55			31.85	5.46	35.46	197	268	Average
2437	106.91	105.06			31.85	5.46	35.46	197	268	Peak
2487.08	53.79	51.8	74	-20.21	31.88	5.53	35.42	197	268	Peak
2488.92	43.82	41.81	54	-10.18	31.9	5.53	35.42	197	268	Average
4874	48.69	40.5	54	-5.31	33.98	8.27	34.06	102	204	Average
4874	53.92	45.73	74	-20.08	33.98	8.27	34.06	102	204	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	111.39	109.46			31.87	5.5	35.44	158	358	Average
2462	113.96	112.03			31.87	5.5	35.44	158	358	Peak
2487.04	52.65	50.66	54	-1.35	31.88	5.53	35.42	158	358	Average
2487.08	59.28	57.29	74	-14.72	31.88	5.53	35.42	158	358	Peak
4924	52.84	44.59	54	-1.16	33.99	8.28	34.02	133	67	Average
4924	56.28	48.03	74	-17.72	33.99	8.28	34.02	133	67	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	104.88	102.95			31.87	5.5	35.44	191	268	Average
2462	107.21	105.28			31.87	5.5	35.44	191	268	Peak
2487.04	46.06	44.07	54	-7.94	31.88	5.53	35.42	191	268	Average
2487.08	55.13	53.14	74	-18.87	31.88	5.53	35.42	191	268	Peak
4924	50.34	42.09	54	-3.66	33.99	8.28	34.02	100	209	Average
4924	54.22	45.97	74	-19.78	33.99	8.28	34.02	100	209	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11g

EUT Test Condition			Measurement Detail						
Channel		Channel 1			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.83	66.81	65.08	74	-7.19	31.8	5.4	35.47	163	357	Peak
2389.92	52.47	50.74	54	-1.53	31.8	5.4	35.47	163	357	Average
2412	104.38	102.61			31.81	5.43	35.47	163	357	Average
2412	112.14	110.37			31.81	5.43	35.47	163	357	Peak
4824	38.93	30.8	54	-15.07	33.97	8.26	34.1	175	143	Average
4824	48.09	39.96	74	-25.91	33.97	8.26	34.1	175	143	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.65	57.57	55.86	74	-16.43	31.8	5.4	35.49	201	268	Peak
2389.92	45.57	43.84	54	-8.43	31.8	5.4	35.47	201	268	Average
2412	97.05	95.28			31.81	5.43	35.47	201	268	Average
2412	104.57	102.8			31.81	5.43	35.47	201	268	Peak
4824	38.67	30.54	54	-15.33	33.97	8.26	34.1	128	163	Average
4824	47.51	39.38	74	-26.49	33.97	8.26	34.1	128	163	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2383.62	54.72	53.03	74	-19.28	31.78	5.4	35.49	160	358	Peak
2389.83	45.14	43.41	54	-8.86	31.8	5.4	35.47	160	358	Average
2437	107.18	105.33			31.85	5.46	35.46	160	358	Average
2437	114.74	112.89			31.85	5.46	35.46	160	358	Peak
2483.56	47.19	45.23	54	-6.81	31.88	5.5	35.42	160	358	Average
2489	56.21	54.2	74	-17.79	31.9	5.53	35.42	160	358	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2385.96	52.7	50.99	74	-21.3	31.8	5.4	35.49	197	268	Peak
2388.75	42.29	40.58	54	-11.71	31.8	5.4	35.49	197	268	Average
2437	100.13	98.28			31.85	5.46	35.46	197	268	Average
2437	107.76	105.91			31.85	5.46	35.46	197	268	Peak
2486.36	43.67	41.68	54	-10.33	31.88	5.53	35.42	197	268	Average
2490.04	53.42	51.41	74	-20.58	31.9	5.53	35.42	197	268	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	103.49	101.56			31.87	5.5	35.44	158	358	Average
2462	111.1	109.17			31.87	5.5	35.44	158	358	Peak
2483.56	52.15	50.19	54	-1.85	31.88	5.5	35.42	158	358	Average
2483.8	64.63	62.67	74	-9.37	31.88	5.5	35.42	158	358	Peak
4924	38.69	30.44	54	-15.31	33.99	8.28	34.02	127	115	Average
4924	48.95	40.7	74	-25.05	33.99	8.28	34.02	127	115	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	96.95	95.02			31.87	5.5	35.44	191	268	Average
2462	104.7	102.77			31.87	5.5	35.44	191	268	Peak
2483.6	46.18	44.22	54	-7.82	31.88	5.5	35.42	191	268	Average
2483.6	59.12	57.16	74	-14.88	31.88	5.5	35.42	191	268	Peak
4924	38.28	30.03	54	-15.72	33.99	8.28	34.02	132	211	Average
4924	47.83	39.58	74	-26.17	33.99	8.28	34.02	132	211	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11n (HT20)

EUT Test Condition			Measurement Detail						
Channel		Channel 1			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.83	67.27	65.54	74	-6.73	31.8	5.4	35.47	163	357	Peak
2389.92	52.97	51.24	54	-1.03	31.8	5.4	35.47	163	357	Average
2412	103.32	101.55			31.81	5.43	35.47	163	357	Average
2412	111.98	110.21			31.81	5.43	35.47	163	357	Peak
4824	38.43	30.3	54	-15.57	33.97	8.26	34.1	161	108	Average
4824	47.78	39.65	74	-26.22	33.97	8.26	34.1	161	108	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.83	45.5	43.77	54	-8.5	31.8	5.4	35.47	201	268	Average
2389.92	59.25	57.52	74	-14.75	31.8	5.4	35.47	201	268	Peak
2412	96.08	94.31			31.81	5.43	35.47	201	268	Average
2412	104.47	102.7			31.81	5.43	35.47	201	268	Peak
4824	38.35	30.22	54	-15.65	33.97	8.26	34.1	131	185	Average
4824	47.28	39.15	74	-26.72	33.97	8.26	34.1	131	185	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 6		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2387.31	55.03	53.32	74	-18.97	31.8	5.4	35.49	160	358	Peak
2389.92	45	43.27	54	-9	31.8	5.4	35.47	160	358	Average
2437	105.57	103.72			31.85	5.46	35.46	160	358	Average
2437	113.01	111.16			31.85	5.46	35.46	160	358	Peak
2483.64	47.09	45.13	54	-6.91	31.88	5.5	35.42	160	358	Average
2489.04	56.31	54.3	74	-17.69	31.9	5.53	35.42	160	358	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2388.57	42.25	40.54	54	-11.75	31.8	5.4	35.49	197	268	Average
2389.11	52.56	50.85	74	-21.44	31.8	5.4	35.49	197	268	Peak
2437	98.71	96.86			31.85	5.46	35.46	197	268	Average
2437	106.96	105.11			31.85	5.46	35.46	197	268	Peak
2484.56	43.91	41.92	54	-10.09	31.88	5.53	35.42	197	268	Average
2487.8	53.29	51.28	74	-20.71	31.9	5.53	35.42	197	268	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	102.37	100.44			31.87	5.5	35.44	158	358	Average
2462	109.81	107.88			31.87	5.5	35.44	158	358	Peak
2483.56	67.1	65.14	74	-6.9	31.88	5.5	35.42	158	358	Peak
2483.76	52.26	50.3	54	-1.74	31.88	5.5	35.42	158	358	Average
4924	39.36	31.11	54	-14.64	33.99	8.28	34.02	169	143	Average
4924	48.23	39.98	74	-25.77	33.99	8.28	34.02	169	143	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2462	95.81	93.88			31.87	5.5	35.44	191	268	Average
2462	103.81	101.88			31.87	5.5	35.44	191	268	Peak
2483.64	46.21	44.25	54	-7.79	31.88	5.5	35.42	191	268	Average
2484.24	58.17	56.18	74	-15.83	31.88	5.53	35.42	191	268	Peak
4924	39.23	30.98	54	-14.77	33.99	8.28	34.02	118	236	Average
4924	48.45	40.2	74	-25.55	33.99	8.28	34.02	118	236	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11n (HT40)

EUT Test Condition			Measurement Detail						
Channel		Channel 3			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2388.66	65.54	63.83	74	-8.46	31.8	5.4	35.49	160	357	Peak
2389.83	52.62	50.89	54	-1.38	31.8	5.4	35.47	160	357	Average
2422	98.22	96.42			31.83	5.43	35.46	160	357	Average
2422	105.83	104.03			31.83	5.43	35.46	160	357	Peak
2483.56	46.26	44.3	54	-7.74	31.88	5.5	35.42	160	357	Average
2488.36	54.79	52.78	74	-19.21	31.9	5.53	35.42	160	357	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.38	44.89	43.18	54	-9.11	31.8	5.4	35.49	219	268	Average
2389.38	56.49	54.78	74	-17.51	31.8	5.4	35.49	219	268	Peak
2422	90.75	88.95			31.83	5.43	35.46	219	268	Average
2422	98.35	96.55			31.83	5.43	35.46	219	268	Peak
2485.64	44.34	42.35	54	-9.66	31.88	5.53	35.42	219	268	Average
2492.56	52.09	50.07	74	-21.91	31.9	5.53	35.41	219	268	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2422 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail					
Channel		Channel 6			Frequency Range		1 GHz ~ 25 GHz	
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)	
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee	

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.65	58.44	56.73	74	-15.56	31.8	5.4	35.49	178	360	Peak
2389.92	47.09	45.36	54	-6.91	31.8	5.4	35.47	178	360	Average
2437	101.16	99.31			31.85	5.46	35.46	178	360	Average
2437	108.89	107.04			31.85	5.46	35.46	178	360	Peak
2483.68	61.77	59.81	74	-12.23	31.88	5.5	35.42	178	360	Peak
2484.12	51.07	49.11	54	-2.93	31.88	5.5	35.42	178	360	Average
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2387.67	55.13	53.42	74	-18.87	31.8	5.4	35.49	197	268	Peak
2389.47	44.9	43.19	54	-9.1	31.8	5.4	35.49	197	268	Average
2437	93.93	92.08			31.85	5.46	35.46	197	268	Average
2437	102.29	100.44			31.85	5.46	35.46	197	268	Peak
2484.04	45.88	43.92	54	-8.12	31.88	5.5	35.42	197	268	Average
2485	55	53.01	74	-19	31.88	5.53	35.42	197	268	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 9		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2382.63	52.84	51.15	74	-21.16	31.78	5.4	35.49	158	358	Peak
2388.66	43.54	41.83	54	-10.46	31.8	5.4	35.49	158	358	Average
2452	98.62	96.75			31.85	5.46	35.44	158	358	Average
2452	106.36	104.49			31.85	5.46	35.44	158	358	Peak
2484.24	52.54	50.55	54	-1.46	31.88	5.53	35.42	158	358	Average
2485.28	63.81	61.82	74	-10.19	31.88	5.53	35.42	158	358	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2349.24	52.29	50.72	74	-21.71	31.74	5.33	35.5	173	268	Peak
2358.96	42.08	40.45	54	-11.92	31.76	5.37	35.5	173	268	Average
2452	91.22	89.35			31.85	5.46	35.44	173	268	Average
2452	98.75	96.88			31.85	5.46	35.44	173	268	Peak
2483.68	57.64	55.68	74	-16.36	31.88	5.5	35.42	173	268	Peak
2485.68	47.39	45.4	54	-6.61	31.88	5.53	35.42	173	268	Average

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2452 MHz: Fundamental frequency.

9 kHz ~ 30 MHz DATA:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz WORST-CASE DATA:

802.11n (HT20)

EUT Test Condition		Measurement Detail					
Channel	Channel 1	Frequency Range			30 MHz ~ 1 GHz		
Input Power	120 Vac, 60 Hz	Detector Function			Peak (PK) Quasi-peak (QP)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By			Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
106.41	29.09	50.55	43.5	-14.41	9.51	1.28	32.25	127	144	Peak
169.86	9.43	30.15	43.5	-34.07	10	1.52	32.24	168	203	Peak
264.63	20.06	36.82	46	-25.94	13.41	1.94	32.11	195	127	Peak
389.6	17.66	30.16	46	-28.34	17.35	2.34	32.19	135	116	Peak
642.3	21.15	28.22	46	-24.85	22.1	2.99	32.16	185	117	Peak
882.4	26.29	29.51	46	-19.71	24.88	3.49	31.59	196	158	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
101.01	13.58	34.88	43.5	-29.92	9.68	1.28	32.26	132	174	Peak
189.57	20.47	40.71	43.5	-23.03	10.4	1.61	32.25	165	120	Peak
234.66	16.75	34.75	46	-29.25	12.31	1.85	32.16	147	265	Peak
428.8	17.79	29.81	46	-28.21	17.75	2.41	32.18	185	126	Peak
794.2	23.82	28.39	46	-22.18	24.23	3.27	32.07	159	127	Peak
915.3	30.92	33.04	46	-15.08	25.72	3.53	31.37	179	125	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 21, 2016	Nov. 20, 2017
RF signal cable Woken	5D-FB	Cable-cond1-01	Dec. 22, 2016	Dec. 21, 2017
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2016	Feb. 25, 2017
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 28, 2016	Jul. 27, 2017
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.


4.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2017/1/24

No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.12	46.72	32.23	56.84	42.35	65.79	55.79	-8.95	-13.44
2	0.16526	10.12	44.78	30.67	54.90	40.79	65.20	55.20	-10.30	-14.41
3	0.19305	10.14	37.08	22.49	47.22	32.63	63.90	53.90	-16.68	-21.27
4	0.22038	10.14	33.63	20.94	43.77	31.08	62.80	52.80	-19.03	-21.72
5	0.27512	10.15	29.15	17.38	39.30	27.53	60.96	50.96	-21.66	-23.43
6	3.18807	10.32	24.57	19.04	34.89	29.36	56.00	46.00	-21.11	-16.64

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2017/1/24

Phase Of Power : Neutral (N)

No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.12	39.81	25.39	49.93	35.51	66.00	56.00	-16.07	-20.49
2	0.17374	10.14	34.15	20.74	44.29	30.88	64.78	54.78	-20.49	-23.90
3	0.20084	10.15	28.81	16.19	38.96	26.34	63.58	53.58	-24.62	-27.24
4	0.22024	10.15	27.74	16.76	37.89	26.91	62.81	52.81	-24.92	-25.90
5	0.29076	10.16	22.70	12.77	32.86	22.93	60.50	50.50	-27.64	-27.57
6	3.07077	10.33	21.09	15.39	31.42	25.72	56.00	46.00	-24.58	-20.28

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 6 dB Bandwidth Measurement

4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	9.61	0.5	Pass
6	2437	9.61	0.5	Pass
11	2462	9.58	0.5	Pass

802.11g


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.10	0.5	Pass
6	2437	16.34	0.5	Pass
11	2462	16.37	0.5	Pass

802.11n (HT20)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.52	0.5	Pass
6	2437	17.57	0.5	Pass
11	2462	17.34	0.5	Pass

802.11n (HT40)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
3	2422	35.47	0.5	Pass
6	2437	35.72	0.5	Pass
9	2452	35.87	0.5	Pass




4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 Test Results

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	226.464	23.55	30	Pass
6	2437	247.172	23.93	30	Pass
11	2462	161.065	22.07	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	219.786	23.42	30	Pass
6	2437	353.997	25.49	30	Pass
11	2462	231.206	23.64	30	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	212.814	23.28	30	Pass
6	2437	322.849	25.09	30	Pass
11	2462	205.116	23.12	30	Pass

802.11n (HT40)


Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
3	2422	132.434	21.22	30	Pass
6	2437	233.346	23.68	30	Pass
9	2452	130.317	21.15	30	Pass

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW $\geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

802.11b

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
1	2412	-1.68	8	Pass
6	2437	-0.75	8	Pass
11	2462	-2.64	8	Pass

802.11g


Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
1	2412	-11.23	8	Pass
6	2437	-6.22	8	Pass
11	2462	-11.09	8	Pass

802.11n (HT20)

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
1	2412	-10.99	8	Pass
6	2437	-7.95	8	Pass
11	2462	-11.35	8	Pass

802.11n (HT40)

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Pass / Fail
3	2422	-16.51	8	Pass
6	2437	-13.31	8	Pass
9	2452	-16.99	8	Pass




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.


4.6.6 EUT Operating Condition


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.







4.6.7 Test Results


The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.

802.11b







802.11g
Ch 1

Ch 6

Ch 11






802.11n (HT20)



Ch 1




Ch 6




Ch 11






802.11n (HT40)


Ch 3




Ch 6



Ch 9





5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---