

# RF Exposure Evaluation Report

**Product** : Pulse Oximeter  
**Trade mark** : N/A  
**Model/Type reference** : PO2  
**Serial Number** : N/A  
**Report Number** : EED32M00325602  
**FCC ID** : 2ADXK-8326  
**Date of Issue** : Nov. 09, 2020  
**Test Standards** : 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF  
Exposure Guidance v06  
**Test result** : PASS

Prepared for:

**Shenzhen Viatom Technology Co., Ltd.**  
**4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road,**  
**Baoan District, Shenzhen, China.**

Prepared by:

**Centre Testing International Group Co., Ltd.**  
**Hongwei Industrial Zone, Bao'an 70 District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Compiled by:

*Sunlight Sun*

Sunlight Sun

Reviewed by:

*Ware Xin*

Ware Xin

Approved by:

*Aaron Ma*

Aaron Ma

Date:

Nov. 09, 2020



Check No.: 3970366882

## 2 Version

Version No.	Date	Description
00	Nov. 09, 2020	Original

### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 VERSION</b> .....	<b>2</b>
<b>3 CONTENTS</b> .....	<b>3</b>
<b>4 GENERAL INFORMATION</b> .....	<b>4</b>
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
<b>5 SAR EVALUATION</b> .....	<b>6</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 EUT RF Exposure.....	7
<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b> .....	<b>8</b>

## 4 General Information

### 4.1 Client Information

Applicant:	Shenzhen Viatom Technology Co., Ltd.
Address of Applicant:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.
Manufacturer:	Shenzhen Viatom Technology Co., Ltd.
Address of Manufacturer:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.
Factory:	Shenzhen Viatom Technology Co., Ltd.
Address of Factory:	4E, 3#, Tingwei Industrial Park, Honglang North 2nd Road, Baoan District, Shenzhen, China.

### 4.2 General Description of EUT

Product Name:	Pulse Oximeter
Model No.(EUT):	PO2
Trade Mark:	N/A
EUT Supports Radios application:	2402MHz to 2480MHz

### 4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK
Test Power Grade:	Default
Test Software of EUT:	DTM Tester
Antenna Type:	Chip antenna
Antenna Gain:	3.45dBi
Power Supply:	DC 5V
Max Conducted Peak Output Power:	-11.247 dBm
Sample Received Date:	Oct. 24, 2020
Sample tested Date:	Oct. 24, 2020 to Nov. 5, 2020
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

#### **4.4 Test Location**

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

#### **4.5 Deviation from Standards**

None.

#### **4.6 Abnormalities from Standard Conditions**

None.

#### **4.7 Other Information Requested by the Customer**

None.

## 5 SAR Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 5.1.2 EUT RF Exposure

The Max Conducted Peak Output Power is -11.247dBm in highest channel(2.480GHz);

The best case gain of the antenna is 3.45dBi.

EIRP= -11.247dBm + 3.45dBi = -7.797dBm

-7.797dBm logarithmic terms convert to numeric result is nearly 0.17mW

According to the formula. calculate the EIRP test result:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}]$

General RF Exposure =  $(0.17\text{mW} / 5 \text{ mm}) \times \sqrt{2.480\text{GHz}} = 0.1$  ①

SAR requirement:

S= 3.0 ② ;

① < ②.

So the SAR report is not required.

## PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32M00325601 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

\*\*\* End of Report \*\*\*