

# FCC ID: 2ADXM8B012BT

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz.

We used a distance 50mm to calculated

Maximum measured transmitter power:

Transmit Frequency (GHz)	Mode	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Result calculation	1-g SAR
2.402	GFSK	-0.210	-0.5±1	0.5	0.348	3.0
2.441	GFSK	-0.129	-0.5±1	0.5	0.350	3.0
2.480	GFSK	-1.368	-0.5±1	0.5	0.353	3.0
2.402	1/4Π-DQPSK	0.843	0.0±1	1.0	0.390	3.0
2.441	1/4Π-DQPSK	0.948	0.0±1	1.0	0.393	3.0
2.480	1/4Π-DQPSK	-0.289	0.0±1	1.0	0.397	3.0
2.402	8DPSK	1.236	1.0±1	2.0	0.491	3.0
2.441	8DPSK	1.364	1.0±1	2.0	0.495	3.0
2.480	8DPSK	0.113	1.0±1	2.0	0.499	3.0

### **Conclusion:**

For the max result :  $0.499 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

SHENZHEN EMTEK CO., LTD.



Lisa Wang/EMC Manager