

# TEST REPORT

**Reference No.**..... : WTS19S12086451W002 V1  
**FCC ID** ..... : 2ADYY-CD8  
**Applicant**..... : TECNO MOBILE LIMITED  
**Address**..... : ROOM 604 6/F SOUTH TOWER WORLD, FINANCE CTR HARBOUR CITY 17 CANTON ROAD TST KL, Hong Kong  
**Manufacturer** ..... : SHENZHEN TECNO TECHNOLOGY CO.,LTD.  
**Address**..... : 101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R. China  
**Product**..... : Mobile Phone  
**Model(s)** ..... : CD8  
**Brand Name**..... : TECNO  
**Standards**..... : FCC CFR47 Part 15.247:2018  
**Date of Receipt sample** .... : 2019-12-11  
**Date of Test** ..... : 2019-12-12 to 2019-12-23  
**Date of Issue**..... : 2019-12-30  
**Test Result**..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

*Ford Wang*

Ford Wang / Project Engineer

Approved by:



*Philo Zhong*

Philo Zhong / Manager

## 2 Contents

	<b>Page</b>
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 CONTENTS .....</b>	<b>2</b>
<b>3 REVISION HISTORY .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION.....</b>	<b>5</b>
4.1 GENERAL DESCRIPTION OF E.U.T. ....	5
4.2 DETAILS OF E.U.T. ....	5
4.3 CHANNEL LIST.....	6
4.4 TEST MODE.....	6
4.5 TEST FACILITY.....	6
<b>5 TEST SUMMARY .....</b>	<b>7</b>
<b>6 EQUIPMENT USED DURING TEST .....</b>	<b>8</b>
6.1 EQUIPMENTS LIST .....	8
6.2 DESCRIPTION OF SUPPORT UNITS .....	9
6.3 MEASUREMENT UNCERTAINTY .....	9
6.4 TEST EQUIPMENT CALIBRATION .....	9
<b>7 CONDUCTED EMISSION .....</b>	<b>10</b>
7.1 E.U.T. OPERATION .....	10
7.2 EUT SETUP.....	10
7.3 MEASUREMENT DESCRIPTION .....	10
7.4 CONDUCTED EMISSION TEST RESULT .....	11
<b>8 RADIATED SPURIOUS EMISSIONS.....</b>	<b>13</b>
8.1 EUT OPERATION.....	13
8.2 TEST SETUP .....	14
8.3 SPECTRUM ANALYZER SETUP .....	15
8.4 TEST PROCEDURE .....	16
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	16
8.6 SUMMARY OF TEST RESULTS .....	17
<b>9 CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>20</b>
9.1 TEST PROCEDURE .....	20
9.2 TEST RESULT .....	21
<b>10 BAND EDGE MEASUREMENT .....</b>	<b>31</b>
10.1 TEST PROCEDURE.....	31
10.2 TEST RESULT .....	32
<b>11 20 DB BANDWIDTH MEASUREMENT .....</b>	<b>38</b>
11.1 TEST PROCEDURE.....	38
11.2 TEST RESULT .....	38
<b>12 MAXIMUM PEAK OUTPUT POWER .....</b>	<b>44</b>
12.1 TEST PROCEDURE.....	44
12.2 TEST RESULT .....	45
<b>13 HOPPING CHANNEL SEPARATION .....</b>	<b>51</b>
13.1 TEST PROCEDURE.....	51
13.2 TEST RESULT .....	52
<b>14 NUMBER OF HOPPING FREQUENCY.....</b>	<b>58</b>
14.1 TEST PROCEDURE.....	58

14.2	TEST RESULT .....	59
<b>15</b>	<b>DWELL TIME .....</b>	<b>61</b>
15.1	TEST PROCEDURE.....	61
15.2	TEST RESULT .....	61
<b>16</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>67</b>
<b>17</b>	<b>RF EXPOSURE.....</b>	<b>68</b>
<b>18</b>	<b>PHOTOGRAPHS OF TEST SETUP AND EUT.....</b>	<b>69</b>

### 3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS19S12086 451W002	2019-12-11	2019-12-12 to 2019-12- 23	2019-12-23	original	-	Replaced
WTS19S12086 451W002 V1	2019-12-11	2019-12-12 to 2019-12- 23	2019-12-30	Version 1	Updated	Valid

## 4 General Information

### 4.1 General Description of E.U.T.

Product:	Mobile Phone
Model(s):	CD8
Model Description:	N/A
GSM Band(s):	GSM 850/900/1800/1900MHz
GPRS/EGPRS Class:	12
WCDMA Band(s):	FDD Band II/IV/V
LTE Band(s):	FDD Band 2/4/5/7
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/ n(HT20/40)/ac(HT20/40/80)
Bluetooth Version:	Bluetooth v4.0 with BLE
GPS:	Support
NFC:	N/A
Hardware Version:	V1.3
Software Version:	CD8-H655SBC-Q-191121V104
Highest frequency (Exclude Radio):	26MHz
Storage Location:	Internal Storage
Note:	N/A

### 4.2 Details of E.U.T.

Operation Frequency:	Bluetooth: 2402~2480MHz
Max. RF output power:	Bluetooth: 6.99dBm
Type of Modulation:	Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK
Antenna installation:	Bluetooth: internal permanent antenna
Antenna Gain:	Bluetooth: 1.5dBi
Ratings:	Battery DC 3.85V, 3900mAh DC 5V, 2.0A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.35A)
Adapter:	Manufacturer: Dongguan Aohai Power Technology CO.,LTD Model No.: A8A-050200U-US1

### 4.3 Channel List

Normal

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	-	-

### 4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests; the worst data were recorded and reported.

Test mode	Low channel	Middle channel	High channel
Transmitting	2402MHz	2441MHz	2480MHz

### 4.5 Test Facility

The test facility has a test site registered with the following organizations:

**ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

**FCC Designation No.: CN1201. Test Firm Registration No.: 523476.**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

## 5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious emissions	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
Conducted Emission	15.207	PASS
20dB Bandwidth	15.247(a)(1)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Frequency Separation	15.247(a)(1)	PASS
Number of Hopping Frequency	15.247(a)(1)(iii)	PASS
Dwell time	15.247(a)(1)(iii)	PASS
Antenna Requirement	15.203	Complies
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

## 6 Equipment Used during Test

### 6.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2019-09-12	2020-09-11
2.	LISN	R&S	ENV216	101215	2019-09-12	2020-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2019-09-12	2020-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2019-09-12	2020-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2019-09-12	2020-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2019-09-12	2020-09-11
4.	Cable	LARGE	RF300	-	2019-09-12	2020-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2019-04-29	2020-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2019-04-09	2020-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2019-04-09	2020-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2019-09-12	2020-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2019-04-09	2020-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2019-04-09	2020-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2019-04-13	2020-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2019-04-13	2020-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2019-04-13	2020-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2019-04-09	2020-04-08
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2019-04-13	2020-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2019-04-13	2020-04-12



RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2019-09-12	2020-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2019-09-12	2020-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2019-09-12	2020-09-11

## 6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

## 6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	$\pm 3.64$ dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	$\pm 5.08$ dB (Bilog antenna 30M~1000MHz)
	$\pm 4.99$ dB (Horn antenna 1000M~25000MHz)
Radio Frequency	$\pm 1 \times 10^{-7}$ Hz
RF Power	$\pm 0.42$ dB
Dwell time	1.0%
Conducted Spurious Emissions	$\pm 2.76$ dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

## 6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

## 7 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2013
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	

Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

### 7.1 E.U.T. Operation

Operating Environment :


Temperature:	22.8 °C
Humidity:	52.6 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in TX Transmitting mode, the test data were shown in the report.

### 7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10: 2013.




### 7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

## 7.4 Conducted Emission Test Result


Remark: only the worst data (GFSK modulation Low channel mode) were reported

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1700	36.83	9.78	46.61	64.96	-18.35	QP	
2	0.1700	24.29	9.78	34.07	54.96	-20.89	AVG	
3	0.2610	33.58	9.77	43.35	61.40	-18.05	QP	
4	0.2610	20.98	9.77	30.75	51.40	-20.65	AVG	
5	0.4140	30.20	9.83	40.03	57.57	-17.54	QP	
6	0.4140	19.44	9.83	29.27	47.57	-18.30	AVG	
7	0.5140	29.19	9.81	39.00	56.00	-17.00	QP	
8	0.5140	19.30	9.81	29.11	46.00	-16.89	AVG	
9	1.8710	33.46	9.94	43.40	56.00	-12.60	QP	
10	1.8710	19.37	9.94	29.31	46.00	-16.69	AVG	
11	6.5220	34.54	10.10	44.64	60.00	-15.36	QP	
12	6.5220	20.18	10.10	30.28	50.00	-19.72	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1740	39.37	9.78	49.15	64.76	-15.61	QP	
2	0.1740	22.58	9.78	32.36	54.76	-22.40	AVG	
3	0.2580	36.14	9.77	45.91	61.49	-15.58	QP	
4	0.2580	21.42	9.77	31.19	51.49	-20.30	AVG	
5	0.3420	33.15	9.80	42.95	59.15	-16.20	QP	
6	0.3420	18.85	9.80	28.65	49.15	-20.50	AVG	
7	0.5180	32.86	9.82	42.68	56.00	-13.32	QP	
8	0.5180	17.73	9.82	27.55	46.00	-18.45	AVG	
9	2.0000	32.34	9.96	42.30	56.00	-13.70	QP	
10	2.0000	21.04	9.96	31.00	46.00	-15.00	AVG	
11	3.1819	35.43	9.93	45.36	56.00	-10.64	QP	
12	3.1819	22.94	9.93	32.87	46.00	-13.13	AVG	

## 8 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.205 &15.209 & 15.247

Test Method: ANSI C63.10: 2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

### 8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX Transmitting mode, the test data were shown in the report.


## 8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto  
 IF Bandwidth..... 10kHz  
 Video Bandwidth..... 10kHz  
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto  
 Detector ..... PK  
 Resolution Bandwidth..... 100kHz  
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed ..... Auto  
 Detector ..... PK  
 Resolution Bandwidth..... 1MHz  
 Video Bandwidth..... 3MHz  
 Detector ..... Ave.  
 Resolution Bandwidth..... 1MHz  
 Video Bandwidth..... 10Hz

## 8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.

## 8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$



## 8.6 Summary of Test Results

### Test Frequency: 9KHz~30MHz

Remark: only the worst data (GFSK modulation Low channel mode) were reported

Frequency	Measurement results dB $\mu$ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB $\mu$ V/m @30m	Limits dB $\mu$ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.021	25.12	QP	21.84	40.00	6.96	29.54	-22.58
15.730	24.85	QP	21.35	40.00	6.20	29.54	-23.34
25.680	25.33	QP	20.67	40.00	6.00	29.54	-23.54

### Test Frequency: 30MHz ~ 8GHz

Remark: only the worst data (GFSK modulation mode) were reported.

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB $\mu$ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)
GFSK Low Channel									
268.32	36.56	QP	124	1.0	H	-13.35	23.21	46.00	-22.79
268.32	42.10	QP	54	1.1	V	-13.35	28.75	46.00	-17.25
4804.00	46.21	PK	38	1.7	V	-1.06	45.15	74.00	-28.85
4804.00	43.83	Ave	38	1.7	V	-1.06	42.77	54.00	-11.23
7206.00	40.86	PK	254	2.0	H	1.33	42.19	74.00	-31.81
7206.00	35.35	Ave	254	2.0	H	1.33	36.68	54.00	-17.32
2326.89	45.32	PK	244	1.9	V	-13.19	32.13	74.00	-41.87
2326.89	38.26	Ave	244	1.9	V	-13.19	25.07	54.00	-28.93
2374.06	42.24	PK	281	1.1	H	-13.14	29.10	74.00	-44.90
2374.06	36.21	Ave	281	1.1	H	-13.14	23.07	54.00	-30.93
2488.55	43.80	PK	101	1.2	V	-13.08	30.72	74.00	-43.28
2488.55	36.09	Ave	101	1.2	V	-13.08	23.01	54.00	-30.99

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB $\mu$ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)
GFSK Middle Channel									
268.32	36.34	QP	67	1.5	H	-13.35	22.99	46.00	-23.01
268.32	43.50	QP	220	1.7	V	-13.35	30.15	46.00	-15.85
4882.00	46.77	PK	213	1.9	V	-0.62	46.15	74.00	-27.85
4882.00	42.76	Ave	213	1.9	V	-0.62	42.14	54.00	-11.86
7323.00	42.16	PK	138	1.4	H	2.21	44.37	74.00	-29.63
7323.00	36.00	Ave	138	1.4	H	2.21	38.21	54.00	-15.79
2343.79	45.76	PK	237	1.1	V	-13.19	32.57	74.00	-41.43
2343.79	37.26	Ave	237	1.1	V	-13.19	24.07	54.00	-29.93
2375.27	43.46	PK	264	1.5	H	-13.14	30.32	74.00	-43.68
2375.27	37.24	Ave	264	1.5	H	-13.14	24.10	54.00	-29.90
2488.76	44.86	PK	99	1.2	V	-13.08	31.78	74.00	-42.22
2488.76	37.52	Ave	99	1.2	V	-13.08	24.44	54.00	-29.56

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB $\mu$ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)
GFSK High Channel									
268.32	35.59	QP	189	1.8	H	-13.35	22.24	46.00	-23.76
268.32	43.64	QP	290	1.0	V	-13.35	30.29	46.00	-15.71
4960.00	46.67	PK	67	2.0	V	-0.24	46.43	74.00	-27.57
4960.00	44.19	Ave	67	2.0	V	-0.24	43.95	54.00	-10.05
7440.00	42.96	PK	226	1.5	H	2.84	45.80	74.00	-28.20
7440.00	34.79	Ave	226	1.5	H	2.84	37.63	54.00	-16.37
2338.69	46.02	PK	237	1.2	V	-13.19	32.83	74.00	-41.17
2338.69	38.56	Ave	237	1.2	V	-13.19	25.37	54.00	-28.63
2354.79	43.46	PK	283	1.2	H	-13.14	30.32	74.00	-43.68
2354.79	37.74	Ave	283	1.2	H	-13.14	24.60	54.00	-29.40
2487.47	42.67	PK	206	2.0	V	-13.08	29.59	74.00	-44.41
2487.47	36.71	Ave	206	2.0	V	-13.08	23.63	54.00	-30.37

**Test Frequency: 8GHz~25GHz**

The measurements were more than 20 dB below the limit and not recorded

## 9 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. Set the spectrum analyzer:

Below 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold

### 9.2 Test Result


9KHz - 30MHz

GFSK


Low Channel



Middle Channel




### High Channel




### Pi/4QPSK


#### Low Channel



### Middle Channel




### High Channel




### 8DPSK

#### Low Channel




#### Middle Channel






### High Channel



30MHz – 25GHz  
GFSK Low Channel

Fundamental



GFSK Middle Channel

Fundamental




### GFSK High Channel

Fundamental



### Pi/4 DQPSK Low Channel

Fundamental



Pi/4 DQPSK Middle Channel

Fundamental



Pi/4 DQPSK High Channel

Fundamental



### 8DPSK Low Channel

Fundamental



### 8DPSK Middle Channel

Fundamental



### 8DPSK High Channel

Fundamental





## 10 Band Edge Measurement

Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: 2013
Test Limit:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

### 10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold

### 10.2 Test Result







GFSK Transmitting Band edge-right side




GFSK Hopping Band edge-right side




Pi/4 DQPSK Transmitting Band edge-left side




Pi/4 DQPSK Hopping Band edge-left side




Pi/4 DQPSK Transmitting Band edge-right side




Pi/4 DQPSK Hopping Band edge-right side




### 8DPSK Transmitting Band edge-left side




### 8DPSK Hopping Band edge-left side



### 8DPSK Transmitting Band edge-right side



### 8DPSK Hopping Band edge-right side



## 11 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Mode: Test in fixing operating frequency at low, Middle, high channel.

### 11.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

### 11.2 Test Result


Modulation	Test Channel	Bandwidth(MHz)
GFSK	Low	0.856
GFSK	Middle	0.856
GFSK	High	0.868
Pi/4 DQPSK	Low	1.252
Pi/4 DQPSK	Middle	1.252
Pi/4 DQPSK	High	1.252
8DPSK	Low	1.252
8DPSK	Middle	1.246
8DPSK	High	1.252

**Test plots**


GFSK Low Channel




GFSK Middle Channel



GFSK High Channel




Pi/4 DQPSK Low Channel







### Pi/4 DQPSK Middle Channel




### Pi/4 DQPSK High Channel




8DPSK Low Channel



8DPSK Middle Channel



### 8DPSK High Channel



## 12 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247 (a)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater 0.125 watts..

Test mode: Test in fixing frequency transmitting mode.

### 12.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Use the following spectrum analyzer settings:
    - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
    - 2) RBW  $\geq$  20 dB bandwidth of the emission being measured.
    - 3) VBW  $\geq$  RBW.
    - 4) Sweep: Auto.
    - 5) Detector function: Peak.
    - 6) Trace: Max hold.
  - b) Allow trace to stabilize.
  - c) Use the marker-to-peak function to set the marker to the peak of the emission.
  - d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
  - e) A plot of the test results and setup description shall be included in the test report.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

## 12.2 Test Result


Modulation	Test Channel	Output Power (dBm)	Limit (dBm)
GFSK	Low	5.53	30
GFSK	Middle	3.98	30
GFSK	High	<b>6.99</b>	30
Pi/4 DQPSK	Low	4.03	21
Pi/4 DQPSK	Middle	2.96	21
Pi/4 DQPSK	High	6.17	21
8DPSK	Low	4.09	21
8DPSK	Middle	3.00	21
8DPSK	High	6.24	21

**Test plots**


GFSK Low Channel




GFSK Middle Channel





### GFSK High Channel




### Pi/4 DQPSK Low Channel









### 8DPSK Low Channel



### 8DPSK Middle Channel





## 13 Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with power no greater than 0.125W.

Test Mode: Test in hopping transmitting operating mode.

### 13.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Span: Wide enough to capture the peaks of two adjacent channels.
  - b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
  - c) Video (or average) bandwidth (VBW)  $\geq$  RBW.
  - d) Sweep: Auto.
  - e) Detector function: Peak.
  - f) Trace: Max hold.
  - g) Allow the trace to stabilize.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section  
Submit this plot.

### 13.2 Test Result


Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	1.000	0.856	PASS
GFSK	Middle	1.000	0.856	PASS
GFSK	High	1.000	0.868	PASS
Pi/4 DQPSK	Low	1.000	0.835	PASS
Pi/4 DQPSK	Middle	1.006	0.835	PASS
Pi/4 DQPSK	High	1.000	0.835	PASS
8DPSK	Low	1.000	0.835	PASS
8DPSK	Middle	1.000	0.831	PASS
8DPSK	High	1.000	0.835	PASS

### Test plots


GFSK Low Channel




GFSK Middle Channel





### GFSK High Channel




### Pi/4 DQPSK Low Channel







### 8DPSK Low Channel



### 8DPSK Middle Channel







## 14 Number of Hopping Frequency

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Mode: Test in hopping transmitting operating mode.

### 14.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer:
  - a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
  - b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
  - c) VBW  $\geq$  RBW.
  - d) Sweep: Auto.
  - e) Detector function: Peak.
  - f) Trace: Max hold.
  - g) Allow the trace to stabilize..
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

### 14.2 Test Result


#### Test Plots:

79 Channels in total


GFSK



### Pi/4 DQPSK



### 8DPSK



## 15 Dwell Time

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10: 2013

Test Limit: Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Mode: Test in hopping transmitting operating mode.

### 15.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

### 15.2 Test Result

DH5 Packet permit maximum  $1600 / 79 / 6$  hops per second in each channel (5 time slots RX, 1 time slot TX).


DH3 Packet permit maximum  $1600 / 79 / 4$  hops per second in each channel (3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum  $1600 / 79 / 2$  hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:


Data Packet	Dwell Time(s)
DH5	$1600/79/6*0.4*79*(MkrDelta)/1000$
DH3	$1600/79/4*0.4*79*(MkrDelta)/1000$
DH1	$1600/79/2*0.4*79*(MkrDelta)/1000$
Remark: Mkr Delta is once pulse time.	

Modulation	Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	DH5	Low	2.880	0.307	0.4
		middle	2.880	0.307	0.4
		High	2.880	0.307	0.4
Pi/4DQPSK	DH5	Low	2.880	0.307	0.4
		middle	2.880	0.307	0.4
		High	2.880	0.307	0.4
8DPSK	DH5	Low	2.850	0.304	0.4
		middle	2.850	0.304	0.4
		High	2.850	0.304	0.4


Remark: Only the worst-case mode DH5 is recorded.




### GFSK DH5 Middle Channel




### GFSK DH5 High Channel



Pi/4DQPSK DH5 Low Channel




Pi/4DQPSK DH5 Middle Channel







### Pi/4DQPSK DH5 High Channel




### 8DPSK DH5 Low Channel



### 8DPSK DH5 Middle Channel



### 8DPSK DH5 High Channel



## **16 Antenna Requirement**

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna, fulfil the requirement of this section.

## **17 RF Exposure**

Remark: refer to SAR test report: WTS19S12086451W001.

## **18 Photographs of test setup and EUT.**

Note: Please refer to appendix: Appendix-CD8-Photos.

=====**End of Report**=====