




# RF TEST REPORT



Report No.: 18070525-FCC-R2

Supersede Report No.: N/A

Applicant	TECNO MOBILE LIMITED	
Product Name	Mobile phone	
Model No.	F3	
Serial No.	N/A	
Test Standard	FCC Part 15.247, ANSI C63.10: 2013	
Test Date	May 16 to 25, 2018	
Issue Date	May 26, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	18070525-FCC-R2
Page	3 of 54

This page has been left blank intentionally.

# CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. TEST SUMMARY .....	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 CHANNEL SEPARATION .....	10
6.3 20DB BANDWIDTH.....	14
6.4 PEAK OUTPUT POWER.....	18
6.5 NUMBER OF HOPPING CHANNEL.....	22
6.6 TIME OF OCCUPANCY (DWELL TIME) .....	24
6.7 BAND EDGE & RESTRICTED BAND .....	28
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	36
6.9 RADIATED EMISSIONS & RESTRICTED BAND .....	42
ANNEX A. TEST INSTRUMENT.....	49
ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT.....	50
ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST/ DECLARATION OF SIMILARITY.....	54

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070525-FCC-R2	NONE	Original	May 26, 2018

## 2. Customer information

Applicant Name	TECNO MOBILE LIMITED
Applicant Add	ROOMS 05-15, 13A/F., SOUTH TOWER, WORLD FINANCE CENTRE, HARBOUR CITY, 17 CANTON ROAD, TSIM SHA TSUI, KOWLOON, HONG KONG
Manufacturer	TECNO MOBILE LIMITED
Manufacturer Add	ROOMS 05-15, 13A/F., SOUTH TOWER, WORLD FINANCE CENTRE, HARBOUR CITY, 17 CANTON ROAD, TSIM SHA TSUI, KOWLOON, HONG KONG

## 3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

## 4. Equipment under Test (EUT) Information

Description of EUT:	Mobile phone
Main Model:	F3
Serial Model:	N/A
Date EUT received:	May 15, 2018
Test Date(s):	May 16 to 25, 2018
Equipment Category :	DSS
Antenna Gain:	Bluetooth: -3.5dBi
Antenna Type:	PIFA antenna
Type of Modulation:	Bluetooth: GFSK, $\pi$ /4DQPSK, 8DPSK
RF Operating Frequency (ies):	Bluetooth: 2402-2480 MHz
Max. Output Power:	2.081dBm
Number of Channels:	Bluetooth: 79CH
Port:	Please refer to the user' s manual
Input Power:	Adapter : Model: A8-501000 Input: AC100-240V~50/60Hz,200mA Output: DC 5.0V, 1.0A Battery : Model: BL-24ET Spec: 3.8V, 2400mAh/2350mAh(typ/min), 9.12Wh/8.93Wh(typ/min) Limited charge voltage: 4.35V

Test Report	18070525-FCC-R2
Page	7 of 54

Trade Name : TECNO

FCC ID: 2ADYY-F3

## 5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

### Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-



## 6. Measurements, Examination And Derived Results

### 6.1 Antenna Requirement

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIF/GPS, the gain is -3.5dBi for Bluetooth/BLE, the gain is -3.5dBi for WIFI, the gain is -3.1dBi for GPS.

A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -4.95dBi for GSM850, -3.87dBi for PCS1900, -4.98dBi for UMTS-FDD Band V, -4.41dBi for UMTS-FDD Band II.


**The antenna meets up with the ANTENNA REQUIREMENT.**

**Result:** Compliance.

## 6.2 Channel Separation

Temperature	25°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 17, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>- The EUT must have its hopping function enabled</li> <li>- Span = wide enough to capture the peaks of two adjacent channels</li> <li>- Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span</li> <li>- Video (or Average) Bandwidth (VBW) ≥ RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.</li> </ul>		

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

### Channel Separation measurement result


Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.005	0.687	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.965	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0682	Pass
	Adjacency Channel	2479			
CH Separation $\pi$ /4 DQPSK	Low Channel	2402	1.005	0.874	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.857	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.861	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.867	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.865	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.859	Pass
	Adjacency Channel	2479			

## Test Plots


### Channel Separation measurement result




GFSK - Low Channel




GFSK - Middle Channel




GFSK - High Channel



$\pi/4$  DPSK - Low Channel




$\pi/4$  DQPSK - Middle Channel



$\pi/4$  DQPSK - High Channel




8DPSK - Low Channel



8DPSK - Middle Channel



8DPSK - High Channel




### 6.3 20dB Bandwidth

Temperature	25°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 17, 2018
Tested By :	Aaron Liang

**Requirement(s):**

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> <li>- Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel</li> <li>- RBW <math>\geq</math> 1% of the 20 dB bandwidth</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold.</li> <li>- The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference</li> </ul>
----------------	--

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data  Yes  N/A


Test Plot  Yes (See below)  N/A

#### Measurement result


Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.030	0.888
	Mid	2441	0.965	0.887
	High	2480	1.023	0.894
$\pi/4$ DQPSK	Low	2402	1.311	1.1715
	Mid	2441	1.285	1.1712
	High	2480	1.292	1.1695
8-DPSK	Low	2402	1.301	1.1889
	Mid	2441	1.298	1.1845
	High	2480	1.289	1.2024

## Test Plots


### 20dB Bandwidth measurement result




GFSK - Low Channel




GFSK - Middle Channel




GFSK - High Channel



$\pi/4$  DPSK - Low Channel




$\pi/4$  DQPSK - Middle Channel




$\pi/4$  DQPSK - High Channel






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

## 6.4 Peak Output Power

Temperature	25°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 17, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with $\geq 75$ channels: $\leq 1$ Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: $\leq 1$ Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: $\leq 0.125$ Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with $\geq 50$ channels: $\leq 1$ Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with $\geq 25$ & $< 50$ channels: $\leq 0.25$ Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: $\leq 1$ Watt	<input type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> <li>- Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel</li> <li>- RBW &gt; the 20 dB bandwidth of the emission being measured</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow the trace to stabilize.</li> </ul>
----------------	--

	<ul style="list-style-type: none"> <li>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data  Yes  N/A  
 Test Plot  Yes (See below)  N/A

**Peak Output Power measurement result**


Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	1.155	125	Pass
		Mid	2441	1.359	1000	Pass
		High	2480	1.991	125	Pass
	$\pi/4$ DQPSK	Low	2402	1.084	125	Pass
		Mid	2441	1.291	125	Pass
		High	2480	1.868	125	Pass
	8-DPSK	Low	2402	1.220	125	Pass
		Mid	2441	1.437	125	Pass
		High	2480	<b>2.081</b>	125	Pass

## Test Plots


### Output Power measurement result




GFSK Output power - Low CH 2402




GFSK Output power - Mid CH 2441




GFSK Output power - High CH 2480




$\pi/4$  DQPSK Output power - Low CH 2402




$\pi/4$  DQPSK Output power - Mid CH 2441




$\pi/4$  DQPSK Output power - High CH 2480




8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480



## 6.5 Number of Hopping Channel

Temperature	25°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 17, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz $\geq$ 15 channels	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer settings:</u>            The EUT must have its hopping function enabled.</p> <ul style="list-style-type: none"> <li>- Span = the frequency band of operation</li> <li>- RBW <math>\geq</math> 1% of the span</li> <li>- VBW <math>\geq</math> RBW</li> <li>- Sweep = auto</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- Allow trace to fully stabilize.</li> <li>- It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data     Yes                       N/A  
 Test Plot     Yes (See below)                       N/A

### Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

### Test Plots


#### Number of Hopping Channels measurement result



## 6.6 Time of Occupancy (Dwell Time)

Temperature	25°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 17, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.  <u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> <li>- Span = zero span, centered on a hopping channel</li> <li>- RBW = 1 MHz</li> <li>- VBW ≥ RBW</li> <li>- Sweep = as necessary to capture the entire dwell time per hopping channel</li> <li>- Detector function = peak</li> <li>- Trace = max hold</li> <li>- use the marker-delta function to determine the dwell time</li> </ul>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data     Yes                       N/A  
 Test Plot     Yes (See below)                       N/A





**Dwell Time measurement result**

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.940	313.600	400	Pass
		Mid	2.990	318.933	400	Pass
		High	2.960	315.733	400	Pass
	π /4 DQPSK	Low	2.970	316.800	400	Pass
		Mid	2.960	315.733	400	Pass
		High	2.930	312.533	400	Pass
	8-DPSK	Low	2.930	312.533	400	Pass
		Mid	2.980	317.867	400	Pass
		High	2.930	312.533	400	Pass
Note: Dwell time=Pulse Time (ms) × (1600 ÷ 6 ÷ 79) ×31.6						


### Test Plots

#### Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

## 6.7 Band Edge & Restricted Band

Temperature	26°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	May 22, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. □	<input checked="" type="checkbox"/>

Test Setup	 <p>The diagram illustrates the test setup for radiated emissions. A Turn Table is placed on a Ground Plane, with EUT &amp; Support Units on top. The height of the EUT &amp; Support Units is indicated as 0.8/1.5m. An Ant. Tower is positioned 3m away from the Turn Table. A 1-4m Variable antenna is attached to the tower. A Test Receiver is connected to the antenna.</p>
------------	---



Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> <li>- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.</li> <li>- 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,</li> </ul>
----------------	--

	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> <li>- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> <li>a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</li> <li>b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</li> <li>c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</li> </ul> </li> <li>- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.</li> <li>- 5. Repeat above procedures until all measured frequencies were complete.</li> </ul>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail



**Test Data**     Yes                       N/A  
**Test Plot**     Yes (See below)       N/A

### Test Plots

#### GFSK Mode:

 <p>         * RBW 1 MHz          * VBW 3 MHz          * Att 5 dB          Ref 102.0 dBµV          SWT 2.5ms          M1[1] 42.09 dBµV          2.355400000 GHz          52.66 dBµV          2.400000000 GHz          Limit-L 74          Line Limit-L 74          PASS          M2[1]          M1          F1          Start 2.31 GHz Stop 2.44 GHz          Date: 22.MAY.2018 01:25:55     </p>	 <p>         * RBW 1 MHz          * VBW 3 MHz          * Att 5 dB          Ref 102.0 dBµV          SWT 2.5ms          M1[1] 42.57 dBµV          2.484970000 GHz          Limit-R 74          Line Limit-R 74          PASS          M1          F1          Start 2.44 GHz Stop 2.5 GHz          Date: 22.MAY.2018 01:27:29     </p>
<p align="center">GFSK-Hopping Left Side-PK Note: F1 is frequency 2400MHz</p>	<p align="center">GFSK-Hopping Right Side-PK Note: F1 is frequency 2483.5MHz</p>
<p align="center">Note: (no need if PK value less than the AV limit)</p>	<p align="center">Note: (no need if PK value less than the AV limit)</p>
<p align="center">GFSK-Hopping Left Side-AV</p>	<p align="center">GFSK-Hopping Right Side-AV</p>

Note: Both Horizontal and vertical polarities were investigated.




GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz





Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV

GFSK-Right Side-AV



Note: Both Horizontal and vertical polarities were investigated.

$\pi$  / 4 DQPSK Mode:

 <p>* Att 5 dB * RBW 1 MHz * VBW 3 MHz M1[1] 41.69 dB<math>\mu</math>V Ref 102.0 dB<math>\mu</math>V SWT 2.5ms 2.367340000 GHz Limit Check PASS M2[1] 51.96 dB<math>\mu</math>V Line Limit-L 74 PASS 2.400000000 GHz 1Pk Max 90 dB<math>\mu</math>V Limit-L 74 M2 M1 Tdf 10 dB<math>\mu</math>V Start 2.31 GHz Stop 2.44 GHz Date: 22.MAY.2018 01:26:23</p>	 <p>* Att 5 dB * RBW 1 MHz * VBW 3 MHz M1[1] 42.57 dB<math>\mu</math>V Ref 102.0 dB<math>\mu</math>V SWT 2.5ms 2.484970000 GHz Limit Check PASS Line Limit-R 74 PASS 1Pk Max 90 dB<math>\mu</math>V Limit-R 74 M1 Tdf 10 dB<math>\mu</math>V Start 2.44 GHz Stop 2.5 GHz Date: 22.MAY.2018 01:28:05</p>
<p><math>\pi</math> / 4 DQPSK-Hopping Left Side-PK Note: F1 is frequency 2400MHz</p>	<p><math>\pi</math> / 4 DQPSK-Hopping Right Side-PK Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p><math>\pi</math> / 4 DQPSK-Hopping Left-AV</p>	<p><math>\pi</math> / 4 DQPSK-Hopping Right-AV</p>

Note: Both Horizontal and vertical polarities were investigated.






$\pi$  / 4 DQPSK-Left Side-PK

Note: F1 is frequency 2400MHz

$\pi$  / 4 DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz





Note: (no need if PK value less than the AV limit)

$\pi$  / 4 DQPSK-Left Side-AV


$\pi$  / 4 DQPSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.


**8-DPSK Mode:**

 <p>Date: 22.MAY.2018 01:26:41</p>	 <p>Date: 22.MAY.2018 01:28:35</p>
<p align="center"><b>8DPSK-Hopping Left Side-PK</b></p> <p align="center"><b>Note: F1 is frequency 2400MHz</b></p>	<p align="center"><b>8DPSK-Hopping Right Side-PK</b></p> <p align="center"><b>Note: F1 is frequency 2483.5MHz</b></p>
<p align="center">Note: (no need if PK value less than the AV limit)</p>	<p align="center">Note: (no need if PK value less than the AV limit)</p>
<p align="center"><b>8DPSK-Hopping Left-AV</b></p>	<p align="center"><b>8DPSK-Hopping Right-AV</b></p>

Note: Both Horizontal and vertical polarities were investigated.



Date: 22.MAY.2018 01:10:43




Date: 22.MAY.2018 01:13:03

8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 22.MAY.2018 01:09:56

Note: (no need if PK value less than the AV limit)

8DPSK-Left Side-AV

8DPSK-Right Side-AV


Note: Both Horizontal and vertical polarities were investigated.

## 6.8 AC Power Line Conducted Emissions

Temperature	26°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	May 22, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<input checked="" type="checkbox"/>														
		<table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBµV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															



Procedure	<ol style="list-style-type: none"> <li>The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.</li> <li>The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains.</li> <li>The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss</li> </ol>
-----------	---


Test Report	18070525-FCC-R2
Page	37 of 54

	<p>coaxial cable.</p> <ol style="list-style-type: none"> <li>4. All other supporting equipment were powered separately from another main supply.</li> <li>5. The EUT was switched on and allowed to warm up to its normal operating condition.</li> <li>6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.</li> <li>7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz.</li> <li>8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).</li> </ol>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data     Yes                       N/A

Test Plot     Yes (See below)             N/A

<b>Test Mode:</b>	<b>Bluetooth Mode</b>
-------------------	-----------------------




**Test Data**

**Phase Line Plot at 120Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1890	36.85	QP	10.03	46.88	64.08	-17.20
2	L1	0.1890	20.16	AVG	10.03	30.19	54.08	-23.89
3	L1	0.4503	36.28	QP	10.03	46.31	56.87	-10.56
4	L1	0.4503	25.70	AVG	10.03	35.73	46.87	-11.14
5	L1	0.8871	25.83	QP	10.03	35.86	56.00	-20.14
6	L1	0.8871	16.26	AVG	10.03	26.29	46.00	-19.71
7	L1	2.8449	20.15	QP	10.05	30.20	56.00	-25.80
8	L1	2.8449	11.03	AVG	10.05	21.08	46.00	-24.92
9	L1	7.9257	14.69	QP	10.12	24.81	60.00	-35.19
10	L1	7.9257	6.37	AVG	10.12	16.49	50.00	-33.51
11	L1	16.3653	13.53	QP	10.25	23.78	60.00	-36.22
12	L1	16.3653	4.96	AVG	10.25	15.21	50.00	-34.79

<b>Test Mode:</b>	<b>Bluetooth Mode</b>
-------------------	-----------------------




**Test Data**

**Phase Neutral Plot at 120Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1851	34.95	QP	10.02	44.97	64.25	-19.28
2	N	0.1851	16.76	AVG	10.02	26.78	54.25	-27.47
3	N	0.3099	29.57	QP	10.02	39.59	59.97	-20.38
4	N	0.3099	13.14	AVG	10.02	23.16	49.97	-26.81
5	N	0.5751	29.22	QP	10.02	39.24	56.00	-16.76
6	N	0.5751	17.56	AVG	10.02	27.58	46.00	-18.42
7	N	1.6125	15.56	QP	10.04	25.60	56.00	-30.40
8	N	1.6125	5.23	AVG	10.04	15.27	46.00	-30.73
9	N	4.2948	17.38	QP	10.06	27.44	56.00	-28.56
10	N	4.2948	6.88	AVG	10.06	16.94	46.00	-29.06
11	N	27.1566	17.06	QP	10.37	27.43	60.00	-32.57
12	N	27.1566	5.18	AVG	10.37	15.55	50.00	-34.45

<b>Test Mode:</b>	<b>Bluetooth Mode</b>
-------------------	-----------------------




**Test Data**

**Phase Line Plot at 240Vac, 60Hz**

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2241	45.94	QP	10.03	55.97	62.67	-6.70
2	L1	0.2241	21.55	AVG	10.03	31.58	52.67	-21.09
3	L1	0.3801	39.27	QP	10.03	49.30	58.28	-8.98
4	L1	0.3801	23.19	AVG	10.03	33.22	48.28	-15.06
5	L1	1.3278	32.03	QP	10.03	42.06	56.00	-13.94
6	L1	1.3278	23.16	AVG	10.03	33.19	46.00	-12.81
7	L1	2.9346	31.02	QP	10.05	41.07	56.00	-14.93
8	L1	2.9346	17.32	AVG	10.05	27.37	46.00	-18.63
9	L1	4.3065	29.66	QP	10.07	39.73	56.00	-16.27
10	L1	4.3065	19.06	AVG	10.07	29.13	46.00	-16.87
11	L1	17.2545	20.15	QP	10.26	30.41	60.00	-29.59
12	L1	17.2545	12.83	AVG	10.26	23.09	50.00	-26.91



<b>Test Mode:</b>	<b>Bluetooth Mode</b>
-------------------	-----------------------



**Test Data**

**Phase Neutral Plot at 240Vac, 60Hz**


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.3021	32.63	QP	10.02	42.65	60.18	-17.53
2	N	0.3021	26.35	AVG	10.02	36.37	50.18	-13.81
3	N	0.4191	37.77	QP	10.02	47.79	57.47	-9.68
4	N	0.4191	32.11	AVG	10.02	42.13	47.47	-5.34
5	N	0.9534	33.19	QP	10.03	43.22	56.00	-12.78
6	N	0.9534	27.01	AVG	10.03	37.04	46.00	-8.96
7	N	1.6125	32.92	QP	10.04	42.96	56.00	-13.04
8	N	1.6125	23.04	AVG	10.04	33.08	46.00	-12.92
9	N	2.9346	30.10	QP	10.05	40.15	56.00	-15.85
10	N	2.9346	20.01	AVG	10.05	30.06	46.00	-15.94
11	N	16.1118	18.70	QP	10.21	28.91	60.00	-31.09
12	N	16.1118	8.99	AVG	10.21	19.20	50.00	-30.80


## 6.9 Radiated Emissions & Restricted Band

Temperature	26°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	May 22, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	<input checked="" type="checkbox"/>																
		<table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (<math>\mu\text{V}/\text{m}</math>)</th> </tr> </thead> <tbody> <tr> <td>0.009~0.490</td> <td>2400/F(KHz)</td> </tr> <tr> <td>0.490~1.705</td> <td>24000/F(KHz)</td> </tr> <tr> <td>1.705~30.0</td> <td>30</td> </tr> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>		Frequency range (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216 960	200	Above 960	500
		Frequency range (MHz)		Field Strength ( $\mu\text{V}/\text{m}$ )															
		0.009~0.490		2400/F(KHz)															
		0.490~1.705		24000/F(KHz)															
		1.705~30.0		30															
		30 – 88		100															
		88 – 216		150															
216 960	200																		
Above 960	500																		





**Procedure**

- The EUT was switched on and allowed to warm up to its normal operating condition.
- The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
  - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
  - The EUT was then rotated to the direction that gave the maximum emission.
  - Finally, the antenna height was adjusted to the height that gave the maximum emission.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.  
The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.
- Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.

**Remark**

**Result**  Pass  Fail

**Test Data**  Yes  N/A

**Test Plot**  Yes (See below)  N/A

**Test Result:**

<b>Test Mode:</b>	Transmitting Mode
-------------------	-------------------

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor (dB/m)	Reading (dBuV/m)	Result (dBuV/m)	Limit@3m (dBuV/m)	Margin (dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

**Note:**


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

**Test Mode:** Bluetooth Mode

**30MHz -1GHz**




**Test Data**

**Horizontal Polarity Plot @3m**

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	( )
1	H	39.4372	31.69	peak	14.31	22.28	0.79	24.51	40.00	-15.49	200	359
2	H	43.8119	33.22	peak	11.38	22.29	0.76	23.07	40.00	-16.93	100	80
3	H	78.6888	27.34	peak	7.63	22.41	1.03	13.59	40.00	-26.41	100	60
4	H	166.0680	28.60	peak	12.11	22.26	1.37	19.82	43.50	-23.68	100	48
5	H	240.8304	30.89	peak	11.53	22.31	1.67	21.78	46.00	-24.22	100	146
6	H	768.7482	24.91	peak	21.02	21.22	2.90	27.61	46.00	-18.39	100	136

### 30MHz -1GHz

80.0 dBuV/m



#### Test Data

#### Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee ( )
1	V	39.4372	37.79	peak	14.31	22.28	0.79	30.61	40.00	-9.39	100	173
2	V	43.6585	39.99	peak	11.49	22.29	0.76	29.95	40.00	-10.05	100	321
3	V	56.5929	34.08	peak	7.67	22.40	0.77	20.12	40.00	-19.88	100	195
4	V	90.8554	33.29	peak	8.21	22.32	0.96	20.14	43.50	-23.36	100	213
5	V	166.6514	31.01	peak	12.07	22.26	1.37	22.19	43.50	-21.31	100	142
6	V	480.5276	25.24	peak	17.31	21.85	2.31	23.01	46.00	-22.99	100	130

### Above 1GHz

<b>Test Mode:</b>	<b>Transmitting Mode</b>
-------------------	--------------------------

#### Low Channel: 8-DPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4804	45.51	AV	V	33.39	7.22	48.46	37.66	54	-16.34
4804	43.05	AV	H	33.39	7.22	48.46	35.2	54	-18.8
4804	67.45	PK	V	33.39	7.22	48.46	59.6	74	-14.4
4804	62.85	PK	H	33.39	7.22	48.46	55	74	-19
7441	26.12	AV	V	37.77	8.06	49.08	22.87	54	-31.13
7441	25.93	AV	H	37.77	8.06	49.08	22.68	54	-31.32
7441	45.48	PK	V	37.77	8.06	49.08	42.23	74	-31.77
7441	47.45	PK	H	37.77	8.06	49.08	44.2	74	-29.8

#### Middle Channel: 8-DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4882	44.69	AV	V	33.62	7.53	48.36	37.48	54	-16.52
4882	46.92	AV	H	33.62	7.53	48.36	39.71	54	-14.29
4882	66.75	PK	V	33.62	7.53	48.36	59.54	74	-14.46
4882	64.87	PK	H	33.62	7.53	48.36	57.66	74	-16.34
13502	27.98	AV	V	40.57	13.26	45.19	36.62	54	-17.38
13502	25.96	AV	H	40.57	13.26	45.19	34.6	54	-19.4
13502	43.36	PK	V	40.57	13.26	45.19	52	74	-22
13502	44.9	PK	H	40.57	13.26	45.19	53.54	74	-20.46

**High Channel: 8-DPSK Mode (Worst Case) (2480 MHz)**

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
4960	44.83	AV	V	33.89	7.86	48.31	38.27	54	-15.73
4960	45.5	AV	H	33.89	7.86	48.31	38.94	54	-15.06
4960	67.54	PK	V	33.89	7.86	48.31	60.98	74	-13.02
4960	69.18	PK	H	33.89	7.86	48.31	62.62	74	-11.38
17941	22.57	AV	V	43.52	19.08	45.24	39.93	54	-14.07
17941	21.3	AV	H	43.52	19.08	45.24	38.66	54	-15.34
17941	43.08	PK	V	43.52	19.08	45.24	60.44	74	-13.56
17941	41.64	PK	H	43.52	19.08	45.24	59	74	-15

**Note:**

- 1, The testing has been conformed to  $10 \times 2480 \text{MHz} = 24,800 \text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.
- 4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.




## Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
<b>AC Line Conducted</b>					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
ISN	ISN T800	34373	09/23/2017	09/22/2018	<input type="checkbox"/>
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
<b>RF conducted test</b>					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
<b>Radiated Emissions</b>					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/17/2017	11/16/2018	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/22/2018	03/21/2019	<input checked="" type="checkbox"/>
Active Antenna (9kHz-30MHz)	AL-130	121031	10/12/2017	10/11/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>


## Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

### Annex B.i. TEST SET UP BLOCK


#### Block Configuration Diagram for AC Line Conducted Emissions



**Block Configuration Diagram for Radiated Emissions ( Below 1GHz ) .**



Block Configuration Diagram for Radiated Emissions ( Above 1GHz ) .



## Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

### Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
TECNO MOBILE LIMITED	Adapter	A8-501000	N/A
TECNO MOBILE LIMITED	Earphone	F3	N/A
Agilent	Wireless Connectivity Test Set	N4010A	N/A
OEM	omnidirectional antenna	AntSuck	N/A

### Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Test Report	18070525-FCC-R2
Page	54 of 54

**Annex C. User Manual / Block Diagram / Schematics / Partlist/  
DECLARATION OF SIMILARITY**

Please see the attachment