

TEST REPORT

Reference No..... : WTS20X08052413W
FCC ID : 2ADYY-KE5K
Applicant : TECNO MOBILE LIMITED
Address : ROOM 604 6/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY
17 CANTON ROAD TST KL
Product Name : Mobile Phone
Test Model. : KE5k
FCC Part 2.1093
Standards : ANSI / IEEE C95.1 : 2005+A1:2010
ANSI / IEEE C95.3 : 2002(R2008)
IEEE 1528 :2013
Date of Receipt sample : Aug.10, 2020
Date of Test..... : Aug.10, 2020 to Aug.18, 2020
Date of Issue : Aug.19, 2020
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

Reviewed By:

Approved & Authorized By:

Jack Sun

Lion Cai

Silin Chen

Jack Sun / Project Engineer

Lion Cai / RF Manager

Silin Chen / Manager

TABLE OF CONTENTS

1. General Information	3
1.1 Product Description for Equipment Under Test (EUT)	3
1.2 Test Standards	6
1.3 Test Methodology	6
1.4 Test Facility	6
2. Summary of Test Results	7
3. Specific Absorption Rate (SAR)	8
3.1 Introduction	8
3.2 SAR Definition	8
4. SAR Measurement System	9
4.1 The Measurement System	9
4.2 Probe	9
4.3 Probe Calibration Process	11
4.4 Phantom	12
4.5 Device Holder	12
4.6 Test Equipment List	13
5. Tissue Simulating Liquids	14
5.1 Composition of Tissue Simulating Liquid	14
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	15
5.3 Tissue Calibration Result	16
6. SAR Measurement Evaluation	17
6.1 Purpose of System Performance Check	17
6.2 System Setup	17
6.3 Validation Results	18
7. EUT Testing Position	20
7.1 Define Two Imaginary Lines on The Handset	20
7.2 Cheek Position	21
7.3 Tilted Position	21
7.4 Body Position	22
7.5 EUT Antenna Position	22
7.6 EUT Testing Position	24
8. SAR Measurement Procedures	25
8.1 Measurement Procedures	25
8.2 Spatial Peak SAR Evaluation	25
8.3 Area & Zoom Scan Procedures	26
8.4 Volume Scan Procedures	26
8.5 SAR Averaged Methods	26
8.6 Power Drift Monitoring	26
9. SAR Test Result	27
9.1 Conducted RF Output Power	27
9.2 Test Results for Standalone SAR Test	65
9.3 Simultaneous Multi-band Transmission SAR Analysis	77
10. Measurement Uncertainty	81
10.1 Uncertainty for EUT SAR Test	81
10.2 Uncertainty for System Performance Check	82
Annex A. Plots of System Performance Check	84
Annex B. Plots of SAR Measurement	108
Annex C. EUT Photos	166
Annex D. Test Setup Photos	167
Annex E. Calibration Certificate	168

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: TECNO MOBILE LIMITED
Address of applicant: ROOM 604 6/F SOUTH TOWER WORLD FINANCE CTR
HARBOUR CITY 17 CANTON ROAD TST KL

Manufacturer: SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Address of manufacturer: 101,Building 24,Waijing Industrial Park,Fumin Community,
Fucheng Street,Longhua District,Shenzhen City,P.R.China

General Description of EUT:	
Product Name:	Mobile Phone
Brand Name:	TECNO
Model No.:	KE5k
Adding Model(s):	/
Rated Voltage:	DC 3.85V
Battery:	4900mAh
Device Category:	Portable Device
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
RF Output Power:	GSM850: 32.85dBm, GSM1900: 30.01dBm EDGE850: 26.65dBm, EDGE1900: 26.56dBm
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -3.38dBi; GSM1900: -0.76dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 4, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 4: 1710~1755MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 4: 2110~2155MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.99dBm, WCDMA Band 4: 22.98dBm WCDMA Band 5: 23.10dBm
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: -0.76dBi, WCDMA Band 2: 0.32dBi, WCDMA Band 5: -3.38dBi
4G	
Support Networks:	FDD-LTE, TDD-LTE
Support Band:	FDD-LTE Band 2, 4, 5, 7, 38, 41
Uplink Frequency:	FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 4: Tx: 1710-1755MHz, FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 7: Tx: 2500-2570MHz, TDD-LTE Band 38: Tx: 2570-2620MHz, TDD-LTE Band 41: Tx: 2555-2655MHz
Downlink Frequency:	FDD-LTE Band 2: Rx: 1930-1990MHz,

	FDD-LTE Band 4: Rx: 2110-2155MHz, FDD-LTE Band 5: Rx: 869-894MHz, FDD-LTE Band 7: Rx: 2620-2690MHz, TDD-LTE Band 38: Rx: 2570-2620MHz, TDD-LTE Band 41: Rx: 2555-2655MHz
RF Output Power:	FDD-LTE Band 2: 23.25dBm, FDD-LTE Band 4: 24.32dBm, FDD-LTE Band 5: 23.67dBm, FDD-LTE Band 7: 24.26dBm, TDD-LTE Band 38: 23.08dBm, TDD-LTE Band 41: 23.86dBm,
Type of Modulation:	QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	FDD-LTE Band 2: -0.76dBi, FDD-LTE Band 4: 0.32dBi, FDD-LTE Band 5: -3.38dBi, FDD-LTE Band 7: 0.46dBi TDD-LTE Band 38: 0.46dBi, TDD-LTE Band 41: 0.46dBi,
WIFI(2.4G)	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
RF Output Power:	16.07dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20) 7 for 802.11n(HT40)
Channel Separation:	5MHz
Antenna Type:	Integral Antenna
Antenna Gain:	3.06dBi
Bluetooth	
Bluetooth Version:	V5.0
Frequency Range:	2402-2480MHz
RF Output Power:	6.728dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Antenna Type:	Integral Antenna
Antenna Gain:	3.06dBi

1.2 Test Standards

The following report is prepared on behalf of the TECNO MOBILE LIMITED in accordance with FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1-2005, ANSI / IEEE C95.3 :2002, IEEE 1528-2013, KDB 447498 D01 v06, KDB 648474 D04 v01r03, KDB 248227 D01 v02r02, KDB 941225 D01 v03r01, KDB 941225 D05 v02r05 , and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010. Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Head SAR	Body-worn (10mm Gap)	Hotspot (10mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	
GSM	0.762	0.249	0.400	1.6
WCDMA	0.760	0.669	0.735	1.6
LTE	0.683	0.704	0.704	1.6
WLAN 2.4G	0.193	0.305	0.305	1.6
Simultaneous Transmission	0.965	1.009	0.996	1.6

Remark:

The highest reported SAR values for head, body-worn, router(hotspot), and simultaneous transmission conditions are 0.762W/kg, 0.704 W/kg, 0.735W/kg, and 1.009W/kg respectively.

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedure specified in IEEE 1528-2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe


For the measurements the Specific Dosimetric E-Field Probe SSE2 SN 45/15 EPGO280 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Probe Length: 330 mm
- Length of Individual Dipoles: 4.5 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter : 5 mm

Waltek Testing Group (Shenzhen) Co., Ltd.
<http://www.semtest.com.cn>

- Distance between dipoles / probe extremity: 2.7mm
 - Probe linearity: <0.25 dB
 - Axial Isotropy: <0.25 dB
 - Spherical Isotropy: <0.50 dB
 - Calibration range: 700 to 3000MHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

δ = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

Waltek Testing Group (Shenzhen) Co., Ltd.

<http://www.semtest.com.cn>

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$\text{SAR} = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 °.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005


4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	MVG	SSE2	SN 45/15 EPGO280	2020-07-03	2021-07-02
750MHz Dipole	MVG	SID750	SN 47/12 DIP 0G750-203	2020-03-11	2021-03-10
835MHz Dipole	MVG	SID835	SN 47/12 DIP 0G835-204	2020-03-11	2021-03-10
1800MHz Dipole	MVG	SID1800	SN 47/12 DIP 1G800-206	2020-03-11	2021-03-10
1900MHz Dipole	MVG	SID1900	SN 47/12 DIP 1G900-207	2020-03-11	2021-03-10
2450MHz Dipole	MVG	SID2450	SN 13/15 DIP 2G450-364	2020-03-11	2021-03-10
2600MHz Dipole	MVG	SID2600	SN 13/15 DIP 2G600-365	2020-03-11	2021-03-10
Dielectric Probe Kit	MVG	SCLMP	SN 47/12 OCPG49	2020-03-11	2021-03-10
SAM Phantom	MVG	SAM	SN/ 47/12 SAM95	N/A	N/A
MULTIMETER	KEITHLEY	Keithley 2000	4006367	2020-04-28	2021-04-27
Signal Generator	Rohde & Schwarz	SMR20	100047	2020-04-28	2021-04-27
Universal Tester	Rohde & Schwarz	CMU200	112012	2020-04-28	2021-04-27
Communications Tester	Rohde & Schwarz	CMW500	148650	2020-04-28	2021-04-27
Network Analyzer	HP	8753C	2901A00831	2020-04-28	2021-04-27
Directional Couplers	Agilent	778D	20160	2020-04-28	2021-04-27


5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head SAR



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Sugar (%)	HEC (%)	Preventol (%)	DGBE (%)
Head						
750	41.1	1.4	57.0	0.2	0.3	0
835	40.3	1.4	57.9	0.2	0.2	0
1700-1900	55.2	0.3	0	0	0	44.5
2450	55.0	0.1	0	0	0	44.9
2600	54.9	0.1	0	0	0	45.0
Body						
750	50.0	0.8	48.8	0.2	0.2	0
835	50.8	0.9	48.1	0.1	0.1	0
1700-1900	70.2	0.4	0	0	0	29.4
2450	68.6	0.1	0	0	0	31.3
2600	68.2	0.1	0	0	0	31.7

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Head		Body	
	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3	0.80	61.9
300	0.87	45.3	0.92	58.2
450	0.87	43.5	0.94	56.7
750	0.89	41.9	0.96	55.5
835	0.90	41.5	0.97	55.2
900	0.97	41.5	1.05	55.0
915	0.98	41.5	1.06	55.0
1450	1.20	40.5	1.30	54.0
1610	1.29	40.3	1.40	53.8
1750	1.37	40.1	1.49	53.4
1800-2000	1.40	40.0	1.52	53.3
2450	1.80	39.2	1.95	52.7
3000	2.40	38.5	2.73	52.0
5200	4.66	36.0	5.30	49.0
5800	5.27	35.3	6.00	48.2

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Head Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
750	21.2	0.86	0.89	-3.37	41.32	41.90	-1.38	±5	2020-08-11
835	21.2	0.87	0.90	-3.33	41.11	41.50	-0.94	±5	2020-08-11
1750	21.3	1.37	1.37	0.00	39.02	40.1	-2.69	±5	2020-08-12
1900	21.3	1.38	1.40	-1.43	38.56	40.00	-3.60	±5	2020-08-12
2450	21.3	1.74	1.80	-3.33	38.15	39.20	-2.68	±5	2020-08-13
2600	21.3	1.93	1.96	-1.53	38.63	39.0	-0.95	±5	2020-08-13

Body Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
750	21.2	0.93	0.96	-3.12	54.96	55.50	-0.97	±5	2020-08-11
835	21.2	0.95	0.97	-2.06	54.85	55.20	-0.63	±5	2020-08-11
1750	21.3	1.46	1.49	-2.01	51.22	53.40	-4.08	±5	2020-08-12
1900	21.3	1.50	1.52	-1.32	52.42	53.30	-1.65	±5	2020-08-12
2450	21.3	1.91	1.95	-2.05	52.01	52.70	-1.31	±5	2020-08-13
2600	21.3	2.12	2.16	-1.85	52.24	52.50	-0.50	±5	2020-08-13


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835MHz, 1800MHz, 1900MHz, 2450MHz, 2600MHz, and 5GHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.

The output power on 5 GHz Waveguide must be calibrated to 20 dBm (100mW) before 5 GHz Waveguide is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance	Date
MHz	(W/kg)	(W/kg)	(W/kg)	(%)	
Head					
750	8.40	2.16	8.64	2.86	2020-08-11
835	9.65	2.41	9.64	-0.10	2020-08-11
1800	38.49	9.61	38.44	-0.13	2020-08-12
1900	39.59	9.91	39.64	0.13	2020-08-12
2450	53.76	13.45	53.8	0.07	2020-08-13
2600	55.07	13.67	54.68	-0.71	2020-08-13
Body					
750	8.40	2.12	8.48	0.95	2020-08-11
835	9.36	2.35	9.4	0.43	2020-08-11
1800	38.29	9.58	38.32	0.08	2020-08-12
1900	39.01	9.78	39.12	0.28	2020-08-12

2450	50.33	12.59	50.36	0.06	2020-08-13
2600	53.92	13.43	53.72	-0.37	2020-08-13

Remark: Referring to IEEE 1528-2013, Section 8.2, The system check shall be performed at a test frequency that is within $\pm 10\%$ or ± 100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Define Two Imaginary Lines on The Handset

- (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Illustration for Handset Vertical and Horizontal Reference Lines

7.2 Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 7.2).




Illustration for Cheek Position

7.3 Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 7.3).




Illustration for Tilted Position

7.4 Body Position

- (a) To position the device parallel to the phantom surface with each side.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 10mm.





Illustration for Body Position

7.5 EUT Antenna Position



Block Diagram for EUT Antenna Position

Distance of EUT antenna-to-edge/surface(mm), Test distance:10mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	<25	<25	<25	50	<25	150
WLAN	<25	<25	60	<25	<25	150
Bluetooth	<25	<25	<25	50	<25	150

7.6 EUT Testing Position

Head/Body mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Head SAR tests				
Antennas	Right Cheek	Left Cheek	Right Tilted	Left Tilted
WWAN	Yes	Yes	Yes	Yes
WLAN	Yes	Yes	Yes	Yes

Body SAR tests, Test distance: 10mm						
Antennas	Front	Back	Right Side	Left Side	Top Side	Bottom Side
WWAN	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	No	Yes	Yes	No

Body-worn SAR tests, Test distance: 10mm		
Antennas	Front	Back
WWAN	Yes	Yes
WLAN	Yes	Yes

Remark:

- Referring to KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test separation distances is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
- Referring to KDB 648474 D04 Handset SAR v01r03, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2 \text{ W/kg}$

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

GSM - Burst Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	32.78	32.85	32.84	33.0	30.00	29.85	29.84	30.5
GPRS (1 slot)	32.79	32.83	32.85	33.0	30.01	29.87	29.87	30.5
GPRS (2 slots)	31.76	31.84	31.85	32.0	28.98	28.89	28.87	29.0
GPRS (3 slots)	29.62	29.71	29.75	30.0	26.95	26.88	26.87	27.0
GPRS (4 slots)	28.44	28.56	28.62	29.0	25.87	25.79	25.79	26.0
EDGE (1 slot)	26.53	26.65	26.52	27.0	26.56	26.4	26.05	27.0
EDGE (2 slots)	25.34	25.39	25.33	25.5	25.49	25.33	24.97	25.5
EDGE (3 slots)	23.1	23.08	23.05	23.5	23.29	23.11	22.79	23.5
EDGE (4 slots)	21.86	21.8	21.65	22.0	22.06	21.89	21.53	22.5

GSM - Source-Based Time-Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	23.78	23.85	23.84	24.0	21.00	20.85	20.84	21.0
GPRS (1 slot)	23.79	23.83	23.85	24.0	21.01	20.87	20.87	21.5
GPRS (2 slots)	25.76	25.84	25.85	26.0	22.98	22.89	22.87	23.0
GPRS (3 slots)	25.37	25.46	25.50	26.0	22.70	22.63	22.62	23.0
GPRS (4 slots)	25.44	25.56	25.62	26.0	22.87	22.79	22.79	23.0
EDGE (1 slot)	17.53	17.65	17.52	18.0	17.56	17.40	17.05	18.0
EDGE (2 slots)	19.34	19.39	19.33	19.5	19.49	19.33	18.97	19.5
EDGE (3 slots)	18.85	18.83	18.80	19.0	19.04	18.86	18.54	19.5
EDGE (4 slots)	18.86	18.80	18.65	19.0	19.06	18.89	18.53	19.5

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Duty cycle factor = 9 dB for 1 Tx slot, 6 dB for 2 Tx slots, 4.25 dB for 3 Tx slots, 3 dB for 4 Tx slots

Remark:

1. For Head SAR testing, GSM should be evaluated, therefore the EUT was set in GSM for GSM850 and GSM1900 due to its highest source-based time-average power.
2. For Body SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS (2TX slots) for GSM850 and

Waltek Testing Group (Shenzhen) Co., Ltd.

<http://www.semtest.com.cn>

GPRS (2TX slots) for GSM1900 due to its highest source-based time-average power.

3. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
4. The DUT do not support DTM function.
5. The DUT do not support Hotspot function.

WCDMA - Average Power (dBm)								
Band	WCDMA Band II				WCDMA Band V			
Channel	9262	9400	9538	Tune-up power (dBm)	4132	4183	4233	Tune-up power (dBm)
Frequency (MHz)	1852.4	1880.0	1907.6		826.4	836.4	846.6	
RMC 12.2k	22.96	22.96	22.99	23.00	22.96	23.10	22.97	23.50
HSDPA Subtest-1	21.96	22.00	21.99	22.50	21.91	22.03	22.00	22.50
HSDPA Subtest-2	21.95	21.96	21.95	22.00	21.87	22.01	21.96	22.50
HSDPA Subtest-3	21.93	21.97	21.95	22.00	21.89	22.02	21.98	22.50
HSDPA Subtest-4	21.92	21.98	21.94	22.00	21.87	22.01	21.97	22.50
HSUPA Subtest-1	21.90	22.00	21.92	22.50	21.73	21.97	21.89	22.00
HSUPA Subtest-2	21.87	21.95	21.91	22.00	21.71	21.95	21.85	22.00
HSUPA Subtest-3	21.85	21.97	21.89	22.00	21.72	21.96	21.86	22.00
HSUPA Subtest-4	21.86	21.98	21.87	22.00	21.71	21.95	21.85	22.00
HSUPA Subtest-5	21.87	21.97	21.86	22.00	21.71	21.95	21.86	22.00

WCDMA - Average Power (dBm)								
Band	WCDMA Band VI							
Channel	1312	1412	1513	Tune-up power (dBm)				
Frequency (MHz)	1712.4	1732.4	1752.6					
RMC 12.2k	22.98	22.87	22.80	23.00				
HSDPA Subtest-1	22.00	21.87	21.80	22.50				
HSDPA Subtest-2	21.96	21.85	21.78	22.00				
HSDPA Subtest-3	21.97	21.85	21.79	22.00				
HSDPA Subtest-4	21.98	21.84	21.76	22.00				
HSUPA Subtest-1	21.88	21.85	21.76	22.00				
HSUPA Subtest-2	21.85	21.82	21.75	22.00				
HSUPA Subtest-3	21.86	21.82	21.73	22.00				
HSUPA Subtest-4	21.85	21.83	21.74	22.00				
HSUPA Subtest-5	21.85	21.82	21.74	22.00				

Remark:

1. per KDB 941225 D01 v03, The 12.2kbps RMC mode was selected for SAR testing(the primary mode).
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR

Waltek Testing Group (Shenzhen) Co., Ltd.

<http://www.semtest.com.cn>

measurement is not required for the secondary mode

FDD-LTE Band 2:

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.03	0
		1	3	23.06	0
		1	5	22.98	0
		3	0	23.07	0
		3	2	23.05	0
		3	3	23.06	0
		6	0	22.05	1
	MCH	1	0	22.56	0
		1	3	22.67	0
		1	5	22.54	0
		3	0	22.61	0
		3	2	22.66	0
		3	3	22.67	0
		6	0	21.66	1
	HCH	1	0	22.89	0
		1	3	22.99	0
		1	5	22.90	0
		3	0	22.86	0
		3	2	22.91	0
		3	3	22.91	0
		6	0	22.00	1
16QAM	LCH	1	0	22.31	1
		1	3	22.48	1
		1	5	22.32	1
		3	0	22.05	1
		3	2	22.06	1
		3	3	22.08	1
		6	0	20.98	2
	MCH	1	0	21.79	1
		1	3	21.92	1
		1	5	21.84	1
		3	0	21.67	1
		3	2	21.72	1
		3	3	21.71	1
		6	0	20.77	2
HCH	1	0	22.02	1	
	1	3	22.15	1	

		1	5	22.04	1
		3	0	21.99	1
		3	2	22.00	1
		3	3	22.01	1
		6	0	20.87	2

Channel Bandwidth: 3 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.00	0
		1	7	23.05	0
		1	14	22.90	0
		8	0	22.02	1
		8	4	21.99	1
		8	7	21.97	1
		15	0	21.98	1
	MCH	1	0	22.59	0
		1	7	22.77	0
		1	14	22.64	0
		8	0	21.63	1
		8	4	21.63	1
		8	7	21.63	1
		15	0	21.55	1
	HCH	1	0	22.97	0
		1	7	23.13	0
		1	14	22.93	0
		8	0	21.92	1
		8	4	21.94	1
		8	7	21.91	1
		15	0	21.94	1
16QAM	LCH	1	0	22.29	1
		1	7	22.49	1
		1	14	22.15	1
		8	0	21.05	2
		8	4	21.08	2
		8	7	21.00	2
		15	0	20.94	2
	MCH	1	0	21.90	1
		1	7	22.12	1
		1	14	21.98	1
		8	0	20.61	2
		8	4	20.60	2

		8	7	20.59	2
		15	0	20.57	2
	HCH	1	0	22.20	1
		1	7	22.45	1
		1	14	22.11	1
		8	0	20.85	2
		8	4	20.89	2
		8	7	20.84	2
		15	0	20.89	2

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.08	0
		1	12	23.23	0
		1	24	22.90	0
		12	0	22.03	1
		12	6	22.00	1
		12	13	21.89	1
		25	0	21.99	1
	MCH	1	0	22.61	0
		1	12	22.84	0
		1	24	22.67	0
		12	0	21.66	1
		12	6	21.63	1
		12	13	21.63	1
		25	0	21.65	1
	HCH	1	0	23.03	0
		1	12	23.17	0
		1	24	23.02	0
		12	0	22.00	1
		12	6	21.96	1
		12	13	21.93	1
		25	0	21.95	1
16QAM	LCH	1	0	22.35	1
		1	12	22.41	1
		1	24	22.15	1
		12	0	21.10	2
		12	6	21.06	2
		12	13	20.98	2
		25	0	21.04	2
	MCH	1	0	21.81	1

		1	12	22.07	1
		1	24	21.93	1
		12	0	20.68	2
		12	6	20.70	2
		12	13	20.70	2
		25	0	20.62	2
	HCH	1	0	22.18	1
		1	12	22.34	1
		1	24	22.10	1
		12	0	20.96	2
		12	6	20.89	2
		12	13	20.88	2
		25	0	20.94	2

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.01	0
		1	24	22.94	0
		1	49	22.68	0
		25	0	22.03	1
		25	12	21.91	1
		25	25	21.87	1
		50	0	21.90	1
	MCH	1	0	22.53	0
		1	24	22.69	0
		1	49	22.67	0
		25	0	21.69	1
		25	12	21.63	1
		25	25	21.70	1
		50	0	21.62	1
	HCH	1	0	22.97	0
		1	24	23.03	0
		1	49	22.94	0
		25	0	22.05	1
		25	12	21.99	1
		25	25	21.94	1
		50	0	21.97	1
16QAM	LCH	1	0	22.28	1
		1	24	22.22	1
		1	49	21.95	1
		25	0	21.10	2

		25	12	20.98	2
		25	25	20.92	2
		50	0	20.96	2
	MCH	1	0	21.91	1
		1	24	22.09	1
		1	49	22.12	1
		25	0	20.70	2
		25	12	20.64	2
		25	25	20.72	2
		50	0	20.68	2
	HCH	1	0	22.15	1
		1	24	22.28	1
		1	49	22.11	1
		25	0	21.06	2
		25	12	20.97	2
25		25	20.95	2	
50		0	20.99	2	

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.95	0
		1	37	22.83	0
		1	74	22.43	0
		37	0	21.99	1
		37	18	21.79	1
		37	38	21.76	1
		75	0	21.85	1
	MCH	1	0	22.53	0
		1	37	22.83	0
		1	74	22.62	0
		37	0	21.77	1
		37	18	21.72	1
		37	38	21.75	1
		75	0	21.77	1
	HCH	1	0	22.89	0
		1	37	23.12	0
		1	74	22.88	0
		37	0	22.13	1
		37	18	22.06	1
		37	38	21.94	1
		75	0	22.06	1

16QAM	LCH	1	0	22.25	1
		1	37	22.19	1
		1	74	21.77	1
		37	0	20.90	2
		37	18	20.77	2
		37	38	20.72	2
		75	0	20.85	2
	MCH	1	0	21.75	1
		1	37	22.05	1
		1	74	21.98	1
		37	0	20.71	2
		37	18	20.67	2
		37	38	20.74	2
		75	0	20.70	2
	HCH	1	0	22.04	1
		1	37	22.28	1
		1	74	22.06	1
		37	0	21.03	2
		37	18	20.98	2
		37	38	20.91	2
		75	0	21.01	2

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.25	0
		1	49	22.10	0
		1	99	22.38	0
		50	0	21.82	1
		50	25	21.73	1
		50	50	21.70	1
		100	0	21.77	1
	MCH	1	0	22.47	0
		1	49	22.77	0
		1	99	22.65	0
		50	0	21.69	1
		50	25	21.63	1
		50	50	21.75	1
		100	0	21.74	1
	HCH	1	0	22.58	0
		1	49	22.95	0
		1	99	22.67	0

		50	0	21.97	1
		50	25	21.98	1
		50	50	21.84	1
		100	0	21.88	1
16QAM	LCH	1	0	22.14	1
		1	49	22.08	1
		1	99	21.56	1
		50	0	20.83	2
		50	25	20.72	2
		50	50	20.67	2
		100	0	20.74	2
	MCH	1	0	21.76	1
		1	49	22.11	1
		1	99	22.00	1
		50	0	20.70	2
		50	25	20.68	2
		50	50	20.78	2
		100	0	20.69	2
	HCH	1	0	21.89	1
		1	49	22.21	1
		1	99	21.92	1
		50	0	20.94	2
		50	25	20.93	2
		50	50	20.89	2
		100	0	20.87	2

FDD-LTE Band 4:

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.03	0
		1	3	23.09	0
		1	5	22.94	0
		3	0	23.06	0
		3	2	23.07	0
		3	3	23.08	0
		6	0	22.1	1
	MCH	1	0	22.55	0
		1	3	22.56	0
		1	5	22.61	0
		3	0	22.53	0

		3	2	22.64	0
		3	3	22.66	0
		6	0	21.51	1
	HCH	1	0	24.05	0
		1	3	24.17	0
		1	5	24.09	0
		3	0	24.11	0
		3	2	24.23	0
		3	3	24.14	0
		6	0	23.12	1
16QAM	LCH	1	0	22.28	1
		1	3	22.23	1
		1	5	22.19	1
		3	0	22.24	1
		3	2	22.16	1
		3	3	22.15	1
		6	0	21.04	2
	MCH	1	0	21.53	1
		1	3	21.72	1
		1	5	21.59	1
		3	0	21.56	1
		3	2	21.62	1
		3	3	21.53	1
		6	0	20.92	2
	HCH	1	0	23.26	1
		1	3	23.39	1
		1	5	23.31	1
		3	0	23.22	1
		3	2	23.22	1
		3	3	23.24	1
		6	0	22.26	2

Channel Bandwidth: 3 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.04	0
		1	7	23.12	0
		1	14	22.8	0
		8	0	22.03	1
		8	4	21.98	1
		8	7	21.93	1
		15	0	21.93	1

	MCH	1	0	22.55	0
		1	7	22.65	0
		1	14	22.63	0
		8	0	21.68	1
		8	4	21.65	1
		8	7	21.73	1
		15	0	21.71	1
	HCH	1	0	23.98	0
		1	7	24.28	0
		1	14	24.14	0
		8	0	23.01	1
		8	4	23.07	1
		8	7	23.1	1
		15	0	23.01	1
16QAM	LCH	1	0	22.36	1
		1	7	22.44	1
		1	14	22.16	1
		8	0	21.07	2
		8	4	21.05	2
		8	7	20.97	2
		15	0	20.9	2
	MCH	1	0	21.56	1
		1	7	21.85	1
		1	14	21.72	1
		8	0	20.53	2
		8	4	20.55	2
		8	7	20.57	2
		15	0	20.53	2
	HCH	1	0	23.23	1
		1	7	23.49	1
		1	14	23.39	1
		8	0	21.98	2
		8	4	22.03	2
		8	7	22.07	2
		15	0	22.03	2

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.08	0
		1	12	23.13	0
		1	24	22.73	0

		12	0	22.95	1
		12	6	22.96	1
		12	13	22.83	1
		25	0	21.91	1
	MCH	1	0	22.57	0
		1	12	22.55	0
		1	24	22.62	0
		12	0	23.23	1
		12	6	23.29	1
		12	13	23.31	1
		25	0	22.5	1
	HCH	1	0	23.87	0
		1	12	24.25	0
		1	24	24.21	0
		12	0	22.94	1
		12	6	23.02	1
		12	13	23.09	1
25		0	23	1	
16QAM	LCH	1	0	22.32	1
		1	12	22.44	1
		1	24	22.03	1
		12	0	21.96	2
		12	6	21.96	2
		12	13	21.84	2
		25	0	20.91	2
	MCH	1	0	21.57	1
		1	12	21.89	1
		1	24	21.64	1
		12	0	21.57	2
		12	6	21.63	2
		12	13	21.75	2
		25	0	21.43	2
	HCH	1	0	23.03	1
		1	12	23.44	1
		1	24	23.34	1
		12	0	21.91	2
		12	6	21.97	2
		12	13	22.05	2
		25	0	22.06	2

Channel Bandwidth: 10 MHz				
Modulation	Channel	RB Configuration	Average Power [dBm]	MPR (dB)

		Size	Offset		
QPSK	LCH	1	0	23	0
		1	24	22.77	0
		1	49	22.53	0
		25	0	21.9	1
		25	12	21.72	1
		25	25	21.66	1
		50	0	21.75	1
	MCH	1	0	22.71	0
		1	24	22.75	0
		1	49	22.78	0
		25	0	21.51	1
		25	12	21.67	1
		25	25	21.58	1
		50	0	21.65	1
	HCH	1	0	23.32	0
		1	24	23.86	0
		1	49	24.09	0
		25	0	22.64	1
		25	12	22.76	1
		25	25	22.96	1
		50	0	22.77	1
16QAM	LCH	1	0	22.36	1
		1	24	22.1	1
		1	49	21.65	1
		25	0	20.93	2
		25	12	20.69	2
		25	25	20.65	2
		50	0	20.74	2
	MCH	1	0	21.51	1
		1	24	21.78	1
		1	49	21.89	1
		25	0	20.59	2
		25	12	20.64	2
		25	25	20.52	2
		50	0	20.63	2
	HCH	1	0	22.54	1
		1	24	23.13	1
		1	49	23.39	1
		25	0	21.63	2
		25	12	21.72	2
		25	25	21.94	2

		50	0	21.74	2
--	--	----	---	-------	---

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.97	0
		1	37	22.68	0
		1	74	22.69	0
		37	0	21.79	1
		37	18	21.62	1
		37	38	21.71	1
		75	0	22.07	1
	MCH	1	0	22.63	0
		1	37	22.5	0
		1	74	22.71	0
		37	0	21.58	1
		37	18	21.51	1
		37	38	21.62	1
		75	0	21.62	1
	HCH	1	0	22.89	0
		1	37	23.42	0
		1	74	23.66	0
		37	0	22.24	1
		37	18	22.47	1
		37	38	22.68	1
		75	0	22.46	1
16QAM	LCH	1	0	22.29	1
		1	37	21.88	1
		1	74	21.69	1
		37	0	21.26	2
		37	18	20.97	2
		37	38	20.8	2
		75	0	21.05	2
	MCH	1	0	21.72	1
		1	37	21.91	1
		1	74	22.03	1
		37	0	20.53	2
		37	18	20.59	2
		37	38	20.68	2
		75	0	20.63	2
HCH	1	0	22.18	1	
	1	37	22.8	1	

		1	74	22.91	1
		37	0	21.17	2
		37	18	21.4	2
		37	38	21.58	2
		75	0	21.38	2

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.51	0
		1	49	22.95	0
		1	99	22.66	0
		50	0	22.02	1
		50	25	21.77	1
		50	50	21.54	1
		100	0	21.75	1
	MCH	1	0	22.67	0
		1	49	22.6	0
		1	99	22.78	0
		50	0	21.61	1
		50	25	21.5	1
		50	50	21.71	1
		100	0	21.66	1
	HCH	1	0	22.51	0
		1	49	24.21	0
		1	99	24.32	0
		50	0	22.91	1
		50	25	22.23	1
		50	50	22.44	1
		100	0	22.21	1
16QAM	LCH	1	0	22.71	1
		1	49	22.14	1
		1	99	21.63	1
		50	0	21.02	2
		50	25	20.75	2
		50	50	20.52	2
		100	0	20.75	2
	MCH	1	0	21.75	1
		1	49	21.97	1
		1	99	22.14	1
		50	0	20.65	2
		50	25	20.55	2

		50	50	20.77	2
		100	0	20.68	2
	HCH	1	0	21.69	1
		1	49	22.51	1
		1	99	22.72	1
		50	0	20.9	2
		50	25	21.22	2
		50	50	21.43	2
		100	0	21.21	2

FDD-LTE Band 5:

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.27	0
		1	3	23.42	0
		1	5	23.31	0
		3	0	23.35	0
		3	2	23.38	0
		3	3	23.36	0
		6	0	22.36	1
	MCH	1	0	23.26	0
		1	3	23.33	0
		1	5	23.24	0
		3	0	23.31	0
		3	2	23.3	0
		3	3	23.33	0
		6	0	22.33	1
	HCH	1	0	23.18	0
		1	3	23.28	0
		1	5	23.15	0
		3	0	23.18	0
		3	2	23.21	0
		3	3	23.18	0
		6	0	22.35	1
16QAM	LCH	1	0	22.58	1
		1	3	22.74	1
		1	5	22.61	1
		3	0	22.5	1
		3	2	22.51	1
		3	3	22.52	1
		6	0	21.34	2
	MCH	1	0	22.58	1
		1	3	22.72	1
		1	5	22.58	1
		3	0	22.29	1
		3	2	22.32	1
		3	3	22.3	1
		6	0	21.28	2
HCH	1	0	22.28	1	
	1	3	22.53	1	

		1	5	22.28	1
		3	0	22.21	1
		3	2	22.21	1
		3	3	22.21	1
		6	0	21.34	2

Channel Bandwidth: 3 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.36	0
		1	7	23.54	0
		1	14	23.34	0
		8	0	22.40	1
		8	4	22.44	1
		8	7	22.40	1
		15	0	22.37	1
	MCH	1	0	23.34	0
		1	7	23.53	0
		1	14	23.31	0
		8	0	22.39	1
		8	4	22.42	1
		8	7	22.36	1
		15	0	22.33	1
	HCH	1	0	23.30	0
		1	7	23.46	0
		1	14	23.22	0
		8	0	22.34	1
		8	4	22.30	1
		8	7	22.26	1
		15	0	22.24	1
16QAM	LCH	1	0	22.69	1
		1	7	22.84	1
		1	14	22.65	1
		8	0	21.44	2
		8	4	21.49	2
		8	7	21.45	2
		15	0	21.32	2
	MCH	1	0	22.64	1
		1	7	22.87	1
		1	14	22.72	1
		8	0	21.36	2
		8	4	21.38	2

		8	7	21.35	2
		15	0	21.30	2
	HCH	1	0	22.51	1
		1	7	22.56	1
		1	14	22.33	1
		8	0	21.21	2
		8	4	21.25	2
		8	7	21.14	2
		15	0	21.18	2

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.39	0
		1	12	23.63	0
		1	24	23.38	0
		12	0	22.59	1
		12	6	22.54	1
		12	13	22.55	1
		25	0	22.41	1
	MCH	1	0	23.36	0
		1	12	23.57	0
		1	24	23.32	0
		12	0	22.69	1
		12	6	22.64	1
		12	13	22.65	1
		25	0	22.39	1
	HCH	1	0	23.41	0
		1	12	23.62	0
		1	24	23.32	0
		12	0	22.68	1
		12	6	22.64	1
		12	13	22.65	1
		25	0	22.28	1
16QAM	LCH	1	0	22.68	1
		1	12	22.91	1
		1	24	22.62	1
		12	0	21.53	2
		12	6	21.5	2
		12	13	21.68	2
		25	0	21.41	2
	MCH	1	0	22.54	1

		1	12	22.77	1
		1	24	22.57	1
		12	0	21.56	2
		12	6	21.52	2
		12	13	21.64	2
		25	0	21.4	2
	HCH	1	0	22.57	1
		1	12	22.67	1
		1	24	22.37	1
		12	0	21.55	2
		12	6	21.63	2
		12	13	21.66	2
		25	0	21.27	2

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.34	0
		1	24	23.41	0
		1	49	23.31	0
		25	0	22.43	1
		25	12	22.39	1
		25	25	22.46	1
		50	0	22.38	1
	MCH	1	0	23.67	0
		1	24	23.42	0
		1	49	23.29	0
		25	0	22.45	1
		25	12	22.35	1
		25	25	22.42	1
		50	0	22.38	1
	HCH	1	0	23.42	0
		1	24	23.45	0
		1	49	23.24	0
		25	0	22.45	1
		25	12	22.40	1
		25	25	22.34	1
		50	0	22.35	1
16QAM	LCH	1	0	22.66	1
		1	24	22.69	1
		1	49	22.55	1
		25	0	21.45	2

		25	12	21.40	2
		25	25	21.46	2
		50	0	21.38	2
	MCH	1	0	22.70	1
		1	24	22.77	1
		1	49	22.72	1
		25	0	21.46	2
		25	12	21.37	2
		25	25	21.46	2
		50	0	21.44	2
	HCH	1	0	22.69	1
		1	24	22.72	1
		1	49	22.36	1
		25	0	21.50	2
		25	12	21.40	2
25		25	21.30	2	
50		0	21.42	2	

FDD-LTE Band 7:

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.39	0
		1	12	23.62	0
		1	24	23.39	0
		12	0	22.37	1
		12	6	22.36	1
		12	13	22.34	1
		25	0	22.32	1
	MCH	1	0	23.89	0
		1	12	24.16	0
		1	24	23.94	0
		12	0	22.83	1
		12	6	22.91	1
		12	13	22.88	1
		25	0	22.85	1
	HCH	1	0	23.35	0
		1	12	23.29	0
		1	24	23.07	0
		12	0	22.22	1
		12	6	22.20	1

		12	13	22.07	1
		25	0	22.11	1
16QAM	LCH	1	0	22.51	1
		1	12	22.78	1
		1	24	22.54	1
		12	0	21.40	2
		12	6	21.41	2
		12	13	21.34	2
		25	0	21.41	2
		MCH	1	0	23.04
	1		12	23.31	1
	1		24	23.11	1
	12		0	22.00	2
	12		6	22.07	2
	12		13	21.96	2
	25		0	21.90	2
	HCH	1	0	22.47	1
		1	12	22.52	1
		1	24	22.12	1
		12	0	21.23	2
		12	6	21.24	2
		12	13	21.07	2
		25	0	21.24	2

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.36	0
		1	24	23.4	0
		1	49	23.39	0
		25	0	22.38	1
		25	12	22.33	1
		25	25	22.38	1
		50	0	22.34	1
	MCH	1	0	23.8	0
		1	24	23.96	0
		1	49	23.95	0
		25	0	22.87	1
		25	12	22.86	1
		25	25	22.93	1
		50	0	22.89	1
	HCH	1	0	23.58	0

		1	24	23.39	0	
		1	49	23.02	0	
		25	0	22.48	1	
		25	12	22.26	1	
		25	25	22.2	1	
		50	0	22.29	1	
16QAM	LCH	1	0	22.52	1	
		1	24	22.59	1	
		1	49	22.61	1	
		25	0	21.41	2	
		25	12	21.36	2	
		25	25	21.4	2	
	MCH	50	0	21.36	2	
		1	0	22.62	1	
		1	24	22.46	1	
		1	49	22.68	1	
		25	0	21.94	2	
		25	12	21.92	2	
	HCH	25	25	22.02	2	
		50	0	21.97	2	
		1	0	22.8	1	
		1	24	22.61	1	
		1	49	22.16	1	
		25	0	21.56	2	
			25	12	21.39	2
			25	25	21.27	2
			50	0	21.41	2

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.31	0
		1	37	23.45	0
		1	74	23.38	0
		37	0	22.49	1
		37	18	22.49	1
		37	38	22.48	1
	MCH	75	0	22.48	1
		1	0	23.78	0
		1	37	24.06	0
		1	74	23.89	0
		37	0	22.88	1

		37	18	22.95	1
		37	38	22.94	1
		75	0	22.98	1
	HCH	1	0	23.82	0
		1	37	23.62	0
		1	74	22.96	0
		37	0	22.79	1
		37	18	22.56	1
		37	38	22.30	1
16QAM	LCH	1	0	22.51	1
		1	37	22.66	1
		1	74	22.59	1
		37	0	21.43	2
		37	18	21.41	2
		37	38	21.45	2
		75	0	21.46	2
	MCH	1	0	23.00	1
		1	37	23.31	1
		1	74	23.17	1
		37	0	21.91	2
		37	18	21.96	2
		37	38	22.01	2
		75	0	21.97	2
	HCH	1	0	22.98	1
1		37	22.79	1	
1		74	22.13	1	
37		0	21.70	2	
37		18	21.55	2	
37		38	21.28	2	
75		0	21.59	2	

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.30	0
		1	49	23.61	0
		1	99	23.45	0
		50	0	22.35	1
		50	25	22.37	1
		50	50	22.46	1
		100	0	22.40	1

	MCH	1	0	23.64	0
		1	49	24.26	0
		1	99	23.91	0
		50	0	22.79	1
		50	25	22.92	1
		50	50	22.89	1
		100	0	22.83	1
	HCH	1	0	23.74	0
		1	49	23.66	0
		1	99	22.76	0
		50	0	22.83	1
		50	25	22.64	1
		50	50	22.39	1
16QAM	LCH	100	0	22.58	1
		1	0	22.39	1
		1	49	22.74	1
		1	99	22.52	1
		50	0	21.37	2
		50	25	21.39	2
		50	50	21.49	2
	MCH	100	0	21.44	2
		1	0	22.89	1
		1	49	23.35	1
		1	99	23.18	1
		50	0	21.89	2
		50	25	22.00	2
		50	50	22.00	2
HCH	100	0	21.90	2	
	1	0	22.98	1	
	1	49	22.93	1	
	1	99	22.03	1	
	50	0	21.90	2	
	50	25	21.69	2	
	50	50	21.44	2	
100	0	21.63	2		

FDD-LTE Band 38:

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.85	0
		1	12	23.06	0
		1	24	22.81	0
		12	0	21.91	1
		12	6	21.91	1
		12	13	21.85	1
		25	0	21.88	1
	MCH	1	0	22.78	0
		1	12	22.99	0
		1	24	22.75	0
		12	0	21.74	1
		12	6	21.78	1
		12	13	21.79	1
		25	0	21.77	1
	HCH	1	0	22.81	0
		1	12	23.07	0
		1	24	22.81	0
		12	0	21.87	1
		12	6	21.84	1
		12	13	21.82	1
		25	0	21.81	1
16QAM	LCH	1	0	22.01	1
		1	12	22.23	1
		1	24	22.01	1
		12	0	20.94	2
		12	6	20.95	2
		12	13	20.89	2
		25	0	20.90	2
	MCH	1	0	22.11	1
		1	12	22.30	1
		1	24	22.07	1
		12	0	20.86	2
		12	6	20.88	2
		12	13	20.85	2
		25	0	20.80	2
HCH	1	0	22.03	1	
	1	12	22.25	1	

		1	24	22.04	1
		12	0	20.78	2
		12	6	20.79	2
		12	13	20.77	2
		25	0	20.83	2

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.86	0
		1	24	22.88	0
		1	49	22.77	0
		25	0	21.91	1
		25	12	21.91	1
		25	25	21.86	1
		50	0	21.89	1
	MCH	1	0	22.88	0
		1	24	22.94	0
		1	49	22.79	0
		25	0	21.86	1
		25	12	21.88	1
		25	25	21.86	1
		50	0	21.85	1
	HCH	1	0	22.85	0
		1	24	22.95	0
		1	49	22.84	0
		25	0	21.91	1
		25	12	21.91	1
		25	25	21.86	1
		50	0	21.90	1
16QAM	LCH	1	0	22.13	1
		1	24	22.14	1
		1	49	22.01	1
		25	0	20.94	2
		25	12	20.90	2
		25	25	20.90	2
		50	0	20.89	2
	MCH	1	0	22.19	1
		1	24	22.20	1
		1	49	22.13	1
		25	0	20.90	2
		25	12	20.91	2

		25	25	20.88	2
		50	0	20.94	2
	HCH	1	0	22.20	1
		1	24	22.28	1
		1	49	22.21	1
		25	0	20.89	2
		25	12	20.91	2
		25	25	20.86	2
		50	0	20.89	2

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.86	0
		1	37	23.04	0
		1	74	22.74	0
		37	0	21.93	1
		37	18	21.89	1
		37	38	21.86	1
		75	0	21.91	1
	MCH	1	0	22.83	0
		1	37	23.00	0
		1	74	22.72	0
		37	0	21.86	1
		37	18	21.86	1
		37	38	21.86	1
		75	0	21.86	1
	HCH	1	0	22.79	0
		1	37	23.03	0
		1	74	22.75	0
		37	0	21.92	1
		37	18	21.90	1
		37	38	21.89	1
		75	0	21.89	1
16QAM	LCH	1	0	22.05	1
		1	37	22.29	1
		1	74	21.95	1
		37	0	20.88	2
		37	18	20.86	2
		37	38	20.82	2
		75	0	20.91	2
	MCH	1	0	22.08	1

		1	37	22.26	1
		1	74	21.98	1
		37	0	20.87	2
		37	18	20.84	2
		37	38	20.82	2
		75	0	20.86	2
	HCH	1	0	22.14	1
		1	37	22.39	1
		1	74	22.13	1
		37	0	20.84	2
		37	18	20.83	2
		37	38	20.81	2
		75	0	20.87	2

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	22.93	0
		1	49	23.08	0
		1	99	22.65	0
		50	0	21.98	1
		50	25	21.93	1
		50	50	21.88	1
		100	0	21.93	1
	MCH	1	0	22.80	0
		1	49	22.99	0
		1	99	22.67	0
		50	0	21.84	1
		50	25	21.87	1
		50	50	21.79	1
		100	0	21.82	1
	HCH	1	0	22.63	0
		1	49	22.89	0
		1	99	22.63	0
		50	0	21.87	1
		50	25	21.85	1
		50	50	21.77	1
		100	0	21.82	1
16QAM	LCH	1	0	22.10	1
		1	49	22.22	1
		1	99	21.93	1
		50	0	20.99	2

		50	25	20.92	2
		50	50	20.89	2
		100	0	20.93	2
	MCH	1	0	22.11	1
		1	49	22.29	1
		1	99	22.00	1
		50	0	20.90	2
		50	25	20.93	2
		50	50	20.89	2
		100	0	20.87	2
	HCH	1	0	21.81	1
		1	49	22.05	1
		1	99	21.80	1
		50	0	20.87	2
		50	25	20.86	2
50		50	20.77	2	
100		0	20.85	2	

FDD-LTE Band 41:

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.29	0
		1	12	23.49	0
		1	24	23.25	0
		12	0	22.3	1
		12	6	22.28	1
		12	13	22.27	1
		25	0	22.24	1
	MCH	1	0	22.97	0
		1	12	23.18	0
		1	24	22.94	0
		12	0	22.29	1
		12	6	22.18	1
		12	13	22.08	1
		25	0	21.96	1
	HCH	1	0	23.53	0
		1	12	23.85	0
		1	24	23.59	0
		12	0	22.57	1
		12	6	22.6	1

		12	13	22.61	1
		25	0	22.55	1
16QAM	LCH	1	0	22.45	1
		1	12	22.66	1
		1	24	22.41	1
		12	0	21.29	2
		12	6	21.28	2
		12	13	21.28	2
		25	0	21.24	2
		MCH	1	0	22.33
	1		12	22.51	1
	1		24	22.3	1
	12		0	21.04	2
	12		6	21.06	2
	12		13	21.06	2
	25		0	20.98	2
	HCH	1	0	22.63	1
		1	12	22.87	1
		1	24	22.69	1
		12	0	21.53	2
		12	6	21.55	2
		12	13	21.53	2
		25	0	21.5	2

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.31	0
		1	24	23.30	0
		1	49	23.25	0
		25	0	22.28	1
		25	12	22.26	1
		25	25	22.33	1
		50	0	22.30	1
	MCH	1	0	22.99	0
		1	24	22.95	0
		1	49	22.91	0
		25	0	21.94	1
		25	12	21.94	1
		25	25	21.94	1
		50	0	21.93	1
	HCH	1	0	23.43	0

		1	24	23.56	0	
		1	49	23.57	0	
		25	0	22.53	1	
		25	12	22.54	1	
		25	25	22.58	1	
		50	0	22.51	1	
16QAM	LCH	1	0	22.54	1	
		1	24	22.55	1	
		1	49	22.47	1	
		25	0	21.29	2	
		25	12	21.28	2	
		25	25	21.33	2	
	MCH	50	0	21.29	2	
		1	0	22.32	1	
		1	24	22.29	1	
		1	49	22.24	1	
		25	0	20.97	2	
		25	12	20.96	2	
	HCH	25	25	20.95	2	
		50	0	20.96	2	
		1	0	22.65	1	
		1	24	22.69	1	
		1	49	22.70	1	
		25	0	21.49	2	
			25	12	21.52	2
			25	25	21.52	2
			50	0	21.47	2

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.24	0
		1	37	23.36	0
		1	74	23.12	0
		37	0	22.26	1
		37	18	22.27	1
		37	38	22.25	1
	MCH	75	0	22.28	1
		1	0	22.94	0
		1	37	23.09	0
		1	74	22.87	0
		37	0	21.97	1

		37	18	21.97	1
		37	38	21.97	1
		75	0	21.95	1
	HCH	1	0	23.38	0
		1	37	23.69	0
		1	74	23.46	0
		37	0	22.55	1
		37	18	22.53	1
		37	38	22.63	1
16QAM	LCH	1	0	22.46	1
		1	37	22.61	1
		1	74	22.31	1
		37	0	21.20	2
		37	18	21.19	2
		37	38	21.18	2
		75	0	21.23	2
	MCH	1	0	22.21	1
		1	37	22.36	1
		1	74	22.11	1
		37	0	20.93	2
		37	18	20.95	2
		37	38	20.91	2
		75	0	20.94	2
	HCH	1	0	22.58	1
		1	37	22.80	1
		1	74	22.63	1
		37	0	21.43	2
37		18	21.46	2	
37		38	21.53	2	
75		0	21.50	2	

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	MPR (dB)
		Size	Offset		
QPSK	LCH	1	0	23.86	0
		1	49	23.26	0
		1	99	22.96	0
		50	0	22.18	1
		50	25	22.16	1
		50	50	22.14	1
		100	0	22.15	1

	MCH	1	0	22.89	0
		1	49	23.06	0
		1	99	22.82	0
		50	0	21.94	1
		50	25	21.96	1
		50	50	21.87	1
		100	0	21.90	1
	HCH	1	0	22.98	0
		1	49	23.27	0
		1	99	23.14	0
		50	0	22.16	1
		50	25	22.20	1
		50	50	22.20	1
		100	0	22.17	1
16QAM	LCH	1	0	22.38	1
		1	49	22.51	1
		1	99	22.21	1
		50	0	21.17	2
		50	25	21.15	2
		50	50	21.13	2
		100	0	21.16	2
	MCH	1	0	22.24	1
		1	49	22.34	1
		1	99	22.10	1
		50	0	20.94	2
		50	25	20.98	2
		50	50	20.93	2
		100	0	20.91	2
	HCH	1	0	22.16	1
		1	49	22.29	1
		1	99	22.15	1
		50	0	21.14	2
		50	25	21.21	2
		50	50	21.16	2
		100	0	21.19	2

Remark:

1. Per KDB941225 D05 v02r05, Start with the largest channel bandwidth then measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle, and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output

Waltek Testing Group (Shenzhen) Co., Ltd.
<http://www.semtest.com.cn>

power for that channel. 6 When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2. Per KDB941225 D05 v02r05, The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.

3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations, and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

4. Per KDB941225 D05 v02r05, For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in 5.2.1, 5.2.2, and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

WLAN(2.4G) - Maximum Average Power					
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)	Tune-up power (dBm)
802.11b	1Mbps	CH 01	2412	15.92	16.5
		CH 06	2437	16.07	16.5
		CH 11	2462	16.00	16.5
802.11g	6Mbps	CH 01	2412	13.61	14.0
		CH 06	2437	13.61	14.0
		CH 11	2462	13.68	14.0
802.11n (20MHz)	MCS0	CH 01	2412	13.48	14.0
		CH 06	2437	13.83	14.0
		CH 11	2462	13.01	14.0
802.11n (40MHz)	MCS0	CH 03	2422	10.88	12.0
		CH 06	2437	11.72	12.0
		CH 09	2452	11.02	12.0

Remark:

1. Per KDB 248227 D01 v02r02, For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.
2. Per KDB 248227 D01 v02r02, For 802.11b DSSS SAR measurements ,when the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration. When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.
- 3 .For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
4. Per KDB 248227 D01 v02r02, When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined by applying the following steps sequentially.
 - 1) The largest channel bandwidth configuration is selected among the multiple configurations in a frequency band with the same specified maximum output power.
 - 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
 - 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.

Bluetooth - Maximum Average Power			
Test Mode	Data Rate	Average Power(dBm)	Tune-up power (dBm)
GFSK	1Mbps	6.692	7.0
Pi/4 QDPSK	2Mbps	6.227	7.0
8DPSK	3Mbps	6.728	7.0

Bluetooth - Maximum Average Power					
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)	Tune-up power (dBm)
BLE	1Mbps	CH 00	2402	-6.859	-5.5
		CH 19	2440	-5.819	-5.5
		CH 39	2480	-5.758	-5.5

Remark:

Bluetooth maximum output power is 6.728dBm and Maximum Tune-Up output power is 7.0dBm,. Per KDB 447498 D01 V06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
7.0	5.01	5	2.441	1.57	3

The exclusion thresholds is $1.57 < 3$, therefore, the RF exposure evaluation is not required.

9.2 Test Results for Standalone SAR Test

Head SAR

GSM850 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
1.	GSM	Right Cheek	190	836.6	32.85	33.0	1.035	0.425	0.440
2.	GSM	Right Tilted	190	836.6	32.85	33.0	1.035	0.204	0.211
3.	GSM	Left Cheek	190	836.6	32.85	33.0	1.035	0.235	0.243
4.	GSM	Left Tilted	190	836.6	32.85	33.0	1.035	0.114	0.118

GSM1900 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	M Hz					
5.	GSM	Right Cheek	512	1850.2	30.00	30.5	1.122	0.303	0.340
6.	GSM	Right Tilted	512	1850.2	30.00	30.5	1.122	0.152	0.171
7.	GSM	Left Cheek	512	1850.2	30.00	30.5	1.122	0.157	0.176
8.	GSM	Left Tilted	512	1850.2	30.00	30.5	1.122	0.078	0.088

GPRS850 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
9.	GPRS_2TX	Right Cheek	251	848.8	31.85	32.0	1.035	0.736	0.762
10.	GPRS_2TX	Right Tilted	251	848.8	31.85	32.0	1.035	0.346	0.358
11.	GPRS_2TX	Left Cheek	251	848.8	31.85	32.0	1.035	0.481	0.498
12.	GPRS_2TX	Left Tilted	251	848.8	31.85	32.0	1.035	0.278	0.288

GPRS1900 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	M Hz					
13.	GPRS_2TX	Right Cheek	512	1850.2	25.94	26.0	1.014	0.436	0.442
14.	GPRS_2TX	Right Tilted	512	1850.2	25.94	26.0	1.014	0.206	0.209
15.	GPRS_2TX	Left Cheek	512	1850.2	25.94	26.0	1.014	0.232	0.235
16.	GPRS_2TX	Left Tilted	512	1850.2	25.94	26.0	1.014	0.124	0.126

WCDMA Band 2 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
17.	RMC	Right Cheek	9538	1907.6	22.99	23.00	1.002	0.418	0.419
18.	RMC	Right Tilted	9538	1907.6	22.99	23.00	1.002	0.204	0.204
19.	RMC	Left Cheek	9538	1907.6	22.99	23.00	1.002	0.236	0.237
20.	RMC	Left Tilted	9538	1907.6	22.99	23.00	1.002	0.146	0.146

WCDMA Band 4 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
21.	RMC	Right Cheek	1312	1712.4	22.98	23.00	1.005	0.757	0.760
22.	RMC	Right Tilted	1312	1712.4	22.98	23.00	1.005	0.355	0.357
23.	RMC	Left Cheek	1312	1712.4	22.98	23.00	1.005	0.414	0.416
24.	RMC	Left Tilted	1312	1712.4	22.98	23.00	1.005	0.276	0.277

WCDMA Band 5 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
25.	RMC	Right Cheek	4183	836.4	23.10	23.50	1.096	0.376	0.412
26.	RMC	Right Tilted	4183	836.4	23.10	23.50	1.096	0.137	0.150
27.	RMC	Left Cheek	4183	836.4	23.10	23.50	1.096	0.23	0.252
28.	RMC	Left Tilted	4183	836.4	23.10	23.50	1.096	0.128	0.140

LTE Band 2– Head SAR Test								
Plot No.	Mode	Test Position Head	Freque	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		ncy MHz					
29.	QPSK 20MHz 1RB	Right Cheek	1860.0	23.25	23.5	1.059	0.512	0.542
30.	QPSK 20MHz 1RB	Right Tilted	1860.0	23.25	23.5	1.059	0.251	0.266
31.	QPSK 20MHz 1RB	Left Cheek	1860.0	23.25	23.5	1.059	0.195	0.207
32.	QPSK 20MHz 1RB	Left Tilted	1860.0	23.25	23.5	1.059	0.109	0.115
33.	QPSK 20MHz 50%RB	Right Cheek	1860.0	21.82	22.5	1.169	0.421	0.492
34.	QPSK 20MHz 50%RB	Right Tilted	1860.0	21.82	22.5	1.169	0.145	0.170
35.	QPSK 20MHz 50%RB	Left Cheek	1860.0	21.82	22.5	1.169	0.144	0.168
36.	QPSK 20MHz 50%RB	Left Tilted	1860.0	21.82	22.5	1.169	0.067	0.078

LTE Band 4– Head SAR Test								
Plot No.	Mode	Test Position Head	Freque	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		ncy MHz					
37.	QPSK 20MHz 1RB	Right Cheek	1745.0	24.32	24.5	1.042	0.628	0.655
38.	QPSK 20MHz 1RB	Right Tilted	1745.0	24.32	24.5	1.042	0.307	0.320
39.	QPSK 20MHz 1RB	Left Cheek	1745.0	24.32	24.5	1.042	0.528	0.550
40.	QPSK 20MHz 1RB	Left Tilted	1745.0	24.32	24.5	1.042	0.289	0.301
41.	QPSK 20MHz 50%RB	Right Cheek	1745.0	22.78	23.5	1.180	0.501	0.591
42.	QPSK 20MHz 50%RB	Right Tilted	1745.0	22.78	23.5	1.180	0.255	0.301
43.	QPSK 20MHz 50%RB	Left Cheek	1745.0	22.78	23.5	1.180	0.244	0.288
44.	QPSK 20MHz 50%RB	Left Tilted	1745.0	22.78	23.5	1.180	0.127	0.150

LTE Band 5– Head SAR Test (M)								
Plot No.	Mode	Test Position Head	Freque ncy	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth		MHz					
45.	QPSK 10MHz 1RB	Right Cheek	836.5	23.67	24.0	1.079	0.372	0.401
46.	QPSK 10MHz 1RB	Right Tilted	836.5	23.67	24.0	1.079	0.151	0.163
47.	QPSK 10MHz 1RB	Left Cheek	836.5	23.67	24.0	1.079	0.25	0.270
48.	QPSK 10MHz 1RB	Left Tilted	836.5	23.67	24.0	1.079	0.112	0.121
49.	QPSK 10MHz 50%RB	Right Cheek	836.5	22.38	23.0	1.153	0.322	0.371
50.	QPSK 10MHz 50%RB	Right Tilted	836.5	22.38	23.0	1.153	0.108	0.125
51.	QPSK 10MHz 50%RB	Left Cheek	836.5	22.38	23.0	1.153	0.17	0.196
52.	QPSK 10MHz 50%RB	Left Tilted	836.5	22.38	23.0	1.153	0.082	0.095

LTE Band 7– Head SAR Test								
Plot No.	Mode	Test Position Head	Freque ncy	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth		MHz					
53.	QPSK 20MHz 1RB	Right Cheek	2535.0	24.26	24.5	1.057	0.646	0.683
54.	QPSK 20MHz 1RB	Right Tilted	2535.0	24.26	24.5	1.057	0.302	0.319
55.	QPSK 20MHz 1RB	Left Cheek	2535.0	24.26	24.5	1.057	0.157	0.166
56.	QPSK 20MHz 1RB	Left Tilted	2535.0	24.26	24.5	1.057	0.072	0.076
57.	QPSK 20MHz 50%RB	Right Cheek	2535.0	22.92	23.5	1.143	0.544	0.622
58.	QPSK 20MHz 50%RB	Right Tilted	2535.0	22.92	23.5	1.143	0.211	0.241
59.	QPSK 20MHz 50%RB	Left Cheek	2535.0	22.92	23.5	1.143	0.135	0.154
60.	QPSK 20MHz 50%RB	Left Tilted	2535.0	22.92	23.5	1.143	0.081	0.093

LTE Band 38– Head SAR Test								
Plot No.	Mode	Test Position Head	Freque ncy	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth		MHz					
61.	QPSK 20MHz 1RB	Right Cheek	2580.0	23.08	23.5	1.102	0.548	0.604
62.	QPSK 20MHz 1RB	Right Tilted	2580.0	23.08	23.5	1.102	0.246	0.271
63.	QPSK 20MHz 1RB	Left Cheek	2580.0	23.08	23.5	1.102	0.202	0.223
64.	QPSK 20MHz 1RB	Left Tilted	2580.0	23.08	23.5	1.102	0.112	0.123
65.	QPSK 20MHz 50%RB	Right Cheek	2580.0	21.93	22.5	1.140	0.434	0.495
66.	QPSK 20MHz 50%RB	Right Tilted	2580.0	21.93	22.5	1.140	0.21	0.239
67.	QPSK 20MHz 50%RB	Left Cheek	2580.0	21.93	22.5	1.140	0.185	0.211
68.	QPSK 20MHz 50%RB	Left Tilted	2580.0	21.93	22.5	1.140	0.101	0.115

LTE Band 41– Head SAR Test								
Plot No.	Mode	Test Position Head	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth		MHz					
69.	QPSK 20MHz 1RB	Right Cheek	2506.0	23.86	24.0	1.033	0.457	0.472
70.	QPSK 20MHz 1RB	Right Tilted	2506.0	23.86	24.0	1.033	0.214	0.221
71.	QPSK 20MHz 1RB	Left Cheek	2506.0	23.86	24.0	1.033	0.182	0.188
72.	QPSK 20MHz 1RB	Left Tilted	2506.0	23.86	24.0	1.033	0.082	0.085
73.	QPSK 20MHz 50%RB	Right Cheek	2506.0	22.18	23.0	1.208	0.344	0.415
74.	QPSK 20MHz 50%RB	Right Tilted	2506.0	22.18	24.0	1.521	0.261	0.397
75.	QPSK 20MHz 50%RB	Left Cheek	2506.0	22.18	24.0	1.521	0.135	0.205
76.	QPSK 20MHz 50%RB	Left Tilted	2506.0	22.18	24.0	1.521	0.101	0.154

WLAN 2.4GHz – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
77.	802.11b	Right Cheek	06	2437	16.07	16.5	1.104	0.126	0.139
78.	802.11b	Right Tilted	06	2437	16.07	16.5	1.104	0.064	0.071
79.	802.11b	Left Cheek	06	2437	16.07	16.5	1.104	0.175	0.193
80.	802.11b	Left Tilted	06	2437	16.07	16.5	1.104	0.092	0.102

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Body-worn SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
81.	GSM	Back	190	836.6	32.85	33.0	1.035	0.206	0.213
82.	GSM	Front	190	836.6	32.85	33.0	1.035	0.113	0.117

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
83.	GSM	Back	512	1850.2	30.00	30.5	1.122	0.222	0.249
84.	GSM	Front	512	1850.2	30.00	30.5	1.122	0.139	0.156

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
85.	RMC 12.2k	Back Side	9538	1907.6	22.99	23.00	1.002	0.216	0.216
86.	RMC 12.2k	Front Face	9538	1907.6	22.99	23.00	1.002	0.242	0.243

WCDMA Band 4 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
87.	RMC 12.2k	Back Side	1312	1712.4	22.98	23.00	1.005	0.666	0.669
88.	RMC 12.2k	Front Side	1312	1712.4	22.98	23.00	1.005	0.444	0.446

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
89.	RMC 12.2k	Back Side	4183	836.4	23.10	23.50	1.096	0.175	0.192
90.	RMC 12.2k	Front Side	4183	836.4	23.10	23.50	1.096	0.118	0.129

LTE Band 2–Body SAR Test (Gap: 10mm)									
Plot No.	Mode		Test Position Body	Frequency MHz	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB								

91.	RMC QPSK 20MHz 1RB	Back Side	1860.0	23.25	23.5	1.059	0.384	0.407
92.	RMC QPSK 20MHz 1RB	Front Side	1860.0	23.25	23.5	1.059	0.168	0.178
93.	RMC QPSK 20MHz 50%RB	Back Side	1860.0	21.82	22.5	1.169	0.221	0.258
94.	RMC QPSK 20MHz 50%RB	Front Side	1860.0	21.82	22.5	1.169	0.124	0.145

LTE Band 4–Body SAR Test (Gap: 10mm)

Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
95.	RMC QPSK 20MHz 1RB	Back Side	1745.0	24.32	24.5	1.042	0.675	0.704
96.	RMC QPSK 20MHz 1RB	Front Side	1745.0	24.32	24.5	1.042	0.375	0.391
97.	RMC QPSK 20MHz 50%RB	Back Side	1745.0	22.78	23.5	1.180	0.421	0.497
98.	RMC QPSK 20MHz 50%RB	Front Side	1745.0	22.78	23.5	1.180	0.152	0.179

LTE Band 5–Body SAR Test (Gap: 10mm)

Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
99.	RMC QPSK 10MHz 1RB	Back Side	836.5	23.67	24.0	1.079	0.217	0.234
100.	RMC QPSK 10MHz 1RB	Front Side	836.5	23.67	24.0	1.079	0.127	0.137
101.	RMC QPSK 10MHz 50%RB	Back Side	836.5	22.38	23.0	1.153	0.112	0.129
102.	RMC QPSK 10MHz 50%RB	Front Side	836.5	22.38	23.0	1.153	0.067	0.077

LTE Band 7–Body SAR Test (Gap: 10mm)

Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
103.	RMC QPSK 20MHz 1RB	Back Side	2535.0	24.26	24.5	1.057	0.59	0.624
104.	RMC QPSK 20MHz 1RB	Front Side	2535.0	24.26	24.5	1.057	0.241	0.255
105.	RMC QPSK 20MHz 50%RB	Back Side	2535.0	22.92	23.5	1.143	0.405	0.463
106.	RMC QPSK 20MHz 50%RB	Front Side	2535.0	22.92	23.5	1.143	0.151	0.173

LTE Band 38–Body SAR Test (Gap: 10mm)

Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
107.	RMC QPSK 20MHz 1RB	Back Side	2580.0	23.08	23.5	1.102	0.623	0.686
108.	RMC QPSK 20MHz 1RB	Front Side	2580.0	23.08	23.5	1.102	0.213	0.235
109.	RMC QPSK 20MHz 50%RB	Back Side	2580.0	21.93	22.5	1.140	0.495	0.564
110.	RMC QPSK 20MHz 50%RB	Front Side	2580.0	21.93	22.5	1.140	0.151	0.172

LTE Band 41–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
111.	RMC QPSK 20MHz 1RB	Back Side	2506.0	23.86	24.0	1.033	0.613	0.633
112.	RMC QPSK 20MHz 1RB	Front Side	2506.0	23.86	24.0	1.033	0.196	0.202
113.	RMC QPSK 20MHz 50%RB	Back Side	2506.0	22.18	23.0	1.208	0.425	0.513
114.	RMC QPSK 20MHz 50%RB	Front Side	2506.0	22.18	24.0	1.208	0.151	0.182

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
115.	802.11b	Back Side	06	2437	16.07	16.5	1.104	0.276	0.305
116.	802.11b	Front Side	06	2437	16.07	16.5	1.104	0.086	0.095

Hotspot SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
117.	GPRS_2TX	Back Side	251	848.8	31.85	32.0	1.035	0.361	0.374
118.	GPRS_2TX	Front Side	251	848.8	31.85	32.0	1.035	0.187	0.194
119.	GPRS_2TX	Left side	251	848.8	31.85	32.0	1.035	0.089	0.092
120.	GPRS_2TX	Top side	251	848.8	31.85	32.0	1.035	0.138	0.143

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
121.	GPRS_2TX	Back Side	512	1850.2	28.98	29.0	1.005	0.398	0.400
122.	GPRS_2TX	Front Side	512	1850.2	28.98	29.0	1.005	0.216	0.217
123.	GPRS_2TX	Left side	512	1850.2	28.98	29.0	1.005	0.145	0.146
124.	GPRS_2TX	Top side	512	1850.2	28.98	29.0	1.005	0.323	0.324

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
125.	RMC 12.2k	Back Side	9538	1907.6	22.99	23.00	1.002	0.216	0.216
126.	RMC 12.2k	Front Face	9538	1907.6	22.99	23.00	1.002	0.242	0.243
127.	RMC 12.2k	Left side	9538	1907.6	22.99	23.00	1.002	0.128	0.128
128.	RMC 12.2k	Top side	9538	1907.6	22.99	23.00	1.002	0.45	0.451

WCDMA Band 4 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
129.	RMC 12.2k	Back Side	1312	1712.4	22.98	23.00	1.005	0.666	0.669
130.	RMC 12.2k	Front Side	1312	1712.4	22.98	23.00	1.005	0.444	0.446
131.	RMC 12.2k	Left side	1312	1712.4	22.98	23.00	1.005	0.132	0.133
132.	RMC 12.2k	Top side	1312	1712.4	22.98	23.00	1.005	0.732	0.735

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
133.	RMC 12.2k	Back Side	4183	836.4	23.10	23.50	1.096	0.175	0.192
134.	RMC 12.2k	Front Side	4183	836.4	23.10	23.50	1.096	0.118	0.129
135.	RMC 12.2k	Left side	4183	836.4	23.10	23.50	1.096	0.15	0.164
136.	RMC 12.2k	Top side	4183	836.4	23.10	23.50	1.096	0.118	0.129

LTE Band 2–Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)	
	Modulation, Bandwidth, RB		MHz						
137.	RMC QPSK 20MHz 1RB	Back Side	1860.0	23.25	23.5	1.059	0.384	0.407	
138.	RMC QPSK 20MHz 1RB	Front Side	1860.0	23.25	23.5	1.059	0.168	0.178	
139.	RMC QPSK 20MHz 1RB	Left side	1860.0	23.25	23.5	1.059	0.156	0.165	
140.	RMC QPSK 20MHz 1RB	Top side	1860.0	23.25	23.5	1.059	0.42	0.445	
141.	RMC QPSK 20MHz 50%RB	Back Side	1860.0	21.82	22.5	1.169	0.221	0.258	
142.	RMC QPSK 20MHz 50%RB	Front Side	1860.0	21.82	22.5	1.169	0.124	0.145	
143.	RMC QPSK 20MHz 50%RB	Left side	1860.0	21.82	22.5	1.169	0.115	0.134	
144.	RMC QPSK 20MHz 50%RB	Top side	1860.0	21.82	22.5	1.169	0.062	0.073	

LTE Band 4–Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)	
	Modulation, Bandwidth, RB		MHz						
145.	RMC QPSK 20MHz 1RB	Back Side	1745.0	24.32	24.5	1.042	0.675	0.704	
146.	RMC QPSK 20MHz 1RB	Front Side	1745.0	24.32	24.5	1.042	0.375	0.391	
147.	RMC QPSK 20MHz 1RB	Left side	1745.0	24.32	24.5	1.042	0.136	0.142	
148.	RMC QPSK 20MHz 1RB	Top side	1745.0	24.32	24.5	1.042	0.663	0.691	
149.	RMC QPSK 20MHz 50%RB	Back Side	1745.0	22.78	23.5	1.180	0.421	0.497	
150.	RMC QPSK 20MHz 50%RB	Front Side	1745.0	22.78	23.5	1.180	0.152	0.179	
151.	RMC QPSK 20MHz 50%RB	Left side	1745.0	22.78	23.5	1.180	0.105	0.124	
152.	RMC QPSK 20MHz 50%RB	Top side	1745.0	22.78	23.5	1.180	0.312	0.368	

LTE Band 5–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power	Rated Limit	Scaling Factor	SAR1g	Scaled SAR1g
	Modulation, Bandwidth, RB	Body	MHz	(dBm)	(dBm)		(W/kg)	(W/kg)
153.	RMC QPSK 10MHz 1RB	Back Side	836.5	23.67	24.0	1.079	0.217	0.234
154.	RMC QPSK 10MHz 1RB	Front Side	836.5	23.67	24.0	1.079	0.127	0.137
155.	RMC QPSK 10MHz 1RB	Left side	836.5	23.67	24.0	1.079	0.142	0.153
156.	RMC QPSK 10MHz 1RB	Top side	836.5	23.67	24.0	1.079	0.123	0.133
157.	RMC QPSK 10MHz 50%RB	Back Side	836.5	22.38	23.0	1.153	0.112	0.129
158.	RMC QPSK 10MHz 50%RB	Front Side	836.5	22.38	23.0	1.153	0.067	0.077
159.	RMC QPSK 10MHz 50%RB	Left side	836.5	22.38	23.0	1.153	0.079	0.091
160.	RMC QPSK 10MHz 50%RB	Top side	836.5	22.38	23.0	1.153	0.109	0.126

LTE Band 7–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power	Rated Limit	Scaling Factor	SAR1g	Scaled SAR1g
	Modulation, Bandwidth, RB	Body	MHz	(dBm)	(dBm)		(W/kg)	(W/kg)
161.	RMC QPSK 20MHz 1RB	Back Side	2535.0	24.26	24.5	1.057	0.59	0.624
162.	RMC QPSK 20MHz 1RB	Front Side	2535.0	24.26	24.5	1.057	0.241	0.255
163.	RMC QPSK 20MHz 1RB	Left side	2535.0	24.26	24.5	1.057	0.379	0.401
164.	RMC QPSK 20MHz 1RB	Top side	2535.0	24.26	24.5	1.057	0.502	0.531
165.	RMC QPSK 20MHz 50%RB	Back Side	2535.0	22.92	23.5	1.143	0.405	0.463
166.	RMC QPSK 20MHz 50%RB	Front Side	2535.0	22.92	23.5	1.143	0.151	0.173
167.	RMC QPSK 20MHz 50%RB	Left side	2535.0	22.92	23.5	1.143	0.206	0.235
168.	RMC QPSK 20MHz 50%RB	Top side	2535.0	22.92	23.5	1.143	0.279	0.319

LTE Band 38–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power	Rated Limit	Scaling Factor	SAR1g	Scaled SAR1g
	Modulation, Bandwidth, RB	Body	MHz	(dBm)	(dBm)		(W/kg)	(W/kg)
169.	RMC QPSK 20MHz 1RB	Back Side	2580.0	23.08	23.5	1.102	0.623	0.686
170.	RMC QPSK 20MHz 1RB	Front Side	2580.0	23.08	23.5	1.102	0.213	0.235
171.	RMC QPSK 20MHz 1RB	Left side	2580.0	23.08	23.5	1.102	0.46	0.507
172.	RMC QPSK 20MHz 1RB	Top side	2580.0	23.08	23.5	1.102	0.287	0.316
173.	RMC QPSK 20MHz 50%RB	Back Side	2580.0	21.93	22.5	1.140	0.495	0.564
174.	RMC QPSK 20MHz 50%RB	Front Side	2580.0	21.93	22.5	1.140	0.151	0.172
175.	RMC QPSK 20MHz 50%RB	Left side	2580.0	21.93	22.5	1.140	0.286	0.326
176.	RMC QPSK 20MHz 50%RB	Top side	2580.0	21.93	22.5	1.140	0.159	0.181

LTE Band 41–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
177.	RMC QPSK 20MHz 1RB	Back Side	2506.0	23.86	24.0	1.033	0.613	0.633
178.	RMC QPSK 20MHz 1RB	Front Side	2506.0	23.86	24.0	1.033	0.196	0.202
179.	RMC QPSK 20MHz 1RB	Left side	2506.0	23.86	24.0	1.033	0.377	0.389
180.	RMC QPSK 20MHz 1RB	Top side	2506.0	23.86	24.0	1.033	0.253	0.261
181.	RMC QPSK 20MHz 50%RB	Back Side	2506.0	22.18	23.0	1.208	0.425	0.513
182.	RMC QPSK 20MHz 50%RB	Front Side	2506.0	22.18	23.0	1.208	0.151	0.182
183.	RMC QPSK 20MHz 50%RB	Left side	2506.0	22.18	23.0	1.208	0.286	0.345
184.	RMC QPSK 20MHz 50%RB	Top side	2506.0	22.18	23.0	1.208	0.171	0.207

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
185.	802.11b	Back Side	06	2437	16.07	16.5	1.104	0.276	0.305
186.	802.11b	Front Side	06	2437	16.07	16.5	1.104	0.086	0.095
187.	802.11b	Right side	06	2437	16.07	16.5	1.104	0.041	0.045
188.	802.11b	Top side	06	2437	16.07	16.5	1.104	0.236	0.261

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

9.3 Simultaneous Multi-band Transmission SAR Analysis

List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Head SAR	Body SAR
1	GSM(Voice/Data) + WLAN(2.4G)(Data)	Yes	Yes
2	WCDMA (Voice/Data)+ (2.4G)(Data)	Yes	Yes
3	LTE(Data) + (2.4G)(Data)	Yes	Yes
7	GSM(Voice/Data) + Bluetooth(Data)	Yes	Yes
8	WCDMA (Voice/Data) + Bluetooth(Data)	Yes	Yes
9	LTE(Data) + Bluetooth(Data)	Yes	Yes

Remark:

1. GSM ,WCDMA and LTE share the same antenna, and cannot transmit simultaneously.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm) 2 ·[$\sqrt{f(\text{GHz})}$]/x] W/kg for test separation distances ≤ 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:

0.501

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	X	SAR(1g) 5mm	SAR(1g) 10mm
7.0	5.01	5/10	2.441	7.5	0.209	0.104

4. The maximum SAR summation is calculated based on the same configuration and test position.

Head SAR**WWAN and WLAN**

Position	WWAN		WLAN(2.4G)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM1900	0.826	0.139	0.965
Right Tilted	GSM1900	0.388	0.071	0.459
Left Cheek	GSM1900	0.540	0.193	0.733
Left Tilted	GSM1900	0.312	0.102	0.414

WWAN and Bluetooth

Position	WWAN		Bluetooth	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM1900	0.826	0.209	1.035
Right Tilted	GSM1900	0.388	0.209	0.597
Left Cheek	GSM1900	0.540	0.209	0.749
Left Tilted	GSM1900	0.312	0.209	0.521

Body-worn SAR**WWAN and WLAN**

Position	WWAN		WLAN(2.4G)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	LTE Band 4	0.704	0.305	1.009
Front	LTE Band 4	0.391	0.095	0.486

Hotspot SAR**WWAN and WLAN**

Position	WWAN		WLAN(2.4G)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	WCDMA Band 4	0.669	0.305	0.974
Front	WCDMA Band 4	0.446	0.095	0.541
Left side	LTE Band 38	0.507	0.045	0.552
Top side	WCDMA Band 4	0.735	0.261	0.996

WWAN and Bluetooth

Position	WWAN		Bluetooth	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	WCDMA Band 4	0.669	0.104	0.773
Front	WCDMA Band 4	0.446	0.104	0.550
Left side	LTE Band 38	0.507	0.104	0.611
Top side	WCDMA Band 4	0.735	0.104	0.839

10. Measurement Uncertainty

10.1 Uncertainty for EUT SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{-Cp})^{1/2}$	$(1_{-Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Test Sample Related									
Test sample positioning	E.4.2	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	E.2.9	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
SAR scaling	E6.5	0.0	R	$\sqrt{3}$	1	1	0.0	0.0	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E3.2	1.9	R	$\sqrt{3}$	1	0.84	1.10	0.90	∞

Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	∞
Liquid permittivity - deviation from target value	E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	∞
Combined Standard Uncertainty			RSS				12.98	12.53	
Expanded Uncertainty (95% Confidence interval)			K=2				25.32	24.43	

10.2 Uncertainty for System Performance Check

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	0	R	$\sqrt{3}$	0	0	0.0	0.0	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞

integration Algorithms for Max. SAR Evaluation									
Dipole									
Dipole axis to liquid Distance	8,E.4.2	1.00	N	$\sqrt{3}$	1	1	0.58	0.58	N-1
Input power and SAR drift measurement	8,6.6.2	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
Deviation of experimental dipole from numerical dipole	E.6.4	5.5	R	$\sqrt{3}$	1	1	3.20	3.20	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E3.2	2.0	R	$\sqrt{3}$	1	0.84	1.10	1.10	∞
Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	
Liquid permittivity - deviation from target value	E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				12.00	11.50	
Expanded Uncertainty (95% Confidence interval)			K=2				23.39	22.43	

Annex A. Plots of System Performance Check

MEASUREMENT 1

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative Permittivity (real part)	41.320574
Conductivity (S/m)	0.862373
Power Variation (%)	0.038363
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.042744
SAR 1g (W/Kg)	2.164534

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.3634	1.8023	1.4523	1.2514	1.1005	1.0245



3D screen shot	Hot spot position
	

MEASUREMENT 2

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	0.038437
Ambient Temperature	21.1
Liquid Temperature	21.3




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.519489
SAR 1g (W/Kg)	2.411253

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.4900	1.8942	1.4811	1.3541	1.1123	1.0539



3D screen shot	Hot spot position
<p>A 3D perspective view of a grey, L-shaped device. A color-coded heatmap is overlaid on the flat surface of the device, showing a central red/orange area (high SAR) that transitions through yellow and green to blue (low SAR) at the edges.</p>	<p>A 2D vertical heatmap showing the SAR distribution. The center is a bright red/orange oval, surrounded by concentric rings of yellow, green, and finally blue at the outer edges, indicating a localized high SAR region.</p>

MEASUREMENT 3

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative Permittivity (real part)	39.024890
Conductivity (S/m)	1.371250
Power Variation (%)	1.401232
Ambient Temperature	21.1
Liquid Temperature	21.2




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.171252
SAR 1g (W/Kg)	9.611250

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.3455	7.1125	5.1026	3.425	3.0242	2.1125



3D screen shot	Hot spot position

MEASUREMENT 4

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.022540
Ambient Temperature	21.1
Liquid Temperature	21.3




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.174526
SAR 1g (W/Kg)	9.913214

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2354	6.8400	5.0121	4.1189	3.0522	2.8424



3D screen shot	Hot spot position

MEASUREMENT 5

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	38.153660
Conductivity (S/m)	1.740236
Power Variation (%)	1.141452
Ambient Temperature	21.1
Liquid Temperature	21.2




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	8.020427
SAR 1g (W/Kg)	13.452457

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	14.1034	12.0012	10.2624	7.4715	5.9022	4.5114



3D screen shot	Hot spot position
<p>A 3D perspective view of a grey, L-shaped device. A rectangular area on the inner surface is highlighted with a color-coded grid, showing a hot spot in the center (red) that fades to blue at the edges.</p>	<p>A 2D heatmap showing a central red oval (hot spot) surrounded by concentric rings of yellow, green, and blue, indicating the spatial distribution of SAR intensity.</p>

MEASUREMENT 6

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative Permittivity (real part)	38.631092
Conductivity (S/m)	1.930182
Power Variation (%)	1.028221
Ambient Temperature	21.1
Liquid Temperature	21.2




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	8.270822
SAR 1g (W/Kg)	13.670282

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	14.0426	12.1354	10.2965	7.4854	5.9354	4.5186



3D screen shot	Hot spot position
<p>A 3D perspective view of a grey, L-shaped device. A rectangular area on the horizontal part of the device is overlaid with a color-coded grid representing SAR distribution. The colors range from blue (low SAR) to red (high SAR), with the highest intensity (red) concentrated in the center of the horizontal surface.</p>	<p>A 2D heatmap showing a central, vertically-oriented oval region of high intensity (red). This region is surrounded by concentric rings of decreasing intensity, transitioning through yellow and green to a blue outer boundary. The background is white.</p>

MEASUREMENT 7

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative Permittivity (real part)	54.964739
Conductivity (S/m)	0.931048
Power Variation (%)	0.034745
Ambient Temperature	21.1
Liquid Temperature	21.3




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.000865
SAR 1g (W/Kg)	2.124211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5132	1.1087	0.8214	0.5160	0.4875	0.4864



3D screen shot	Hot spot position
<p>A 3D perspective view of a grey device with a color-coded SAR distribution on its top surface. The distribution shows a central hot spot (red) that fades to blue at the edges.</p>	<p>A 2D heatmap showing the SAR distribution. The central area is red, indicating the highest SAR, surrounded by yellow, green, and blue areas representing decreasing SAR levels.</p>

MEASUREMENT 8

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.901472
Ambient Temperature	21.1
Liquid Temperature	21.3




Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.028956
SAR 1g (W/Kg)	2.354211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5789	1.1300	0.8795	0.5940	0.5011	0.5100



3D screen shot	Hot spot position

MEASUREMENT 9

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Measurement duration: 12 minutes 21 seconds

E-field Probe: SSE2 - SN 45/15 EPGO280; ConvF: Refer to the Calibration Certificate; Calibrated: 2020/07/03

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative Permittivity (real part)	51.224510
Conductivity (S/m)	1.461261
Power Variation (%)	0.845690
Ambient Temperature	21.1
Liquid Temperature	21.2

