



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: TECNO MOBILE LIMITED

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

FCC ID: 2ADYY-KL8

Product Name: Mobile Phone

Standard(s): 47 CFR Part 2
47 CFR Part 22, Subpart H
47 CFR Part 24, Subpart E
47 CFR Part 27
ANSI C63.26-2015

The above device has been tested and found compliant with the requirement of the relative standards by
China Certification ICT Co., Ltd (Dongguan)

Report Number: 2403U81808E-RF-00E

Date Of Issue: 2024/7/29

Reviewed By: Calvin Chen
Title: RF Engineer

Calvin Chen

Approved By: Sun Zhong
Title: Manager

Sun Zhong

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)
No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	10
1.2.2 Support Equipment List and Details	10
1.2.3 Support Cable List and Details	10
1.2.4 Block Diagram of Test Setup	11
1.3 MEASUREMENT UNCERTAINTY	12
2. SUMMARY OF TEST RESULTS	13
3. REQUIREMENTS AND TEST PROCEDURES	14
3.1 Applicable Standard For Part 22 Subpart H:.....	14
3.1.1 RF Output Power	14
3.1.2 Spurious Emissions.....	14
3.1.3 Frequency stability.....	14
3.2 Applicable Standard For Part 24 Subpart E:.....	16
3.2.1 RF Output Power	16
3.2.2 Spurious Emissions.....	16
3.2.3 Frequency stability.....	16
3.3 Applicable Standard For Part 27:.....	17
3.3.1 RF Output Power	17
3.3.2 Spurious Emissions.....	18
3.3.3 Frequency stability.....	19
3.4 Test Method:	20
3.4.1 RF Output Power	20
3.4.2 Occupied Bandwidth.....	21
3.4.3 Transmitter unwanted emissions-at antenna terminals	22
3.4.4 Out of band emission	23
3.4.5 Frequency stability.....	24
3.4.6 Transmitter unwanted emissions-Radiated Spurious emissions.....	25
4. TEST DATA AND RESULTS	27
4.1 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 850 BAND	27
4.2 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 1900 BAND	33
4.3 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 2	39
4.4 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 4	46
4.5 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 5:.....	53
4.6 LTE BAND RF CONDUCTED DATA.....	60
4.7 RADIATED SPURIOUS EMISSIONS.....	61
5. EUT PHOTOGRAPHS	98
6.TEST SETUP PHOTOGRAPHS	99

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2403U81808E-RF-00E	Original Report	2024/7/29

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

General:

EUT Name:	Mobile Phone
EUT Model:	KL8
Operation Bands and modes:	GSM/GPRS/EDGE: 850/1900 WCDMA: Band 2/4/5 LTE: Band 2/4/5/7/12/17/38/41/42/66
Modulation Type:	GMSK, 8PSK, BPSK, QPSK, 16QAM
Rated Input Voltage:	DC 3.87V from battery or DC 5V/7.5V charging from adapter
Serial Number:	RF: 2N75-2 RE: 2N75-1
EUT Received Date:	2024/6/18
EUT Received Status:	Good

Operation Voltage(V_{DC}) ▲:

Lowest:	3.45	Normal:	3.87	Highest:	4.45
---------	------	---------	------	----------	------

Antenna Information ▲:

PRX:

Antenn	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G_T) (dBi)	Lc (dB)
ANT7	FPC	GSM850	824-849	-5.68	0
		PCS1900	1850-1910	-3.18	0
		WCDMA B4	1710-1755	-3.04	0
		WCDMA B5	824-849	-5.68	0
		LTE B4	1710-1755	-3.04	0
		LTE B5	824-849	-5.68	0
		LTE B7	2500-2570	-3.09	0
		LTE B12	699-716	-7.06	0
		LTE B17	704-716	-7.06	0
		LTE B38	2570-2620	-3.09	0
		LTE B41	2496-2690	-3.09	0
		LTE B66	1710-1780	-3.04	0
ANT0	FPC	LTE B42	3450-3550	-2.92	0

Note: Lc= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

DRX:

Antenna Manufacturer	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G _T) (dBi)	L _c (dB)
ANT3	FPC	GSM850	824-849	-8.52	0.8
		PCS1900	1850-1910	-3.38	0.8
		WCDMA B2	1850-1910	-3.38	0.8
		WCDMA B4	1710-1755	-4.74	0.8
		WCDMA B5	824-849	-8.52	0.8
		LTE B2	1850-1910	-3.38	0.8
		LTE B4	1710-1755	-4.74	0.8
		LTE B5	824-849	-8.52	0.8
		LTE B7	2500-2570	-9.92	0.9
		LTE B12	699-716	-9.24	0.8
		LTE B17	704-716	-9.24	0.8
		LTE B38	2570-2620	-9.92	0.9
		LTE B41	2496-2690	-9.92	0.9
		LTE B66	1710-1780	-4.74	0.8
ANT6	FPC	LTE B42	3450-3550	-5.17	0.9

PM:

Antenna Manufacturer	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G _T) (dBi)	L _c (dB)
ANT5	FPC	WCDMA B2	1850-1910	-8.78	0
		LTE B2	1850-1910	-8.78	0
		LTE B4	1710-1755	-11.44	0
		LTE B7	2500-2570	-7.74	0
		LTE B38	2570-2620	-7.74	0
		LTE B41	2496-2690	-7.74	0
		LTE B66	1710-1780	-11.44	0
ANT2	FPC	LTE B42	3450-3550	-6.6	0

Note: L_c= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

DM:

Antenna Manufacturer	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain(G _T) (dBi)	L _c (dB)
ANT4	FPC	LTE B42	3450-3550	-4.25	0.9

Note: L_c= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

Accessory Information:

Accessory Description	Manufacturer	Model
Adapter	TECNO	U180TSA
Earphone	Unknown	Unknown

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No
The maximum power was configured per 3GPP Standard for each operation modes as below setting:	
GSM/GPRS/EGPRS	
Function: Menu select > GSM Mobile Station > GSM 850/1900	
Press Connection control to choose the different menus	
Press RESET > choose all the reset all settings	
Connection Press Signal Off to turn off the signal and change settings	
Network Support > GSM + GPRS or GSM + EGSM	
Main Service > Packet Data	
Service selection > Test Mode A – Auto Slot Config. off	
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting	
> Slot configuration > Uplink/Gamma	
> 33 dBm for GPRS 850	
> 30 dBm for GPRS 1900	
> 27 dBm for EGPRS 850	
> 26 dBm for EGPRS 1900	
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel	
Frequency Offset > + 0 Hz	
Mode > BCCH and TCH	
BCCH Level > -85 dBm (May need to adjust if link is not stable)	
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]	
Channel Type > Off	
P0 > 4 dB	
Slot Config > Unchanged (if already set under MS signal)	
TCH > choose desired test channel	
Hopping > Off	
Main Timeslot > 3	
Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)	
Bit Stream > 2E9-1 PSR Bit Stream	
AF/RF Connection Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input	
Press Signal on to turn on the signal and change settings	

WCDMA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2		4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β	11/15	6/15	1 /15	2/15	15/15
	βd	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30 15	2/15	5/15
HSDPA Specific Settings	$\beta c/\beta d$	11/15	6/15	15/9	2/15	-
	βhs	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
	DACK	8				
	DNAK	8				
	DCQI	8				
HSUPA Specific Settings	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$Ahs=\beta hs/\beta c$	30/15				
	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	A Index	20	12	1	17	21
HSUPA Specific Settings	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate k ps	242.1	174.9	82.8	205.8	308.9
	Reference E_FCl	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO4 E-TFCI 71 E-TFCI 92 E-TFCI 75 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	*	*	*	*	*

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE(TDD):

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	2192 $\cdot T_s$	2560 $\cdot T_s$	$7680 \cdot T_s$	2192 $\cdot T_s$	2560 $\cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$			$20480 \cdot T_s$	4384 $\cdot T_s$	5120 $\cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$			-		

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Calculated Duty Cycle = Extended cyclic prefix in uplink x (T_s) x # of S + # of U

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = $5120 \times [1/(15000 \times 2048)] \times 2 + 6 \text{ ms} = 63.33\%$

where

 $T_s = 1/(15000 \times 2048)$ seconds**1.2.2 Support Equipment List and Details****1.2.2 Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
R&S	Wideband Radio Communication Tester	CMW500	143458
Unknown	Antenna	Unknown	Unknown

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1	Adapter	EUT
Cable	No	No	2	CMW500	Antenna
Earphone Cable	No	No	1.2	EUT	Earphone

1.2.4 Block Diagram of Test Setup

Radiation Test:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
RF Frequency	$\pm 0.082 \times 10^{-6}$

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§2.1046; §22.913; §27.50; § 24.232	RF Output Power	PASS
FCC§2.1046; § 24.232; §27.50; §22.913	Peak-to-average Ratio(PAR)	PASS
FCC§2.1049; §27.53; §22.905, §22.917; § 24.238	Occupied Bandwidth	PASS
FCC§2.1051; §27.53; §22.917; § 24.238	Spurious Emissions at Antenna Terminal	PASS
FCC§2.1051; § 24.238; §22.917; §27.53	Out of band emission,Band Edge	PASS
FCC§ 2.1055; §27.54; § 24.235; § 22.355	Frequency stability vs. temperature &Frequency stability vs. voltage Compliance	PASS
FCC§ 2.1053; § 22.917; §27.53; § 24.238	Field Strength of Spurious Radiation	PASS

3. REQUIREMENTS AND TEST PROCEDURES

3.1 Applicable Standard For Part 22 Subpart H:

3.1.1 RF Output Power

FCC §22.913

(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7watts.

(d) *Power measurement.* Measurement of the ERP of Cellular base transmitters and repeaters must be made using an average power measurement technique. The peak-toaverage ratio (PAR) of the transmission must not exceed 13 dB. Power measurements for base transmitters and repeaters must be made in accordance with either of the following:

- (1) A Commission-approved average power technique (*see* FCC Laboratory's Knowledge Database);or
- (2) For purposes of this section, peak transmit power must be measured over an interval of continuous transmission using instrumentation calibrated in terms of an rmsequivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, *etc.*, so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

3.1.2 Spurious Emissions

FCC §22.917

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

(1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz

3.1.3 Frequency stability

FCC §22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1 - Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20	20	50
50 to 450	5	5	50
450 to 512	2.5	5	5
821 to 896	1.5	2.5	2.5
928 to 929	5	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10	n/a	n/a

3.2 Applicable Standard For Part 24 Subpart E:

3.2.1 RF Output Power

FCC §24.232

(c)Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

(d)Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Spurious Emissions

FCC §24.238

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

3.2.3 Frequency stability

FCC §24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.3 Applicable Standard For Part 27:

3.3.1 RF Output Power

FCC §27.50

(a)(3) *Mobile and portable stations.*

(i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) *Automatic transmit power control.* Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) *Prohibition on external vehicle-mounted antennas.* The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c)(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d)(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

3.3.2 Spurious Emissions

FCC §27.53

(a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts:

(4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz;

(iii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the

purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log_{10} (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(h) AWS emission limits

(1) **General protection levels.** Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log_{10} (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log_{10} (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log_{10} (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log_{10} (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log_{10} (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.3.3 Frequency stability

FCC §27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.4 Test Method:

3.4.1 RF Output Power

According to CFR Part 2.1046, ANSI C63.26-2015 Section 5.2.5.5:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

where:


ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup Block:



Note: The Insertion loss of the RF cable and coaxial Attenuator was offset into the Reading of CMW500.

3.4.2 Occupied Bandwidth


According to CFR Part 2.1049, ANSI C63.26-2015 Section 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times$ OBW is sufficient).
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times$ RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3. NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.
- d) Set the detection mode to peak, and the trace mode to max-hold.
- e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

Test Setup Block:




3.4.3 Transmitter unwanted emissions-at antenna terminals

According to ANSI C63.26-2015 Section 5.7.4:

the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz),⁸ effectively depicting the unwanted emission limit in terms of a power spectral density. In those cases where no reference bandwidth is explicitly specified, the values in the preceding sentence should be used.

Test Setup Block:




3.4.4 Out of band emission

According to ANSI C63.26-2015 Section 5.7.3:

Typically, a measurement (resolution) bandwidth smaller than the reference bandwidth is allowed for measurements within a specified frequency range at the edge of the authorized frequency block/band (e.g., within the first Y MHz outside of the authorized frequency band/block, where the value of Y is specified in the relevant rule part). Some FCC out-of-band emission rules permit the use of a narrower RBW (typically limited to a minimum RBW of 1 % of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth. Beyond the specified frequency range in which this relaxation of the uniform reference bandwidth is permitted, it typically is also acceptable to use a narrower RBW (again limited to a minimum of 1 % of OBW) to increase accuracy, but the measurement result must subsequently be integrated over the full reference bandwidth.

Test Setup Block:



3.4.5 Frequency stability

According to ANSI C63.26-2015 Section 5.6:

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage.


The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10 °C intervals of temperatures between –30 °C and +50 °C at the manufacturer's rated supply voltage, and
- b) At +20 °C temperature and ±15% supply voltage variations. If a product is specified to operate over a range of input voltage then the –15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage.

During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.

Test Setup Block:



3.4.6 Transmitter unwanted emissions-Radiated Spurious emissions

According to ANSI C63.26-2015 Section 5.5.3:

Test setup:




Figure 6—Test site-up for radiated ERP and/or EIRP measurements




Figure 7—Substitution method set-up for radiated emission

Test Procedure:

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
 - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
 - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$Pe = Ps(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBD)}$$

where

Pe = equivalent emission power in dBm

Ps = source (signal generator) power in dBm

NOTE—dBD refers to the measured antenna gain in decibels relative to a half-wave dipole.

- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: gain (dBD) = gain (dBi) – 2.15 dB. If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

4. TEST DATA AND RESULTS

4.1 Antenna Port Test Data and Results for GSM 850 band

Serial Number:	2N75-2	Test Date:	2024/7/22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Chin Qin	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.5	Relative Humidity: (%)	59	ATM Pressure: (kPa)	100.4
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency for Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	824.2	836.6	848.8
GPRS	824.2	836.6	848.8
EDGE	824.2	836.6	848.8

Test Data:

RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	30.43	30.58	30.62	22.79	38.45
GPRS 1 Slot	30.47	30.49	30.54	22.71	38.45
GPRS 2 Slots	30.32	30.33	30.27	22.5	38.45
GPRS 3 Slots	29.15	29.17	29.12	21.34	38.45
GPRS 4 Slots	27.81	27.89	27.93	20.1	38.45
EDGE 1 Slot	26.94	26.77	26.72	19.11	38.45
EDGE 2 Slots	25.73	25.51	25.51	17.9	38.45
EDGE 3 Slots	23.61	23.42	23.48	15.78	38.45
EDGE 4 Slots	22.34	22.19	22.12	14.51	38.45

Note:
ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd)
Gr(dBd)=Gr(dBi)-2.15
Use ANT7 to calculate maximum ERP.

Result:	Pass
---------	------

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.237	0.237	0.239	0.264	0.263	0.266
EDGE	0.252	0.25	0.248	0.323	0.31	0.321

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
---------	---


Out of band emission, Band Edge


Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
---------	--


Frequency Stability					
Test Modulation:	GMSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.87	12	0.014	2.5
	-20	3.87	7	0.008	2.5
	-10	3.87	23	0.027	2.5
	0	3.87	9	0.011	2.5
	10	3.87	10	0.012	2.5
	20	3.87	4	0.005	2.5
	30	3.87	19	0.023	2.5
	40	3.87	1	0.001	2.5
	50	3.87	46	0.055	2.5
Frequency Stability vs. Voltage	20	3.45	20	0.024	2.5
	20	4.5	35	0.042	2.5
				Result:	Pass

Test Modulation:	8PSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.87	31	0.037	2.5
	-20	3.87	6	0.007	2.5
	-10	3.87	4	0.005	2.5
	0	3.87	15	0.018	2.5
	10	3.87	2	0.002	2.5
	20	3.87	28	0.033	2.5
	30	3.87	1	0.001	2.5
	40	3.87	30	0.036	2.5
	50	3.87	2	0.002	2.5
Frequency Stability vs. Voltage	20	3.45	7	0.008	2.5
	20	4.5	33	0.039	2.5
				Result:	Pass

Test Plots (Note: The 14.5 dB is the Insertion loss of the RF cable and Power Splitter, which was offset into the Spectrum Analyzer):







4.2 Antenna Port Test Data and Results for GSM 1900 band

Serial Number:	2N75-2	Test Date:	2024/7/22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Chin Qin	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.5	Relative Humidity: (%)	59	ATM Pressure: (kPa)	100.4
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency for Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	1850.2	1880	1909.8
GPRS	1850.2	1880	1909.8
EDGE	1850.2	1880	1909.8

Test Data:

RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	27.4	27.49	27.57	24.39	33
GPRS 1 Slot	27.37	27.35	27.49	24.31	33
GPRS 2 Slots	27.26	27.21	27.34	24.16	33
GPRS 3 Slots	25.94	25.75	25.94	22.76	33
GPRS 4 Slots	24.71	24.59	24.64	21.53	33
EDGE 1 Slot	25.47	25.32	25.01	22.29	33
EDGE 2 Slots	24.06	24.14	23.83	20.96	33
EDGE 3 Slots	21.83	21.93	21.39	18.75	33
EDGE 4 Slots	20.47	20.56	20.14	17.38	33

Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gr(dBi)
Use ANT7 to calculate maximum EIRP.

Result:	Pass
---------	------

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.24	0.237	0.237	0.279	0.263	0.267
EDGE	0.25	0.248	0.253	0.321	0.315	0.32

Note: The test plots please refer to the Plots of Occupied Bandwidth


Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.


Frequency Stability						
Test Mode:	GMSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.87	1850.059	1850.000	1909.926	1910.000
	-20	3.87	1850.076	1850.000	1909.946	1910.000
	-10	3.87	1850.068	1850.000	1909.925	1910.000
	0	3.87	1850.068	1850.000	1909.926	1910.000
	10	3.87	1850.066	1850.000	1909.922	1910.000
	20	3.87	1850.080	1850.000	1909.919	1910.000
	30	3.87	1850.066	1850.000	1909.941	1910.000
	40	3.87	1850.073	1850.000	1909.947	1910.000
	50	3.87	1850.053	1850.000	1909.941	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.063	1850.000	1909.947	1910.000
	20	4.5	1850.068	1850.000	1909.930	1910.000
					Result:	Pass

Test Mode:	8PSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.87	1850.060	1850.000	1909.948	1910.000
	-20	3.87	1850.070	1850.000	1909.936	1910.000
	-10	3.87	1850.055	1850.000	1909.935	1910.000
	0	3.87	1850.053	1850.000	1909.938	1910.000
	10	3.87	1850.059	1850.000	1909.934	1910.000
	20	3.87	1850.073	1850.000	1909.928	1910.000
	30	3.87	1850.070	1850.000	1909.941	1910.000
	40	3.87	1850.050	1850.000	1909.940	1910.000
	50	3.87	1850.067	1850.000	1909.929	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.052	1850.000	1909.946	1910.000
	20	4.5	1850.063	1850.000	1909.942	1910.000
					Result:	Pass

Test Plots (Note: The 14.5 dB is the Insertion loss of the RF cable and Power Splitter, which was offset into the Spectrum Analyzer):







4.3 Antenna Port Test Data and Results for WCDMA Band 2

Serial Number:	2N75-2	Test Date:	2024/7/23
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.7	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency for Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1852.4	1880	1907.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	22.58	22.71	22.93	18.75	33
HSDPA Subtest 1	22.71	22.72	22.92	18.74	33
HSDPA Subtest 2	22.72	22.76	22.91	18.73	33
HSDPA Subtest 3	22.71	22.77	22.93	18.75	33
HSDPA Subtest 4	22.72	22.79	22.91	18.73	33
HSUPA Subtest 1	22.73	22.8	22.91	18.73	33
HSUPA Subtest 2	22.73	22.79	22.9	18.72	33
HSUPA Subtest 3	22.72	22.79	22.91	18.73	33
HSUPA Subtest 4	22.72	22.8	22.92	18.74	33
HSUPA Subtest 5	22.73	22.81	22.91	18.73	33

Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gr(dBi)

Use ANT3 to calculate maximum EIRP.

Result: Pass

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	3.08	3.08	2.98	13
HSDPA	3.91	4.29	3.94	13
HSUPA	3.91	3.88	3.85	13

Result: Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.151	4.151	4.167	4.728	4.75	4.76
HSDPA	4.151	4.151	4.167	4.744	4.724	4.731
HSUPA	4.167	4.151	4.151	4.734	4.721	4.734

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal


Result: Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


Out of band emission, Band Edge


Result: Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability						
Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.87	1850.304	1850.000	1909.683	1910.000
	-20	3.87	1850.307	1850.000	1909.686	1910.000
	-10	3.87	1850.317	1850.000	1909.685	1910.000
	0	3.87	1850.307	1850.000	1909.683	1910.000
	10	3.87	1850.303	1850.000	1909.672	1910.000
	20	3.87	1850.317	1850.000	1909.667	1910.000
	30	3.87	1850.302	1850.000	1909.671	1910.000
	40	3.87	1850.293	1850.000	1909.692	1910.000
	50	3.87	1850.313	1850.000	1909.671	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.307	1850.000	1909.685	1910.000
	20	4.5	1850.308	1850.000	1909.687	1910.000
					Result:	Pass

Test Plots (Note: The 14.5 dB is the Insertion loss of the RF cable and Power Splitter, which was offset into the Spectrum Analyzer):







Out of band emission, Band Edge

Mode	Lowest	Highest
R99	<p style="text-align: center;">Center 1.85 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:34:35</p>	<p style="text-align: center;">Center 1.91 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:37:44</p>
HSUPA	<p style="text-align: center;">Center 1.85 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:46:13</p>	<p style="text-align: center;">Center 1.91 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:49:39</p>
HSDPA	<p style="text-align: center;">Center 1.85 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:49:47</p>	<p style="text-align: center;">Center 1.91 GHz 1 MHz/1 MHz Span 10 MHz</p> <p style="font-size: small;">Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:49:26</p>

4.4 Antenna Port Test Data and Results for WCDMA Band 4

Serial Number:	2N75-2	Test Date:	2024/7/23
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.7	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1712.4	1732.6	1752.6

Test Data:

RF Output Power					
Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	17.07	17.26	17.14	14.22	30
HSDPA Subtest 1	17.14	17.25	17.21	14.21	30
HSDPA Subtest 2	17.12	17.25	17.2	14.21	30
HSDPA Subtest 3	17.12	17.25	17.19	14.21	30
HSDPA Subtest 4	17.13	17.23	17.23	14.19	30
HSUPA Subtest 1	17.04	17.2	17.16	14.16	30
HSUPA Subtest 2	17.07	17.2	17.15	14.16	30
HSUPA Subtest 3	17.06	17.17	17.18	14.14	30
HSUPA Subtest 4	17.07	17.18	17.14	14.14	30
HSUPA Subtest 5	17.08	17.24	17.15	14.2	30

Note: EIRP=Conducted Power(dBm) - Lc(dB) + G_T(dBi)
Use ANT7 to calculate maximum EIRP.

Result:	Pass
---------	------

Peak-to-average Ratio(PAR)					
Test Mode	Peak-to-average Ratio(dB)			Limit (dB)	
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	3.33	3.33	3.27	13	
HSDPA	4.07	4.07	4.46	13	
HSUPA	4.33	4.13	4.04	13	

Result:	Pass
---------	------

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.151	4.167	4.151	4.728	4.728	4.728
HSDPA	4.167	4.167	4.151	4.728	4.744	4.728
HSUPA	4.151	4.167	4.151	4.712	4.728	4.724

Note: The test plots please refer to the Plots of Occupied Bandwidth


Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability


Test Mode:		Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.87	1710.326	1710.000	1754.668	1755.000
	-20	3.87	1710.320	1710.000	1754.674	1755.000
	-10	3.87	1710.324	1710.000	1754.673	1755.000
	0	3.87	1710.323	1710.000	1754.681	1755.000
	10	3.87	1710.315	1710.000	1754.678	1755.000
	20	3.87	1710.333	1710.000	1754.667	1755.000
	30	3.87	1710.320	1710.000	1754.672	1755.000
	40	3.87	1710.331	1710.000	1754.680	1755.000
	50	3.87	1710.333	1710.000	1754.676	1755.000
Frequency Stability vs. Voltage	20	3.45	1710.332	1710.000	1754.671	1755.000
	20	4.5	1710.319	1710.000	1754.682	1755.000
					Result:	Pass


Test Plots (Note: The 14.5 dB is the Insertion loss of the RF cable and Power Splitter, which was offset into the Spectrum Analyzer):





Spurious Emissions at Antenna Terminal





4.5 Antenna Port Test Data and Results for WCDMA Band 5:

Serial Number:	2N75-2	Test Date:	2024/7/23
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.7	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-------------------	------	------------------------	----	---------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	100147	2024/4/1	2025/3/31
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Unknown	Coaxial tee connector	Unknown	2204004	Each time	N/A
Anritsu	Radio Communication Analyzer	MT8820C	6201010144	2024/7/12	2025/7/11
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2024/4/1	2025/3/31
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	826.4	836.6	846.6

Test Data:

RF Output Power					
Test Mode	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	23.18	23.22	23.31	15.48	38.45
HSDPA Subtest 1	23.21	23.26	23.26	15.43	38.45
HSDPA Subtest 2	23.22	23.25	23.29	15.46	38.45
HSDPA Subtest 3	23.22	23.25	23.3	15.47	38.45
HSDPA Subtest 4	23.21	23.24	23.26	15.43	38.45
HSUPA Subtest 1	23.19	23.24	23.29	15.46	38.45
HSUPA Subtest 2	23.23	23.25	23.26	15.43	38.45
HSUPA Subtest 3	23.19	23.24	23.25	15.42	38.45
HSUPA Subtest 4	23.2	23.25	23.29	15.46	38.45
HSUPA Subtest 5	23.21	23.21	23.26	15.43	38.45

Note:
ERP= Conducted Power(dBm) - Lc(dB) + G_T(dBd)
G_T(dBd)=G_T(dBi)-2.15
Use ANT7 to calculate maximum ERP.

	Result:	Pass
--	----------------	-------------

Peak-to-average Ratio(PAR)					
Test Mode	Peak-to-average Ratio(dB)			Limit (dB)	
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	3.43	3.27	3.33		13
HSDPA	4.23	4.17	3.56		13
HSUPA	4.58	3.94	4.62		13

	Result:	Pass
--	----------------	-------------

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.167	4.151	4.135	4.712	4.696	4.712
HSDPA	4.167	4.167	4.151	4.744	4.728	4.744
HSUPA	4.167	4.167	4.151	4.728	4.728	4.721


Note: The test plots please refer to the Plots of Occupied Bandwidth


Spurious Emissions at Antenna Terminal					
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.				


Out of band emission, Band Edge					
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.				

Frequency Stability					
Test Modulation:	WCDMA R99		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.87	21	0.025	2.5
	-20	3.87	40	0.048	2.5
	-10	3.87	21	0.025	2.5
	0	3.87	9	0.011	2.5
	10	3.87	9	0.011	2.5
	20	3.87	13	0.016	2.5
	30	3.87	3	0.004	2.5
	40	3.87	6	0.007	2.5
	50	3.87	41	0.049	2.5
Frequency Stability vs. Voltage	20	3.45	24	0.029	2.5
	20	4.5	9	0.011	2.5
					Result: Pass







Test Plots (Note: The 14.5 dB is the Insertion loss of the RF cable and Power Splitter, which was offset into the Spectrum Analyzer):







Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 09:35:39</p>	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 09:43:03</p>
HSUPA	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:22:09</p>	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:26:15</p>
HSDPA	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 09:59:12</p>	 <p>Comment: ProjectNo.:2403U81808E-RF Tester:Arthur Su Date: 23.JUL.2024 10:08:40</p>

4.6 LTE Band RF Conducted data

Please refer to Annex "2403U81808E-RF-00E Appendix E" for detail test data.

4.7 Radiated Spurious Emissions

1) 30 - 1000MHz

Serial Number:	RE: 2N75-1	Test Date:	2024/7/24
Test Site:	966-2	Test Mode:	Transmitting
Tester:	Carl Xue	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.3	Relative Humidity: (%)	54	ATM Pressure: (kPa)	100.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
R&S	EMI Test Receiver	ESR3	102724	2024/2/29	2025/2/28
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0100-03	2023/12/4	2024/12/3
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0370-01	2023/12/4	2024/12/3
XQY	Coaxial Cable	XQY-CMR400UF-NJ-NJ-7M	24056379	2024/6/11	2025/6/10
Sonoma	Amplifier	310N	186165	2023/12/4	2024/12/3
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2024/7/15	2025/7/14
Agilent	Signal Generator	E8247C	MY43321352	2023/11/17	2024/11/16

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

PRX:**Cellular Band (PART 22H)****GSM 850:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 824.2 MHz								
708.48	H	20.37	-52.78	0.00	0.53	-53.31	-13.00	40.31
731.69	V	21.76	-47.47	0.00	0.53	-48.00	-13.00	35.00
Frequency: 836.6 MHz								
709.75	H	20.25	-52.87	0.00	0.52	-53.39	-13.00	40.39
727.68	V	21.38	-47.94	0.00	0.52	-48.46	-13.00	35.46
Frequency: 848.8 MHz								
716.54	H	20.19	-52.80	0.00	0.50	-53.30	-13.00	40.30
726.64	V	21.43	-47.91	0.00	0.52	-48.43	-13.00	35.43

WCDMA Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 826.4 MHz								
726.57	H	20.67	-52.11	0.00	0.52	-52.63	-13.00	39.63
695.64	V	19.37	-50.63	0.00	0.55	-51.18	-13.00	38.18
Frequency: 836.6 MHz								
724.36	H	20.92	-51.91	0.00	0.51	-52.42	-13.00	39.42
683.61	V	19.28	-50.94	0.00	0.53	-51.47	-13.00	38.47
Frequency: 846.6 MHz								
727.46	H	20.62	-52.15	0.00	0.52	-52.67	-13.00	39.67
697.17	V	19.72	-50.25	0.00	0.55	-50.80	-13.00	37.80

PCS Band (PART 24E)**GSM 1900:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
278.16	H	42.36	-68.88	0.00	0.32	-69.20	-13.00	56.20
60.73	V	42.37	-63.39	-9.91	0.14	-73.44	-13.00	60.44
Frequency: 1880 MHz								
279.41	H	41.96	-69.25	0.00	0.32	-69.57	-13.00	56.57
59.85	V	42.18	-63.76	-10.37	0.14	-74.27	-13.00	61.27
Frequency: 1909.8 MHz								
276.64	H	42.68	-68.59	0.00	0.32	-68.91	-13.00	55.91
61.43	V	42.65	-62.87	-9.54	0.14	-72.55	-13.00	59.55

AWS Band(Part 27)**WCDMA Band 4:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1712.4 MHz								
208.14	H	40.47	-72.26	0.00	0.26	-72.52	-13.00	59.52
106.64	V	39.29	-67.31	0.00	0.19	-67.50	-13.00	54.50
Frequency: 1732.6 MHz								
208.58	H	40.59	-72.13	0.00	0.26	-72.39	-13.00	59.39
106.28	V	39.45	-67.17	0.00	0.19	-67.36	-13.00	54.36
Frequency: 1752.6 MHz								
208.76	H	40.68	-72.04	0.00	0.26	-72.30	-13.00	59.30
106.73	V	39.62	-66.97	0.00	0.19	-67.16	-13.00	54.16

LTE Bands:(The Worst modulation and bandwidth(1RB) was below)**LTE Band 4:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
207.85	H	41.16	-71.57	0.00	0.26	-71.83	-13.00	58.83
107.68	V	40.96	-65.57	0.00	0.19	-65.76	-13.00	52.76
1.4MHz QPSK, Frequency: 1732.5 MHz								
207.12	H	40.97	-71.78	0.00	0.26	-72.04	-13.00	59.04
110.56	V	41.64	-64.70	0.00	0.20	-64.90	-13.00	51.90
1.4MHz QPSK, Frequency: 1754.3 MHz								
211.52	H	41.33	-71.33	0.00	0.26	-71.59	-13.00	58.59
113.69	V	41.75	-64.39	0.00	0.19	-64.58	-13.00	51.58

LTE Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 824.7 MHz								
698.46	H	19.76	-53.57	0.00	0.55	-54.12	-13.00	41.12
628.65	V	20.32	-50.89	0.00	0.48	-51.37	-13.00	38.37
1.4MHz QPSK, Frequency: 836.5 MHz								
724.36	H	20.18	-52.65	0.00	0.51	-53.16	-13.00	40.16
654.15	V	19.46	-51.29	0.00	0.52	-51.81	-13.00	38.81
1.4MHz QPSK, Frequency: 848.3 MHz								
677.84	H	19.34	-54.10	0.00	0.51	-54.61	-13.00	41.61
436.81	V	20.16	-53.93	0.00	0.41	-54.34	-13.00	41.34

LTE Band 7:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
207.54	H	40.58	-72.16	0.00	0.26	-72.42	-25.00	47.42
106.38	V	39.16	-67.46	0.00	0.19	-67.65	-25.00	42.65
5MHz QPSK, Frequency: 2535 MHz								
207.61	H	40.75	-71.99	0.00	0.26	-72.25	-25.00	47.25
106.54	V	39.57	-67.03	0.00	0.19	-67.22	-25.00	42.22
5MHz QPSK, Frequency: 2567.5 MHz								
206.89	H	40.66	-72.09	0.00	0.26	-72.35	-25.00	47.35
105.92	V	39.63	-67.02	0.00	0.19	-67.21	-25.00	42.21

LTE Band 12:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
597.64	H	19.28	-54.63	0.00	0.51	-55.14	-13.00	42.14
573.61	V	19.66	-52.03	0.00	0.46	-52.49	-13.00	39.49
1.4MHz QPSK, Frequency: 707.5 MHz								
618.45	H	19.81	-53.95	0.00	0.49	-54.44	-13.00	41.44
564.82	V	20.32	-51.36	0.00	0.46	-51.82	-13.00	38.82
1.4MHz QPSK, Frequency: 715.3 MHz								
515.36	H	19.65	-55.88	0.00	0.44	-56.32	-13.00	43.32
623.26	V	20.13	-51.18	0.00	0.48	-51.66	-13.00	38.66

LTE Band 17:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 706.5 MHz								
621.63	H	19.25	-54.49	0.00	0.49	-54.98	-13.00	41.98
589.69	V	20.23	-51.48	0.00	0.48	-51.96	-13.00	38.96
5MHz QPSK, Frequency: 710 MHz								
638.46	H	20.19	-53.46	0.00	0.52	-53.98	-13.00	40.98
642.34	V	19.16	-51.80	0.00	0.52	-52.32	-13.00	39.32
5MHz QPSK, Frequency: 713.5 MHz								
583.62	H	20.15	-54.03	0.00	0.46	-54.49	-13.00	41.49
629.71	V	20.11	-51.08	0.00	0.48	-51.56	-13.00	38.56

LTE Band 38:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
208.13	H	40.26	-72.47	0.00	0.26	-72.73	-25.00	47.73
104.86	V	41.43	-65.28	0.00	0.19	-65.47	-25.00	40.47
5MHz QPSK, Frequency: 2595 MHz								
207.85	H	40.47	-72.26	0.00	0.26	-72.52	-25.00	47.52
105.35	V	41.56	-65.12	0.00	0.19	-65.31	-25.00	40.31
5MHz QPSK, Frequency: 2617.5 MHz								
207.69	H	40.35	-72.39	0.00	0.26	-72.65	-25.00	47.65
105.81	V	41.37	-65.28	0.00	0.19	-65.47	-25.00	40.47

LTE Band 41:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
208.79	H	41.35	-71.37	0.00	0.26	-71.63	-25.00	46.63
106.52	V	40.61	-66.00	0.00	0.19	-66.19	-25.00	41.19
5MHz QPSK, Frequency: 2593 MHz								
209.31	H	41.46	-71.25	0.00	0.26	-71.51	-25.00	46.51
106.75	V	40.12	-66.47	0.00	0.19	-66.66	-25.00	41.66
5MHz QPSK, Frequency: 2687.5 MHz								
209.48	H	41.28	-71.42	0.00	0.26	-71.68	-25.00	46.68
105.98	V	40.32	-66.32	0.00	0.19	-66.51	-25.00	41.51

LTE Band 42:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
209.49	H	41.59	-71.11	0.00	0.26	-71.37	-13.00	58.37
106.77	V	40.42	-66.17	0.00	0.19	-66.36	-13.00	53.36
5MHz QPSK, Frequency: 3500 MHz								
209.61	H	41.27	-71.43	0.00	0.26	-71.69	-13.00	58.69
106.13	V	40.35	-66.28	0.00	0.19	-66.47	-13.00	53.47
5MHz QPSK, Frequency: 3547.5 MHz								
209.15	H	41.72	-70.99	0.00	0.26	-71.25	-13.00	58.25
106.49	V	40.15	-66.46	0.00	0.19	-66.65	-13.00	53.65

LTE Band 66:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:					1710.7	MHz		
208.19	H	39.47	-73.26	0.00	0.26	-73.52	-13.00	60.52
105.97	V	39.81	-66.83	0.00	0.19	-67.02	-13.00	54.02
1.4MHz QPSK, Frequency:					1745	MHz		
208.69	H	39.37	-73.35	0.00	0.26	-73.61	-13.00	60.61
106.01	V	39.46	-67.18	0.00	0.19	-67.37	-13.00	54.37
1.4MHz QPSK, Frequency:					1779.3	MHz		
208.48	H	39.61	-73.11	0.00	0.26	-73.37	-13.00	60.37
106.27	V	39.68	-66.94	0.00	0.19	-67.13	-13.00	54.13

DRX:

GSM 850:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolut e Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cabl e Loss (dB)			
Frequency:					824.2	MHz		
720.18	H	20.17	-52.74	0.00	0.49	-53.23	-13.00	40.23
734.65	V	21.46	-47.70	0.00	0.54	-48.24	-13.00	35.24
Frequency:					836.6	MHz		
717.16	H	20.61	-52.36	0.00	0.50	-52.86	-13.00	39.86
719.18	V	21.37	-48.13	0.00	0.49	-48.62	-13.00	35.62
Frequency:					848.8	MHz		
704.61	H	20.38	-52.85	0.00	0.55	-53.40	-13.00	40.40
719.54	V	21.67	-47.82	0.00	0.49	-48.31	-13.00	35.31

WCDMA Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolut e Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cabl e Loss (dB)			
Frequency:					826.4	MHz		
720.62	H	20.17	-52.73	0.00	0.49	-53.22	-13.00	40.22
694.26	V	19.48	-50.54	0.00	0.55	-51.09	-13.00	38.09
Frequency:					836.6	MHz		
719.53	H	20.69	-52.24	0.00	0.49	-52.73	-13.00	39.73
684.48	V	19.65	-50.55	0.00	0.53	-51.08	-13.00	38.08
Frequency:					846.6	MHz		
718.82	H	20.76	-52.18	0.00	0.49	-52.67	-13.00	39.67
676.64	V	19.73	-50.61	0.00	0.51	-51.12	-13.00	38.12

PCS Band (PART 24E)**GSM 1900:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
278.64	H	42.45	-68.77	0.00	0.32	-69.09	-13.00	56.09
60.48	V	42.37	-63.48	-10.05	0.14	-73.67	-13.00	60.67
Frequency: 1880 MHz								
279.61	H	42.36	-68.84	0.00	0.32	-69.16	-13.00	56.16
60.85	V	42.19	-63.53	-9.85	0.14	-73.52	-13.00	60.52
Frequency: 1909.8 MHz								
279.15	H	42.16	-69.05	0.00	0.32	-69.37	-13.00	56.37
60.63	V	42.61	-63.19	-9.97	0.14	-73.30	-13.00	60.30

WCDMA Band 2:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
323.58	H	40.18	-70.18	0.00	0.34	-70.52	-13.00	57.52
105.94	V	39.18	-67.46	0.00	0.19	-67.65	-13.00	54.65
Frequency: 1880 MHz								
323.15	H	40.46	-69.91	0.00	0.34	-70.25	-13.00	57.25
105.60	V	39.48	-67.19	0.00	0.19	-67.38	-13.00	54.38
Frequency: 1907.6 MHz								
322.53	H	40.38	-70.00	0.00	0.34	-70.34	-13.00	57.34
105.78	V	39.81	-66.84	0.00	0.19	-67.03	-13.00	54.03

AWS Band(Part 27)**WCDMA Band 4:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1712.4 MHz								
208.16	H	40.18	-72.55	0.00	0.26	-72.81	-13.00	59.81
106.36	V	39.65	-66.97	0.00	0.19	-67.16	-13.00	54.16
Frequency: 1732.6 MHz								
208.65	H	40.32	-72.40	0.00	0.26	-72.66	-13.00	59.66
106.49	V	39.72	-66.89	0.00	0.19	-67.08	-13.00	54.08
Frequency: 1752.6 MHz								
207.87	H	40.27	-72.46	0.00	0.26	-72.72	-13.00	59.72
106.72	V	39.34	-67.25	0.00	0.19	-67.44	-13.00	54.44

LTE Bands:(The Worst modulation and bandwidth(1RB) was below)**LTE Band 2:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
283.61	H	40.16	-70.95	0.00	0.32	-71.27	-13.00	58.27
105.34	V	39.84	-66.84	0.00	0.19	-67.03	-13.00	54.03
1.4MHz QPSK, Frequency: 1880 MHz								
217.64	H	41.21	-71.33	0.00	0.27	-71.60	-13.00	58.60
108.62	V	39.78	-66.69	0.00	0.19	-66.88	-13.00	53.88
1.4MHz QPSK, Frequency: 1909.3 MHz								
236.19	H	40.33	-71.84	0.00	0.29	-72.13	-13.00	59.13
110.07	V	39.96	-66.42	0.00	0.19	-66.61	-13.00	53.61

LTE Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
204.24	H	39.47	-73.34	0.00	0.26	-73.60	-13.00	60.60
103.49	V	39.56	-67.24	0.00	0.19	-67.43	-13.00	54.43
1.4MHz QPSK, Frequency: 1732.5 MHz								
209.31	H	40.13	-72.58	0.00	0.26	-72.84	-13.00	59.84
105.49	V	40.32	-66.35	0.00	0.19	-66.54	-13.00	53.54
1.4MHz QPSK, Frequency: 1754.3 MHz								
214.29	H	39.31	-73.30	0.00	0.27	-73.57	-13.00	60.57
107.88	V	39.47	-67.05	0.00	0.19	-67.24	-13.00	54.24

LTE Band 5:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 824.7 MHz								
679.64	H	20.45	-52.98	0.00	0.52	-53.50	-13.00	40.50
712.37	V	19.29	-50.36	0.00	0.51	-50.87	-13.00	37.87
1.4MHz QPSK, Frequency: 836.5 MHz								
724.69	H	19.58	-53.24	0.00	0.51	-53.75	-13.00	40.75
684.58	V	20.17	-50.03	0.00	0.53	-50.56	-13.00	37.56
1.4MHz QPSK, Frequency: 848.3 MHz								
706.66	H	19.78	-53.41	0.00	0.54	-53.95	-13.00	40.95
649.67	V	20.33	-50.50	0.00	0.52	-51.02	-13.00	38.02

LTE Band 7:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
207.86	H	40.31	-72.42	0.00	0.26	-72.68	-25.00	47.68
107.65	V	41.63	-64.90	0.00	0.19	-65.09	-25.00	40.09
5MHz QPSK, Frequency: 2535 MHz								
207.12	H	40.22	-72.53	0.00	0.26	-72.79	-25.00	47.79
104.75	V	41.37	-65.35	0.00	0.19	-65.54	-25.00	40.54
5MHz QPSK, Frequency: 2567.5 MHz								
208.52	H	40.17	-72.55	0.00	0.26	-72.81	-25.00	47.81
106.77	V	41.45	-65.14	0.00	0.19	-65.33	-25.00	40.33

LTE Band 12:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
625.18	H	20.41	-53.31	0.00	0.48	-53.79	-13.00	40.79
576.61	V	20.34	-51.35	0.00	0.46	-51.81	-13.00	38.81
1.4MHz QPSK, Frequency: 707.5 MHz								
647.69	H	20.37	-53.23	0.00	0.52	-53.75	-13.00	40.75
618.62	V	19.22	-52.17	0.00	0.49	-52.66	-13.00	39.66
1.4MHz QPSK, Frequency: 715.3 MHz								
589.63	H	20.19	-53.87	0.00	0.48	-54.35	-13.00	41.35
651.36	V	19.29	-51.51	0.00	0.52	-52.03	-13.00	39.03

LTE Band 17:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 706.5 MHz								
633.68	H	20.36	-53.32	0.00	0.51	-53.83	-13.00	40.83
598.64	V	20.39	-51.34	0.00	0.51	-51.85	-13.00	38.85
5MHz QPSK, Frequency: 710 MHz								
587.94	H	20.63	-53.47	0.00	0.47	-53.94	-13.00	40.94
614.52	V	19.32	-52.15	0.00	0.48	-52.63	-13.00	39.63
5MHz QPSK, Frequency: 713.5 MHz								
643.64	H	19.45	-54.17	0.00	0.52	-54.69	-13.00	41.69
636.59	V	20.17	-50.90	0.00	0.52	-51.42	-13.00	38.42

LTE Band 38:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2572.5 MHz								
210.71	H	40.31	-72.37	0.00	0.26	-72.63	-25.00	47.63
105.46	V	41.54	-65.14	0.00	0.19	-65.33	-25.00	40.33
5MHz QPSK, Frequency: 2595 MHz								
210.64	H	40.35	-72.33	0.00	0.26	-72.59	-25.00	47.59
105.27	V	41.67	-65.02	0.00	0.19	-65.21	-25.00	40.21
5MHz QPSK, Frequency: 2617.5 MHz								
209.79	H	40.28	-72.42	0.00	0.26	-72.68	-25.00	47.68
104.95	V	41.58	-65.13	0.00	0.19	-65.32	-25.00	40.32

LTE Band 41:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
209.33	H	41.42	-71.29	0.00	0.26	-71.55	-25.00	46.55
106.49	V	40.51	-66.10	0.00	0.19	-66.29	-25.00	41.29
5MHz QPSK, Frequency: 2593 MHz								
209.47	H	41.52	-71.18	0.00	0.26	-71.44	-25.00	46.44
106.83	V	40.23	-66.36	0.00	0.19	-66.55	-25.00	41.55
5MHz QPSK, Frequency: 2687.5 MHz								
208.85	H	41.32	-71.39	0.00	0.26	-71.65	-25.00	46.65
106.28	V	40.19	-66.43	0.00	0.19	-66.62	-25.00	41.62

LTE Band 42:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
208.95	H	41.73	-70.98	0.00	0.26	-71.24	-13.00	58.24
106.13	V	40.26	-66.37	0.00	0.19	-66.56	-13.00	53.56
5MHz QPSK, Frequency: 3500 MHz								
209.18	H	41.36	-71.35	0.00	0.26	-71.61	-13.00	58.61
105.95	V	40.17	-66.47	0.00	0.19	-66.66	-13.00	53.66
5MHz QPSK, Frequency: 3547.5 MHz								
209.76	H	41.24	-71.46	0.00	0.26	-71.72	-13.00	58.72
106.48	V	40.51	-66.10	0.00	0.19	-66.29	-13.00	53.29

LTE Band 66:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
208.64	H	39.62	-73.10	0.00	0.26	-73.36	-13.00	60.36
106.15	V	39.68	-66.95	0.00	0.19	-67.14	-13.00	54.14
1.4MHz QPSK, Frequency: 1745 MHz								
208.58	H	39.84	-72.88	0.00	0.26	-73.14	-13.00	60.14
106.34	V	39.47	-67.15	0.00	0.19	-67.34	-13.00	54.34
1.4MHz QPSK, Frequency: 1779.3 MHz								
208.17	H	39.18	-73.55	0.00	0.26	-73.81	-13.00	60.81
106.84	V	39.71	-66.88	0.00	0.19	-67.07	-13.00	54.07

PM:**WCDMA Band 2:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
322.18	H	40.43	-69.96	0.00	0.34	-70.30	-13.00	57.30
105.79	V	39.62	-67.03	0.00	0.19	-67.22	-13.00	54.22
Frequency: 1880 MHz								
321.79	H	40.64	-69.75	0.00	0.34	-70.09	-13.00	57.09
105.54	V	39.76	-66.91	0.00	0.19	-67.10	-13.00	54.10
Frequency: 1907.6 MHz								
323.32	H	40.15	-70.22	0.00	0.34	-70.56	-13.00	57.56
105.69	V	39.43	-67.23	0.00	0.19	-67.42	-13.00	54.42

LTE Bands:(The Worst modulation and bandwidth(1RB) was below)**LTE Band 2:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
203.69	H	39.48	-73.34	0.00	0.26	-73.60	-13.00	60.60
121.53	V	39.18	-66.72	0.00	0.20	-66.92	-13.00	53.92
1.4MHz QPSK, Frequency: 1880 MHz								
208.58	H	40.51	-72.21	0.00	0.26	-72.47	-13.00	59.47
107.13	V	41.72	-64.85	0.00	0.19	-65.04	-13.00	52.04
1.4MHz QPSK, Frequency: 1909.3 MHz								
215.26	H	39.49	-73.10	0.00	0.27	-73.37	-13.00	60.37
108.64	V	40.26	-66.21	0.00	0.19	-66.40	-13.00	53.40

LTE Band 4:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
204.51	H	40.59	-72.21	0.00	0.26	-72.47	-13.00	59.47
109.81	V	39.74	-66.65	0.00	0.19	-66.84	-13.00	53.84
1.4MHz QPSK, Frequency: 1732.5 MHz								
216.46	H	39.89	-72.67	0.00	0.27	-72.94	-13.00	59.94
105.64	V	40.96	-65.70	0.00	0.19	-65.89	-13.00	52.89
1.4MHz QPSK, Frequency: 1754.3 MHz								
209.31	H	39.64	-73.07	0.00	0.26	-73.33	-13.00	60.33
108.63	V	40.17	-66.30	0.00	0.19	-66.49	-13.00	53.49

LTE Band 7:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2502.5	MHz		
207.85	H	41.27	-71.46	0.00	0.26	-71.72	-25.00	46.72
106.15	V	40.36	-66.27	0.00	0.19	-66.46	-25.00	41.46
5MHz QPSK, Frequency:					2535	MHz		
209.64	H	41.43	-71.27	0.00	0.26	-71.53	-25.00	46.53
104.51	V	39.84	-66.90	0.00	0.19	-67.09	-25.00	42.09
5MHz QPSK, Frequency:					2567.5	MHz		
206.40	H	41.38	-71.38	0.00	0.26	-71.64	-25.00	46.64
103.68	V	40.18	-66.61	0.00	0.19	-66.80	-25.00	41.80

LTE Band 38:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2572.5	MHz		
210.49	H	40.22	-72.46	0.00	0.26	-72.72	-25.00	47.72
106.27	V	42.46	-64.16	0.00	0.19	-64.35	-25.00	39.35
5MHz QPSK, Frequency:					2595	MHz		
210.78	H	40.28	-72.40	0.00	0.26	-72.66	-25.00	47.66
104.90	V	42.63	-64.08	0.00	0.19	-64.27	-25.00	39.27
5MHz QPSK, Frequency:					2617.5	MHz		
209.87	H	40.19	-72.50	0.00	0.26	-72.76	-25.00	47.76
106.38	V	42.58	-64.04	0.00	0.19	-64.23	-25.00	39.23

LTE Band 41:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2498.5	MHz		
209.33	H	41.66	-71.05	0.00	0.26	-71.31	-25.00	46.31
106.56	V	40.16	-66.44	0.00	0.19	-66.63	-25.00	41.63
5MHz QPSK, Frequency:					2593	MHz		
209.64	H	41.35	-71.35	0.00	0.26	-71.61	-25.00	46.61
106.19	V	40.42	-66.21	0.00	0.19	-66.40	-25.00	41.40
5MHz QPSK, Frequency:					2687.5	MHz		
208.92	H	41.29	-71.42	0.00	0.26	-71.68	-25.00	46.68
106.45	V	40.23	-66.38	0.00	0.19	-66.57	-25.00	41.57

LTE Band 42:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
209.43	H	41.64	-71.06	0.00	0.26	-71.32	-13.00	58.32
105.89	V	40.22	-66.43	0.00	0.19	-66.62	-13.00	53.62
5MHz QPSK, Frequency: 3500 MHz								
209.84	H	41.38	-71.32	0.00	0.26	-71.58	-13.00	58.58
105.96	V	40.46	-66.18	0.00	0.19	-66.37	-13.00	53.37
5MHz QPSK, Frequency: 3547.5 MHz								
209.52	H	41.49	-71.21	0.00	0.26	-71.47	-13.00	58.47
105.63	V	40.39	-66.27	0.00	0.19	-66.46	-13.00	53.46

LTE Band 66:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
209.78	H	39.81	-72.89	0.00	0.26	-73.15	-13.00	60.15
106.89	V	39.45	-67.13	0.00	0.19	-67.32	-13.00	54.32
1.4MHz QPSK, Frequency: 1745 MHz								
209.65	H	39.48	-73.22	0.00	0.26	-73.48	-13.00	60.48
106.46	V	39.18	-67.43	0.00	0.19	-67.62	-13.00	54.62
1.4MHz QPSK, Frequency: 1779.3 MHz								
209.48	H	39.67	-73.03	0.00	0.26	-73.29	-13.00	60.29
106.17	V	39.42	-67.21	0.00	0.19	-67.40	-13.00	54.40

DM:**LTE Bands:(The Worst modulation and bandwidth(1RB) was below)****LTE Band 42:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
209.37	H	41.73	-70.97	0.00	0.26	-71.23	-13.00	58.23
105.83	V	40.59	-66.06	0.00	0.19	-66.25	-13.00	53.25
5MHz QPSK, Frequency: 3500 MHz								
209.76	H	41.49	-71.21	0.00	0.26	-71.47	-13.00	58.47
106.13	V	40.37	-66.26	0.00	0.19	-66.45	-13.00	53.45
5MHz QPSK, Frequency: 3547.5 MHz								
209.41	H	41.65	-71.05	0.00	0.26	-71.31	-13.00	58.31
106.48	V	40.26	-66.35	0.00	0.19	-66.54	-13.00	53.54

2) Above 1GHz

Serial Number:	2N75-1	Test Date:	2024/7/15
Test Site:	966-1	Test Mode:	Transmitting
Tester:	Mack Huang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.6	Relative Humidity: (%)	67	ATM Pressure: (kPa)	100.9

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	9912-5985	2023/12/6	2026/12/5
R&S	Spectrum Analyzer	FSV40	101591	2024/4/1	2025/3/31
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2024/1/15	2025/1/14
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2024/1/15	2025/1/14
BACL	Preamplifier	1313-A20M18G	4032311	2024/4/1	2025/3/31
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2023/7/16	2024/7/15
Agilent	Signal Generator	E8247C	MY43321352	2023/11/17	2024/11/16
PASTERNACK	Horn Antenna	PE9852/2F-20	112002	2024/2/4	2027/2/3
PASTERNACK	Horn Antenna	PE9852/2F-20	112001	2024/2/4	2027/2/3
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2024/1/15	2025/1/14
PASTERNACK	Horn Antenna	PE9850/2F-20	072001	2024/2/4	2027/2/3
PASTERNACK	Horn Antenna	PE9850/2F-20	072002	2024/2/4	2027/2/3
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2024/1/15	2025/1/14
JD	Multiplex Switch Test Control Set	DT7220SCU	DQ77925	2023/8/6	2024/8/5
JD	Filter Switch Unit	DT7220FSU	DQ77928	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

PRX:

Cellular Band (PART 22H)**GSM850(1-10GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 824.2 MHz								
1648.400	H	39.73	-64.72	8.68	0.80	-56.84	-13.00	43.84
1648.400	V	40.81	-63.72	8.68	0.80	-55.84	-13.00	42.84
2472.600	H	39.25	-61.78	9.38	1.00	-53.40	-13.00	40.40
2472.600	V	39.41	-61.57	9.38	1.00	-53.19	-13.00	40.19
3296.800	H	35.85	-61.53	10.32	1.15	-52.36	-13.00	39.36
3296.800	V	35.10	-62.04	10.32	1.15	-52.87	-13.00	39.87
Frequency: 836.6 MHz								
1673.200	H	40.31	-64.11	8.71	0.85	-56.25	-13.00	43.25
1673.200	V	40.06	-64.47	8.71	0.85	-56.61	-13.00	43.61
2509.800	H	41.60	-59.23	9.42	1.01	-50.82	-13.00	37.82
2509.800	V	43.03	-57.81	9.42	1.01	-49.40	-13.00	36.40
3346.400	H	34.96	-63.10	10.34	1.16	-53.92	-13.00	40.92
3346.400	V	35.44	-62.48	10.34	1.16	-53.30	-13.00	40.30
Frequency: 848.8 MHz								
1697.600	H	38.77	-65.62	8.74	0.90	-57.78	-13.00	44.78
1697.600	V	39.64	-64.88	8.74	0.90	-57.04	-13.00	44.04
2546.400	H	41.52	-59.09	9.47	1.01	-50.63	-13.00	37.63
2546.400	V	42.13	-58.43	9.47	1.01	-49.97	-13.00	36.97
3395.200	H	35.12	-63.67	10.36	1.19	-54.50	-13.00	41.50
3395.200	V	35.20	-63.56	10.36	1.19	-54.39	-13.00	41.39

WCDMA Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 826.4 MHz								
1652.800	H	37.28	-67.17	8.68	0.81	-59.30	-13.00	46.30
1652.800	V	35.45	-69.08	8.68	0.81	-61.21	-13.00	48.21
2479.200	H	35.11	-65.89	9.39	1.01	-57.51	-13.00	44.51
2479.200	V	34.10	-66.87	9.39	1.01	-58.49	-13.00	45.49
3305.600	H	34.52	-62.93	10.32	1.15	-53.76	-13.00	40.76
3305.600	V	34.69	-62.54	10.32	1.15	-53.37	-13.00	40.37
Frequency: 836.6 MHz								
1673.200	H	35.41	-69.01	8.71	0.85	-61.15	-13.00	48.15
1673.200	V	36.23	-68.30	8.71	0.85	-60.44	-13.00	47.44
2509.800	H	34.87	-65.96	9.42	1.01	-57.55	-13.00	44.55
2509.800	V	35.28	-65.56	9.42	1.01	-57.15	-13.00	44.15
3346.400	H	34.01	-64.05	10.34	1.16	-54.87	-13.00	41.87
3346.400	V	34.33	-63.59	10.34	1.16	-54.41	-13.00	41.41
Frequency: 846.6 MHz								
1693.200	H	37.61	-66.79	8.73	0.89	-58.95	-13.00	45.95
1693.200	V	36.58	-67.94	8.73	0.89	-60.10	-13.00	47.10
2539.800	H	35.33	-65.32	9.46	1.01	-56.87	-13.00	43.87
2539.800	V	34.53	-66.08	9.46	1.01	-57.63	-13.00	44.63
3386.400	H	34.41	-64.25	10.35	1.18	-55.08	-13.00	42.08
3386.400	V	34.87	-63.74	10.35	1.18	-54.57	-13.00	41.57

PCS Band (PART 24E)**GSM1900(1-20GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
3700.400	H	35.39	-63.59	10.60	1.25	-54.24	-13.00	41.24
3700.400	V	34.87	-64.09	10.60	1.25	-54.74	-13.00	41.74
5550.600	H	47.22	-48.95	11.44	1.49	-39.00	-13.00	26.00
5550.600	V	45.42	-50.58	11.44	1.49	-40.63	-13.00	27.63
Frequency: 1880 MHz								
3760.000	H	34.67	-63.03	10.66	1.24	-53.61	-13.00	40.61
3760.000	V	35.69	-61.89	10.66	1.24	-52.47	-13.00	39.47
5640.000	H	43.73	-53.07	11.33	1.54	-43.28	-13.00	30.28
5640.000	V	42.74	-53.94	11.33	1.54	-44.15	-13.00	31.15
Frequency: 1909.8 MHz								
3819.600	H	34.69	-62.30	10.72	1.29	-52.87	-13.00	39.87
3819.600	V	35.44	-61.40	10.72	1.29	-51.97	-13.00	38.97
5729.400	H	41.33	-55.81	11.22	1.59	-46.18	-13.00	33.18
5729.400	V	42.03	-54.98	11.22	1.59	-45.35	-13.00	32.35

1710-1780 MHz Band (PART 27)**WCDMA Band 4(1-18GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:			1712.4	MHz				
3424.800	H	35.44	-63.48	10.37	1.17	-54.28	-13.00	41.28
3424.800	V	34.66	-64.23	10.37	1.17	-55.03	-13.00	42.03
5137.200	H	38.69	-57.51	11.28	1.46	-47.69	-13.00	34.69
5137.200	V	37.26	-58.83	11.28	1.46	-49.01	-13.00	36.01
Frequency:			1732.6	MHz				
3465.200	H	35.10	-63.92	10.39	1.15	-54.68	-13.00	41.68
3465.200	V	34.22	-64.75	10.39	1.15	-55.51	-13.00	42.51
5197.800	H	36.21	-60.74	11.32	1.44	-50.86	-13.00	37.86
5197.800	V	37.54	-59.26	11.32	1.44	-49.38	-13.00	36.38
Frequency:			1752.6	MHz				
3505.200	H	37.68	-61.38	10.41	1.18	-52.15	-13.00	39.15
3505.200	V	35.05	-63.95	10.41	1.18	-54.72	-13.00	41.72
5257.800	H	37.93	-58.87	11.35	1.47	-48.99	-13.00	35.99
5257.800	V	38.49	-58.09	11.35	1.47	-48.21	-13.00	35.21

LTE Bands:(The Worst modulation and bandwidth(1RB) was below)**LTE Band 4(1-18GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:			1710.7	MHz				
3421.400	H	38.22	-60.69	10.37	1.17	-51.49	-13.00	38.49
3421.400	V	35.58	-63.30	10.37	1.17	-54.10	-13.00	41.10
5132.100	H	49.98	-46.16	11.28	1.47	-36.35	-13.00	23.35
5132.100	V	45.47	-50.56	11.28	1.47	-40.75	-13.00	27.75
1.4MHz QPSK, Frequency:			1732.5	MHz				
3465.000	H	35.11	-63.91	10.39	1.15	-54.67	-13.00	41.67
3465.000	V	34.33	-64.64	10.39	1.15	-55.40	-13.00	42.40
5197.500	H	38.80	-58.15	11.32	1.44	-48.27	-13.00	35.27
5197.500	V	36.80	-60.00	11.32	1.44	-50.12	-13.00	37.12
1.4MHz QPSK, Frequency:			1754.3	MHz				
3508.600	H	39.67	-59.37	10.41	1.19	-50.15	-13.00	37.15
3508.600	V	34.60	-64.37	10.41	1.19	-55.15	-13.00	42.15
5262.900	H	46.06	-50.73	11.36	1.47	-40.84	-13.00	27.84
5262.900	V	43.43	-53.13	11.36	1.47	-43.24	-13.00	30.24

LTE Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:					824.7	MHz		
1649.400	H	40.12	-64.33	8.68	0.80	-56.45	-13.00	43.45
1649.400	V	37.47	-67.06	8.68	0.80	-59.18	-13.00	46.18
2474.100	H	34.80	-66.22	9.38	1.00	-57.84	-13.00	44.84
2474.100	V	34.36	-66.62	9.38	1.00	-58.24	-13.00	45.24
3298.800	H	35.16	-62.21	10.32	1.15	-53.04	-13.00	40.04
3298.800	V	35.02	-62.11	10.32	1.15	-52.94	-13.00	39.94
1.4MHz QPSK, Frequency:					836.5	MHz		
1673.000	H	39.51	-64.91	8.71	0.85	-57.05	-13.00	44.05
1673.000	V	37.28	-67.25	8.71	0.85	-59.39	-13.00	46.39
2509.500	H	34.56	-66.27	9.42	1.01	-57.86	-13.00	44.86
2509.500	V	35.01	-65.84	9.42	1.01	-57.43	-13.00	44.43
3346.000	H	34.55	-63.51	10.34	1.16	-54.33	-13.00	41.33
3346.000	V	34.63	-63.29	10.34	1.16	-54.11	-13.00	41.11
1.4MHz QPSK, Frequency:					848.3	MHz		
1696.600	H	36.93	-67.46	8.74	0.89	-59.61	-13.00	46.61
1696.600	V	36.11	-68.41	8.74	0.89	-60.56	-13.00	47.56
2544.900	H	35.42	-65.20	9.47	1.01	-56.74	-13.00	43.74
2544.900	V	34.87	-65.70	9.47	1.01	-57.24	-13.00	44.24
3393.200	H	34.23	-64.53	10.36	1.19	-55.36	-13.00	42.36
3393.200	V	35.20	-63.52	10.36	1.19	-54.35	-13.00	41.35

LTE Band 7(1-26GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2502.5	MHz		
5005.000	H	35.46	-60.01	11.20	1.47	-50.28	-25.00	25.28
5005.000	V	34.37	-60.97	11.20	1.47	-51.24	-25.00	26.24
7507.500	H	34.95	-59.12	10.90	1.95	-50.17	-25.00	25.17
7507.500	V	35.22	-59.35	10.90	1.95	-50.40	-25.00	25.40
5MHz QPSK, Frequency:					2535	MHz		
5070.000	H	35.12	-60.54	11.24	1.47	-50.77	-25.00	25.77
5070.000	V	34.36	-61.19	11.24	1.47	-51.42	-25.00	26.42
7605.000	H	34.87	-58.61	10.88	2.01	-49.74	-25.00	24.74
7605.000	V	35.91	-58.28	10.88	2.01	-49.41	-25.00	24.41
5MHz QPSK, Frequency:					2567.5	MHz		
5135.000	H	42.60	-53.57	11.28	1.47	-43.76	-25.00	18.76
5135.000	V	42.31	-53.75	11.28	1.47	-43.94	-25.00	18.94
7702.500	H	35.83	-57.39	10.86	1.97	-48.50	-25.00	23.50
7702.500	V	34.77	-59.11	10.86	1.97	-50.22	-25.00	25.22

LTE Band 12(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
1399.400	H	35.54	-68.26	8.22	0.71	-60.75	-13.00	47.75
1399.400	V	34.28	-69.56	8.22	0.71	-62.05	-13.00	49.05
2099.100	H	34.33	-67.53	9.16	0.91	-59.28	-13.00	46.28
2099.100	V	35.96	-65.85	9.16	0.91	-57.60	-13.00	44.60
2798.800	H	43.06	-57.46	9.88	1.04	-48.62	-13.00	35.62
2798.800	V	41.96	-58.43	9.88	1.04	-49.59	-13.00	36.59
1.4MHz QPSK, Frequency: 707.5 MHz								
1415.000	H	35.34	-68.41	8.26	0.72	-60.87	-13.00	47.87
1415.000	V	34.66	-69.14	8.26	0.72	-61.60	-13.00	48.60
2122.500	H	34.56	-67.46	9.17	0.92	-59.21	-13.00	46.21
2122.500	V	35.54	-66.46	9.17	0.92	-58.21	-13.00	45.21
2830.000	H	40.87	-59.58	9.93	1.06	-50.71	-13.00	37.71
2830.000	V	38.94	-61.45	9.93	1.06	-52.58	-13.00	39.58
1.4MHz QPSK, Frequency: 715.3 MHz								
1430.600	H	35.78	-67.90	8.31	0.73	-60.32	-13.00	47.32
1430.600	V	35.44	-68.30	8.31	0.73	-60.72	-13.00	47.72
2145.900	H	34.21	-67.98	9.19	0.93	-59.72	-13.00	46.72
2145.900	V	34.35	-67.85	9.19	0.93	-59.59	-13.00	46.59
2861.200	H	41.87	-58.50	9.98	1.07	-49.59	-13.00	36.59
2861.200	V	40.63	-59.75	9.98	1.07	-50.84	-13.00	37.84

LTE Band 17(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			706.5	MHz				
1413.000	H	34.63	-69.13	8.26	0.72	-61.59	-13.00	48.59
1413.000	V	34.87	-68.93	8.26	0.72	-61.39	-13.00	48.39
2119.500	H	35.25	-66.75	9.17	0.92	-58.50	-13.00	45.50
2119.500	V	34.30	-67.68	9.17	0.92	-59.43	-13.00	46.43
2826.000	H	34.85	-65.61	9.92	1.06	-56.75	-13.00	43.75
2826.000	V	35.11	-65.28	9.92	1.06	-56.42	-13.00	43.42
5MHz QPSK, Frequency:			710	MHz				
1420.000	H	34.55	-69.18	8.28	0.73	-61.63	-13.00	48.63
1420.000	V	34.33	-69.45	8.28	0.73	-61.90	-13.00	48.90
2130.000	H	35.01	-67.06	9.18	0.92	-58.80	-13.00	45.80
2130.000	V	34.85	-67.22	9.18	0.92	-58.96	-13.00	45.96
2840.000	H	36.58	-63.84	9.94	1.06	-54.96	-13.00	41.96
2840.000	V	35.13	-65.26	9.94	1.06	-56.38	-13.00	43.38
5MHz QPSK, Frequency:			713.5	MHz				
1427.000	H	34.21	-69.49	8.30	0.73	-61.92	-13.00	48.92
1427.000	V	35.20	-68.56	8.30	0.73	-60.99	-13.00	47.99
2140.500	H	34.33	-67.82	9.18	0.93	-59.57	-13.00	46.57
2140.500	V	34.87	-67.28	9.18	0.93	-59.03	-13.00	46.03
2854.000	H	35.81	-64.58	9.97	1.07	-55.68	-13.00	42.68
2854.000	V	35.25	-65.13	9.97	1.07	-56.23	-13.00	43.23

LTE Band 38(1-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			2572.5	MHz				
5145.000	H	42.17	-54.13	11.29	1.44	-44.28	-25.00	19.28
5145.000	V	39.07	-57.11	11.29	1.44	-47.26	-25.00	22.26
7717.500	H	34.47	-58.78	10.86	1.99	-49.91	-25.00	24.91
7717.500	V	35.41	-58.46	10.86	1.99	-49.59	-25.00	24.59
5MHz QPSK, Frequency:			2595	MHz				
5190.000	H	43.45	-53.41	11.31	1.44	-43.54	-25.00	18.54
5190.000	V	43.91	-52.80	11.31	1.44	-42.93	-25.00	17.93
7785.000	H	34.98	-58.41	10.84	1.99	-49.56	-25.00	24.56
7785.000	V	35.55	-58.27	10.84	1.99	-49.42	-25.00	24.42
5MHz QPSK, Frequency:			2617.5	MHz				
5235.000	H	52.12	-44.75	11.34	1.46	-34.87	-25.00	9.87
5235.000	V	52.83	-43.85	11.34	1.46	-33.97	-25.00	8.97
7852.500	H	35.11	-58.37	10.83	2.03	-49.57	-25.00	24.57
7852.500	V	35.74	-58.13	10.83	2.03	-49.33	-25.00	24.33

LTE Band 41(1-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBr/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2498.5	MHz	ANT 0	
4997.000	H	38.55	-56.90	11.20	1.48	-47.18	-25.00	22.18
4997.000	V	36.79	-58.52	11.20	1.48	-48.80	-25.00	23.80
7495.500	H	34.52	-59.58	10.90	1.94	-50.62	-25.00	25.62
7495.500	V	35.85	-58.75	10.90	1.94	-49.79	-25.00	24.79
5MHz QPSK, Frequency:					2593	MHz		
5186.000	H	43.40	-53.41	11.31	1.44	-43.54	-25.00	18.54
5186.000	V	44.38	-52.28	11.31	1.44	-42.41	-25.00	17.41
7779.000	H	34.74	-58.64	10.84	1.99	-49.79	-25.00	24.79
7779.000	V	35.23	-58.59	10.84	1.99	-49.74	-25.00	24.74
5MHz QPSK, Frequency:					2687.5	MHz		
5375.000	H	37.20	-59.31	11.43	1.49	-49.37	-25.00	24.37
5375.000	V	36.24	-60.26	11.43	1.49	-50.32	-25.00	25.32
8062.500	H	36.88	-56.06	10.81	2.12	-47.37	-25.00	22.37
8062.500	V	35.69	-57.75	10.81	2.12	-49.06	-25.00	24.06

LTE Band 42(1-36GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBr/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					3452.5	MHz		
6905.000	H	34.46	-61.62	11.22	1.87	-52.27	-25.00	27.27
6905.000	V	35.55	-60.40	11.22	1.87	-51.05	-25.00	26.05
10357.500	H	35.10	-57.20	11.49	2.49	-48.20	-25.00	23.20
10357.500	V	34.20	-58.21	11.49	2.49	-49.21	-25.00	24.21
5MHz QPSK, Frequency:					3500	MHz		
7000.000	H	34.39	-60.71	11.20	1.89	-51.40	-25.00	26.40
7000.000	V	34.56	-60.39	11.20	1.89	-51.08	-25.00	26.08
10500.000	H	35.10	-56.50	11.40	2.52	-47.62	-25.00	22.62
10500.000	V	34.77	-56.92	11.40	2.52	-48.04	-25.00	23.04
5MHz QPSK, Frequency:					3547.5	MHz		
7095.000	H	34.36	-58.98	11.14	1.89	-49.73	-25.00	24.73
7095.000	V	35.07	-58.20	11.14	1.89	-48.95	-25.00	23.95
10642.500	H	34.89	-56.67	11.40	2.50	-47.77	-25.00	22.77
10642.500	V	34.26	-57.44	11.40	2.50	-48.54	-25.00	23.54

LTE Band 66(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:					1710.7	MHz		
3421.400	H	37.86	-61.05	10.37	1.17	-51.85	-13.00	38.85
3421.400	V	36.22	-62.66	10.37	1.17	-53.46	-13.00	40.46
5132.100	H	48.99	-47.15	11.28	1.47	-37.34	-13.00	24.34
5132.100	V	46.92	-49.11	11.28	1.47	-39.30	-13.00	26.30
1.4MHz QPSK, Frequency:					1745	MHz		
3490.000	H	38.97	-60.11	10.40	1.17	-50.88	-13.00	37.88
3490.000	V	34.46	-64.56	10.40	1.17	-55.33	-13.00	42.33
5235.000	H	40.50	-56.37	11.34	1.46	-46.49	-13.00	33.49
5235.000	V	38.68	-58.00	11.34	1.46	-48.12	-13.00	35.12
1.4MHz QPSK, Frequency:					1779.3	MHz		
3558.600	H	41.45	-57.23	10.46	1.22	-47.99	-13.00	34.99
3558.600	V	36.17	-62.40	10.46	1.22	-53.16	-13.00	40.16
5337.900	H	44.61	-51.98	11.40	1.47	-42.05	-13.00	29.05
5337.900	V	44.90	-51.55	11.40	1.47	-41.62	-13.00	28.62

DRX:**GSM850(1-10GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency:					824.2	MHz		
1648.400	H	38.16	-66.29	8.68	0.80	-58.41	-13.00	45.41
1648.400	V	37.12	-67.41	8.68	0.80	-59.53	-13.00	46.53
2472.600	H	33.28	-67.75	9.38	1.00	-59.37	-13.00	46.37
2472.600	V	33.17	-67.81	9.38	1.00	-59.43	-13.00	46.43
3296.800	H	33.61	-63.77	10.32	1.15	-54.60	-13.00	41.60
3296.800	V	33.27	-63.87	10.32	1.15	-54.70	-13.00	41.70
Frequency:					836.6	MHz		
1673.200	H	37.85	-66.57	8.71	0.85	-58.71	-13.00	45.71
1673.200	V	38.81	-65.72	8.71	0.85	-57.86	-13.00	44.86
2509.800	H	34.05	-66.78	9.42	1.01	-58.37	-13.00	45.37
2509.800	V	33.68	-67.16	9.42	1.01	-58.75	-13.00	45.75
3346.400	H	33.93	-64.13	10.34	1.16	-54.95	-13.00	41.95
3346.400	V	33.54	-64.38	10.34	1.16	-55.20	-13.00	42.20
Frequency:					848.8	MHz		
1697.600	H	35.76	-68.63	8.74	0.90	-60.79	-13.00	47.79
1697.600	V	36.56	-67.96	8.74	0.90	-60.12	-13.00	47.12
2546.400	H	33.52	-67.09	9.47	1.01	-58.63	-13.00	45.63
2546.400	V	33.96	-66.60	9.47	1.01	-58.14	-13.00	45.14
3395.200	H	33.20	-65.59	10.36	1.19	-56.42	-13.00	43.42
3395.200	V	33.13	-65.63	10.36	1.19	-56.46	-13.00	43.46

WCDMA Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 826.4 MHz								
1652.800	H	35.36	-69.09	8.68	0.81	-61.22	-13.00	48.22
1652.800	V	35.08	-69.45	8.68	0.81	-61.58	-13.00	48.58
2479.200	H	33.28	-67.72	9.39	1.01	-59.34	-13.00	46.34
2479.200	V	33.08	-67.89	9.39	1.01	-59.51	-13.00	46.51
3305.600	H	33.87	-63.58	10.32	1.15	-54.41	-13.00	41.41
3305.600	V	33.37	-63.86	10.32	1.15	-54.69	-13.00	41.69
Frequency: 836.6 MHz								
1673.200	H	35.54	-68.88	8.71	0.85	-61.02	-13.00	48.02
1673.200	V	35.13	-69.40	8.71	0.85	-61.54	-13.00	48.54
2509.800	H	33.12	-67.71	9.42	1.01	-59.30	-13.00	46.30
2509.800	V	34.18	-66.66	9.42	1.01	-58.25	-13.00	45.25
3346.400	H	33.69	-64.37	10.34	1.16	-55.19	-13.00	42.19
3346.400	V	33.61	-64.31	10.34	1.16	-55.13	-13.00	42.13
Frequency: 846.6 MHz								
1693.200	H	35.63	-68.77	8.73	0.89	-60.93	-13.00	47.93
1693.200	V	35.88	-68.64	8.73	0.89	-60.80	-13.00	47.80
2539.800	H	33.36	-67.29	9.46	1.01	-58.84	-13.00	45.84
2539.800	V	33.24	-67.37	9.46	1.01	-58.92	-13.00	45.92
3386.400	H	33.14	-65.52	10.35	1.18	-56.35	-13.00	43.35
3386.400	V	33.36	-65.25	10.35	1.18	-56.08	-13.00	43.08

PCS Band (PART 24E)**GSM1900(1-20GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1850.2 MHz								
3700.400	H	34.33	-64.65	10.60	1.25	-55.30	-13.00	42.30
3700.400	V	35.02	-63.94	10.60	1.25	-54.59	-13.00	41.59
5550.600	H	34.88	-61.29	11.44	1.49	-51.34	-13.00	38.34
5550.600	V	33.90	-62.10	11.44	1.49	-52.15	-13.00	39.15
Frequency: 1880 MHz								
3760.000	H	34.12	-63.58	10.66	1.24	-54.16	-13.00	41.16
3760.000	V	33.87	-63.71	10.66	1.24	-54.29	-13.00	41.29
5640.000	H	34.66	-62.14	11.33	1.54	-52.35	-13.00	39.35
5640.000	V	34.28	-62.40	11.33	1.54	-52.61	-13.00	39.61
Frequency: 1909.8 MHz								
3819.600	H	34.77	-62.22	10.72	1.29	-52.79	-13.00	39.79
3819.600	V	34.31	-62.53	10.72	1.29	-53.10	-13.00	40.10
5729.400	H	35.20	-61.94	11.22	1.59	-52.31	-13.00	39.31
5729.400	V	34.87	-62.14	11.22	1.59	-52.51	-13.00	39.51

WCDMA Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
3704.800	H	35.12	-63.77	10.60	1.25	-54.42	-13.00	41.42
3704.800	V	34.63	-64.23	10.60	1.25	-54.88	-13.00	41.88
5557.200	H	34.20	-62.02	11.43	1.49	-52.08	-13.00	39.08
5557.200	V	33.99	-62.08	11.43	1.49	-52.14	-13.00	39.14
Frequency: 1880 MHz								
3760.000	H	34.21	-63.49	10.66	1.24	-54.07	-13.00	41.07
3760.000	V	35.09	-62.49	10.66	1.24	-53.07	-13.00	40.07
5640.000	H	34.33	-62.47	11.33	1.54	-52.68	-13.00	39.68
5640.000	V	34.89	-61.79	11.33	1.54	-52.00	-13.00	39.00
Frequency: 1907.6 MHz								
3815.200	H	34.85	-62.10	10.72	1.29	-52.67	-13.00	39.67
3815.200	V	33.88	-62.92	10.72	1.29	-53.49	-13.00	40.49
5722.800	H	34.16	-62.97	11.23	1.58	-53.32	-13.00	40.32
5722.800	V	35.07	-61.93	11.23	1.58	-52.28	-13.00	39.28

1710-1780 MHz Band (PART 27)**WCDMA Band 4(1-18GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1712.4 MHz								
3424.800	H	35.01	-63.91	10.37	1.17	-54.71	-13.00	41.71
3424.800	V	34.85	-64.04	10.37	1.17	-54.84	-13.00	41.84
5137.200	H	34.32	-61.88	11.28	1.46	-52.06	-13.00	39.06
5137.200	V	34.69	-61.40	11.28	1.46	-51.58	-13.00	38.58
Frequency: 1732.6 MHz								
3465.200	H	34.88	-64.14	10.39	1.15	-54.90	-13.00	41.90
3465.200	V	33.69	-65.28	10.39	1.15	-56.04	-13.00	43.04
5197.800	H	34.21	-62.74	11.32	1.44	-52.86	-13.00	39.86
5197.800	V	34.57	-62.23	11.32	1.44	-52.35	-13.00	39.35
Frequency: 1752.6 MHz								
3505.200	H	35.01	-64.05	10.41	1.18	-54.82	-13.00	41.82
3505.200	V	34.66	-64.34	10.41	1.18	-55.11	-13.00	42.11
5257.800	H	34.87	-61.93	11.35	1.47	-52.05	-13.00	39.05
5257.800	V	34.20	-62.38	11.35	1.47	-52.50	-13.00	39.50

LTE Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
3701.400	H	34.75	-64.21	10.60	1.25	-54.86	-13.00	41.86
3701.400	V	35.42	-63.52	10.60	1.25	-54.17	-13.00	41.17
5552.100	H	34.63	-61.55	11.44	1.49	-51.60	-13.00	38.60
5552.100	V	34.99	-61.03	11.44	1.49	-51.08	-13.00	38.08
1.4MHz QPSK, Frequency: 1880 MHz								
3760.000	H	34.95	-62.75	10.66	1.24	-53.33	-13.00	40.33
3760.000	V	35.22	-62.36	10.66	1.24	-52.94	-13.00	39.94
5640.000	H	36.02	-60.78	11.33	1.54	-50.99	-13.00	37.99
5640.000	V	34.78	-61.90	11.33	1.54	-52.11	-13.00	39.11
1.4MHz QPSK, Frequency: 1909.3 MHz								
3818.600	H	34.84	-62.14	10.72	1.29	-52.71	-13.00	39.71
3818.600	V	35.01	-61.82	10.72	1.29	-52.39	-13.00	39.39
5727.900	H	35.59	-61.54	11.23	1.59	-51.90	-13.00	38.90
5727.900	V	36.22	-60.78	11.23	1.59	-51.14	-13.00	38.14

LTE Band 4(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	35.10	-63.81	10.37	1.17	-54.61	-13.00	41.61
3421.400	V	34.78	-64.10	10.37	1.17	-54.90	-13.00	41.90
5132.100	H	34.66	-61.48	11.28	1.47	-51.67	-13.00	38.67
5132.100	V	34.82	-61.21	11.28	1.47	-51.40	-13.00	38.40
1.4MHz QPSK, Frequency: 1732.5 MHz								
3465.000	H	34.42	-64.60	10.39	1.15	-55.36	-13.00	42.36
3465.000	V	35.22	-63.75	10.39	1.15	-54.51	-13.00	41.51
5197.500	H	34.13	-62.82	11.32	1.44	-52.94	-13.00	39.94
5197.500	V	34.87	-61.93	11.32	1.44	-52.05	-13.00	39.05
1.4MHz QPSK, Frequency: 1754.3 MHz								
3508.600	H	39.84	-59.20	10.41	1.19	-49.98	-13.00	36.98
3508.600	V	35.55	-63.42	10.41	1.19	-54.20	-13.00	41.20
5262.900	H	34.11	-62.68	11.36	1.47	-52.79	-13.00	39.79
5262.900	V	34.39	-62.17	11.36	1.47	-52.28	-13.00	39.28

LTE Band 5(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 824.7 MHz								
1649.400	H	38.08	-66.37	8.68	0.80	-58.49	-13.00	45.49
1649.400	V	39.31	-65.22	8.68	0.80	-57.34	-13.00	44.34
2474.100	H	38.66	-62.36	9.38	1.00	-53.98	-13.00	40.98
2474.100	V	39.64	-61.34	9.38	1.00	-52.96	-13.00	39.96
3298.800	H	35.62	-61.75	10.32	1.15	-52.58	-13.00	39.58
3298.800	V	35.79	-61.34	10.32	1.15	-52.17	-13.00	39.17
1.4MHz QPSK, Frequency: 836.5 MHz								
1673.000	H	45.32	-59.10	8.71	0.85	-51.24	-13.00	38.24
1673.000	V	43.74	-60.79	8.71	0.85	-52.93	-13.00	39.93
2509.500	H	37.65	-63.18	9.42	1.01	-54.77	-13.00	41.77
2509.500	V	38.16	-62.69	9.42	1.01	-54.28	-13.00	41.28
3346.000	H	36.20	-61.86	10.34	1.16	-52.68	-13.00	39.68
3346.000	V	38.46	-59.46	10.34	1.16	-50.28	-13.00	37.28
1.4MHz QPSK, Frequency: 848.3 MHz								
1696.600	H	34.25	-70.14	8.74	0.89	-62.29	-13.00	49.29
1696.600	V	35.37	-69.15	8.74	0.89	-61.30	-13.00	48.30
2544.900	H	34.14	-66.48	9.47	1.01	-58.02	-13.00	45.02
2544.900	V	34.80	-65.77	9.47	1.01	-57.31	-13.00	44.31
3393.200	H	34.06	-64.70	10.36	1.19	-55.53	-13.00	42.53
3393.200	V	34.79	-63.93	10.36	1.19	-54.76	-13.00	41.76

LTE Band 7(1-26GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
5005.000	H	36.12	-59.35	11.20	1.47	-49.62	-25.00	24.62
5005.000	V	34.55	-60.79	11.20	1.47	-51.06	-25.00	26.06
7507.500	H	35.30	-58.77	10.90	1.95	-49.82	-25.00	24.82
7507.500	V	34.87	-59.70	10.90	1.95	-50.75	-25.00	25.75
5MHz QPSK, Frequency: 2535 MHz								
5070.000	H	37.82	-57.84	11.24	1.47	-48.07	-25.00	23.07
5070.000	V	34.77	-60.78	11.24	1.47	-51.01	-25.00	26.01
7605.000	H	34.01	-59.47	10.88	2.01	-50.60	-25.00	25.60
7605.000	V	34.26	-59.93	10.88	2.01	-51.06	-25.00	26.06
5MHz QPSK, Frequency: 2567.5 MHz								
5135.000	H	34.78	-61.39	11.28	1.47	-51.58	-25.00	26.58
5135.000	V	35.58	-60.48	11.28	1.47	-50.67	-25.00	25.67
7702.500	H	35.22	-58.00	10.86	1.97	-49.11	-25.00	24.11
7702.500	V	34.96	-58.92	10.86	1.97	-50.03	-25.00	25.03

LTE Band 12(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBr/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
1399.400	H	34.65	-69.15	8.22	0.71	-61.64	-13.00	48.64
1399.400	V	35.01	-68.83	8.22	0.71	-61.32	-13.00	48.32
2099.100	H	34.80	-67.06	9.16	0.91	-58.81	-13.00	45.81
2099.100	V	34.33	-67.48	9.16	0.91	-59.23	-13.00	46.23
2798.800	H	35.95	-64.57	9.88	1.04	-55.73	-13.00	42.73
2798.800	V	35.84	-64.55	9.88	1.04	-55.71	-13.00	42.71
1.4MHz QPSK, Frequency: 707.5 MHz								
1415.000	H	34.24	-69.51	8.26	0.72	-61.97	-13.00	48.97
1415.000	V	35.02	-68.78	8.26	0.72	-61.24	-13.00	48.24
2122.500	H	34.77	-67.25	9.17	0.92	-59.00	-13.00	46.00
2122.500	V	34.69	-67.31	9.17	0.92	-59.06	-13.00	46.06
2830.000	H	35.87	-64.58	9.93	1.06	-55.71	-13.00	42.71
2830.000	V	34.32	-66.07	9.93	1.06	-57.20	-13.00	44.20
1.4MHz QPSK, Frequency: 715.3 MHz								
1430.600	H	37.04	-66.64	8.31	0.73	-59.06	-13.00	46.06
1430.600	V	36.22	-67.52	8.31	0.73	-59.94	-13.00	46.94
2145.900	H	35.64	-66.55	9.19	0.93	-58.29	-13.00	45.29
2145.900	V	35.27	-66.93	9.19	0.93	-58.67	-13.00	45.67
2861.200	H	35.77	-64.60	9.98	1.07	-55.69	-13.00	42.69
2861.200	V	34.57	-65.81	9.98	1.07	-56.90	-13.00	43.90

LTE Band 17(1-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					706.5	MHz		
1413.000	H	34.14	-69.62	8.26	0.72	-62.08	-13.00	49.08
1413.000	V	35.36	-68.44	8.26	0.72	-60.90	-13.00	47.90
2119.500	H	33.86	-68.14	9.17	0.92	-59.89	-13.00	46.89
2119.500	V	34.75	-67.23	9.17	0.92	-58.98	-13.00	45.98
2826.000	H	34.26	-66.20	9.92	1.06	-57.34	-13.00	44.34
2826.000	V	34.86	-65.53	9.92	1.06	-56.67	-13.00	43.67
5MHz QPSK, Frequency:					710	MHz		
1420.000	H	34.20	-69.53	8.28	0.73	-61.98	-13.00	48.98
1420.000	V	34.85	-68.93	8.28	0.73	-61.38	-13.00	48.38
2130.000	H	34.36	-67.71	9.18	0.92	-59.45	-13.00	46.45
2130.000	V	33.98	-68.09	9.18	0.92	-59.83	-13.00	46.83
2840.000	H	35.02	-65.40	9.94	1.06	-56.52	-13.00	43.52
2840.000	V	34.17	-66.22	9.94	1.06	-57.34	-13.00	44.34
5MHz QPSK, Frequency:					713.5	MHz		
1427.000	H	34.20	-69.50	8.30	0.73	-61.93	-13.00	48.93
1427.000	V	35.33	-68.43	8.30	0.73	-60.86	-13.00	47.86
2140.500	H	33.85	-68.30	9.18	0.93	-60.05	-13.00	47.05
2140.500	V	34.01	-68.14	9.18	0.93	-59.89	-13.00	46.89
2854.000	H	34.53	-65.86	9.97	1.07	-56.96	-13.00	43.96
2854.000	V	33.99	-66.39	9.97	1.07	-57.49	-13.00	44.49

LTE Band 38(1-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2572.5	MHz		
5145.000	H	40.12	-56.18	11.29	1.44	-46.33	-25.00	21.33
5145.000	V	34.79	-61.39	11.29	1.44	-51.54	-25.00	26.54
7717.500	H	34.33	-58.92	10.86	1.99	-50.05	-25.00	25.05
7717.500	V	34.11	-59.76	10.86	1.99	-50.89	-25.00	25.89
5MHz QPSK, Frequency:					2595	MHz		
5190.000	H	42.70	-54.16	11.31	1.44	-44.29	-25.00	19.29
5190.000	V	35.56	-61.15	11.31	1.44	-51.28	-25.00	26.28
7785.000	H	34.13	-59.26	10.84	1.99	-50.41	-25.00	25.41
7785.000	V	34.77	-59.05	10.84	1.99	-50.20	-25.00	25.20
5MHz QPSK, Frequency:					2617.5	MHz		
5235.000	H	48.10	-48.77	11.34	1.46	-38.89	-25.00	13.89
5235.000	V	37.77	-58.91	11.34	1.46	-49.03	-25.00	24.03
7852.500	H	34.57	-58.91	10.83	2.03	-50.11	-25.00	25.11
7852.500	V	34.23	-59.64	10.83	2.03	-50.84	-25.00	25.84

LTE Band 41(1-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolut e Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2498.5 MHz								
4997.000	H	42.01	-53.44	11.20	1.48	-43.72	-25.00	18.72
4997.000	V	37.84	-57.47	11.20	1.48	-47.75	-25.00	22.75
7495.500	H	34.11	-59.99	10.90	1.94	-51.03	-25.00	26.03
7495.500	V	34.06	-60.54	10.90	1.94	-51.58	-25.00	26.58
5MHz QPSK, Frequency: 2593 MHz								
5186.000	H	41.33	-55.48	11.31	1.44	-45.61	-25.00	20.61
5186.000	V	37.34	-59.32	11.31	1.44	-49.45	-25.00	24.45
7779.000	H	34.30	-59.08	10.84	1.99	-50.23	-25.00	25.23
7779.000	V	34.15	-59.67	10.84	1.99	-50.82	-25.00	25.82
5MHz QPSK, Frequency: 2687.5 MHz								
5375.000	H	54.87	-41.64	11.43	1.49	-31.70	-25.00	6.70
5375.000	V	48.23	-48.27	11.43	1.49	-38.33	-25.00	13.33
8062.500	H	34.51	-58.43	10.81	2.12	-49.74	-25.00	24.74
8062.500	V	34.43	-59.01	10.81	2.12	-50.32	-25.00	25.32

LTE Band 42(1-36GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolut e Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 3452.5 MHz								
6905.000	H	34.55	-61.53	11.22	1.87	-52.18	-25.00	27.18
6905.000	V	34.63	-61.32	11.22	1.87	-51.97	-25.00	26.97
10357.500	H	35.01	-57.29	11.49	2.49	-48.29	-25.00	23.29
10357.500	V	34.87	-57.54	11.49	2.49	-48.54	-25.00	23.54
5MHz QPSK, Frequency: 3500 MHz								
7000.000	H	34.77	-60.33	11.20	1.89	-51.02	-25.00	26.02
7000.000	V	34.65	-60.30	11.20	1.89	-50.99	-25.00	25.99
10500.000	H	34.21	-57.39	11.40	2.52	-48.51	-25.00	23.51
10500.000	V	34.58	-57.11	11.40	2.52	-48.23	-25.00	23.23
5MHz QPSK, Frequency: 3547.5 MHz								
7095.000	H	33.86	-59.48	11.14	1.89	-50.23	-25.00	25.23
7095.000	V	34.10	-59.17	11.14	1.89	-49.92	-25.00	24.92
10642.500	H	34.77	-56.79	11.40	2.50	-47.89	-25.00	22.89
10642.500	V	34.35	-57.35	11.40	2.50	-48.45	-25.00	23.45

LTE Band 66(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	34.37	-64.54	10.37	1.17	-55.34	-13.00	42.34
3421.400	V	34.22	-64.66	10.37	1.17	-55.46	-13.00	42.46
5132.100	H	33.89	-62.25	11.28	1.47	-52.44	-13.00	39.44
5132.100	V	34.02	-62.01	11.28	1.47	-52.20	-13.00	39.20
1.4MHz QPSK, Frequency: 1745 MHz								
3490.000	H	34.78	-64.30	10.40	1.17	-55.07	-13.00	42.07
3490.000	V	35.02	-64.00	10.40	1.17	-54.77	-13.00	41.77
5235.000	H	34.33	-62.54	11.34	1.46	-52.66	-13.00	39.66
5235.000	V	34.14	-62.54	11.34	1.46	-52.66	-13.00	39.66
1.4MHz QPSK, Frequency: 1779.3 MHz								
3558.600	H	34.20	-64.48	10.46	1.22	-55.24	-13.00	42.24
3558.600	V	33.58	-64.99	10.46	1.22	-55.75	-13.00	42.75
5337.900	H	34.37	-62.22	11.40	1.47	-52.29	-13.00	39.29
5337.900	V	34.87	-61.58	11.40	1.47	-51.65	-13.00	38.65

PM:

WCDMA Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
Frequency: 1852.4 MHz								
3704.800	H	34.75	-64.14	10.60	1.25	-54.79	-13.00	41.79
3704.800	V	35.11	-63.75	10.60	1.25	-54.40	-13.00	41.40
5557.200	H	34.96	-61.26	11.43	1.49	-51.32	-13.00	38.32
5557.200	V	34.38	-61.69	11.43	1.49	-51.75	-13.00	38.75
Frequency: 1880 MHz								
3760.000	H	34.02	-63.68	10.66	1.24	-54.26	-13.00	41.26
3760.000	V	34.33	-63.25	10.66	1.24	-53.83	-13.00	40.83
5640.000	H	33.89	-62.91	11.33	1.54	-53.12	-13.00	40.12
5640.000	V	34.72	-61.96	11.33	1.54	-52.17	-13.00	39.17
Frequency: 1907.6 MHz								
3815.200	H	34.66	-62.29	10.72	1.29	-52.86	-13.00	39.86
3815.200	V	34.15	-62.65	10.72	1.29	-53.22	-13.00	40.22
5722.800	H	35.24	-61.89	11.23	1.58	-52.24	-13.00	39.24
5722.800	V	34.23	-62.77	11.23	1.58	-53.12	-13.00	40.12

LTE Bands:

(The Worst modulation and bandwidth(1RB) was below)

LTE Band 2(1-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.7 MHz								
3701.400	H	36.70	-62.26	10.60	1.25	-52.91	-13.00	39.91
3701.400	V	35.88	-63.06	10.60	1.25	-53.71	-13.00	40.71
5552.100	H	34.20	-61.98	11.44	1.49	-52.03	-13.00	39.03
5552.100	V	34.55	-61.47	11.44	1.49	-51.52	-13.00	38.52
1.4MHz QPSK, Frequency: 1880 MHz								
3760.000	H	34.55	-63.15	10.66	1.24	-53.73	-13.00	40.73
3760.000	V	35.63	-61.95	10.66	1.24	-52.53	-13.00	39.53
5640.000	H	35.32	-61.48	11.33	1.54	-51.69	-13.00	38.69
5640.000	V	34.87	-61.81	11.33	1.54	-52.02	-13.00	39.02
1.4MHz QPSK, Frequency: 1909.3 MHz								
3818.600	H	35.89	-61.09	10.72	1.29	-51.66	-13.00	38.66
3818.600	V	36.01	-60.82	10.72	1.29	-51.39	-13.00	38.39
5727.900	H	34.37	-62.76	11.23	1.59	-53.12	-13.00	40.12
5727.900	V	35.81	-61.19	11.23	1.59	-51.55	-13.00	38.55

LTE Band 4(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1710.7 MHz								
3421.400	H	35.44	-63.47	10.37	1.17	-54.27	-13.00	41.27
3421.400	V	34.78	-64.10	10.37	1.17	-54.90	-13.00	41.90
5132.100	H	37.52	-58.62	11.28	1.47	-48.81	-13.00	35.81
5132.100	V	36.11	-59.92	11.28	1.47	-50.11	-13.00	37.11
1.4MHz QPSK, Frequency: 1732.5 MHz								
3465.000	H	38.50	-60.52	10.39	1.15	-51.28	-13.00	38.28
3465.000	V	34.89	-64.08	10.39	1.15	-54.84	-13.00	41.84
5197.500	H	34.54	-62.41	11.32	1.44	-52.53	-13.00	39.53
5197.500	V	35.20	-61.60	11.32	1.44	-51.72	-13.00	38.72
1.4MHz QPSK, Frequency: 1754.3 MHz								
3508.600	H	34.28	-64.76	10.41	1.19	-55.54	-13.00	42.54
3508.600	V	34.22	-64.75	10.41	1.19	-55.53	-13.00	42.53
5262.900	H	35.06	-61.73	11.36	1.47	-51.84	-13.00	38.84
5262.900	V	36.85	-59.71	11.36	1.47	-49.82	-13.00	36.82

LTE Band 7(1-26GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 2502.5 MHz								
5005.000	H	34.11	-61.36	11.20	1.47	-51.63	-25.00	26.63
5005.000	V	34.78	-60.56	11.20	1.47	-50.83	-25.00	25.83
7507.500	H	35.03	-59.04	10.90	1.95	-50.09	-25.00	25.09
7507.500	V	34.60	-59.97	10.90	1.95	-51.02	-25.00	26.02
5MHz QPSK, Frequency: 2535 MHz								
5070.000	H	34.58	-61.08	11.24	1.47	-51.31	-25.00	26.31
5070.000	V	33.69	-61.86	11.24	1.47	-52.09	-25.00	27.09
7605.000	H	35.01	-58.47	10.88	2.01	-49.60	-25.00	24.60
7605.000	V	34.27	-59.92	10.88	2.01	-51.05	-25.00	26.05
5MHz QPSK, Frequency: 2567.5 MHz								
5135.000	H	34.10	-62.07	11.28	1.47	-52.26	-25.00	27.26
5135.000	V	34.22	-61.84	11.28	1.47	-52.03	-25.00	27.03
7702.500	H	33.78	-59.44	10.86	1.97	-50.55	-25.00	25.55
7702.500	V	34.06	-59.82	10.86	1.97	-50.93	-25.00	25.93

LTE Band 38(1-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2572.5	MHz		
5145.000	H	34.20	-62.10	11.29	1.44	-52.25	-25.00	27.25
5145.000	V	36.11	-60.07	11.29	1.44	-50.22	-25.00	25.22
7717.500	H	45.99	-47.26	10.86	1.99	-38.39	-25.00	13.39
7717.500	V	58.44	-35.43	10.86	1.99	-26.56	-25.00	1.56
5MHz QPSK, Frequency:					2595	MHz		
5190.000	H	34.89	-61.97	11.31	1.44	-52.10	-25.00	27.10
5190.000	V	36.14	-60.57	11.31	1.44	-50.70	-25.00	25.70
7785.000	H	55.94	-37.45	10.84	1.99	-28.60	-25.00	3.60
7785.000	V	57.00	-36.82	10.84	1.99	-27.97	-25.00	2.97
5MHz QPSK, Frequency:					2617.5	MHz		
5235.000	H	34.79	-62.08	11.34	1.46	-52.20	-25.00	27.20
5235.000	V	36.89	-59.79	11.34	1.46	-49.91	-25.00	24.91
7852.500	H	53.02	-40.46	10.83	2.03	-31.66	-25.00	6.66
7852.500	V	52.71	-41.16	10.83	2.03	-32.36	-25.00	7.36

LTE Band 41(1-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					2498.5	MHz		
4997.000	H	35.21	-60.24	11.20	1.48	-50.52	-25.00	25.52
4997.000	V	34.39	-60.92	11.20	1.48	-51.20	-25.00	26.20
7495.500	H	34.87	-59.23	10.90	1.94	-50.27	-25.00	25.27
7495.500	V	34.99	-59.61	10.90	1.94	-50.65	-25.00	25.65
5MHz QPSK, Frequency:					2593	MHz		
5186.000	H	44.01	-52.80	11.31	1.44	-42.93	-25.00	17.93
5186.000	V	36.55	-60.11	11.31	1.44	-50.24	-25.00	25.24
7779.000	H	34.85	-58.53	10.84	1.99	-49.68	-25.00	24.68
7779.000	V	35.09	-58.73	10.84	1.99	-49.88	-25.00	24.88
5MHz QPSK, Frequency:					2687.5	MHz		
5375.000	H	57.50	-39.01	11.43	1.49	-29.07	-25.00	4.07
5375.000	V	51.19	-45.31	11.43	1.49	-35.37	-25.00	10.37
8062.500	H	35.02	-57.92	10.81	2.12	-49.23	-25.00	24.23
8062.500	V	34.87	-58.57	10.81	2.12	-49.88	-25.00	24.88

LTE Band 42(1-36GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:					3452.5	MHz		
6905.000	H	34.11	-61.97	11.22	1.87	-52.62	-25.00	27.62
6905.000	V	34.87	-61.08	11.22	1.87	-51.73	-25.00	26.73
10357.500	H	35.02	-57.28	11.49	2.49	-48.28	-25.00	23.28
10357.500	V	34.69	-57.72	11.49	2.49	-48.72	-25.00	23.72
5MHz QPSK, Frequency:					3500	MHz		
7000.000	H	34.14	-60.96	11.20	1.89	-51.65	-25.00	26.65
7000.000	V	33.98	-60.97	11.20	1.89	-51.66	-25.00	26.66
10500.000	H	34.05	-57.55	11.40	2.52	-48.67	-25.00	23.67
10500.000	V	33.78	-57.91	11.40	2.52	-49.03	-25.00	24.03
5MHz QPSK, Frequency:					3547.5	MHz		
7095.000	H	34.22	-59.12	11.14	1.89	-49.87	-25.00	24.87
7095.000	V	34.30	-58.97	11.14	1.89	-49.72	-25.00	24.72
10642.500	H	34.81	-56.75	11.40	2.50	-47.85	-25.00	22.85
10642.500	V	33.66	-58.04	11.40	2.50	-49.14	-25.00	24.14

LTE Band 66(1-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency:					1710.7	MHz		
3421.400	H	34.85	-64.06	10.37	1.17	-54.86	-13.00	41.86
3421.400	V	35.23	-63.65	10.37	1.17	-54.45	-13.00	41.45
5132.100	H	35.01	-61.13	11.28	1.47	-51.32	-13.00	38.32
5132.100	V	36.44	-59.59	11.28	1.47	-49.78	-13.00	36.78
1.4MHz QPSK, Frequency:					1745	MHz		
3490.000	H	38.57	-60.51	10.40	1.17	-51.28	-13.00	38.28
3490.000	V	35.44	-63.58	10.40	1.17	-54.35	-13.00	41.35
5235.000	H	35.66	-61.21	11.34	1.46	-51.33	-13.00	38.33
5235.000	V	38.70	-57.98	11.34	1.46	-48.10	-13.00	35.10
1.4MHz QPSK, Frequency:					1779.3	MHz		
3558.600	H	39.69	-58.99	10.46	1.22	-49.75	-13.00	36.75
3558.600	V	35.77	-62.80	10.46	1.22	-53.56	-13.00	40.56
5337.900	H	40.03	-56.56	11.40	1.47	-46.63	-13.00	33.63
5337.900	V	37.95	-58.50	11.40	1.47	-48.57	-13.00	35.57

DM:**LTE Band 42(1-36GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency:			3452.5	MHz				
6905.000	H	34.57	-61.51	11.22	1.87	-52.16	-25.00	27.16
6905.000	V	35.10	-60.85	11.22	1.87	-51.50	-25.00	26.50
10357.500	H	34.12	-58.18	11.49	2.49	-49.18	-25.00	24.18
10357.500	V	33.85	-58.56	11.49	2.49	-49.56	-25.00	24.56
5MHz QPSK, Frequency:			3500	MHz				
7000.000	H	34.97	-60.13	11.20	1.89	-50.82	-25.00	25.82
7000.000	V	34.23	-60.72	11.20	1.89	-51.41	-25.00	26.41
10500.000	H	34.20	-57.40	11.40	2.52	-48.52	-25.00	23.52
10500.000	V	33.77	-57.92	11.40	2.52	-49.04	-25.00	24.04
5MHz QPSK, Frequency:			3547.5	MHz				
7095.000	H	34.44	-58.90	11.14	1.89	-49.65	-25.00	24.65
7095.000	V	34.15	-59.12	11.14	1.89	-49.87	-25.00	24.87
10642.500	H	34.53	-57.03	11.40	2.50	-48.13	-25.00	23.13
10642.500	V	35.01	-56.69	11.40	2.50	-47.79	-25.00	22.79

5. EUT PHOTOGRAPHS

Please refer to the attachment 2403U81808E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2403U81808E-RF-INP EUT INTERNAL PHOTOGRAPHS

6.TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2403U81808E-RF-00E-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====