

**Test Plot35#: LTE Band 12\_Body Back\_1RB\_Middle Ant7****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 707.5 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f=707.5$  MHz;  $\sigma = 0.863$  S/m;  $\epsilon_r = 42.943$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(8.79, 10.07, 9.05) @707.5 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (8x14x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.114 W/kg


**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.284 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.136 W/kg

**SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.067 W/kg**

Maximum value of SAR (measured) = 0.121 W/kg



0 dB = 0.121 W/kg = -9.17 dB dBW/kg

**Test Plot36#: LTE Band 41\_Body Back\_1RB\_Middle Ant3****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic TDD-LTE (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium parameters used:  $f=2593$  MHz;  $\sigma = 1.944$  S/m;  $\epsilon_r = 38.167$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(6.91, 7.77, 7.08) @2593 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.624 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.835 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.742 W/kg

**SAR(1 g) = 0.411 W/kg; SAR(10 g) = 0.219 W/kg**

Maximum value of SAR (measured) = 0.617 W/kg



0 dB = 0.617 W/kg = -2.10 dB dBW/kg

**Test Plot37#: LTE Band 41\_Head Right Cheek\_1RB\_Middle Ant5****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic TDD-LTE (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium parameters used:  $f=2593$  MHz;  $\sigma = 1.948$  S/m;  $\epsilon_r = 38.453$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(6.91, 7.77, 7.08) @2593 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.0947 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.6000 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.121 W/kg

**SAR(1 g) = 0.059 W/kg; SAR(10 g) = 0.031 W/kg**

Maximum value of SAR (measured) = 0.0951 W/kg



0 dB = 0.0951 W/kg = -10.22 dB dBW/kg

**Test Plot38#: LTE Band 41\_Body Back\_1RB\_Middle Ant5****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic TDD-LTE (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium parameters used:  $f=2593$  MHz;  $\sigma = 1.948$  S/m;  $\epsilon_r = 38.453$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(6.91, 7.77, 7.08) @2593 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.215 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.286 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.293 W/kg

**SAR(1 g) = 0.123 W/kg; SAR(10 g) = 0.048 W/kg**

Maximum value of SAR (measured) = 0.223 W/kg



0 dB = 0.223 W/kg = -6.52 dB dBW/kg

**Test Plot39#: LTE Band 41\_Head Right Tilt\_1RB\_Middle Ant7****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic TDD-LTE (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium parameters used:  $f=2593$  MHz;  $\sigma = 1.944$  S/m;  $\epsilon_r = 38.167$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(6.91, 7.77, 7.08) @2593 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.439 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.457 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.486 W/kg

**SAR(1 g) = 0.267 W/kg; SAR(10 g) = 0.135 W/kg**

Maximum value of SAR (measured) = 0.413 W/kg



0 dB = 0.413 W/kg = -3.84 dB dBW/kg

**Test Plot40#: LTE Band 41\_Body Back\_1RB\_Middle Ant7****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic TDD-LTE (0); Frequency: 2593 MHz; Duty Cycle: 1:1.58  
Medium parameters used:  $f=2593$  MHz;  $\sigma = 1.944$  S/m;  $\epsilon_r = 38.167$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(6.91, 7.77, 7.08) @2593 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.364 W/kg


**Zoom Scan (8x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.604 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.426 W/kg

**SAR(1 g) = 0.242 W/kg; SAR(10 g) = 0.116 W/kg**

Maximum value of SAR (measured) = 0.358 W/kg



0 dB = 0.358 W/kg = -4.46 dB dBW/kg

**Test Plot41#: LTE Band 66\_Body Bottom\_1RB\_Middle Ant3****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f=1745$  MHz;  $\sigma = 1.367$  S/m;  $\epsilon_r = 40.589$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.56, 8.56, 7.71) @1745 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.546 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.73 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.613 W/kg

**SAR(1 g) = 0.364 W/kg; SAR(10 g) = 0.197 W/kg**

Maximum value of SAR (measured) = 0.522 W/kg



0 dB = 0.522 W/kg = -2.82 dB dBW/kg

**Test Plot42#: LTE Band 66\_Head Right Cheek\_1RB\_Middle Ant5****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 1745 MHz;Duty Cycle: 1:1  
Medium parameters used:  $f=1745$  MHz;  $\sigma = 1.361$  S/m;  $\epsilon_r = 40.492$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.56, 8.56, 7.71) @1745 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354;Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (8x9x1):**Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0900 W/kg


**Zoom Scan (5x5x7)/Cube 0:**Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.269 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.357 W/kg

**SAR(1 g) = 0.068 W/kg; SAR(10 g) = 0.032 W/kg**

Maximum value of SAR (measured) = 0.0992 W/kg



0 dB = 0.0992 W/kg = -10.03 dB dBW/kg



**Test Plot43#: LTE Band 66\_Body Back\_50%RB\_Middle Ant5****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f=1745$  MHz;  $\sigma = 1.361$  S/m;  $\epsilon_r = 40.492$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.56, 8.56, 7.71) @1745 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (8x14x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.179 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.9300 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.242 W/kg

**SAR(1 g) = 0.091 W/kg; SAR(10 g) = 0.039 W/kg**

Maximum value of SAR (measured) = 0.162 W/kg



0 dB = 0.162 W/kg = -7.90 dB dBW/kg

**Test Plot44#: LTE Band 66\_Head Right Tilt\_1RB\_Middle Ant7****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 1745 MHz;Duty Cycle: 1:1  
Medium parameters used:  $f=1745$  MHz;  $\sigma = 1.367$  S/m;  $\epsilon_r = 40.589$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.56, 8.56, 7.71) @1745 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354;Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (8x9x1):**Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.645 W/kg


**Zoom Scan (5x5x7)/Cube 0:**Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.65 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.804 W/kg

**SAR(1 g) = 0.467 W/kg; SAR(10 g) = 0.246 W/kg**

Maximum value of SAR (measured) = 0.678 W/kg



0 dB = 0.678 W/kg = -1.69 dB dBW/kg

**Test Plot45#: LTE Band 66\_Body Top\_1RB\_Middle Ant7****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: Generic FDD-LTE (0); Frequency: 1745 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f=1745$  MHz;  $\sigma = 1.367$  S/m;  $\epsilon_r = 40.589$ ;  $\rho = 1000$  kg/m<sup>3</sup> ;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.56, 8.56, 7.71) @1745 MHz; Calibrated: 2024/3/27;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.265 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.27 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.297 W/kg

**SAR(1 g) = 0.199 W/kg; SAR(10 g) = 0.123 W/kg**

Maximum value of SAR (measured) = 0.268 W/kg



0 dB = 0.268 W/kg = -5.72 dB dBW/kg

**Test Plot 46#: 2.4G WIFI\_Head Left Cheek\_Middle Chain 0****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.794$  S/m;  $\epsilon_r = 39.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.05, 7.92, 7.22) @ 2437 MHz; Calibrated: 2024/3/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.419 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.459 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.557 W/kg

**SAR(1 g) = 0.246 W/kg; SAR(10 g) = 0.119 W/kg**

Maximum value of SAR (measured) = 0.422 W/kg



0 dB = 0.422 W/kg = -3.75 dBW/kg

**Test Plot 47#:2.4G WIFI\_Body Back\_Middle Chain 0****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: 802.11b; Frequency: 2437 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.794$  S/m;  $\epsilon_r = 39.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.05, 7.92, 7.22) @ 2437 MHz; Calibrated: 2024/3/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.113 W/kg


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.093 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 0.153 W/kg

**SAR(1 g) = 0.066 W/kg; SAR(10 g) = 0.033 W/kg**

Maximum value of SAR (measured) = 0.111 W/kg



0 dB = 0.111 W/kg = -9.55 dBW/kg

**Test Plot 48#: 2.4G WIFI\_Head Left Cheek\_Middle Chain 1****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.794$  S/m;  $\epsilon_r = 39.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.05, 7.92, 7.22) @ 2437 MHz; Calibrated: 2024/3/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (10x11x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.218 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.9800 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.346 W/kg

**SAR(1 g) = 0.154 W/kg; SAR(10 g) = 0.075 W/kg**

Maximum value of SAR (measured) = 0.255 W/kg



0 dB = 0.255 W/kg = -5.93 dBW/kg

**Test Plot 49#: 2.4G WIFI\_Body Right\_Middle\_Chain 1****DUT: Mobile Phone; Type: KL8; Serial: 2N76-1;**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.794$  S/m;  $\epsilon_r = 39.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7329; ConvF(7.05, 7.92, 7.22) @ 2437 MHz; Calibrated: 2024/3/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1354; Calibrated: 2023/11/17
- Phantom: Twin SAM; Type: Twin SAM V5.0; Serial: TP:1412
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (6x17x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.101 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.703 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.146 W/kg

**SAR(1 g) = 0.072 W/kg; SAR(10 g) = 0.035 W/kg**

Maximum value of SAR (measured) = 0.118 W/kg



0 dB = 0.118 W/kg = -9.28 dBW/kg