



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20210801369E-02  
**Applicant:** Shenzhen Hollyland Technology Co.,Ltd  
**Address of Applicant:** 8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China.  
**Equipment Under Test (EUT):**  
**Product:** WIRELESS VIDEO TRANSMISSION SYSTEM  
**Model No.:** COSMO C1, COSMO C2, COSMO C3, COSMO M1, COSMO M2, COSMO M3  
**Test Model No.:** COSMO C1  
**Brand Name:** HOLLYLAND  
**FCC ID:** 2ADZC-9620T  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2021-08-17  
**Date of Test:** 2021-08-17 to 2021-10-19  
**Date of Issue:** 2021-10-25  
**Test Result :** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Lewis Zhou  
( Lewis Zhou )

**Reviewed By:** Rock Huang  
( Rock Huang )

**Approved By:** Jack ai  
( Jack ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210801369E-02	Rev.01	Initial report	2021-10-25

## 2 Contents

	Page
<b>1 VERSION</b> .....	2
<b>2 CONTENTS</b> .....	3
<b>3 GENERAL INFORMATION</b> .....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
<b>4 RF EXPOSURE EVALUATION</b> .....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Limits</i> .....	5
4.1.2 <i>Test Procedure</i> .....	5
4.1.3 <i>EUT RF Exposure Evaluation standalone operations</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Hollyland Technology Co.,Ltd
Address of Applicant:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyuan Street, Baoan District Shenzhen, China.
Manufacturer:	Shenzhen Hollyland Technology Co.,Ltd
Address of Manufacturer:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyuan Street, Baoan District Shenzhen, China.
Factory:	Shenzhen Hollyland Technology Co.,Ltd BanTian Branch
Address of Factory:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyuan Street, Baoan District Shenzhen, China.

#### 3.2 General Description of EUT

Product Name:	WIRELESS VIDEO TRANSMISSION SYSTEM	
Model No.:	COSMO C1, COSMO C2, COSMO C3, COSMO M1, COSMO M2, COSMO M3	
Test Model No.:	COSMO C1	
Trade Mark:	HOLLYLAND	
EUT Supports Radios application	5GHz: custom: U-NII-1: 5.15-5.25GHz; U-NII-3: 5.725-5.850GHz;	
Hardware Version:	F782381028	
Software Version:	V1.0.1.2	
Power Supply:	DC 12V 2A	
Adapter:	Adapter: MODEL: A241-120200I INPUT: 100-240V~50/60Hz 0.8A Max OUTPUT: 12V 2A, 24W	
Product Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location	
Test Software of EUT:	ARSirisu Debug Tool (manufacturer declare)	
Antenna Type:	External antenna	
Antenna Gain:	5G custom	4 dBi

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

#### 4.1.3 EUT RF Exposure Evaluation standalone operations

##### For 5G WIFI

Antenna Gain: 4 dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.512 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

##### Measurement Data

(U-NII-1)				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5180MHz)	8.54	8.0±1	9.0	7.943
Middle(5200MHz)	8.96	8.5±1	9.5	8.913
Highest(5240MHz)	9.52	9.0±1	10.0	10.000

(U-NII-3)				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5760MHz)	10.47	10.0±1	11.0	12.589
Middle(5780MHz)	10.75	10.0±1	11.0	12.589
Highest(5820MHz)	11.97	11.5±1	12.5	17.783

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
17.783	4	0.0089	1.0	PASS

Note: 1) Refer to report No. CQASZ20210801369E-03 for EUT test Max Conducted Peak Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (17.783 * 2.512) / (4 * 3.1416 * 20^2) = 0.0089$