


## Appendix A: Test Results of Wi-Fi 802.11 ac



<b>Table of Contents</b>	<b>Page</b>
APPENDIX A.1 TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS .....	<b>2</b>
APPENDIX A.2 TEST RESULTS OF RADIATED SPURIOUS EMISSION .....	<b>3</b>
APPENDIX A.3 TEST RESULTS OF FREQUENCY STABILITY .....	<b>10</b>
APPENDIX A.4 TEST RESULTS OF POWER SPECTRAL DENSITY .....	<b>16</b>
APPENDIX A.5 TEST RESULTS OF 6DB & 26DB & 99% BANDWIDTH .....	<b>21</b>
APPENDIX A.6 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER .....	<b>30</b>

## Appendix A.1 Test Results of Conducted Emission on AC Mains



## Appendix A.2 Test Results of Radiated Spurious Emission

Note: Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 40GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported. All the data rate and configurations have been tested and only the worst case mode (ac(VHT20)) reported.

Below 1GHz:									
Test Mode:		Mode 1(worst mode)							
Horizontal									
 <p>The plot shows radiated spurious emissions in dBuV/m versus frequency in MHz. The y-axis ranges from 0.0 to 80.0 dBuV/m, and the x-axis ranges from 30.000 to 1000.000 MHz. A red line represents the limit, and a green line represents the margin. The blue line shows the measured emissions. Several peaks are marked with 'x' and numbered 1 through 6.</p>									
No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (deg.)	Height (cm)	Remark
1	115.7256	41.85	-14.36	27.49	43.50	-16.01			QP
2*	338.4001	51.94	-8.95	42.99	46.00	-3.01			QP
3	446.4141	45.20	-5.48	39.72	46.00	-6.28			QP
4	595.1327	42.21	-3.00	39.21	46.00	-6.79			QP
5!	744.8660	41.67	-0.89	40.78	46.00	-5.22			QP
6	893.8567	36.92	1.07	37.99	46.00	-8.01			QP
Vertical									
 <p>The plot shows radiated spurious emissions in dBuV/m versus frequency in MHz. The y-axis ranges from 0.0 to 80.0 dBuV/m, and the x-axis ranges from 30.000 to 1000.000 MHz. A red line represents the limit, and a green line represents the margin. The blue line shows the measured emissions. Several peaks are marked with 'x' and numbered 1 through 6.</p>									
No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (deg.)	Height (cm)	Remark
1	52.2080	43.75	-11.60	32.15	40.00	-7.85			QP
2	338.4001	43.11	-8.95	34.16	46.00	-11.84			QP
3*	501.1790	46.12	-4.84	41.28	46.00	-4.72			QP
4	595.1326	41.30	-3.00	38.30	46.00	-7.70			QP
5	744.8660	39.58	-0.89	38.69	46.00	-7.31			QP
6	893.8567	37.09	1.07	38.16	46.00	-7.84			QP

Above 1GHz:

Band I:

Note: All antennas and bandwidths are tested, and only the worst data (802.11ac(VHT20) MIMO) is reported in the report.

## 802.11 ac20-Low Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1010.465	53.28	-23.14	30.14	54.00	-23.86	AVG
2	1011.652	64.29	-23.18	41.11	68.30	-27.19	peak
3	2454.225	68.18	-19.97	48.21	68.30	-20.09	peak
4	2456.489	54.26	-19.97	34.29	54.00	-19.71	AVG
5	4975.246	61.15	-15.6	45.55	68.30	-22.75	peak
6	4976.021	50.37	-15.6	34.77	54.00	-19.23	AVG
7	5885.269	57.84	-12.21	45.63	68.30	-22.67	peak
8	5886.348	46.85	-12.2	34.65	54.00	-19.35	AVG
9	14782.33	54.24	-0.99	53.25	68.30	-15.05	peak
10	14783.34	39.05	-0.98	38.07	54.00	-15.93	AVG
11	17996.09	34.84	4.44	39.28	54.00	-14.72	AVG
12	18000	50.38	4.46	54.84	68.30	-13.46	peak

## 802.11 ac20-Low Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2037.255	52.21	-21.14	31.07	54.00	-22.93	AVG
2	2038.994	65.07	-21.13	43.94	68.30	-24.36	peak
3	5240.979	55.18	-14.61	40.57	54.00	-13.43	AVG
4	5241.49	67.62	-14.61	53.01	68.30	-15.29	peak
5	7816.81	57.55	-9.13	48.42	68.30	-19.88	peak
6	7817.354	46.07	-9.13	36.94	54.00	-17.06	AVG
7	10144.5	55.54	-6.06	49.48	68.30	-18.82	peak
8	10146.98	43.62	-6.06	37.56	54.00	-16.44	AVG
9	12496.58	53.58	-2.88	50.7	68.30	-17.6	peak
10	12498.5	40.82	-2.87	37.95	54.00	-16.05	AVG
11	17996.33	36.33	4.44	40.77	54.00	-13.23	AVG
12	18000	49.38	4.46	53.84	68.30	-14.46	peak

## 802.11 ac20-Middle Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1023.44	67.11	-23.62	43.49	68.30	-24.81	peak
2	1023.44	52.05	-23.62	28.43	54.00	-25.57	AVG
3	2398.016	65.41	-19.88	45.53	68.30	-22.77	peak
4	2398.016	49.19	-19.88	29.31	54.00	-24.69	AVG
5	6569.953	58.17	-11.03	47.14	68.30	-21.16	peak
6	6569.953	40.16	-11.03	29.13	54.00	-24.87	AVG
7	8879.167	57.2	-7.81	49.39	68.30	-18.91	peak
8	8879.167	38.39	-7.81	30.58	54.00	-23.42	AVG
9	12863.79	55.27	-3.04	52.23	68.30	-16.07	peak
10	12863.79	37.89	-3.04	34.85	54.00	-19.15	AVG
11	14194.95	54.31	-1.12	53.19	68.30	-15.11	peak
12	14194.95	37.11	-1.12	35.99	54.00	-18.01	AVG



802.11 ac20-Middle Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2370.396	65.52	-19.98	45.54	68.30	-22.76	peak
2	2370.396	48.61	-19.98	28.63	54.00	-25.37	AVG
3	3660.067	61.47	-17.37	44.1	68.30	-24.2	peak
4	3660.067	43.78	-17.37	26.41	54.00	-27.59	AVG
5	7124.925	58.25	-9.79	48.46	68.30	-19.84	peak
6	7124.925	40.26	-9.79	30.47	54.00	-23.53	AVG
7	9354.324	55.97	-6.45	49.52	68.30	-18.78	peak
8	9354.324	40.3	-6.45	33.85	54.00	-20.15	AVG
9	11861.81	55.52	-3.5	52.02	68.30	-16.28	peak
10	11861.81	40.48	-3.5	36.98	54.00	-17.02	AVG
11	13165.32	55.49	-2.8	52.69	68.30	-15.61	peak
12	13165.32	37.69	-2.8	34.89	54.00	-19.11	AVG

802.11 ac20-High Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1010.598	54.7	-23.14	31.56	54.00	-22.44	AVG
2	1011.652	66.55	-23.18	43.37	68.30	-24.93	peak
3	2452.498	54.26	-19.98	34.28	54.00	-19.72	AVG
4	2454.225	67	-19.97	47.03	68.30	-21.27	peak
5	5004.148	62.67	-15.59	47.08	68.30	-21.22	peak
6	5006.701	49.8	-15.59	34.21	54.00	-19.79	AVG
7	9463.32	55.65	-6.37	49.28	68.30	-19.02	peak
8	9465.998	41.42	-6.38	35.04	54.00	-18.96	AVG
9	14030.8	41.65	-1.98	39.67	54.00	-14.33	AVG
10	14031.46	54.19	-1.98	52.21	68.30	-16.09	peak
11	17995.14	34.99	4.44	39.43	54.00	-14.57	AVG
12	18000	50.59	4.46	55.05	68.30	-13.25	peak

802.11 ac20-High Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5004.148	61.6	-15.59	46.01	68.30	-22.29	peak
2	5006.812	50.34	-15.59	34.75	54.00	-19.25	AVG
3	5716.557	49.98	-13.15	36.83	54.00	-17.17	AVG
4	5717.266	62.61	-13.15	49.46	68.30	-18.84	peak
5	7417.01	49.5	-9.08	40.42	54.00	-13.58	AVG
6	7419.751	60.41	-9.08	51.33	68.30	-16.97	peak
7	10687.37	54.64	-5.72	48.92	68.30	-19.38	peak
8	10688.67	43.37	-5.72	37.65	54.00	-16.35	AVG
9	14192.77	41.78	-1.13	40.65	54.00	-13.35	AVG
10	14194.95	52.85	-1.12	51.73	68.30	-16.57	peak
11	17997	35.84	4.45	40.29	54.00	-13.71	AVG
12	18000	49.13	4.46	53.59	68.30	-14.71	peak



Band IV:

Note: All antennas and bandwidths are tested, and only the worst data (802.11ac(VHT20) MIMO) is reported in the report.

802.11 ac20-Low Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2425.957	64.66	-19.93	44.73	68.30	-23.57	peak
2	2426.199	51.02	-19.93	31.09	54.00	-22.91	AVG
3	5004.148	62.57	-15.59	46.98	68.30	-21.32	peak
4	5005.998	50.16	-15.59	34.57	54.00	-19.43	AVG
5	8879.167	56.95	-7.81	49.14	68.30	-19.16	peak
6	8880.299	42.92	-7.81	35.11	54.00	-18.89	AVG
7	12000.03	54.04	-2.95	51.09	68.30	-17.21	peak
8	12003.55	39.92	-2.95	36.97	54.00	-17.03	AVG
9	14782.33	53.76	-0.99	52.77	68.30	-15.53	peak
10	14784	39.55	-0.98	38.57	54.00	-15.43	AVG
11	17996.09	35.68	4.44	40.12	54.00	-13.88	AVG
12	18000	51.1	4.46	55.56	68.30	-12.74	peak

802.11 ac20-Low Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1005.809	66.86	-22.96	43.9	68.30	-24.4	peak
2	1007.944	55.81	-23.04	32.77	54.00	-21.23	AVG
3	5004.148	62.81	-15.59	47.22	68.30	-21.08	peak
4	5006.379	51.55	-15.59	35.96	54.00	-18.04	AVG
5	5783.884	63.3	-12.95	50.35	68.30	-17.95	peak
6	5785.333	50.39	-12.95	37.44	54.00	-16.56	AVG
7	10564.27	54.37	-5.69	48.68	68.30	-19.62	peak
8	10566.88	41.45	-5.68	35.77	54.00	-18.23	AVG
9	14277.41	52.33	-1.26	51.07	68.30	-17.23	peak
10	14279.85	39.35	-1.27	38.08	54.00	-15.92	AVG
11	17996.86	35.83	4.44	40.27	54.00	-13.73	AVG
12	18000	49.86	4.46	54.32	68.30	-13.98	peak

802.11 ac20-Middle Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2411.946	67.11	-19.9	47.21	68.30	-21.09	peak
2	2411.946	48.21	-19.9	28.31	54.00	-25.69	AVG
3	5004.148	61.51	-15.59	45.92	68.30	-22.38	peak
4	5004.148	40.73	-15.59	25.14	54.00	-28.86	AVG
5	7506.206	56.28	-8.97	47.31	68.30	-20.99	peak
6	7506.206	36.3	-8.97	27.33	54.00	-26.67	AVG
7	9354.324	55.73	-6.45	49.28	68.30	-19.02	peak
8	9354.324	36.23	-6.45	29.78	54.00	-24.22	AVG
9	11930.72	54.49	-3.22	51.27	68.30	-17.03	peak
10	11930.72	34.67	-3.22	31.45	54.00	-22.55	AVG
11	13473.91	54.26	-2.48	51.78	68.30	-16.52	peak
12	13473.91	33.5	-2.48	31.02	54.00	-22.98	AVG



802.11 ac20-Middle Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2398.016	64.3	-19.88	44.42	68.30	-23.88	peak
2	2398.016	44.18	-19.88	24.3	54.00	-29.7	AVG
3	6921.535	57.48	-10.02	47.46	68.30	-20.84	peak
4	6921.535	38.15	-10.02	28.13	54.00	-25.87	AVG
5	8827.884	57.35	-7.96	49.39	68.30	-18.91	peak
6	8827.884	37.7	-7.96	29.74	54.00	-24.26	AVG
7	9408.664	55.54	-6.22	49.32	68.30	-18.98	peak
8	9408.664	35.52	-6.22	29.3	54.00	-24.7	AVG
9	12789.5	55.12	-2.82	52.3	68.30	-16	peak
10	12789.5	34.97	-2.82	32.15	54.00	-21.85	AVG
11	14782.33	55.01	-0.99	54.02	68.30	-14.28	peak
12	14782.33	35.61	-0.99	34.62	54.00	-19.38	AVG

802.11 ac20-High Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1011.652	65.19	-23.18	42.01	68.30	-26.29	peak
2	1011.652	65.19	-23.18	42.01	54.00	-11.99	AVG
3	2384.166	63.95	-19.93	44.02	68.30	-24.28	peak
4	2384.166	63.95	-19.93	44.02	54.00	-9.98	AVG
5	3414.304	71.94	-18.37	53.57	68.30	-14.73	peak
6	3415.165	58.48	-18.37	40.11	54.00	-13.89	AVG
7	5004.148	61.5	-15.59	45.91	68.30	-22.39	peak
8	5006.565	49.56	-15.59	33.97	54.00	-20.03	AVG
9	12424.41	53.93	-3.18	50.75	68.30	-17.55	peak
10	12427	41.43	-3.16	38.27	54.00	-15.73	AVG
11	17996.89	35.63	4.44	40.07	54.00	-13.93	AVG
12	18000	50.91	4.46	55.37	68.30	-12.93	peak

802.11 ac20-High Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1005.809	66.86	-22.96	43.9	68.30	-24.4	peak
2	1007.662	54.65	-23.03	31.62	54.00	-22.38	AVG
3	3574.512	50.43	-17.36	33.07	54.00	-20.93	AVG
4	3576.241	61.44	-17.34	44.1	68.30	-24.2	peak
5	5004.148	62.81	-15.59	47.22	68.30	-21.08	peak
6	5006.348	49.96	-15.59	34.37	54.00	-19.63	AVG
7	5783.884	63.3	-12.95	50.35	68.30	-17.95	peak
8	5785.421	47.7	-12.95	34.75	54.00	-19.25	AVG
9	14782.33	52.05	-0.99	51.06	68.30	-17.24	peak
10	14784.66	37.85	-0.98	36.87	54.00	-17.13	AVG
11	17996.12	32.27	4.44	36.71	54.00	-17.29	AVG
12	18000	50.86	4.46	55.32	68.30	-12.98	peak

## Node:

- 1、 Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 40GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported..
- 2、 Radiated emissions measured in frequency above 1GHz were made with an instrument using peak/average detector mode.
- 3、 Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4、 Margin (dB), result in dBuV/m – limit in dBuV/m.



### Restricted band Requirements

**Note:**

Since the distance of band IV exceeds 200 MHz and the distance limit is greater than 20 dB, only band I data is reflected in this document.

All antennas and bandwidths are tested, and only the worst data (802.11ac(VHT20) MIMO) is reported in the report.

#### Band I

##### 802.11ac20-Low

###### Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5066.292	37.71	9.83	47.54	68.30	-20.76	peak
2	5066.292	29.16	9.83	38.99	54.00	-15.01	AVG
3	5150.000	35.22	10.26	45.48	68.30	-22.82	peak
4	5150.000	29.10	10.26	39.36	54.00	-14.64	AVG

###### Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5106.132	38.66	10.02	48.68	68.30	-19.62	peak
2	5106.132	28.72	10.02	38.74	54.00	-15.26	AVG
3	5150.000	43.75	10.26	54.01	68.30	-14.29	peak
4	5150.000	30.30	10.26	40.56	54.00	-13.44	AVG

##### 802.11ac20-High

###### Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	43.83	3.95	47.78	68.30	-20.52	peak
2	5350.000	32.37	3.95	36.32	54.00	-17.68	AVG
3	5380.341	45.80	3.98	49.78	68.30	-18.52	peak
4	5380.341	30.19	3.98	34.17	54.00	-19.83	AVG




###### Vertical







No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	44.29	3.95	48.24	68.30	-20.06	peak
2	5350.000	32.27	3.95	36.22	54.00	-17.78	AVG
3	5371.323	45.97	3.97	49.94	68.30	-18.36	peak
4	5371.323	31.09	3.97	35.06	54.00	-18.94	AVG







## Appendix A.3 Test Results of Frequency Stability

Wi-Fi 802.11ac mode:





Frequency (MHz)	Voltage (V)	Temperature (°C)	Measured Frequency (MHz)	Deviation (ppm)	Limit (ppm)	Result
5180	7.4 Vdc	-10	5179.956	8.59	25	Pass
		0	5179.956	8.59	25	Pass
		10	5179.956	8.59	25	Pass
		20	5179.956	8.59	25	Pass
		30	5179.956	8.59	25	Pass
	6 Vdc	25	5179.956	8.59	25	Pass
		16 Vdc	25	5179.956	8.59	25
	120 Vac	-10	5179.948	10.04	25	Pass
		0	5179.948	10.04	25	Pass
		10	5179.949	10.04	25	Pass
		20	5179.947	10.23	25	Pass
		30	5179.950	9.65	25	Pass
	85 Vac	25	5179.950	9.65	25	Pass
	240 Vac	25	5179.951	9.46	25	Pass












Frequency (MHz)	Voltage (V)	Temperature (°C)	Measured Frequency (MHz)	Deviation (ppm)	Limit (ppm)	Result	
5825	7.4 Vdc	-10	5824.950	8.58	25	Pass	
		0	5824.950	8.58	25	Pass	
		10	5824.950	8.58	25	Pass	
		20	5824.950	8.58	25	Pass	
		30	5824.950	8.58	25	Pass	
		40	5824.950	8.58	25	Pass	
	6 Vdc	25	5824.950	8.58	25	Pass	
		16 Vdc	25	5824.950	8.58	25	Pass
	120 Vac	25	-10	5824.944	9.61	25	Pass
			0	5824.941	10.13	25	Pass
			10	5824.940	10.30	25	Pass
			20	5824.941	10.13	25	Pass
			30	5824.941	10.13	25	Pass
	40	5824.942	9.96	25	Pass		
85 Vac	25	5824.942	9.96	25	Pass		
240 Vac	25	5824.940	10.30	25	Pass		








## Appendix A.4 Test Results of Power Spectral Density

802.11ac20 mode:								
CH	Freq.	ANT1_Power Spectral Density (dBm/MHz)	ANT2_Power Spectral Density (dBm/MHz)	Total_Power Spectral Density (dBm/MHz)	IC_Power Spectral Density (dBm/MHz)	IC Limit (dBm/MHz)	FCC Limit (dBm/MHz)	Result
36	5180	3.314	3.081	6.209	8.549	10	11	Pass
44	5220	2.764	2.985	5.886	8.226	10	11	Pass
48	5240	2.833	2.803	5.828	8.168	10	11	Pass


Note:

1) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz.


CH	Freq.	ANT1_Power Spectral Density (dBm/500KHz)	ANT2_Power Spectral Density (dBm/500KHz)	Total_Power Spectral Density (dBm/500KHz)	Limit (dBm/500KHz)	Result
149	5745	1.731	3.411	5.662	30	Pass
157	5785	2.094	3.641	5.946	30	Pass
165	5825	1.889	2.304	5.112	30	Pass








802.11ac20 5785



802.11ac20 5825

**ANT2**



**802.11ac40 mode:**


CH	Freq.	ANT1_Power Spectral Density (dBm/MHz)	ANT2_Power Spectral Density (dBm/MHz)	Total_Power Spectral Density (dBm/MHz)	IC_Power Spectral Density (dBm/MHz)	IC Limit (dBm/MHz)	FCC Limit (dBm/MHz)	Result
38	5190	2.601	2.338	5.482	7.822	10	11	Pass
46	5230	2.378	2.533	5.466	7.806	10	11	Pass

Note:

1) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz.

CH	Freq.	ANT1_Power Spectral Density (dBm/500KHz)	ANT2_Power Spectral Density (dBm/500K Hz)	Total_Power Spectral Density (dBm/500K Hz)	Limit (dBm/500KHz)	Result
151	5755	-1.740	1.360	3.091	30	Pass
159	5795	-1.295	-0.004	2.409	30	Pass





**ANT2**





## Appendix A.5 Test Results of 6dB & 26dB & 99% BANDWIDTH




802.11ac20 mode:					
Channel	Frequency (MHz)	ANT1 Emission Bandwidth		ANT2 Emission Bandwidth	
		26dB Bandwidth (MHz)	99% Bandwidth (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
36	5180	19.59	17.626	19.32	17.562
44	5220	19.50	17.620	19.32	17.677
48	5240	19.57	17.585	19.65	17.635

Channel	Frequency (MHz)	ANT1 Emission Bandwidth		ANT2 Emission Bandwidth	
		6dB Bandwidth (MHz)	99% Bandwidth (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
149	5745	17.58	17.690	17.65	17.619
157	5785	17.25	17.666	17.25	17.619
165	5825	17.56	17.652	16.65	17.664







**6dB Bandwidth**


**99% Bandwidth**

**802.11ac20 5745**

**802.11ac20 5785**

**802.11ac20 5825**


**ANT2**
**26dB Bandwidth & 99% Bandwidth**

**802.11ac20 5180**
**802.11ac20 5220**

**802.11ac20 5240**




**6dB Bandwidth**


**99% Bandwidth**

**802.11ac20 5745**

**802.11ac20 5785**

**802.11ac20 5825**


**802.11ac40 mode:**

Channel	Frequency (MHz)	ANT1 Emission Bandwidth		ANT2 Emission Bandwidth	
		26dB Bandwidth (MHz)	99% Bandwidth (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
38	5190	41.18	36.008	40.99	36.070
46	5230	41.42	36.056	41.27	36.149


Channel	Frequency (MHz)	ANT1 Emission Bandwidth		ANT2 Emission Bandwidth	
		6dB Bandwidth (MHz)	99% Bandwidth (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
151	5755	34.30	36.140	27.64	36.124
159	5795	32.87	36.180	27.53	36.027

**ANT1**
**26dB Bandwidth & 99% Bandwidth**



802.11ac40 5190




802.11ac40 5230







**6dB Bandwidth**


802.11ac40 5755



802.11ac40 5795

**99% Bandwidth**


**ANT2**
**26dB Bandwidth & 99% Bandwidth**

**802.11ac40 5190**

**802.11ac40 5230**
**6dB Bandwidth**

**802.11ac40 5755**

**802.11ac40 5795**
**99% Bandwidth**

**802.11ac40 5755**

**802.11ac40 5795**

## Appendix A.6 Test Results of Maximum Conducted Output Power

For FCC:

802.11ac20 mode						
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total (dBm) Conducted	Limit (dBm)	Result
36	5180	11.524	12.645	15.131	23.98	Pass
44	5220	11.643	11.302	14.486	23.98	Pass
48	5240	11.857	11.754	14.816	23.98	Pass
149	5745	13.754	15.422	17.678	30	Pass
157	5785	13.434	14.386	16.946	30	Pass
165	5825	13.616	13.792	16.715	30	Pass

**Note:**

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz

802.11ac40 mode						
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total (dBm) Conducted	Limit (dBm)	Result
38	5190	14.036	13.918	16.988	23.98	Pass
46	5230	13.724	13.853	16.799	23.98	Pass
151	5755	13.792	15.561	17.776	30	Pass
159	5795	13.763	14.730	17.284	30	Pass

**Note:**

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz

For IC:

802.11ac20 mode							
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total E.I.R.P (dBm)	Limit (dBm)		Result
36	5180	11.524	12.645	17.471	22.45 <sup>Note3</sup>	23	Pass
44	5220	11.643	11.302	16.826	22.47 <sup>Note3</sup>	23	Pass
48	5240	11.857	11.754	17.156	22.46 <sup>Note3</sup>	23	Pass

802.11ac20 mode						
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total Conducted Power (dBm)	Limit (dBm)	Result
149	5745	13.754	15.422	17.678	30	Pass
157	5785	13.434	14.386	16.946	30	Pass
165	5825	13.616	13.792	16.715	30	Pass

**Note:**

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz;
- 3) the maximum e.i.r.p. shall not exceed 30 mW or  $1.76 + 10 \log_{10}B$ , dBm, whichever is less, where B is the 99% emission bandwidth in megahertz.

802.11ac40 mode						
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total E.I.R.P (dBm)	Limit (dBm)	Result
38	5190	14.036	13.918	19.328	23	Pass
46	5230	13.724	13.853	19.139	23	Pass

802.11ac40 mode						
CH	Freq.	ANT1_Conducted Power (dBm)	ANT2_Conducted Power (dBm)	Total Conducted Power (dBm)	Limit (dBm)	Result
151	5755	13.792	15.561	17.776	30	Pass
159	5795	13.763	14.730	17.284	30	Pass

**Note:**

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 802.11 ac: 2.34 dBi for 5150MHz-5250MHz, 3.14 dBi for 5725MHz-5850MHz