



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240300429E-03	Rev.01	Initial report	2024-04-07

## 2 Contents


	Page
<b>1 VERSION</b> .....	2
<b>2 CONTENTS</b> .....	3
.....	3
<b>3 GENERAL INFORMATION</b> .....	4
3.1 CLIENT INFORMATION .....	4
3.2 GENERAL DESCRIPTION OF EUT .....	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC .....	5
3.4 GENERAL DESCRIPTION OF 5G WIFI CLASSIC .....	5
<b>4 MPE EVALUATION</b> .....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6
4.1.1 <i>Limits</i> .....	6
4.1.2 <i>Test Procedure</i> .....	6
4.1.3 <i>EUT RF Exposure</i> .....	7

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Hollyland Technology Co., Ltd
Address of Applicant:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China
Manufacturer:	Shenzhen Hollyland Technology Co., Ltd
Address of Manufacturer:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China
Factory:	Shenzhen Hollyland Technology Co., Ltd
Address of Factory:	8F, Building 5D, Skyworth Innovation Valley, Tangtou Road. Shiyan Street, Baoan District Shenzhen, China

#### 3.2 General Description of EUT

Product Name:	WIRELESS VIDEO TRANSMISSION SYSTEM
Model No.:	Pyro S
Test Model No.:	Pyro S
Trade Mark:	
Software Version:	V1.0.1.1
Hardware Version:	V38
EUT Power Supply:	Model No.:GQ24-120200-AX Input:100-240V~50/60Hz 1.0A Max Output:12.0V 2.0A 24W

### 3.3 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	DIRECT CONNECTED EXTERNAL Antenna
Antenna Gain:	ANT1:3.78dBi, ANT2:3.78dBi ANT1+ANT2:6.79dBi

### 3.4 General Description of 5G WIFI Classic

Operation Frequency:	IEEE 802.11a/n/ac(20M): 5180MHz ~5240 MHz IEEE802.11n/ac(40M): 5190MHz ~5230 MHz IEEE 802.11a/n/ac(20M): 5745MHz ~5825 MHz IEEE802.11n/ac(40M): 5755MHz ~5795 MHz
Type of Modulation:	OFDM
Number of Channel:	IEEE 802.11a/n/ac(20M): 5180MHz ~5240 MHz/ 4 channel IEEE 802.11n/ac(40M): 5190MHz ~5230 MHz/ 2 channel IEEE 802.11a/n/ac(20M): 5745MHz ~5825 MHz/ 5 channel IEEE 802.11n/ac(40M): 5755MHz ~5795 MHz/ 2 channel
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	DIRECT CONNECTED EXTERNAL Antenna
Antenna Gain:	ANT1:3.77dBi@5GHz: Wi-Fi: U-NII-1, 3.32dBi@5GHz: Wi-Fi: U-NII-3 ANT2:3.77dBi@5GHz: Wi-Fi: U-NII-1, 3.32dBi@5GHz: Wi-Fi: U-NII-3 ANT1+ANT2: 6.78dBi@5GHz: Wi-Fi: U-NII-1, 6.33dBi@5GHz: Wi-Fi: U-NII-3

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

## 4 MPE Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.1.3 EUT RF Exposure

#### 1) For 2.4G WIFI Classic

##### Measurement Data

11B mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	15.05	12.90	13.0±1	14.0	25.12
Middle(2437MHz)	15.26	13.11	13.0±1	14.0	25.12
Highest(2462MHz)	15.12	12.97	13.0±1	14.0	25.12
11G mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	18.62	16.47	16.5±1	17.5	56.23
Middle(2437MHz)	19.16	17.01	17.0±1	18.0	63.10
Highest(2462MHz)	18.98	16.83	17.0±1	18.0	63.10
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	24.57	22.42	22.5±1	23.5	223.87
Middle(2437MHz)	25.05	22.90	23.0±1	24.0	251.19
Highest(2462MHz)	24.85	22.70	22.5±1	23.5	223.87
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2422MHz)	24.82	22.67	22.5±1	23.5	223.87
Middle(2437MHz)	24.90	22.75	22.5±1	23.5	223.87
Highest(2452MHz)	24.91	22.76	22.5±1	23.5	223.87

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240300429E-01 for EUT test Max Conducted Peak Output Power value.  
 2) EUT's module is more than 20cm away from the human body.

3) For 5G WIFI Classic

Measurement Data

Ant1:

U-NII-1:

11A mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5180MHz)	8.30	6.15	6.0±1	7.0	5.01
Middle(5200MHz)	14.16	12.01	12.0±1	13.0	19.95
Highest(5240MHz)	13.41	11.26	11.5±1	12.5	17.78
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5180MHz)	12.93	10.78	10.5±1	11.5	14.13
Middle(5200MHz)	11.69	9.54	9.5±1	10.5	11.22
Highest(5240MHz)	11.03	8.88	9.0±1	10.0	10.00
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5190MHz)	8.06	5.91	6.0±1	7.0	5.01
Highest(5230MHz)	4.54	2.39	2.5±1	3.5	2.24
11AC20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5180MHz)	9.43	7.28	7.5±1	8.5	7.08
Middle(5200MHz)	9.24	7.09	7.0±1	8.0	6.31
Highest(5240MHz)	7.02	4.87	5.0±1	6.0	3.98
11AC40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5190MHz)	7.67	5.52	5.5±1	6.5	4.47
Highest(5230MHz)	5.16	3.01	3.0±1	4.0	2.51



U-NII-3:

11A mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5745MHz)	16.86	14.71	14.5±1	15.5	35.48
Middle(5785MHz)	16.42	14.27	14.5±1	15.5	35.48
Highest(5825MHz)	17.06	14.91	15.0±1	16.0	39.81
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5745MHz)	14.44	12.29	12.5±1	13.5	22.39
Middle(5785MHz)	14.15	12.00	12.0±1	13.0	19.95
Highest(5825MHz)	14.33	12.18	12.0±1	13.0	19.95
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5755MHz)	9.98	7.83	8.0±1	9.0	7.94
Highest(5795MHz)	9.89	7.74	8.0±1	9.0	7.94
11AC20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5745MHz)	9.79	7.64	7.5±1	8.5	7.08
Middle(5785MHz)	9.53	7.38	7.5±1	8.5	7.08
Highest(5825MHz)	10.23	8.08	8.0±1	9.0	7.94
11AC40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5755MHz)	9.98	7.83	8.0±1	9.0	7.94
Highest(5795MHz)	9.89	7.74	8.0±1	9.0	7.94

**Measurement Data**

Ant1+Ant2:

U-NII-1:

11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5180MHz)	17.53	15.38	15.5±1	16.5	44.67
Middle(5200MHz)	16.41	14.26	14.5±1	15.5	35.48
Highest(5240MHz)	15.90	13.75	13.5±1	14.5	28.18
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5190MHz)	12.20	10.05	10.0±1	11.0	12.59
Highest(5230MHz)	10.42	8.27	8.5±1	9.5	8.91
11AC20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5180MHz)	13.61	11.46	11.5±1	12.5	17.78
Middle(5200MHz)	13.32	11.17	11.0±1	12.0	15.85
Highest(5240MHz)	11.6	9.45	9.5±1	10.5	11.22
11AC40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5190MHz)	12.35	10.2	10.5±1	11.5	14.13
Highest(5230MHz)	10.7	8.55	8.5±1	9.5	8.91

U-NII-3:

11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5745MHz)	19.08	16.93	17.0±1	18.0	63.10
Middle(5785MHz)	19.05	16.90	17.0±1	18.0	63.10
Highest(5825MHz)	19.16	17.01	17.0±1	18.0	63.10
11N40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5755MHz)	14.67	12.52	12.5±1	13.5	22.39
Highest(5795MHz)	14.65	12.50	12.5±1	13.5	22.39
11AC20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5745MHz)	14.39	12.24	12.5±1	13.5	22.39
Middle(5785MHz)	14.31	12.16	12.0±1	13.0	19.95
Highest(5825MHz)	15.5	13.35	13.5±1	14.5	28.18
11AC40 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(5755MHz)	15.06	12.91	13.0±1	14.0	25.12
Highest(5795MHz)	14.96	12.81	13.0±1	14.0	25.12

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240300429E-02 for EUT test Max Conducted Peak Output Power value.  
2) EUT's module is more than 20cm away from the human body.

\*\*\* END OF REPORT \*\*\*