

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological

Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Report No.: GZEM180900070802

### TEST REPORT

Application No.: GZEM1809000708CR

Applicant: Dongguan Siyoto Electronics Co., Ltd.

Address of Applicant: No.15,16,17, Seven street of north Qiaodong, Dongjiang Village, Qiaotou

Town, DongGuan, Guangdong, China

Manufacturer:The same as applicantAddress of Manufacturer:The same as applicantFactory:The same as applicantAddress of Factory:The same as applicant

**Equipment Under Test (EUT):** 

FCC ID: 2ADZHHA-S31BT

EUT Name: WIRELESS STEREO HEADSET

Model No.: HA-S31BT, HA-S35BT¤

Please refer to section 2 of this report which indicates which model was

actually tested and which were electrically identical.

Trade Mark: JVC

Standard(s): 47 CFR Part 15, Subpart C 15.247

 Date of Receipt:
 2018-09-30

 Date of Test:
 2018-10-16

 Date of Issue:
 2018-10-29

Test Result: Pass\*



Kobe Jian Lab Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: GZEM180900070802

Page: 2 of 11

| Revision Record                      |  |            |  |          |  |  |  |
|--------------------------------------|--|------------|--|----------|--|--|--|
| Version Chapter Date Modifier Remark |  |            |  |          |  |  |  |
| 01                                   |  | 2018-10-29 |  | Original |  |  |  |
|                                      |  |            |  |          |  |  |  |
|                                      |  |            |  |          |  |  |  |
|                                      |  |            |  |          |  |  |  |

| Authorized for issue by: |                               |            |
|--------------------------|-------------------------------|------------|
| Tested By                | Kevin zhang                   |            |
|                          |                               | 2018-10-16 |
|                          | Kevin_Zhang /Project Engineer | Date       |
| Checked By               | Riday Liu                     | 2018-10-29 |
|                          | Ricky_Liu /Reviewer           | Date       |



Report No.: GZEM180900070802

Page: 3 of 11

### 2 Test Summary

| Radio Spectrum Technical Requirement  |   |                    |                    |      |  |  |
|---------------------------------------|---|--------------------|--------------------|------|--|--|
| Item Standard Method Requirement Resu |   |                    |                    |      |  |  |
| RF Exposure                           | 47 CFR Part 1.1307,<br>Part 2.1093, KDB<br>447498 | CFR 47 Part 2.1093 | CFR 47 Part 2.1093 | Pass |  |  |

#### **¤** Declaration of EUT Family Grouping:

Model No.: HA-S31BT, HA-S35BT

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference being the model name.

Therefore only one model HA-S31BT was tested in this report.



Report No.: GZEM180900070802

Page: 4 of 11

### 3 Contents

| _ | •     | _                                      | Page |
|---|-------|--|------|
| 1 | Cov   | er Page                                |      |
| 2 | Tes   | t Summary                              |      |
| _ |       |  |      |
| 3 | Con   | tents                                  |      |
| 4 | Gen   | eral Information                       | Ę    |
|   | 4.1   | Details of E.U.T                       |      |
|   | 4.2   | Description of Support Units           |      |
|   | 4.3   | Measurement Uncertainty                |      |
|   | 4.4   | Test Location                          |      |
|   | 4.5   | Test Facility                          |      |
|   | 4.6   | Deviation from Standards               | 8    |
|   | 4.7   | Abnormalities from Standard Conditions |      |
| 5 | Equ   | ipment List                            |      |
| 6 | Rad   | io Spectrum Technical Requirement      | 10   |
| ٠ |       | ·                                      |      |
|   | 6.1   | RF_Exposure                            |      |
|   |       | 1 Test Requirement:                    |      |
|   | 6.1.2 |  |      |
| 7 | Pho   | tographs                               | 11   |
|   | 7.1   | EUT Constructional Details             | 11   |
|   |       |  |      |



Report No.: GZEM180900070802

Page: 5 of 11

### 4 General Information

#### 4.1 Details of E.U.T.

Power Supply: DC 5.0V supplied by USB port for battery charging.

DC 3.7V 430mAh built-in battery for normal working.

Test Voltage: DC 3.7V

Cable: micro USB port

Aux in port

Antenna Gain 1.2 dBi

Antenna Type Integrated Antenna

Channel Spacing 1MHz

Modulation Type GFSK, π/4DQPSK, 8DPSK

Number of Channels 79

Operation Frequency 2402MHz to 2480MHz

Spectrum Spread Frequency Hopping Spread Spectrum(FHSS)

Technology

### 4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No.      |
|-------------|--------------|-----------|-----------------|
| Laptop      | Lenovo       | T430u     | REF. No.SEA1800 |



Report No.: GZEM180900070802

Page: 6 of 11

### 4.3 Measurement Uncertainty

| No.         | Item                            | Measurement Uncertainty |
|-------------|---------------------------------|-------------------------|
| 1           | Radio Frequency                 | ±5.5 x 10-8             |
| 2           | Duty cycle                      | ±0.57%                  |
| 3           | Occupied Bandwidth              | ±3%                     |
| 4           | RF Conducted power              | ±0.68dB                 |
| 5           | RF Power Density                | ±1.50dB                 |
| 6           | Conducted Spurious Emissions    | ±1.04dB                 |
| 7           | RF Radiated Power               | ±4.5dB (below 1GHz)     |
| /           | nr nadiated rower               | ±4.8dB (above 1GHz)     |
| 8           | Padiated Spurious Emission Test | ±4.5dB (30MHz-1GHz)     |
| 0           | Radiated Spurious Emission Test | ±4.8dB (1GHz-18GHz)     |
| 9           | Temperature                     | ±0.4℃                   |
| 10          | Humidity                        | ±1.3%                   |
| 11          | Supply Voltages                 | ±1.5%                   |
| 12 Time ±3% |                                 | ±3%                     |

#### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Report No.: GZEM180900070802

Page: 7 of 11

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### ● NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

#### ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

#### ● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

#### ● CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to

ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

#### ● FCC Recognized 2.948 Listed Test Firm(Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

#### FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818, Jul 13, 2017.

#### ● Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

#### ● VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

#### ● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Report No.: GZEM180900070802

Page: 8 of 11

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: GZEM180900070802

Page: 9 of 11

### 5 Equipment List

| Conducted Peak Output Power |                         |          |                 |            |              |  |
|-----------------------------|-------------------------|----------|-----------------|------------|--------------|--|
| Equipment                   | Manufacturer            | Model No | Inventory<br>No | Cal Date   | Cal Due Date |  |
| EXA Signal Analzer          | Agilent<br>Technologies | N9010A   | EMC2138         | 2017-11-15 | 2018-11-14   |  |
| 6dB Attenuator              | HP                      | 8491A    | EMC2062         | 2018-04-04 | 2020-04-03   |  |
| Test Software JS1120-3      | HangTianXing            | V2.6     | GZE100-69       | N/A        | N/A          |  |

| General used equipment |              |          |                 |            |              |  |
|------------------------|--------------|----------|-----------------|------------|--------------|--|
| Equipment              | Manufacturer | Model No | Inventory<br>No | Cal Date   | Cal Due Date |  |
| DMM                    | Fluke        | 73       | EMC0006         | 2018-07-20 | 2019-07-19   |  |
| DMM                    | Fluke        | 73       | EMC0007         | 2018-07-19 | 2019-07-18   |  |



Report No.: GZEM180900070802

Page: 10 of 11

### 6 Radio Spectrum Technical Requirement

#### 6.1 RF Exposure

#### 6.1.1 Test Requirement:

CFR 47 Part 2.1093

Limit:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 6.1.2 Conclusion

The Max conducted output power is 2.372 dBm in Lowest channel (2.441 GHz);

The best case gain of the antenna is 1.2 dBi.

EIRP = 2.372 dBm + (1.2 dBi) = 3.572 dBm

2.372 dBm logarithmic terms convert to numeric result is nearly 1.727 mW

According to the formula. calculate the test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}]$ 

General RF Exposure =  $(1.727 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.441} \text{ GHz} = 0.54 \text{ }\bigcirc$ 

SAR requirement:

S= 3.0 ②;

(1) < (2).

So the SAR report is not required.



Report No.: GZEM180900070802

Page: 11 of 11

### 7 Photographs

### 7.1 EUT Constructional Details

Refer to report GZEM180900070801 for more details.

--End of Report—