
FCC Test Report

Report No.: AGC01097150702FE03

FCC ID : 2ADZIASP-718
APPLICATION PURPOSE : Original Equipment
PRODUCT DESIGNATION : Levitating Air Speaker
BRAND NAME : N/A
MODEL NAME : ASP-718, ASP-746
CLIENT : ATake Digital Technology (Shenzhen) Co., Ltd.
DATE OF ISSUE : July 22, 2015
STANDARD(S)
TEST PROCEDURE(S) : FCC Part 15 Rules
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	July 22, 2015	Valid	Original Report

TABLE OF CONTENTS



- 1. VERIFICATION OF CONFORMITY 4**
- 2. GENERAL INFORMATION 5**
 - 2.1. PRODUCT DESCRIPTION 5
 - 2.2. TABLE OF CARRIER FREQUENCYS..... 5
- 3. MEASUREMENT UNCERTAINTY..... 6**
- 4. DESCRIPTION OF TEST MODES..... 6**
- 5. SYSTEM TEST CONFIGURATION 7**
 - 5.1. CONFIGURATION OF EUT SYSTEM..... 7
 - 5.2. EQUIPMENT USED IN EUT SYSTEM..... 7
 - 5.3. SUMMARY OF TEST RESULTS 7
- 6. TEST FACILITY 8**
- 7 ALL TEST EQUIPMENT LIST 8**
- 8. RADIATED EMISSION 10**
 - 8.1TEST LIMIT..... 10
 - 8.2. MEASUREMENT PROCEDURE.....11
 - 8.3. TEST SETUP 13
 - 8.4. TEST RESULT(Worst modulation:GFSK)..... 15
- 9. BAND EDGE EMISSION 27**
 - 9.1. MEASUREMENT PROCEDURE..... 28
 - 9.2 TEST SETUP 28
 - 9.3 RADIATED TEST RESULT(Worst modulation:GFSK) 29
- 10. 20DB BANDWIDTH..... 33**
 - 10.1. MEASUREMENT PROCEDURE..... 33
 - 10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 33
 - 10.3. LIMITS AND MEASUREMENT RESULTS..... 33
- 11. FCC LINE CONDUCTED EMISSION TEST 40**
 - 11.1. LIMITS OF LINE CONDUCTED EMISSION TEST 40
 - 11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 40
 - 11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 41
 - 11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 41
 - 11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 42
- APPENDIX A: PHOTOGRAPHS OF TEST SETUP 44**
- APPENDIX B: PHOTOGRAPHS OF EUT 46**

1. VERIFICATION OF CONFORMITY

Applicant	ATake Digital Technology (Shenzhen) Co., Ltd.
Address	15th Building, Changxing Industry Zone, Changzhen Village, Gongming , Guangming New District, Shenzhen, Guangdong, China.
Manufacturer	ATake Digital Technology (Shenzhen) Co., Ltd.
Address	15th Building, Changxing Industry Zone, Changzhen Village, Gongming , Guangming New District, Shenzhen, Guangdong, China
Product Designation	Levitating Air Speaker
Brand Name	N/A
Test Model	ASP-718
Series Model	ASP-746
Difference description	All the same except for the model name.
Date of test	July 15, 2015 to July 15, 2015
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Prepared By	
	_____ Matt Zhang July 22, 2015
Checked By	
	_____ Forrest Lei July 22, 2015
Authorized By	
	_____ Solger Zhang July 22, 2015

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	0.35dBm(Max)
Bluetooth Version	V3.0
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of channels	79 for traditional BT
Hardware Version	ASP_718_6685C
Software Version	V1.0
Antenna Designation	PCB Antenna (Met 15.203 Antenna requirement)
Antenna Gain	0dBi
Power Supply	DC 3.7V by battery

Note: The USB port only used for charging and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCIES

Traditional Bluetooth channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Normal operation (BT)


Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.


5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Levitating Air Speaker	N/A	ASP-718	EUT
2	PC	Dell	A1465	A.E
3	Control box	N/A	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWIDTH	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7 ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2015	July 2, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 3, 2015	July 2, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 3, 2015	July 2, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 3, 2015	July 2, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF78020833 9	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2015	July 2, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2014	July 22, 2015
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 3, 2015	July 2, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 6, 2015	July 7, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 6, 2015	July 5, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 7, 2015	July 6, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF78020833 9	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2015	July 2, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 7, 2015	July 6, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 7, 2015	July 6, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 7, 2015	July 6, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 3, 2015	July 2, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6, 2015	June 5, 2016

8. RADIATED EMISSION

8.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark: (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz




**8.4. TEST RESULT(Worst modulation:GFSK)
 FOR TRADITIONAL BLUETOOTH**

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 24.6
Limit: FCC Class B 3M Radiation	Power:	Humidity: 57.5 %
EUT: Levitating Air Speaker	Distance: 3m	
M/N: ASP-718		
Mode: Low channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	81.7333	26.81	9.73	36.54	40.00	-3.46	peak			
2	*	114.0667	28.75	11.45	40.20	43.50	-3.30	peak			
3		170.6500	19.82	13.06	32.88	43.50	-10.62	peak			
4	!	253.1000	27.03	13.99	41.02	46.00	-4.98	peak			
5		398.6000	17.33	19.06	36.39	46.00	-9.61	peak			
6		679.9000	5.64	24.65	30.29	46.00	-15.71	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Low channel TX
 Note:

Polarization: *Vertical*
 Power:
 Distance: 3m

Temperature: 24.6
 Humidity: 57.5 %


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	27.91	8.51	36.42	40.00	-3.58	peak			
2		89.8167	31.95	5.31	37.26	43.50	-6.24	peak			
3	!	118.9167	32.45	6.32	38.77	43.50	-4.73	peak			
4		170.6500	16.76	14.66	31.42	43.50	-12.08	peak			
5		251.4833	21.12	13.94	35.06	46.00	-10.94	peak			
6		954.7333	1.31	29.95	31.26	46.00	-14.74	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Middle channel TX
 Note:


Polarization: *Horizontal*
 Power:
 Distance: 3m

Temperature: 24.6
 Humidity: 57.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		39.7000	18.91	11.51	30.42	40.00	-9.58	peak			
2	*	83.3500	27.01	9.66	36.67	40.00	-3.33	peak			
3	!	114.0667	28.05	11.45	39.50	43.50	-4.00	peak			
4	!	254.7167	26.86	14.04	40.90	46.00	-5.10	peak			
5		409.9166	12.36	19.37	31.73	46.00	-14.27	peak			
6		697.6833	3.62	25.13	28.75	46.00	-17.25	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Middle channel TX
 Note:

Polarization: *Vertical*
 Power:
 Distance: 3m

Temperature: 24.6
 Humidity: 57.5 %


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	28.07	8.51	36.58	40.00	-3.42	peak			
2		89.8167	31.19	5.31	36.50	43.50	-7.00	peak			
3	!	120.5333	30.53	7.08	37.61	43.50	-5.89	peak			
4		169.0333	22.02	14.76	36.78	43.50	-6.72	peak			
5		249.8667	25.08	13.89	38.97	46.00	-7.03	peak			
6		938.5667	1.26	29.68	30.94	46.00	-15.06	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
 Limit: FCC Class B 3M Radiation
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: High channel TX
 Note:


Polarization: *Horizontal*
 Power:
 Distance: 3m

Temperature: 24.6
 Humidity: 57.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
									cm	degree	
1		88.2000	25.57	9.46	35.03	43.50	-8.47	peak			
2	*	115.6833	27.19	11.56	38.75	43.50	-4.75	peak			
3		254.7167	23.54	14.04	37.58	46.00	-8.42	peak			
4		409.9166	18.01	19.37	37.38	46.00	-8.62	peak			
5		780.1332	1.01	27.05	28.06	46.00	-17.94	peak			
6		949.8833	1.20	30.00	31.20	46.00	-14.80	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 24.6
Limit: FCC Class B 3M Radiation Power: Humidity: 57.5 %
EUT: Levitating Air Speaker Distance: 3m
M/N: ASP-718
Mode: High channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	28.02	8.51	36.53	40.00	-3.47	peak			
2		89.8167	30.85	5.31	36.16	43.50	-7.34	peak			
3	!	117.3000	32.66	5.52	38.18	43.50	-5.32	peak			
4		169.0333	21.00	14.76	35.76	43.50	-7.74	peak			
5		249.8667	24.11	13.89	38.00	46.00	-8.00	peak			
6		765.5833	1.83	26.84	28.67	46.00	-17.33	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

**RADIATED EMISSION ABOVE 1GHZ
FOR TRADITIONAL BLUETOOTH**

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Levitating Air Speaker
M/N: ASP-718
Mode: Low Channel TX
Note:


Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1		1900.000	57.21	-11.17	46.04	74.00	-27.96	peak			
2		2402.000	105.23	-9.68	95.55	114.00	-18.45	peak			
3	*	2402.000	98.12	-9.68	88.44	94.00	-5.56	AVG	150	173	
4		4791.667	48.15	-2.35	45.80	74.00	-28.20	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL




Site: site #1 Polarization: *Vertical* Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
 EUT: Levitating Air Speaker Distance: 3m
 M/N: ASP-718
 Mode: Low Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree		
									cm	degree		
1		1350.000	60.22	-15.44	44.78	74.00	-29.22	peak				
2		2402.000	104.23	-9.68	94.55	114.00	-19.45	peak				
3	*	2402.000	97.57	-9.68	87.89	94.00	-6.11	AVG	150	184		
4		4725.000	48.37	-2.52	45.85	74.00	-28.15	peak				

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Middle Channel TX
 Note:


Polarization: *Horizontal*
 Power:
 Distance: 3m

Temperature: 26
 Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1658.333	58.89	-13.71	45.18	74.00	-28.82	peak			
2		2441.000	104.29	-9.63	94.66	114.00	-19.34	peak			
3	*	2441.000	97.61	-9.63	87.98	94.00	-6.02	AVG	150	130	
4		4683.333	48.03	-2.63	45.40	74.00	-28.60	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Middle Channel TX
 Note:


Polarization: *Vertical*
 Power:
 Distance: 3m

Temperature: 26
 Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1825.000	58.42	-11.96	46.46	74.00	-27.54	peak			
2		2441.000	104.73	-9.63	95.10	114.00	-18.90	peak			
3	*	2441.000	96.86	-9.63	87.23	94.00	-6.77	AVG	150	194	
4		4216.667	49.02	-4.07	44.95	74.00	-29.05	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
 EUT: Levitating Air Speaker Distance: 3m
 M/N: ASP-718
 Mode: High Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1758.333	58.36	-12.66	45.70	74.00	-28.30	peak			
2		2480.000	104.87	-9.59	95.28	114.00	-18.72	peak			
3	*	2480.000	97.54	-9.59	87.95	94.00	-6.05	AVG	150	0	
4		4450.000	49.34	-3.28	46.06	74.00	-27.94	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: High Channel TX
 Note:

Polarization: *Vertical*
 Power:
 Distance: 3m

Temperature: 26
 Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2083.333	55.58	-10.03	45.55	74.00	-28.45	peak			
2		2480.000	104.87	-9.59	95.28	114.00	-18.72	peak			
3	*	2480.000	96.32	-9.59	86.73	94.00	-7.27	AVG	150	11	
4		4783.333	47.58	-2.37	45.21	74.00	-28.79	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.
 Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
 The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	105.23	-9.68	95.55	114	-18.45	Horizontal
2402	104.23	-9.68	94.55	114	-19.45	Vertical
2441	104.29	-9.63	94.66	114	-19.34	Horizontal
2441	104.73	-9.63	95.10	114	-18.90	Vertical
2480	104.87	-9.59	95.28	114	-18.72	Horizontal
2480	104.87	-9.59	95.28	114	-18.72	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	98.12	-9.68	88.44	94	-5.56	Horizontal
2402	97.57	-9.68	87.89	94	-6.11	Vertical
2441	97.61	-9.63	87.98	94	-6.02	Horizontal
2441	96.86	-9.63	87.23	94	-6.77	Vertical
2480	97.54	-9.59	87.95	94	-6.05	Horizontal
2480	96.32	-9.59	86.73	94	-7.27	Vertical

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.


2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO


(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




CONDUCTED TEST SETUP



**9.3 RADIATED TEST RESULT(Worst modulation:GFSK)
FOR TRADITIONAL BLEUTOOTH**

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




Site: site #1
 Limit: FCC Class B 3M Radiation above 1GHZ(PK)
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Low Channel TX
 Note:

Polarization: *Horizontal*
 Power:
 Distance:

Temperature: 26
 Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2330.858	33.89	10.24	44.13	74.00	-29.87	peak			
2		2390.000	33.50	10.31	43.81	74.00	-30.19	peak			
3	*	2402.000	84.72	10.32	95.04	74.00	21.04	peak			


TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
 EUT: Levitating Air Speaker Distance:
 M/N: ASP-718
 Mode: Low Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2332.567	32.43	10.25	42.68	74.00	-31.32	peak			
2		2390.000	32.71	10.31	43.02	74.00	-30.98	peak			
3	*	2402.000	85.09	10.32	95.41	74.00	21.41	peak			


TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Levitating Air Speaker	Distance:	
M/N: ASP-718		
Mode: High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.55	10.41	95.96	74.00	21.96	peak			
2		2483.500	32.69	10.41	43.10	74.00	-30.90	peak			
3		2491.970	33.98	10.42	44.40	74.00	-29.60	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1	Polarization: <i>Vertical</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Levitating Air Speaker	Distance:	
M/N: ASP-718		
Mode: High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.32	10.41	95.73	74.00	21.73	peak			
2		2483.500	31.76	10.41	42.17	74.00	-31.83	peak			
3		2494.427	32.94	10.42	43.36	74.00	-30.64	peak			

RESULT: PASS


Note: The other modes radiation emission have enough 20dB margin.
 Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.
 The "Factor" value can be calculated automatically by software of measurement system.

10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
 RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




10.3. LIMITS AND MEASUREMENT RESULTS


FOR TRADITIONAL BLUETOOTH

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.039	PASS
	Middle Channel	1.039	PASS
	High Channel	1.038	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2Mbps LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.119	PASS
	Middle Channel	1.118	PASS
	High Channel	1.113	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.166	PASS
	Middle Channel	1.168	PASS
	High Channel	1.166	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC which received 120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

**11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST
 FOR TRADITIONAL BLUETOOTH**


Line Conducted Emission Test Line 1-L



Site: Conduction Phase: **L1** Temperature: 24.8
 Limit: FCC Class B Conduction(QP) Power: Humidity: 55.7 %
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Normal operation with charging
 Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1539	40.46		22.12	10.16	50.62		32.28	65.78	55.78	-15.16	-23.50	P	
2	0.3820	35.94		26.91	10.32	46.26		37.23	58.23	48.23	-11.97	-11.00	P	
3	0.7180	26.57		12.99	10.34	36.91		23.33	56.00	46.00	-19.09	-22.67	P	
4	1.5620	21.09		9.61	10.36	31.45		19.97	56.00	46.00	-24.55	-26.03	P	
5	8.3740	29.65		20.14	10.34	39.99		30.48	60.00	50.00	-20.01	-19.52	P	
6	22.0780	15.75		8.17	10.12	25.87		18.29	60.00	50.00	-34.13	-31.71	P	

Line Conducted Emission Test Line 2-N



Site: Conduction Phase: **N** Temperature: 24.8
 Limit: FCC Class B Conduction(QP) Power: Humidity: 55.7 %
 EUT: Levitating Air Speaker
 M/N: ASP-718
 Mode: Normal operation with charging
 Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor (dB)	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1620	41.12		14.51	10.17	51.29		24.68	65.36	55.36	-14.07	-30.68	P	
2	0.3820	35.90		23.32	10.32	46.22		33.64	58.23	48.23	-12.01	-14.59	P	
3	0.7500	25.84		12.22	10.31	36.15		22.53	56.00	46.00	-19.85	-23.47	P	
4	1.6019	19.05		3.98	10.35	29.40		14.33	56.00	46.00	-26.60	-31.67	P	
5	8.4500	24.20		15.56	10.34	34.54		25.90	60.00	50.00	-25.46	-24.10	P	
6	22.3380	12.81		1.93	10.12	22.93		12.05	60.00	50.00	-37.07	-37.95	P	

APPENDIX A: PHOTOGRAPHS OF TEST SETUP
FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP







APPENDIX B: PHOTOGRAPHS OF EUT

Model_ASP-718
ALL VIEW OF EUT





TOP VIEW OF EUT





BOTTOM VIEW OF EUT





FRONT VIEW OF EUT





BACK VIEW OF EUT





LEFT VIEW OF EUT






RIGHT VIEW OF EUT







OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




OPEN VIEW OF EUT-3




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3




INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



INTERNAL VIEW OF EUT-6



----END OF REPORT----