



FCC RADIO TEST REPORT

FCC ID : 2ADZR34003800FM20
Equipment : FastMile 4G Receiver
Brand Name : NOKIA
Model Name : 4G01-A
Applicant : Nokia Shanghai Bell Co., Ltd.
388#, Ningqiao Road, China (Shanghai) Pilot
Free Trade Zone, Shanghai 201206, China
Manufacturer : Nokia Shanghai Bell Co., Ltd.
388#, Ningqiao Road, China (Shanghai) Pilot
Free Trade Zone, Shanghai 201206, China
Standard : 47 CFR Part 2, 96

The product was received on Nov. 15, 2019 and testing was started from Jan. 02, 2020 and completed on Feb. 21, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Product Specification of Equipment Under Test	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	8
2.4 Measurement Results Explanation Example	8
2.5 Frequency List of Low/Middle/High Channels.....	9
3 Conducted Test Items.....	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power	11
3.3 Peak-to-Average Ratio	12
3.4 EIRP and Power Density.....	13
3.5 Occupied Bandwidth	14
3.6 Conducted Band Edge	15
3.7 Conducted Spurious Emission	16
3.8 Frequency Stability.....	17
4 Radiated Test Items	18
4.1 Measuring Instruments.....	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test.....	19
4.4 Radiated Spurious Emission	20
5 List of Measuring Equipment.....	21
6 Uncertainty of Evaluation	23
Appendix A. Test Results of Conducted Test.....	24
Appendix B. Test Results of EIRP and Radiated Test.....	322
Appendix C. Test Setup Photographs.....	330



History of this test report

Report No.	Version	Description	Issued Date
FG9N1515A	01	Initial issue of report	Feb. 26, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
3.3	§96.41	Peak-to-Average Ratio	Pass	
3.4	§96.41	Effective Isotropic Radiated Power	Pass	-
		Power Density	Pass	-
3.5	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.6	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.7	§2.1051 §96.41	Conducted Spurious Emission	Pass	
3.8	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-
4.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	Under limit 3.01 dB at 7250.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Yimin Ho



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	FastMile 4G Receiver
Brand Name	NOKIA
Model Name	4G01-A
FCC ID	2ADZR34003800FM20
EUT supports Radios application	LTE, Bluetooth
Installation type	Outdoor fixed
HW Version	3FE75113AA
SW Version	FASTMILE_D010000B11T0101E0181
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 48: 3552.5 MHz ~ 3697.5 MHz
Rx Frequency	LTE Band 48: 3552.5 MHz ~ 3697.5 MHz
Bandwidth	LTE Band 48: 5 MHz / 10 MHz / 15 MHz / 20 MHz
Maximum Output Power to Antenna	<SISO> LTE Band 48: 23.60 dBm <MIMO> LTE Band 48: 20.41 dBm
Antenna Type	Dipole Antenna
Antenna Gain	15 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No.
	TH05-HY
Test Engineer	Jacky Wang
Temperature	23 ~ 25°C
Relative Humidity	55 ~ 58%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	22 ~ 26°C
Relative Humidity	58 ~ 62%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v02
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane for SISO Antenna and Y plane for MIMO Antenna) were recorded in this report.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	48	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak EIRP Density	48	-	-	v	v	v	v	v	v	v			v	v	v	v
26dB and 99% Bandwidth	48	-	-	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	48	-	-	v	v	v	v	v	v	v	v		v	v		v
Peak-to-Average Ratio	48	-	-				v	v	v	v	v		v	v	v	v
Conducted Spurious Emission	48	-	-	v	v	v	v	v	v	v	v		v	v	v	v
E.I.R.P	48	-	-	v	v	v	v	v	v	v	v		v	v	v	v
Frequency Stability	48	-	-		v			v			v				v	
Radiated Spurious Emission	48	Worst Case											v	v	v	
Remark	<ol style="list-style-type: none"> The mark "v " means that this configuration is chosen for testing The mark "- " means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5

3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Power Density, Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power

3.2.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio



3.4 EIRP and Power Density

3.4.1 Description of the EIRP and Power Density Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for LTE Band 48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

EIRP and PSD limits for CBRS equipment as below table:

Device	Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
Category B CBSD	47	37

3.4.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 Eqpt v02 Section 3.2(b)

1. Set instrument center frequency to OBW center frequency.
2. Set span to at least 1.5 times the OBW.
3. Set the RBW to the specified reference bandwidth (often 1 MHz).
4. Set VBW $\geq 3 \times$ RBW.
5. Detector = RMS (power averaging).
6. Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
7. Sweep time = auto couple.
8. Employ trace averaging (RMS) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level within the reference bandwidth (PSD).
10. Determine the EIRP by adding the effective antenna gain to the adjusted power level.



3.5 Occupied Bandwidth

3.5.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.5.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.6 Conducted Band Edge

3.6.1 Description of Conducted Band Edge Measurement

The conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any emission shall not exceed -25 dBm/MHz

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is -40dBm/MHz.



3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



For radiated emissions above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
ERP (dBm) = EIRP - 2.15
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is -40dBm/MHz



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jan. 06, 2020~ Feb. 21, 2020	Dec. 25, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	41912 & 05	30MHz~1GHz	Oct. 12, 2019	Jan. 06, 2020~ Feb. 21, 2020	Oct 11, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-132 8	1GHz ~ 18GHz	Nov. 14, 2019	Jan. 06, 2020~ Feb. 21, 2020	Nov. 13, 2020	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-152 2	1GHz ~ 18GHz	Sep. 19, 2019	Jan. 06, 2020~ Feb. 21, 2020	Sep. 18, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz ~ 40GHz	Dec. 10, 2019	Jan. 06, 2020~ Feb. 21, 2020	Dec. 09, 2020	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 576	18GHz ~ 40GHz	May 14, 2019	Jan. 06, 2020~ Feb. 21, 2020	May 13, 2020	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2019	Jan. 06, 2020~ Feb. 21, 2020	Mar. 24, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA00101800 -30-10P	160118000 4	1GHz~18GHz	Sep. 27, 2019	Jan. 06, 2020~ Feb. 21, 2020	Sep. 26, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jan. 06, 2020~ Feb. 21, 2020	Dec. 12, 2020	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A023 75	1GHz~26.5GHz	May 27, 2019	Jan. 06, 2020~ Feb. 21, 2020	May 26, 2020	Radiation (03CH12-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101408	10Hz~40GHz	Aug. 13, 2019	Jan. 06, 2020~ Feb. 21, 2020	Aug. 12, 2020	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	101107	100kHz~40GHz	Aug. 27, 2019	Jan. 06, 2020~ Feb. 21, 2020	Aug. 26, 2020	Radiation (03CH12-HY)
Hygrometer	TECEPEL	DTM-303B	TP161243	N/A	May 11, 2019	Jan. 06, 2020~ Feb. 21, 2020	May 10, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30M-18G	Mar. 13, 2019	Jan. 06, 2020~ Feb. 21, 2020	Mar. 12, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Feb. 26, 2019	Jan. 06, 2020~ Feb. 21, 2020	Feb. 25, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Feb. 26, 2019	Jan. 06, 2020~ Feb. 21, 2020	Feb. 25, 2020	Radiation (03CH12-HY)
Base Station	Anritsu	MT8821C	620143281 6	GSM / GPRS /WCDMA / LTE FDD/TDD with 44) /LTE-3CC DLCA,2CC ULCA	May 05, 2019	Jan. 06, 2020~ Feb. 21, 2020	May 04, 2020	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jan. 06, 2020~ Feb. 21, 2020	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Jan. 06, 2020~ Feb. 21, 2020	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jan. 06, 2020~ Feb. 21, 2020	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-00098 9	N/A	N/A	Jan. 06, 2020~ Feb. 21, 2020	N/A	Radiation (03CH12-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
<SISO Mode>								
Base Station(Measure)	Anritsu	MT8821C	620166475 5	GSM / GPRS /WCDMA / LTE FDD/TDD with 44) /LTE-3CC DLCA,2CC ULCA	Mar. 03, 2019	Jan. 02, 2020~ Jan. 23, 2020	Mar. 02, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 15, 2019	Jan. 02, 2020~ Jan. 23, 2020	Nov. 14, 2020	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃~90℃	Sep. 02, 2019	Jan. 02, 2020~ Jan. 23, 2020	Sep. 01, 2020	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 09, 2019	Jan. 02, 2020~ Jan. 23, 2020	Oct. 08, 2020	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#A	1-18GHz	Jan. 15, 2019	Jan. 02, 2020~ Jan. 12, 2020	Jan. 14, 2020	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#A	1-18GHz	Jan. 13, 2020	Jan. 13, 2020~ Jan. 23, 2020	Jan. 12, 2021	Conducted (TH05-HY)
<MIMO Mode>								
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 15, 2019	Jan. 21, 2020~ Feb. 16, 2020	Nov. 14, 2020	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃~90℃	Sep. 02, 2019	Jan. 21, 2020~ Feb. 16, 2020	Sep. 01, 2020	Conducted (TH05-HY)
AC Power Source	AC POWER	AFC-500W	F10407001 1	50Hz~60Hz	Apr. 12, 2019	Jan. 21, 2020~ Feb. 16, 2020	Apr. 11, 2020	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SMA Directional Coupler	#A	1-18GHz	Jan. 13, 2020	Jan. 21, 2020~ Feb. 16, 2020	Jan. 12, 2021	Conducted (TH05-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.24
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.62
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.06
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

<Ant. 0>

LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.34	21.92	22.28
20	1	49		22.22	21.84	22.72
20	1	99		22.17	21.82	22.94
20	50	0		22.26	22.01	22.54
20	50	24		22.26	21.96	22.61
20	50	50		22.28	22.07	23.00
20	100	0		22.22	22.04	22.83
20	1	0	16-QAM	21.51	21.14	21.51
20	1	49		21.59	21.14	22.09
20	1	99		21.36	21.16	22.21
20	50	0		21.35	21.03	21.57
20	50	24		21.31	20.95	21.63
20	50	50		21.34	21.10	22.04
20	100	0		21.28	21.06	21.87
20	1	0	64-QAM	20.52	20.13	20.58
20	1	49		20.59	20.11	21.04
20	1	99		20.38	20.14	21.22
20	50	0		20.20	20.00	20.65
20	50	24		20.15	19.96	20.75
20	50	50		20.19	20.07	21.15
20	100	0		20.14	20.05	20.98
15	1	0	QPSK	22.47	21.97	22.54
15	1	37		22.44	22.10	23.00
15	1	74		22.21	21.80	23.04
15	36	0		22.19	21.83	22.61
15	36	20		22.32	22.07	22.86
15	36	39		22.26	22.10	23.03
15	75	0		22.38	22.02	22.92
15	1	0	16-QAM	21.48	21.16	21.68
15	1	37		21.68	21.30	22.22
15	1	74		21.32	21.04	22.20
15	36	0		21.17	20.82	21.56
15	36	20		21.33	21.01	21.84
15	36	39		21.27	21.10	22.03
15	75	0		21.43	21.04	21.94
15	1	0	64-QAM	20.52	20.15	20.67
15	1	37		20.70	20.26	21.21
15	1	74		20.33	20.09	21.22
15	36	0		20.05	19.86	20.70
15	36	20		20.20	20.06	20.97
15	36	39		20.15	20.12	21.15
15	75	0		20.30	20.04	21.08



LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.29	21.67	22.61
10	1	25		22.26	21.84	22.96
10	1	49		22.25	21.91	22.97
10	25	0		22.36	22.02	23.03
10	25	12		22.40	22.08	23.09
10	25	25		22.42	22.11	23.08
10	50	0		22.39	22.13	23.06
10	1	0	16-QAM	21.41	20.97	21.89
10	1	25		21.61	21.23	22.30
10	1	49		21.53	21.29	22.24
10	25	0		21.39	20.97	22.06
10	25	12		21.44	21.15	22.11
10	25	25		21.44	21.18	22.10
10	50	0		21.45	21.18	22.11
10	1	0	64-QAM	20.45	19.96	20.87
10	1	25		20.64	20.21	21.29
10	1	49		20.49	20.26	21.25
10	25	0		20.30	20.05	21.23
10	25	12		20.36	20.16	21.29
10	25	25		20.36	20.22	21.29
10	50	0		20.28	20.17	21.22
5	1	0	QPSK	22.94	22.58	23.45
5	1	12		23.09	22.71	23.60
5	1	24		22.83	22.57	23.46
5	12	0		22.66	22.23	23.13
5	12	7		22.22	21.91	22.82
5	12	13		22.18	21.85	22.64
5	25	0		22.18	21.86	22.78
5	1	0	16-QAM	22.28	21.84	22.75
5	1	12		22.47	21.98	22.91
5	1	24		22.22	21.88	22.80
5	12	0		21.72	21.21	22.16
5	12	7		21.27	20.87	21.84
5	12	13		21.21	20.83	21.66
5	25	0		21.21	20.84	21.79
5	1	0	64-QAM	21.07	20.55	21.61
5	1	12		21.08	20.75	21.80
5	1	24		20.84	20.61	21.69
5	12	0		20.62	20.29	21.34
5	12	7		20.22	19.97	21.03
5	12	13		20.14	19.91	20.87
5	25	0		20.14	19.91	20.99



<For MIMO Antenna>

LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	20.18	20.00	20.10
20	1	49		19.85	19.39	19.82
20	1	99		20.12	20.20	20.41
20	50	0		19.90	19.71	19.81
20	50	24		19.75	19.66	19.84
20	50	50		19.92	19.64	20.10
20	100	0		19.81	19.68	19.98
20	1	0	16-QAM	20.40	20.21	20.01
20	1	49		19.66	19.49	20.14
20	1	99		20.13	19.78	20.20
20	50	0		19.93	19.78	19.79
20	50	24		19.79	19.61	19.77
20	50	50		19.91	19.61	20.08
20	100	0		19.81	19.70	20.02
20	1	0	64-QAM	20.15	20.06	19.88
20	1	49		19.64	19.47	19.87
20	1	99		20.11	19.62	20.31
20	50	0		19.93	19.80	19.84
20	50	24		19.77	19.65	19.83
20	50	50		19.88	19.67	20.08
20	100	0		19.82	19.71	19.94
15	1	0	QPSK	20.09	19.67	19.94
15	1	37		19.96	19.81	19.90
15	1	74		19.57	19.84	20.08
15	36	0		19.67	19.46	19.66
15	36	20		19.80	19.60	19.89
15	36	39		19.72	19.63	19.87
15	75	0		19.89	19.56	20.07
15	1	0	16-QAM	20.26	19.79	19.81
15	1	37		20.00	19.71	19.80
15	1	74		19.89	19.86	20.09
15	36	0		19.68	19.52	19.69
15	36	20		19.83	19.62	19.88
15	36	39		19.71	19.61	19.86
15	75	0		19.91	19.63	19.84
15	1	0	64-QAM	19.94	19.74	19.97
15	1	37		19.76	19.63	19.78
15	1	74		19.88	19.67	19.90
15	36	0		19.67	19.49	19.70
15	36	20		19.83	19.60	19.88
15	36	39		19.72	19.63	19.87
15	75	0		19.88	19.63	20.03



LTE Band 48 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	20.09	19.71	20.09
10	1	25		20.08	19.71	19.94
10	1	49		19.90	19.70	20.11
10	25	0		19.97	19.57	20.13
10	25	12		20.12	19.85	20.02
10	25	25		20.18	19.89	19.98
10	50	0		20.07	19.76	20.07
10	1	0	16-QAM	20.13	19.90	20.24
10	1	25		20.18	19.74	19.91
10	1	49		19.89	19.66	20.26
10	25	0		19.98	19.60	20.07
10	25	12		20.15	19.82	20.03
10	25	25		20.18	19.89	19.99
10	50	0		20.07	19.77	20.14
10	1	0	64-QAM	20.05	19.64	19.96
10	1	25		20.05	19.67	19.83
10	1	49		19.74	19.70	20.02
10	25	0		20.37	19.61	20.15
10	25	12		20.12	19.82	20.12
10	25	25		20.24	19.92	20.01
10	50	0		20.09	19.79	20.14
5	1	0	QPSK	19.43	19.46	19.39
5	1	12		19.97	19.28	19.90
5	1	24		19.78	19.02	19.55
5	12	0		20.18	19.93	20.15
5	12	7		19.99	19.38	19.80
5	12	13		19.98	19.18	19.86
5	25	0		19.94	19.38	19.73
5	1	0	16-QAM	19.52	19.56	19.40
5	1	12		20.01	19.34	19.86
5	1	24		19.82	19.05	19.66
5	12	0		20.24	19.95	20.13
5	12	7		20.11	19.37	19.83
5	12	13		20.08	19.18	19.81
5	25	0		20.00	19.38	19.74
5	1	0	64-QAM	19.33	19.27	19.26
5	1	12		19.78	19.17	19.63
5	1	24		19.71	18.86	19.46
5	12	0		20.23	19.97	20.12
5	12	7		20.14	19.39	19.83
5	12	13		20.11	19.17	19.83
5	25	0		19.97	19.38	19.76



LTE Band 48

<Ant. 0>


Peak-to-Average Ratio

Mode	LTE Band 48 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	5.04	5.39	6.09	6.20	PASS
Middle CH	5.07	5.33	6.49	6.23	
Highest CH	5.48	5.36	6.41	6.26	
Mode	LTE Band 48 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.09	6.46	-	-	PASS
Middle CH	6.14	6.52	-	-	
Highest CH	6.14	6.49	-	-	




LTE Band 48 / 20MHz / QPSK

Lowest Channel / 1RB




Date: 20.NOV.2019 17:41:55

Lowest Channel / Full RB




Date: 20.NOV.2019 17:42:10

Middle Channel / 1RB




Date: 20.NOV.2019 17:42:29

Middle Channel / Full RB




Date: 20.NOV.2019 17:42:46

Highest Channel / 1RB



Date: 20.NOV.2019 17:43:00

Highest Channel / Full RB




Date: 20.NOV.2019 17:43:15




LTE Band 48 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 20.NOV.2019 17:39:56

Lowest Channel / Full RB




Date: 20.NOV.2019 17:40:10

Middle Channel / 1RB




Date: 20.NOV.2019 17:40:25

Middle Channel / Full RB




Date: 20.NOV.2019 17:41:03

Highest Channel / 1RB



Date: 20.NOV.2019 17:41:18

Highest Channel / Full RB




Date: 20.NOV.2019 17:41:40




LTE Band 48 / 20MHz / 64QAM

Lowest Channel / 1RB




Date: 20.NOV.2019 17:38:14

Lowest Channel / Full RB




Date: 20.NOV.2019 17:38:31

Middle Channel / 1RB




Date: 20.NOV.2019 17:38:49

Middle Channel / Full RB




Date: 20.NOV.2019 17:39:05

Highest Channel / 1RB



Date: 20.NOV.2019 17:39:22

Highest Channel / Full RB



Date: 20.NOV.2019 17:39:39



26dB Bandwidth

Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.21	5.01	9.95	9.79	14.66	14.21	18.62	18.62
Middle CH	-	-	-	-	5.18	5.04	9.87	10.01	14.33	14.12	18.62	18.66
Highest CH	-	-	-	-	5.03	5.05	10.07	9.73	14.15	14.21	18.82	18.86
Mode	LTE Band 48 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.98	-	9.89	-	14.45	-	18.78	-
Middle CH	-	-	-	-	5.11	-	9.63	-	14.39	-	18.74	-
Highest CH	-	-	-	-	4.91	-	9.63	-	14.12	-	18.98	-



LTE Band 48

Lowest Channel / 5MHz / QPSK




Date: 20.NOV.2019 18:46:15

Lowest Channel / 5MHz / 16QAM



Date: 20.NOV.2019 18:46:28

Middle Channel / 5MHz / QPSK




Date: 20.NOV.2019 18:47:01

Middle Channel / 5MHz / 16QAM




Date: 20.NOV.2019 18:47:13

Highest Channel / 5MHz / QPSK



Date: 20.NOV.2019 18:47:49

Highest Channel / 5MHz / 16QAM



Date: 20.NOV.2019 18:48:01




LTE Band 48

Lowest Channel / 10MHz / QPSK




Date: 20.NOV.2019 18:48:39

Lowest Channel / 10MHz / 16QAM




Date: 20.NOV.2019 18:48:51

Middle Channel / 10MHz / QPSK




Date: 20.NOV.2019 18:49:28

Middle Channel / 10MHz / 16QAM




Date: 20.NOV.2019 18:49:38

Highest Channel / 10MHz / QPSK



Date: 20.NOV.2019 18:50:14

Highest Channel / 10MHz / 16QAM




Date: 20.NOV.2019 18:50:28




LTE Band 48

Lowest Channel / 15MHz / QPSK




Date: 20.NOV.2019 18:51:03

Lowest Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:51:15

Middle Channel / 15MHz / QPSK




Date: 20.NOV.2019 18:51:50

Middle Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:52:02

Highest Channel / 15MHz / QPSK



Date: 20.NOV.2019 18:52:38

Highest Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:52:49




LTE Band 48

Lowest Channel / 20MHz / QPSK




Date: 20.NOV.2019 18:53:27

Lowest Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:53:39

Middle Channel / 20MHz / QPSK




Date: 20.NOV.2019 18:54:14

Middle Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:54:25

Highest Channel / 20MHz / QPSK



Date: 20.NOV.2019 18:55:01

Highest Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:55:13




LTE Band 48

Lowest Channel / 5MHz / 64QAM




Date: 20.NOV.2019 18:55:39

Lowest Channel / 10MHz / 64QAM




Date: 20.NOV.2019 18:56:52

Middle Channel / 5MHz / 64QAM




Date: 20.NOV.2019 18:56:02

Middle Channel / 10MHz / 64QAM




Date: 20.NOV.2019 18:57:15

Highest Channel / 5MHz / 64QAM



Date: 20.NOV.2019 18:56:28

Highest Channel / 10MHz / 64QAM



Date: 20.NOV.2019 18:57:39




LTE Band 48

Lowest Channel / 15MHz / 64QAM




Date: 20.NOV.2019 18:58:04

Lowest Channel / 20MHz / 64QAM




Date: 20.NOV.2019 18:58:17

Middle Channel / 15MHz / 64QAM




Date: 20.NOV.2019 18:58:27

Middle Channel / 20MHz / 64QAM




Date: 20.NOV.2019 18:59:40

Highest Channel / 15MHz / 64QAM



Date: 20.NOV.2019 18:58:51

Highest Channel / 20MHz / 64QAM



Date: 20.NOV.2019 17:00:03




Occupied Bandwidth

Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.51	4.48	9.05	8.99	13.40	13.40	17.90	17.78
Middle CH	-	-	-	-	4.52	4.47	9.03	9.05	13.52	13.46	17.98	17.86
Highest CH	-	-	-	-	4.54	4.50	9.01	9.09	13.46	13.49	17.94	17.82
Mode	LTE Band 48 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.51	-	9.05	-	13.46	-	17.98	-
Middle CH	-	-	-	-	4.51	-	8.95	-	13.49	-	17.82	-
Highest CH	-	-	-	-	4.49	-	9.07	-	13.43	-	17.82	-




LTE Band 48


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 48

Lowest Channel / 10MHz / QPSK




Date: 20.NOV.2019 18:48:15

Lowest Channel / 10MHz / 16QAM




Date: 20.NOV.2019 18:48:27

Middle Channel / 10MHz / QPSK




Date: 20.NOV.2019 18:49:03

Middle Channel / 10MHz / 16QAM



Date: 20.NOV.2019 18:49:15

Highest Channel / 10MHz / QPSK



Date: 20.NOV.2019 18:49:50

Highest Channel / 10MHz / 16QAM




Date: 20.NOV.2019 18:50:02




LTE Band 48

Lowest Channel / 15MHz / QPSK




Date: 20.NOV.2019 18:50:39

Lowest Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:50:51

Middle Channel / 15MHz / QPSK




Date: 20.NOV.2019 18:51:27

Middle Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:51:39

Highest Channel / 15MHz / QPSK



Date: 20.NOV.2019 18:52:13

Highest Channel / 15MHz / 16QAM




Date: 20.NOV.2019 18:52:25




LTE Band 48

Lowest Channel / 20MHz / QPSK




Date: 20.NOV.2019 18:53:03

Lowest Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:53:15

Middle Channel / 20MHz / QPSK




Date: 20.NOV.2019 18:53:51

Middle Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:54:03

Highest Channel / 20MHz / QPSK



Date: 20.NOV.2019 18:54:37

Highest Channel / 20MHz / 16QAM




Date: 20.NOV.2019 18:54:49




LTE Band 48

Lowest Channel / 5MHz / 64QAM




Date: 20.NOV.2019 18:55:27

Lowest Channel / 10MHz / 64QAM




Date: 20.NOV.2019 18:56:40

Middle Channel / 5MHz / 64QAM




Date: 20.NOV.2019 18:55:51

Middle Channel / 10MHz / 64QAM




Date: 20.NOV.2019 18:57:03

Highest Channel / 5MHz / 64QAM



Date: 20.NOV.2019 18:56:14

Highest Channel / 10MHz / 64QAM




Date: 20.NOV.2019 18:57:27




LTE Band 48

Lowest Channel / 15MHz / 64QAM




Date: 20.NOV.2019 18:57:52

Lowest Channel / 20MHz / 64QAM




Date: 20.NOV.2019 18:59:05

Middle Channel / 15MHz / 64QAM




Date: 20.NOV.2019 18:58:16

Middle Channel / 20MHz / 64QAM




Date: 20.NOV.2019 18:59:28

Highest Channel / 15MHz / 64QAM



Date: 20.NOV.2019 18:58:39


Highest Channel / 20MHz / 64QAM



Date: 20.NOV.2019 18:59:51



Conducted Band Edge






LTE Band 48 / 5MHz


QPSK

Middle Channel / 1RB0

Middle Channel / 1RBmax




Date: 20 NOV 2019 00:41:30



Date: 20 NOV 2019 01:05:23

Middle Channel / FullIRB

N/A



Date: 20 NOV 2019 00:53:27




LTE Band 48 / 5MHz


QPSK

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 20 NOV 2019 00:42:49



Date: 20 NOV 2019 01:06:43

Highest Channel / FullIRB

N/A



Date: 20 NOV 2019 00:54:46




LTE Band 48 / 10MHz


QPSK

Lowest Channel / 1RB0

Lowest Channel / 1RBmax




Date: 20 NOV 2019 11:13:43



Date: 20 NOV 2019 11:37:38

Lowest Channel / FullIRB

N/A



Date: 20 NOV 2019 11:25:41




LTE Band 48 / 10MHz


QPSK

MiddleChannel / 1RB0

Middle Channel / 1RBmax




Date: 20 NOV 2019 11:15:03



Date: 20 NOV 2019 11:38:58

Middle Channel / FullIRB

N/A



Date: 20 NOV 2019 11:27:01




LTE Band 48 / 10MHz


QPSK

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 20 NOV 2019 11:21:41



Date: 20 NOV 2019 11:45:36

Highest Channel / FullIRB

N/A



Date: 20 NOV 2019 11:33:39




LTE Band 48 / 15MHz


QPSK

Lowest Channel / 1RB0

Lowest Channel / 1RBmax




Date: 20 NOV 2019 11:46:58



Date: 20 NOV 2019 12:10:54

Lowest Channel / FullRB

N/A



Date: 20 NOV 2019 11:58:56




LTE Band 48 / 15MHz


QPSK

Middle Channel / 1RB0

Middle Channel / 1RBmax




Date: 20 NOV 2019 11:53:37



Date: 20 NOV 2019 12:17:33

Middle Channel / FullIRB

N/A



Date: 20 NOV 2019 12:05:35




LTE Band 48 / 15MHz

QPSK

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 20 NOV 2019 11:54:56



Date: 20 NOV 2019 12:18:53

Highest Channel / FullIRB

N/A



Date: 20 NOV 2019 12:06:55





LTE Band 48 / 20MHz

QPSK

Lowest Channel / 1RB0

Lowest Channel / 1RBmax




Date: 30 DEC 2019 10:41:06

Date: 20 NOV 2019 14:02:30

Lowest Channel / FullIRB

N/A



Date: 20 NOV 2019 12:25:34




LTE Band 48 / 20MHz


QPSK

Middle Channel / 1RB0

Middle Channel / 1RBmax




Date: 30 DEC 2019 10:48:24



Date: 20 NOV 2019 14:03:50

Middle Channel / FullIRB

N/A



Date: 20 NOV 2019 12:26:54





LTE Band 48 / 20MHz

QPSK

Highest Channel / 1RB0

Highest Channel / 1RBmax




Date: 30 DEC 2019 10:55:52

Date: 20 NOV 2019 14:10:28

Highest Channel / FullIRB

N/A



Date: 20 NOV 2019 12:33:33





LTE Band 48 / 5MHz

16QAM

Lowest Channel / 1RB0

Lowest Channel / 1RBmax




Date: 30 DEC 2019 10:38:24

Date: 20 NOV 2019 01:00:05

Lowest Channel / FullIRB

N/A



Date: 20 NOV 2019 00:48:08




LTE Band 48 / 5MHz


16QAM

Middle Channel / 1RB0

Middle Channel / 1RBmax




Date: 20 NOV 2019 00:40:10



Date: 20 NOV 2019 01:04:04

Middle Channel / FullIRB

N/A



Date: 20 NOV 2019 00:52:07