

FCC RF EXPOSURE REPORT

FCC ID: 2ADZRG240WB

Project No. : 1411C236
Equipment : GPON ONU
Model : G-240W-B
Applicant : Alcatel-Lucent Shanghai Bell Co. Ltd.
Address : 6B602, 388 Ningqiao Road Pudong, Shanghai,
China

According: : FCC Guidelines for Human Exposure IEEE
C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

2.4G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Airgain	N2420S	Embedded	U.FL	3.20
2	Airgain	N2420S	Embedded	U.FL	3.20
3	Airgain	N2420S	Embedded	U.FL	3.20

5G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Airgain	N5x20B	Embedded	N/A	2.90
2	Airgain	N5x20B	Embedded	N/A	2.90
3	Airgain	N5x20B	Embedded	N/A	2.90
4	Airgain	N5x20B	Embedded	N/A	2.90

2.4G Only MPE

EUT :	GPON ONU	Model Name :	G-240W-B
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX N20 MODE /CH01, CH06, CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.20	2.0893	29.59	909.9133	0.37839934	1	Complies

5G Only MPE

EUT :	GPON ONU	Model Name :	G-240W-B
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX AC40 MODE/CH151,CH159		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.90	1.9498	23.62	230.1442	0.09570847	1	Complies

So for 2.4G+5G simultaneous transmission MPE:

$$0.3784/1+0.0957/1=0.4741$$

Note: the calculated distance is 20 cm.