

## FCC 47 CFR MPE REPORT

Chunghsin Technology Group CO., LTD

32 inch HD DLED TV

Model Number:ELST3216H

Additional Model: WD32HBR105 , WD32HBB101

FCC ID: 2AE2W-3216H

Prepared for:	Chunghsin Technology Group CO., LTD
	NO. 618-2 GONGREN WEST ROAD, JIAOJIANG AREA, TAIZHOU, ZHEJIANG, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1802004
Date of Test:	February 03 ~ February 07, 2017
Date of Report:	February 07, 2017

## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   2 ,   H   2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

#### (b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   2 ,   H   2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 3、Conducted Power Result

#### 3.1 Antenna

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	16.58	45.499	16±2	2	1.585
	2437	16.95	49.545	16±2	2	1.585
	2462	17.67	58.479	17±2	2	1.585
IEEE 802.11g	2412	10.65	11.614	10±2	2	1.585
	2437	11.67	14.689	11±2	2	1.585
	2462	11.25	13.335	11±2	2	1.585
IEEE 802.11n HT20	2412	10.65	11.614	10±2	2	1.585
	2437	10.86	12.190	10±2	2	1.585
	2462	10.88	12.246	10±2	2	1.585
IEEE 802.11n HT40	2422	9.11	8.147	9±2	2	1.585
	2437	9.19	8.299	9±2	2	1.585
	2452	9.26	8.433	9±2	2	1.585

#### 4、Calculated Result and Limit

##### 4.1 Antenna

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm <sup>2</sup> )	Limited of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	19	2	1.585	0.02505	1	Compiles
IEEE 802.11g	13	2	1.585	0.00629	1	Compiles
IEEE 802.11n HT20	12	2	1.585	0.00500	1	Compiles
IEEE 802.11n HT40	11	2	1.585	0.00397	1	Compiles