



FCC PART 15, SUBPART C  
ISED C RSS-247, ISSUE 2, FEBRUARY 2017



TEST REPORT

For

**Roost, Inc.**

1250 Borregas Ave., Sunnyvale, CA 94089, USA

**FCC ID: 2AE5A-SRRKP**  
**IC: 20891-SRRKP**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Keypad
<b>Prepared By:</b> Deepak Mishra Test Technician	
<b>Report Number:</b> R2103243-247	
<b>Report Date:</b> 2021-07-23	
<b>Reviewed By:</b> Zhao Zhao RF Project Engineer	
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: +1 (408) 732-9162, Fax: +1 (408) 732-9164	



**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA\*, NIST, or any agency of the Federal Government.

\* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*”

## TABLE OF CONTENTS

<b>1 General Description.....</b>	<b>5</b>
1.1 Product Description for Equipment Under Test (EUT) .....	5
1.2 Mechanical Description of EUT .....	5
1.3 Objective.....	5
1.4 Related Submittal(s)/Grant(s) .....	5
1.5 Test Methodology .....	5
1.6 Measurement Uncertainty .....	5
1.7 Test Facility Accreditations .....	6
<b>2 System Test Configuration.....</b>	<b>8</b>
2.1 Justification.....	8
2.2 EUT Exercise Software.....	8
2.3 Duty Cycle Correction Factor .....	8
2.4 Equipment Modifications.....	10
2.5 Local Support Equipment .....	10
2.6 Remote Support Equipment.....	10
2.7 Interface Ports and Cabling.....	10
<b>3 Summary of Test Results .....</b>	<b>11</b>
<b>4 FCC §15.203 &amp; ISEDC RSS-Gen §6.8 - Antenna Requirements .....</b>	<b>12</b>
4.1 Applicable Standards .....	12
4.2 Antenna Description .....	12
<b>5 FCC §2.1091, §15.247(i) &amp; ISEDC RSS-102- RF Exposure.....</b>	<b>13</b>
5.1 Applicable Standards .....	13
5.2 MPE Prediction.....	14
5.3 MPE Results for the FCC .....	14
5.4 RF exposure evaluation exemption for IC .....	14
<b>6 FCC §15.209, §15.247(d) &amp; ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions.....</b>	<b>15</b>
6.1 Applicable Standards .....	15
6.2 Test Setup .....	16
6.3 Test Procedure .....	18
6.4 Corrected Amplitude & Margin Calculation.....	18
6.5 Test Equipment List and Details.....	19
6.6 Test Environmental Conditions .....	19
6.7 Summary of Test Results .....	20
6.8 Radiated Emissions Test Results .....	21
<b>7 FCC §15.247(a) (1)(i) &amp; ISEDC RSS-247 §5.1, RSS-Gen §6.6- Emission Bandwidth.....</b>	<b>24</b>
7.1 Applicable Standards .....	24
7.2 Measurement Procedure.....	24
7.3 Test Equipment List and Details.....	24
7.4 Test Environmental Conditions .....	24
7.5 Test Results.....	25
<b>8 FCC §15.247(b) (2) &amp; ISEDC RSS-247 §5.4 - Output Power .....</b>	<b>29</b>
8.1 Applicable Standards .....	29
8.2 Measurement Procedure.....	29
8.3 Test Equipment List and Details.....	29
8.4 Test Environmental Conditions .....	29
8.5 Test Results.....	30
<b>9 FCC §15.247(d) &amp; ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges.....</b>	<b>32</b>
9.1 Applicable Standards .....	32
9.2 Measurement Procedure.....	32
9.3 Test Equipment List and Details.....	32

9.4 Test Environmental Conditions ..... 33

9.5 Test Results..... 33

**10 FCC §15.247(a) (1) (i) & ISEDC RSS-247 §5.1(c) - Dwell Time..... 36**

10.1 Applicable Standards ..... 36

10.2 Measurement Procedure..... 36

10.3 Test Equipment List and Details..... 36

10.4 Test Environmental Conditions ..... 37

10.5 Test Results..... 37

**11 FCC §15.247(a)(1)(i) & ISEDC RSS-247 §5.1(c) - Number of Hopping Channels ..... 41**

11.1 Applicable Standards ..... 41

11.2 Test Procedure ..... 41

11.3 Test Equipment List and Details..... 41

11.4 Test Environmental Conditions ..... 41

11.5 Test Results..... 42

**12 FCC §15.247(a) (1) & ISEDC RSS-247 §5.1(c) - Hopping Channel Separation ..... 43**

12.1 Applicable Standards ..... 43

12.2 Test Procedure ..... 43

12.3 Test Equipment List and Details..... 43

12.4 Test Environmental Conditions ..... 43

12.5 Test Results..... 44

**13 Annex A - Test Setup Photographs ..... 46**

**14 Annex B - EUT Photographs ..... 47**

**15 Annex C (Normative) - A2LA Electrical Testing Certificate..... 48**

### DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R2103243-247	Original Report	2021-07-23

## 1 General Description

---

### 1.1 Product Description for Equipment Under Test (EUT)

This test report was prepared on behalf of *Roost, Inc.* and their product model: *RKP-320, FCC ID: 2AE5A-SRRKP, IC: 20891-SRRKP* or the “EUT” as referred to in this report. It is a 900 MHz Radio (Sub 1G) with 1 antenna.

### 1.2 Mechanical Description of EUT

The EUT measures approximately 10 cm ( $\Phi$ ), 2 cm (H) and weigh 200 g.

*The test data gathered are from typical production samples:*

*Radiated Sample SN: 21580112700132*

*Conducted Sample SN: 21580112700228*

### 1.3 Objective

This report was prepared on behalf of *Roost, Inc.* in accordance with Part 2, Subpart J, and Part 15, Subparts B and C of the Federal Communication Commission’s rules and ISEDC RSS-247 Issue 2, February 2017.

The objective was to determine compliance with FCC Part 15.247 and ISEDC RSS-247 for Output Power, Antenna Requirements, 20 dB Bandwidth, 100 kHz Bandwidth of Band Edges Measurement, Conducted and Radiated Spurious Emissions, Number of Hopping Channels, Dwell Time, and Hopping Channel Separation.

### 1.4 Related Submittal(s)/Grant(s)

N/A

### 1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

### 1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR16-4-2:2011, The Treatment of Uncertainty in EMC Measurements, the values ranging from  $\pm 2.0$  dB for Conducted Emissions tests and  $\pm 4.0$  dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BAEL Corp.

## 1.7 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

**A- An independent, 3<sup>rd</sup>-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3297.02)**, in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (\*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report..

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

**B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.03)** to certify

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.

- For the Canada (Industry Canada):

- 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
- 2 All Scope 2-Licensed Personal Mobile Radio Services;
- 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
- 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
- 5 All Scope 5-Licensed Fixed Microwave Radio Services
- 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.

- For Singapore (Info-Communications Development Authority (IDA)):

- 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2

- For the Hong Kong Special Administrative Region:

- 1 All Radio Equipment, per KHCA 10XX-series Specifications;
- 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
- 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.

- For Japan:

- 1 MIC Telecommunication Business Law (Terminal Equipment):
  - All Scope A1 - Terminal Equipment for the Purpose of Calls;
  - All Scope A2 - Other Terminal Equipment
- 2 Radio Law (Radio Equipment):
  - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
  - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
  - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

**C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.01) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:**

- 1 Electronics and Office Equipment:
  - for Telephony (ver. 3.0)
  - for Audio/Video (ver. 3.0)
  - for Battery Charging Systems (ver. 1.1)
  - for Set-top Boxes & Cable Boxes (ver. 4.1)
  - for Televisions (ver. 6.1)
  - for Computers (ver. 6.0)
  - for Displays (ver. 6.0)
  - for Imaging Equipment (ver. 2.0)
  - for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
  - for Commercial Dishwashers (ver. 2.0)
  - for Commercial Ice Machines (ver. 2.0)
  - for Commercial Ovens (ver. 2.1)
  - for Commercial Refrigerators and Freezers
- 3 Lighting Products
  - For Decorative Light Strings (ver. 1.5)
  - For Luminaires (including sub-components) and Lamps (ver. 1.2)
  - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
  - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
  - for Residential Ceiling Fans (ver. 3.0)
  - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
  - For Water Coolers (ver. 3.0)

**D. A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:**

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Industry Canada - IC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
  - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
  - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
  - o EMC Directive 2014/30/EC US-EU EMC & Telecom MRA CAB
  - o Radio & Teleterminal Equipment (R&TTE) Directive 1995/5/EC  
US -EU EMC & Telecom MRA CAB
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA)  
APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Development Authority - IDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
- USA:
  - o ENERGY STAR Recognized Test Laboratory – US EPA
  - o Telecommunications Certification Body (TCB) – US FCC;

Vietnam: APEC Tel MRA -Phase I

## 2 System Test Configuration

### 2.1 Justification

The EUT was configured for testing in accordance to ANSI C63.10.

The worst-case data rates are determined by measuring the peak power across all data rates.

### 2.2 EUT Exercise Software

The EUT has built-in test firmware.

Channel Frequency (MHz)	Power Setting
902.2	Default
915	Default
927.8	Default

### 2.3 Duty Cycle Correction Factor

According to KDB 558074 D01 DTS Meas Guidance v05r02 section 6.0:

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be utilized to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data is being acquired (i.e., no transmitter off-time is to be considered).

Channel Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
902.2	-	-	100	0
915	-	-	100	0
927.8	-	-	100	0


Duty Cycle = On Time (ms) / Period (ms)

Duty Cycle Correction Factor (dB) =  $10 \cdot \log(1/\text{Duty Cycle})$


Please refer to the following plots.




### 902.2 MHz



### 915 MHz



### 927.8 MHz



## 2.4 Equipment Modifications

None.

## 2.5 Local Support Equipment

Manufacturer	Description	Model
Dell	Laptop	Latitude E6410

## 2.6 Remote Support Equipment

Manufacturer	Description	Model
Roost	Base Station	N/A

## 2.7 Interface Ports and Cabling

Cable Description	Length (m)	To	From
SMA Cable	< 1 m	EUT	PSA

### 3 Summary of Test Results

Results reported relate only to the product tested.

FCC & ISEDC Rules	Description of Test	Results
FCC §15.203 ISEDC RSS-Gen §6.8	Antenna Requirement	Compliant
FCC §15.207, §15.212 ISEDC RSS-Gen §8.8	AC Line Conducted Emissions	N/A*
FCC §2.1091, §15.247(i) ISEDC RSS-102	RF Exposure	Compliant
FCC §2.1053, §15.205, §15.209, §15.247(d) ISEDC RSS-247 §5.5 ISEDC RSS-Gen §8.9, §8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(1)(i) ISEDC RSS-247 §5.1 ISEDC RSS-Gen §6.6	20 dB & 99% Emission Bandwidth	Compliant
FCC §15.247(b)(2) ISEDC RSS-247 §5.4	Maximum Peak Output Power	Compliant
FCC §15.247(d) ISEDC RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §15.247(a)(1)(i) ISEDC RSS-247 §5.1(c)	Number of Hopping Channels	Compliant
FCC §15.247(a)(1) ISEDC RSS-247 §5.1(c)	Hopping Channel Separation	Compliant
FCC §15.247(a)(1)(i) ISEDC RSS-247 §5.1(c)	Dwell Time	Compliant

Note: N/A\* The EUT is battery powered.

## 4 FCC §15.203 & ISEDC RSS-Gen §6.8 - Antenna Requirements

### 4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to ISEDC RSS-Gen §6.8: Transmitter Antenna

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### 4.2 Antenna Description

The antennas used by the EUT have unique coupling to the intentional radiator.

Antenna usage	Frequency Range (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
900 MHz ISM Band	902-928	Chip Antenna	-5

Note: antenna gain is information provided by customer.

## 5 FCC §2.1091, §15.247(i) & ISEDC RSS-102- RF Exposure

### 5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

#### 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

## 5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 5.3 MPE Results for the FCC

<u>Maximum peak output power at antenna input terminal (dBm):</u>	12.23
<u>Maximum peak output power at antenna input terminal (mW):</u>	16.711
<u>Prediction distance (cm):</u>	20
<u>Prediction frequency (MHz):</u>	902.2
<u>Maximum Antenna Gain, typical (dBi):</u>	-5
<u>Maximum Antenna Gain (numeric):</u>	0.316
<u>Power density of prediction frequency at 20.0 cm (mW/cm<sup>2</sup>):</u>	0.00105
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u>	0.60

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.00105mW/cm<sup>2</sup>. Limit is 0.60 mW/cm<sup>2</sup>.

## 5.4 RF exposure evaluation exemption for IC

Maximum EIRP power = 12.23dBm - 5 dBi = 7.23 dBm which is lesser than  $1.31 \times 10^{-2} f^{0.6834} = 1.3706 \text{ W} = 31.37 \text{ dBm}$

The RF exposure evaluation is compliant.

## 6 FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

### 6.1 Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3.3458 – 3.358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISEDC RSS-Gen 8.9,

Except when the requirements applicable to a given device state otherwise, emission from licence-exempt transmitters shall comply with the field strength limits shown in the table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

#### General Field Strength Limits for Licence-Exemption Transmitters at Frequencies above 30 MHz

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ at 3 meters)
30-88	100
88-216	150
216-960	200
Above 960*	500

\* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

As per ISEDC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

## 6.2 Test Setup


The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and ISEDC RSS-247 limits.

The spacing between the peripherals was 10 centimeters.


External I/O cables were draped along the edge of the test table and bundle when necessary.




Below 1 GHz:



Above 1 GHz at 3m:



Above 1 GHz at 1m:



### 6.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto
- (2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

### 6.4 Corrected Amplitude & Margin Calculation

For emissions below 1 GHz and for above 1GHz scans.

The Corrected Amplitude (CA) is calculated by adding the Correction Factor to the S.A. Reading. The basic equation is as follows:

$$\text{CA} = \text{S.A. Reading} + \text{Correction Factor}$$

For example, a corrected amplitude of 40.3 dBuV/m = S.A. Reading (32.5 dBuV) + Correction Factor (7.8 dB/m)

The Correction Factor is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) together. This calculation is done in the measurement software, and reported in the test result section. The basic equation is as follows:

$$\text{Correction Factor} = \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

For emission above 1 GHz,

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

## 6.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Analyzer, Spectrum	E4440A	US45303156	2020-04-24	18 months
Rohde & Schwarz	Receiver, EMI Test....	ESCI 1166.5950K03..	100337	2021-03-21	2 years
Sunol Science Corp	System Controller	SC99V	011003-1	N/R	N/R
Sunol Sciences	Biconilog Antenna	JB3	A020106-2	2019-11-20	2 years
IW Microwave	157 Series Cable Armored with 2.92mm Male Plugs on Both Sides	KPS-1571AN-2400 ...	DC 1922	2020-07-06	1 year
Fairview Microwave	Times Microwave LMR 400 UltraFex Coaxial Cable 35'	FMC0101405-420	BACL1904161	2020-06-18	1 year
HP	Pre Amplifier	8447D	2443A04374	2020-08-17	1 year
-	SMA cable	-	-	Each time <sup>1</sup>	N/A
Agilent	Preamplifier	8449B	3147A00400	2021-03-02	1 year
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	2.5 years

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability: BACL Corp.** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

## 6.6 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	44%
ATM Pressure:	102.7 kPa

The testing was performed by Deepak Mishra from 2021-04-05 to 2021-04-11 in 5m chamber 3.

## 6.7 Summary of Test Results

According to the data hereinafter, the EUT complied with FCC Title 47, Part 15C/ISED RSS-247 standard's radiated emissions limits, and had the worst margin of:


<b>Mode: Transmitting</b>			
<b>Margin (dB)</b>	<b>Frequency (MHz)</b>	<b>Polarization (Horizontal/Vertical)</b>	<b>Transmitting Channel</b>
-8.47	2783.4	Vertical	927.8 MHz

Please refer to the following table and plots for specific test result details.

### 6.8 Radiated Emissions Test Results

#### 1) 30 MHz – 1 GHz Worst Case, Measured at 3 meters

Worst Case: 902.2 MHz




Frequency (MHz)	S.A. Reading (dBuV)	Correction Factor	Corrected Amplitude (dBuV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dBuV/m)	Margin (dB)	Comment
206.66525	35.95	-7.53	28.42	180	H	272	43.5	-15.08	QP
203.0155	33.25	-6.38	26.86	143	H	304	43.5	-16.64	QP
209.3055	34.88	-7.66	27.22	123	H	77	43.5	-16.28	QP
31.47675	19.96	1.33	21.28	240	H	223	40	-18.72	QP
269.684	26.02	-4.78	21.23	182	H	112	46	-24.77	QP
886.85725	18.49	4.82	23.31	109	V	169	46	-22.69	QP

## 2) 1-10 GHz

Frequency (MHz)	S.A. Reading (dBµV)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dBµV/m)	FCC/ISED		Comment
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dBµV/m)	Margin (dB)	
Low Channel Frequency: 902.2 MHz											
1804	48.76	271	222	H	30.90	4.54	37.26	46.94	74	-27.06	PK
1804	40.10	271	222	H	30.90	4.54	37.26	38.28	54	-15.72	Ave
1804	47.58	239	150	V	30.90	4.54	37.26	45.76	74	-28.24	PK
1804	39.00	240	152	V	30.90	4.54	37.26	37.18	54	-16.82	Ave
2706	49.56	271	290	H	32.60	5.67	36.80	51.04	74	-22.96	PK
2706	41.26	271	290	H	32.60	5.67	36.80	42.74	54	-11.26	Ave
2706	48.70	187	285	V	32.60	5.67	36.80	50.18	74	-23.82	PK
2706	41.40	187	285	V	32.60	5.67	36.80	42.88	54	-11.12	Ave
Middle Channel Frequency: 915 MHz											
1830	48.92	217	232	H	30.90	4.54	37.26	47.10	74	-26.90	PK
1830	38.74	217	232	H	30.90	4.54	37.26	36.92	54	-17.08	Ave
1830	49.60	261	204	V	30.90	4.54	37.26	47.78	74	-26.22	PK
1830	41.74	261	204	V	30.90	4.54	37.26	39.92	54	-14.08	Ave
2745	47.87	182	237	H	32.60	5.67	36.79	49.35	74	-24.65	PK
2745	38.40	182	237	H	32.60	5.67	36.79	39.88	54	-14.12	Ave
2745	48.76	146	100	V	32.60	5.67	36.79	50.24	74	-23.76	PK
2745	41.37	146	100	V	32.60	5.67	36.79	42.85	54	-11.15	Ave
3660	46.16	0	150	H	33.50	7.09	36.56	50.19	74	-23.81	PK
3660	33.11	0	150	H	33.50	7.09	36.56	37.14	54	-16.86	Ave
3660	46.69	0	150	V	33.50	7.09	36.56	50.72	74	-23.28	PK
3660	33.14	0	150	V	33.50	7.09	36.56	37.17	54	-16.83	Ave
High Channel Frequency: 927.8 MHz											
1855.6	47.00	0	150	H	31.30	4.54	37.25	45.59	74	-28.41	PK
1855.6	35.00	0	150	H	31.30	4.54	37.25	33.59	54	-20.41	AV
1855.6	47.00	0	100	V	31.30	4.54	37.25	45.59	74	-28.41	PK
1855.6	35.00	0	100	V	31.30	4.54	37.25	33.59	54	-20.41	AV
2783.4	48.98	260	192	H	32.70	5.67	36.79	50.56	74	-23.44	PK
2783.4	43.50	260	192	H	32.70	5.67	36.79	45.08	54	-8.92	AV
2783.4	49.75	178	268	V	32.70	5.67	36.79	51.33	74	-22.67	PK
<b>2783.4</b>	<b>43.95</b>	<b>178</b>	<b>268</b>	<b>V</b>	<b>32.70</b>	<b>5.67</b>	<b>36.79</b>	<b>45.53</b>	<b>54</b>	<b>-8.47</b>	<b>AV</b>

**1 GHz – 10 GHz Worst Case, Measured at 1 meter**



## 7 FCC §15.247(a) (1)(i) & ISEDC RSS-247 §5.1, RSS-Gen §6.6- Emission Bandwidth

### 7.1 Applicable Standards

According to FCC §15.247(a) (1) and ISEDC RSS-247 §5.1: the maximum 20 dB bandwidth of the hopping channel shall be presented.

### 7.2 Measurement Procedure

Span = approximately 2 to 5 times the 99% occupied bandwidth, centered on a hopping channel

RBW = 1% to 5 % of the 99% occupied bandwidth

VBW = 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 7.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rhode & Schwarz	Signal Analyzer	FSQ26	200749	2019-11-07	2 years
-	SMA cable	-	-	Each time <sup>1</sup>	N/A
-	10 dB attenuator	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

### 7.4 Test Environmental Conditions

Temperature:	27° C
Relative Humidity:	39 %
ATM Pressure:	100.7 kPa

The testing was performed by Deepak Mishra on 2021-06-18 in RF Bench.




## 7.5 Test Results

Channel	Frequency (MHz)	99% OBW (kHz)	20 dB OBW (kHz)
Low	902.2	90.769	86.667
Middle	915	92.821	87.692
High	927.8	92.308	86.667


Please refer to the following plots for detailed test results.

### Low Channel 902.2 MHz

### 99% Bandwidth




### -20 dB Bandwidth




### Middle Channel 915 MHz

#### 99% Bandwidth




#### -20 dB Bandwidth




### High Channel 927.8 MHz

### 99% Bandwidth



### -20 dB Bandwidth



## 8 FCC §15.247(b) (2) & ISEDC RSS-247 §5.4 - Output Power

### 8.1 Applicable Standards

According to FCC §15.247(b) (2): For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

According to RSS-247 §5.4: For frequency hopping systems operating in the band 902-928 MHz, For FHSs operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W if the hopset uses 50 or more hopping channels; the maximum peak conducted output power shall not exceed 0.25 W and the e.i.r.p. shall not exceed 1 W if the hopset uses less than 50 hopping channels.

### 8.2 Measurement Procedure

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSQ26	200749	2019-11-07	2 years
-	SMA cable	-	-	Each time <sup>1</sup>	N/A
-	10dB attenuator	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

### 8.4 Test Environmental Conditions


Temperature:	25° C
Relative Humidity:	29 %
ATM Pressure:	102.3 KPa

The testing was performed by Deepak Mishra on 2021-06-04 in RF Bench.


### 8.5 Test Results

Channel	Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)
Low	902.2	12.23	30
Middle	915	12.18	30
High	927.8	11.86	30


Low Channel 902.2 MHz



### Middle Channel 915 MHz



### High Channel 927.8 MHz



## 9 FCC §15.247(d) & ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges

### 9.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

According to ISEDC RSS-247 §5.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### 9.2 Measurement Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW = 100 kHz

VBW = 300 kHz

Sweep = coupled

Detector function = peak

Trace = max hold

For hopping mode, a radiated sample was measured with horn antenna. Delta between the emission levels at fundamental frequency and band-edge frequency was measured.

### 9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSQ26	200749	2019-11-07	2 years
Rhode & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	1 year
EMCO	Antenna, Horn	3115	9511-4627	2020-10-12	2 years
-	SMA cable	-	-	Each time <sup>1</sup>	N/A
-	10 dB attenuator	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".



### 9.4 Test Environmental Conditions


Temperature:	24.7° C
Relative Humidity:	48 %
ATM Pressure:	100.6 KPa

The testing was performed by Deepak Mishra on 2021-06-18 in RF Bench.


### 9.5 Test Results

Please refer to the following plots for detailed test results.


Low Channel 902.2 MHz




### High Channel 927.8 MHz



### Hopping mode at Low Edge 902.2 MHz



### Hopping mode at High Edge 927.8 MHz



## 10 FCC §15.247(a) (1) (i) & ISEDC RSS-247 §5.1(c) - Dwell Time

### 10.1 Applicable Standards

According to FCC §15.247(a) (1) (i) and RSS-247 §5.1(c): For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz

### 10.2 Measurement Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW ≤ channel spacing and where possible RBW should be set  $\gg 1/T$ , where T is the expected dwell time per channel

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\text{(Number of hops in the period specified in the requirements)} = \text{(number of hops on spectrum analyzer)} \times \text{(period specified in the requirements / analyzer sweep time)}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

### 10.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rhode & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	1 year
EMCO	Antenna, Horn	3115	9511-4627	2020-10-12	2 years
-	SMA cable	-	-	Each time	N/A

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 02 October 2018) "A2LA Policy on Metrological Traceability".

## 10.4 Test Environmental Conditions

<b>Temperature:</b>	22.8 ° C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.4 KPa

The testing was performed by Deepak Mishra from 2021-07-12 in RF Bench.

## 10.5 Test Results


Channel	Frequency	No. of Pulses (per 20 sec)	Pulse Width (ms)	Total Dwell Time (sec)	Limit (sec)	Results
Low	902.2	4	26.09	0.1044	0.400	Compliant
Middle	915	4	27.54	0.1102	0.400	Compliant
High	927.8	4	26.09	0.1044	0.400	Compliant

Total Dwell Time (*sec*) = (Number of Pulses per 20 seconds x Pulse Width (*ms*))/1000


Please refer to the following plots for detailed test results.

### Low Channel 902.2 MHz

### Number of Pulses




### Pulse Duration




### Middle Channel 915 MHz

### Number of Pulses




### Pulse Duration




### High Channel 927.8 MHz

### Number of Pulses



### Pulse Duration





## 11 FCC §15.247(a)(1)(i) & ISEDC RSS-247 §5.1(c) - Number of Hopping Channels

### 11.1 Applicable Standards

According to FCC §15.247(a) (1) (i) and ISEDC RSS-247 §5.1(c)-: For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz

### 11.2 Test Procedure

Span = the frequency band of operation

RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 11.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rhode & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	1 year
EMCO	Antenna, Horn	3115	9511-4627	2020-10-12	2 years
-	SMA cable	-	-	Each time l	N/A

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".


### 11.4 Test Environmental Conditions

Temperature:	22.8 °C
Relative Humidity:	50 %
ATM Pressure:	101.4kKPa

The testing was performed by Deepak Mishra from 2021-07-12 in RF Bench.

### 11.5 Test Results

Total 65 channels; please refer to the plots hereinafter.



## 12 FCC §15.247(a) (1) & ISEDC RSS-247 §5.1(c) - Hopping Channel Separation

### 12.1 Applicable Standards

According to FCC §15.247(a) (1) : Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

According to FCC §15.247(a) (1) (i) and ISEDC RSS-247 §5.1(c): For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz

### 12.2 Test Procedure

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\approx$  30% of the channel spacing, adjust as necessary to best identify the center of each individual channel

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 12.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rhode & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	1 year
EMCO	Antenna, Horn	3115	9511-4627	2020-10-12	2 years
-	SMA cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable and attenuator included in the test set-up will be checked each time before testing.

**Statement of Traceability: BACL Corp.** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

### 12.4 Test Environmental Conditions


Temperature:	22.8° C
Relative Humidity:	50 %
ATM Pressure:	101.4 KPa

The testing was performed by Deepak Mishra on 2021-07-12 in RF Bench.


### 12.5 Test Results

Channel	Frequency (MHz)	Channel Separation (kHz)	Limit > 20 dB OBW (kHz)
Low	902.2	353.1	86.667
Middle	915	405.2	87.692
High	927.8	399.4	86.667


Low Channel 902.2 MHz



### Middle Channel 915 MHz



### High Channel 927.8 MHz



---

## **13 Annex A - Test Setup Photographs**

---

Please refer to attachment.

---

## **14 Annex B - EUT Photographs**

---

Please refer to attachment.

# 15 Annex C (Normative) - A2LA Electrical Testing Certificate



## Accredited Laboratory

A2LA has accredited

### BAY AREA COMPLIANCE LABORATORIES CORP.

Sunnyvale, CA

for technical competence in the field of

### Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This laboratory also meets A2LA R222 - *Specific Requirements EPA ENERGY STAR Accreditation Program*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

Presented this 10<sup>th</sup> day of March 2021.



Trace McInturf, Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 3297.02  
Valid to September 30, 2022

*For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*

Please follow the web link below for a full ISO 17025 scope

<https://www.a2la.org/scopepdf/3297-02.pdf>

--- END OF REPORT ---