

Appendix 5

RF Exposure Information

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)	Separation Distance (mm)
2402	-4.66	0.342	5
2441	-4.50	0.355	5
2480	-4.99	0.317	5

According to KDB 447498 D01:

These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,24 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(0.342/5) \cdot \sqrt{2.402} = 0.106 < 3.0$$

$$(0.355/5) \cdot \sqrt{2.441} = 0.111 < 3.0$$

$$(0.317/5) \cdot \sqrt{2.480} = 0.099 < 3.0$$

Conclusion:

No SAR is required.