

# Appendix 5

## RF Exposure Information

www.tuv.com

### Maximum transmitter power

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2402	-4.54	0.352
2441	-5.09	0.310
2480	-5.73	0.267

According to KDB 447498 D01:

#### Standalone SAR test exclusion considerations:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$   
for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

#### Result:

$$(0.35/5) \cdot \sqrt{2.402} = 0.109 < 3.0$$

$$(0.31/5) \cdot \sqrt{2.441} = 0.097 < 3.0$$

$$(0.27/5) \cdot \sqrt{2.480} = 0.084 < 3.0$$

#### Conclusion:

No SAR is required