## FCC §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## **Applicable Standard**

According to subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Report No.: RSZ170508003-00A

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposure									
0.3-3.0	614	1.63	*100 6						
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup> 6						
30-300	61.4	0.163	1.0	6					
300-1,500			f/300	6					
1,500-100,000			5	6					
	(B) Limits for G	eneral Population/Uncontrolled E	xposure						
0.3-1.34	614	1.63	*100 30						
1.34-30	824/f	2.19/f	*180/f²	30					
30-300	27.5	0.073	0.2 30						
300-1,500			f/1500	30					
1,500-100,000			1.0	30					

f = frequency in MHz

## Result

## **Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 90 Page 9 of 44

<sup>\* =</sup> Plane-wave equivalent power density

For TNB, The Controlled Exposure limit shall be applied:

Frequency (MHz)	Antenna Gain		<b>Conducted Power</b>	Evaluation	Power	MPE Limit
	(dBi)	(numeric)	(mW)	Distance (cm)	Density (mW/cm <sup>2</sup> )	$(mW/cm^2)$
450-512	3.5	2.24	22854.41	60	1.13	1.5

Report No.: RSZ170508003-00A

Note: The target conducted power is 46.60 dBm(45708.82mW), 50% duty cycle was used in evaluation, so the power is 22854.41mW.

Simultaneous transmitting consideration:

Refer to the DSS and DTS report, the highest MPE for 2.4G band is 0.0001 mW/cm<sup>2</sup>

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} = 0.0001/1 + 1.13/1.5 = 0.7534 < 1$$

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 60cm from nearby persons.

**Result: Compliance** 

FCC Part 90 Page 10 of 44