

TEST REPORT

Applicant Name & Address : L'Image Home Products Inc.
1175 Place du Frere Andre, Montreal, QC, H3B3X9, Canada
Manufacturing Site : ZhongShan WinStar Electrical co., ltd
Sandun industry district, Minzhong town, zhongshan city, guangdong China

Sample Description
Product : RF remote control
FCC ID : 2AE6Q30810356
Model No. : 30810356
Electrical Rating : Battery CR2025 3V *1
Brand Name : Sunbeam, Beach Lighting, Polaroid, Home luminaire, Noma

Date Received : 26 May 2015
Date Test Conducted : 26 May 2015 -13 June 2015
Test standards : 47 CFR PART 15 Subpart C: 2014 section 15.249

Test Result : Pass


Conclusion : The submitted samples complied with the above rules/standards.

Remark : None.


*****End of Page*****

Prepared and Checked By:

Approved By:



Jackson Zhang
Engineer
Intertek Guangzhou



Helen Ma
Team Leader
Intertek Guangzhou
30 July 2015 _____
Date

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China
Tel / Fax: 86-20-8213 9688/86-20-3205 7538

CONTENT

TEST REPORT	1
CONTENT	2
1.0 Summary of Test.....	3
2.0 General Description.....	4
2.1 Product Description.....	4
2.2 Related Submittal(s) Grants	5
2.3 Test Methodology	5
2.4 Test Facility.....	5
3.0 System Test Configuration	6
3.1 Justification	6
3.2 EUT Exercising Software.....	7
3.3 Special Accessories	7
3.4 Measurement Uncertainty	7
3.5 Equipment Modification.....	7
3.6 Support Equipment List and Description	7
4.0 Measurement Results.....	8
4.1 Antenna Requirement:.....	8
4.2 Occupied Bandwidth:	9
4.7 Radiated Emission	12
4.8 Band Edges Requirement	24
4.9 Conducted Emissions at Mains Terminals	26
10.0 Test Equipment List.....	27



Report No.: 150526074GZU-001
Issued: 2015-07-30

1.0 Summary of Test

TEST	TEST REQUIREMENT	TEST METHOD	RESULT
Antenna Requirement	FCC PART 15 C Section 15.203	FCC PART 15 C Section 15.203	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9	PASS
Radiated Emission	FCC PART 15 C section 15.249 (a), (d)	ANSI C63.10: Clause 6.4, 6.5 & 6.6	PASS
Band Edges Measurement	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.10	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	N/A
Remark: N/A: not applicable. Refer to the relative section for the details. EUT: In this whole report EUT means Equipment Under Test. Tx: In this whole report Tx (or tx) means Transmitter. RF: In this whole report RF means Radio Frequency. ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.			



Report No.: 150526074GZU-001
Issued: 2015-07-30

2.0 General Description

2.1 Product Description

Operating Frequency	2434 MHz
Type of Modulation:	GFSK
Number of Channels	1 Channels
Antenna Type	Integral
Function:	Transmit command
Power Supply:	DC 3V
Power cord:	N/A

2.2 Related Submittal(s) Grants

Remaining portions are subject to the following procedures:

1. Receiver portion: exempt from technical requirement of this Part.

2.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10:2013. Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans and final tests were performed in the semi-anechoic chamber to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise.

2.4 Test Facility

All of the tests are performed at:

Shenzhen EMTEK Co., Ltd

Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052
P.R.China

This test facility and site measurement data have been fully placed on file with the FCC test firm registration number is 406365.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. The spurious emissions more than 20 dB below the permissible value are not reported.

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

3.2 EUT Exercising Software

N/A

3.3 Special Accessories

No special accessories used.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by L'Image Home Products Inc. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

3.6 Support Equipment List and Description

N/A

4.0 Measurement Results

4.1 Antenna Requirement:


Standard requirement

15.203 requirement:

For intentional device. According to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


EUT Antenna

The antenna is an integral antenna and no consideration of replacement.



4.2 Occupied Bandwidth:

- Test Requirement: FCC PART 15 C section 15.215(c)
(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated
- Test Method: ANSI C63.10: Clause 6.9
- Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The highest, middle and the lowest channels were selected for the final test as listed below.
- Test Configuration:



Test Procedure:

The transmitter was operated at its maximum carrier power measured under normal test conditions.

- a) The instrument center frequency was set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer was between 1.5 times and 5.0 times the OBW(20 dB Bandwidth).

- b) The nominal IF filter bandwidth (3 dB RBW) was in the range of 1% to 5% of the OBW, and VBW was approximately three times the RBW.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope was more than $[10 \log (OBW/RBW)]$ below the reference level.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) The dynamic range of the instrument at the selected RBW was more than 10 dB below the target “-20 dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW was at least 30 dB below the reference value.
- f) Peak detection and max hold mode (until the trace stabilizes) was used.
- g) Used the 20dB bandwidth function of the instrument and reported the measured bandwidth.
- h) The occupied bandwidth was reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division was clearly labeled. Tabular data was reported in addition to the plot(s).

20 dB bandwidth:

Channel No.	Frequency (MHz)	Measured 20 dB bandwidth (kHz)	Limit (FL MHz)	Limit (FH MHz)	Result
0	2434	3340	2400	2483.5	Pass

20dB bandwidth:

Result plot as follows:



4.7 Radiated Emission

Test Requirement:

FCC PART 15 C section 15.249 (a), (d)

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dB μ V/m @ 3m)	Field Strength of Harmonics (dB μ V/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0

Note: The limits shown in the above table are based on measurements using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using a CISPR quasi-peak detector.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Test Method:

ANSI C63.10: Clause 6.4, 6.5 and 6.6

Test Status:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The lowest, middle and the lowest channels were selected for the final test as listed below.

Test site:

Measurement Distance: 3m (Semi-Anechoic Chamber)

Limit:

The field strength of radiated emission outside of the specified frequency bands, except for harmonics at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field Strength (dB μ V/m @ 3m)
30-88	40.0
88-216	43.5
216-960	46.0
Above 960	54.0

Detector:

For Peak and Quasi-Peak value:

200 Hz for 9 kHz to 150 kHz

9 kHz for 150 kHz to 30 MHz

120 kHz for 30 MHz to 1GHz

RBW = 1 MHz for $f \geq 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak for $f \geq 1$ GHz, QP for $f < 1$ GHz

Trace = max hold

According 15.35(c), when the field strength (or envelope power) is not constant or it is in pulses, and an average detector is specified to be used, the value of field strength or power shall be determined by averaging over one complete pulse train, including blanking intervals within the pulse train, as long as the pulse train does not exceed 0.1 seconds. In cases where the pulse train exceeds 0.1 second, the average value of field strength or output power shall be determined during a 0.1 second interval during which the field strength or power is at its maximum value.

The average correction factor was computed by analyzing the on time in 100ms over one complete pulse train. Analysis of the remote transmitter on time in one complete pulse train, therefore the average value of fundamental frequency was: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

The duration of one cycle =5.7ms


Effective period of the cycle =(0.35x2) ms=0.7 ms

DC =0.7/5.7=0.1228 or 12.28%

Therefore, the averaging factor is found by 20lg0.1228=-18.21

Please refer to below plots for more details.

Change colour is worst case's test data was presented in this test report.






RBW 1 MHz Delta 2 [T1]
VBW 3 MHz -46.61 dB
SWT 25 ms 350.000000 μ s

Ref 100 dB μ V

*Att 10 dB

1 PK
VIEW



Center 2.4339 GHz


2.5 ms/

Section 15.205 Restricted bands of operation.


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 -	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.69525	960 - 1240	7.25 - 7.75
4.125 - 4.128	16.80425 -	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	16.80475	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	25.5 - 25.67	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	37.5 - 38.25	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	73 - 74.6	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	74.8 - 75.2	2200 - 2300	14.47 - 14.5
8.291 - 8.294	108 - 121.94	2310 - 2390	15.35 - 16.2
8.362 - 8.366	123 - 138	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	149.9 - 150.05	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.52475 -	3260 - 3267	23.6 - 24.0
12.29 - 12.293	156.52525	3332 - 3339	31.2 - 31.8
12.51975 -	156.7 - 156.9	3345.8 - 3358	36.43 - 36.5
12.52025	162.0125 - 167.17	3600 - 4400	
12.57675 -	167.72 - 173.2		
12.57725	240 - 285		
13.36 - 13.41	322 - 335.4		

Test Configuration:


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 40 GHz emissions:



Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the special distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3) 1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

For testing performed with the horn antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

4) The receiver was scanned from 9 kHz to 25 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement
 The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

Radiated Emissions (Below 1GHz)


Operation Frequency: 2434MHz

Antenna Polarization	Frequency [MHz]	Measured Net at 3m [dB(μV/m)]	Limit at 3m [dB(μV/m)]
Horizontal	30.000	<30.0	40.0
Horizontal	100.000	<33.5	43.5
Horizontal	300.000	<36.0	46.0
Vertical	30.000	<30.0	40.0
Vertical	100.000	<33.5	43.5
Vertical	300.000	<36.0	46.0


Test Curve:

Operation Frequency: 2434MHz

Horizontal:



Vertical:





Report No.: 150526074GZU-001
 Issued: 2015-07-30

Radiated Emissions (Above 1GHz)

Operation Frequency: 2434MHz

Horizontal:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	2434.240	120.43	-22.87	97.56	114.00	-16.44	peak
2	*	2434.240	97.56	-18.21	79.35	94.00	-14.65	AVG

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		5573.000	58.58	-13.69	44.89	74.00	-29.11	peak
2		5573.000	39.92	-13.69	26.23	54.00	-27.77	AVG
3		12356.00	54.14	-3.12	51.02	74.00	-22.98	peak
4		12356.00	36.87	-3.12	33.75	54.00	-20.25	AVG
5		13240.00	52.28	-0.75	51.53	74.00	-22.47	peak
6		13240.00	34.18	-0.75	33.43	54.00	-20.57	AVG
7		14328.00	49.25	2.24	51.49	74.00	-22.51	peak
8		14328.00	31.92	2.24	34.16	54.00	-19.84	AVG
9		15756.00	53.24	-1.16	52.08	74.00	-21.92	peak
10		15756.00	36.62	-1.16	35.46	54.00	-18.54	AVG
11		16470.00	52.21	-0.14	52.07	74.00	-21.93	peak
12	*	16470.00	36.48	-0.14	36.34	54.00	-17.66	AVG

Vertical:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	*	2434.160	106.46	-22.87	83.59	114.00	-30.41	peak
2	*	2434.160	83.59	-18.21	65.38	94.00	-28.62	AVG

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		5624.000	57.33	-13.63	43.70	74.00	-30.30	peak
2		5624.000	39.23	-13.63	25.60	54.00	-28.40	AVG
3		8021.000	55.43	-8.26	47.17	74.00	-26.83	peak
4		8021.000	37.86	-8.26	29.60	54.00	-24.40	AVG
5		10877.00	54.06	-4.56	49.50	74.00	-24.50	peak
6		10877.00	36.23	-4.56	31.67	54.00	-22.33	AVG
7		12322.00	53.57	-3.20	50.37	74.00	-23.63	peak
8		12322.00	35.61	-3.20	32.41	54.00	-21.59	AVG
9		14362.00	49.24	2.22	51.46	74.00	-22.54	peak
10		14362.00	31.31	2.22	33.53	54.00	-20.47	AVG
11		17031.00	49.22	2.48	51.70	74.00	-22.30	peak
12	*	17031.00	31.67	2.48	34.15	54.00	-19.85	AVG

- Notes:
1. AT frequencies equal to or less than 1000MHz, quasi-peak detector was used, above 1000MHz, Peak detector was used.
 2. All measurements were made at 3 meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. When Peak emission level was below AV limit, the AV emission level did not be recorded.

4.8 Band Edges Requirement


Test Requirement: FCC PART 15 C section 15.249 (d)
(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Frequency Band: 2400 MHz to 2483.5 MHz


Test Method: ANSI C63.10: Clause 6.10


Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The lowest, middle and the highest channels were selected for the final test as listed below.

Test Configuration:



**Test result with plots as follows:
Result plot as follows:**





Peak Measurement

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

4.9 Conducted Emissions at Mains Terminals

N/A



Report No.: 150526074GZU-001
 Issued: 2015-07-30

10.0 Test Equipment List

Radiated Emission

Equipment No.	Equipment	Model	Manufacturer	Cal. Due date (YYYY-MM-DD)	Calibration Interval
EE089	EMI Test Receiver	ESU	Rohde & Schwarz	May 17, 2015	1Y
EE040	Pre-Amplifier	8447F	HP		
EE043	Bilog Antenna	VULB9163	Schwarzbeck	May 29, 2015	1Y
EE147	Cable	AK9513	Schwarzbeck	May 17, 2015	1Y
EE169	Cable	N/A	Rosenberger	May 17, 2015	1Y
EE168	Cable	AK9513	Schwarzbeck	May 29, 2015	1Y
EE170	Cable	AK9513	Schwarzbeck	May 29, 2015	1Y
EE096	Pre-Amplifier	PAM-0126	A.H.	May 17, 2015	1Y
EE094	Horn Antenna	BBHA 9120	Schwarzbeck	May 29, 2015	1Y
EE097	Cable	0.5M SF104-26.5	H+B	May 29, 2015	1Y
EE100	Cable	3M SF104- 26.5	H+B	May 29, 2015	1Y
EE101	Cable	6M SF104- 26.5	H+B	May 29, 2015	1Y
EE095	Horn Antenna	BBHA 9170	Schwarzbeck	May 17, 2015	1Y
EE255	Band reject Filter(50dB)	WRCGV- 2400(2400- 2485MHz)	WI/DE	May 17, 2015	1Y