

# Maximum Permissible Exposure Evaluation

**FCC ID: 2AE6WRP-R1**

## 1. Client Information

**Applicant** : Shenzhen omimo Technology Co.,Ltd.  
**Address** : Room1212, Chuangjian Building, No.6023, Shennan Boulevard, Futian District, Shenzhen, China  
**Manufacturer** : Shenzhen omimo Technology Co.,Ltd.  
**Address** : Room1212, Chuangjian Building, No.6023, Shennan Boulevard, Futian District, Shenzhen, China

## 2. General Description of EUT

<b>EUT Name</b>	:	omimo WIFI Repeater	
<b>Models No.</b>	:	RP-R1	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels 802.11n(HT40): 7 channels
		RF Output Power:	802.11b: 14.54 dBm 802.11g: 14.64 dBm 802.11n (HT20): 14.33 dBm 802.11n (HT40): 14.41 dBm
		Antenna Gain:	1 dBi PCB Antenna
		Modulation Type:	802.11b: DSSS(BPSK, QPSK, CCK) 802.11g/n:OFDM(BPSK,QPSK,16QAM, 64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n(HT20):14.44/28.88/43.34/57.78/86.66/115.56 /130/144.44Mbps 802.11n(HT40):30/60/90/120/180/240/270/300Mbps

<b>Power Supply</b>	:	DC 5V supplied by AC/DC Adapter.
<b>Power Rating</b>	:	Input: AC 100~240V, 50/60Hz Output: DC 5V
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual

### MPE Calculations for WIFI

**1. Antenna Gain:**

PCB Antenna: 1 dBi.

**2. EUT Operation Condition:**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**3. Exposure Evaluation:**

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

**S:** power density

**P:** power input to the antenna

**G:** power gain of the antenna in the direction of interest relative to an isotropic radiator.

**R:** distance to the center of radiation of the antenna

**4. Test Result:**

Worst Maximum MPE Result											
Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted Power(max) (dBm) [P]		ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm <sup>2</sup> ) [S]			Power Density Limit (mW/ cm <sup>2</sup> )	Result
			Ant a	Ant b			Ant 1	Ant 2	Sum		
802.11b	1	2412	14.28	14.34	1	20	0.0067	0.0068	---	1.000	PASS
		2437	14.52	14.48	1	20	0.0071	0.0070	---		
		2462	14.54	14.41	1	20	0.0071	0.0069	---		
802.11g	1	2412	14.14	14.34	1	20	0.0065	0.0068	---		
		2437	14.49	14.14	1	20	0.0070	0.0065	---		
		2462	14.64	14.16	1	20	0.0073	0.0065	---		
802.11n (HT20)	2	2412	11.14	11.07	1	20	0.0033	0.0032	0.0064		
		2437	11.57	10.91	1	20	0.0036	0.0031	0.0067		
		2462	11.17	11.46	1	20	0.0033	0.0035	0.0068		
802.11n (HT40)	2	2422	11.71	10.90	1	20	0.0037	0.0031	0.0068		
		2437	11.35	11.45	1	20	0.0032	0.0035	0.0067		
		2452	11.05	11.28	1	20	0.0034	0.0034	0.0068		

Note:  
 (1) N<sub>TX</sub>= Number of Transmit Antennas  
 (2) RF Output power specifies that Maximum Conducted Peak Output Power.

**5. Conclusion:**

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

**Limits for General Population/ Uncontrolled Exposure**

Frequency Range (MHz)	Power density (mW/ cm <sup>2</sup> )
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n (2412~2462 MHz)

MPE limit S: 1 mW/ cm<sup>2</sup>

The MPE is calculated as **0.0073mW / cm<sup>2</sup> < limit 1 mW / cm<sup>2</sup>**. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

**Note**

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----