

RF EXPOSURE REPORT

Equipment Under Test	Car AVN
Model Name	DGU-12T5-Y461A-2
Variant Model Name	DGU-12T5-Y461A-1, DGU-12T5-Q261A-1, DGU-12T5-Q261A-2, DGU-12T5-Y461SA-1, DGU-12T5-Q261SA-1, DGU-12T5-Y461SA-2, DGU-12T5-Q261SA-2, DGU-12T5-Y461SA-3, DGU-12T5-Q261SA-3 DGU-12T5-Y461SA-4, DGU-12T5-Q261SA-4
FCC ID	2AE77-DGU12T5Y461A2
Applicant	DIGEN
Manufacturer	DIGEN
Date of Test(s)	2023. 06. 12 ~ 2023. 06. 28
Date of Issue	2023. 07. 03

In the configuration tested, the EUT complied with the standards specified above.

Issue to	Issue by
DIGEN 89, Seongseo4chacheomdan-ro Dalseo-gu, Daegu, South Korea Tel.: +82 70-7100-1740 Fax: +82 2-532-8811	DEKRA Korea Co., Ltd. 498-2, Geumeo-ro, Pogok-eup, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17030 Tel.: +82-31-338-8837 Fax: +82-31-338-8847

RF EXPOSURE

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissible Exposure: RF exposure is calculated.

Frequency Range	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Averaging Time [minute]
Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*(100)	30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1	30

f=frequency in MHz, *= plane-wave equivalent power density

MPE (Maximum Permissible Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

MPE Calculations : Bluetooth BDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : -0.09 dBm
- Target Power & Tolerance 0.00 dBm & $\pm$ 1.00 dB
(Maximum : 1.00 dBm & Minimum : -1.00 dBm)
- Maximum Peak Antenna Gain : 3.40 dBi
- Maximum Output Power for the Calculation : 1.00 dBm

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE calculation for this exposure is shown below.

- EIRP = P + G = <u>1.00</u> dBm + <u>3.40</u> dBi = <u>4.40</u> dBm = <u>2.75</u> mW	- NOTE P : Max tuneup Power (dBm) G : Maximum Peak Antenna Gain (dBi)
---	--

Power Density at the specific separation

- S = EIRP / (4 X R²π) = 2.75 / (4 X 20² X π) = <u>0.000 548</u> mW/cm²	- NOTE S : Maximum Power Density (mW/cm²) EIRP : Equivalent Isotropic Radiated Power (mW) R : Distance to the center of the radiation of the antenna (<u>20</u> cm)
---	--

MPE Calculations : Bluetooth EDR

- Frequency Range : 2 402 MHz ~ 2 480 MHz
- Measured RF Output Power (Peak) : 1.73 dBm
- Target Power & Tolerance 0.75 dBm & $\pm$ 1.00 dB
(Maximum : 1.75 dBm & Minimum : -0.25 dBm)
- Maximum Peak Antenna Gain : 3.40 dBi
- Maximum Output Power for the Calculation : 1.75 dBm

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the
The MPE calculation for this exposure is shown below.

- EIRP = P + G = <u>1.75</u> dBm + <u>3.40</u> dBi = <u>5.15</u> dBm = <u>3.27</u> mW	- NOTE P : Max tuneup Power (dBm) G : Maximum Peak Antenna Gain (dBi)
---	--

Power Density at the specific separation

- S = EIRP / (4 X R²π) = 3.27 / (4 X 20² X π) = <u>0.000 651</u> mW/cm²	- NOTE S : Maximum Power Density (mW/cm²) EIRP : Equivalent Isotropic Radiated Power (mW) R : Distance to the center of the radiation of the antenna (<u>20</u> cm)
---	--