

## FCC - TEST REPORT

Report Number : **68.950.15.029.01** Date of Issue: Jun 15, 2015

Model : SE-MJ771BT-W, SE-MJ771BT-K

Product Type : Wireless Stereo Headphones

Applicant : Onkyo & Pioneer Innovations Corporation

Address : Onkyo Yaesu Bldg, 2-3-12 Yaesu, Chuo-Ku, Tokyo, Japan

Production Facility : UNI-ART PRECISE ELECTRONICS (SHENZHEN) LTD

Address : No.8 XinSha Road, Shajing Town, Baoan District 518125 Shenzhen,  
Guangdong, China

Test Result :  **Positive**     **Negative**

Total pages including  
Appendices : 41

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval*



# 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment Under Test .....	4
4	Summary of Test Standards .....	5
5	Summary of Test Results .....	6
6	General Remarks.....	7
7	Test Setups .....	8
8	Systems test configuration .....	9
9	Technical Requirement .....	10
9.1	Conducted Emission .....	10
9.2	Conducted peak output power .....	13
9.3	20 dB bandwidth and 99% Occupied Bandwidth.....	14
9.4	Carrier Frequency Separation .....	21
9.5	Number of hopping frequencies .....	24
9.6	Dwell Time .....	26
9.7	Spurious RF conducted emissions .....	29
9.8	Band edge testing.....	33
9.9	Spurious radiated emissions for transmitter .....	38
10	Test Equipment List.....	40
11	System Measurement Uncertainty .....	41



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch  
Building 12&13, Zhiheng Wisdomland Business Park,  
Nantou Checkpoint Road 2, Nanshan District,  
Shenzhen City, 518052,  
P. R. China

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

### 3 Description of the Equipment Under Test

Product:	Wireless Stereo Headphones
Model no.:	SE-MJ771BT-W, SE-MJ771BT-K
FCC ID:	2AE79-MJ771BT
Brand Name:	N/A
Options and accessories:	USB Cable, Audio-in Cable
Rating:	3.7VDC (Supplied by Li-ion rechargeable battery) 5VDC (Charged by USB port)
RF Transmission Frequency:	2402-2480MHz
No. of Operated Channel:	79
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Duty Cycle:	33.16%
Antenna Type:	Internal Antenna
Antenna Gain:	0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Wireless Stereo Headphones with Bluetooth function operating at 2.4GHz

## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2014 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to Public Notice DA 00-705 -Frequency Hopping Spread Spectrum Test Procedure released by FCC on March 30, 2000 and C63.10 (2009).

## 5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Site	Test Result
§15.207	Conducted emission on AC power port	10	Site 1	N/A
§15.247(b)(1)	Conducted peak output power	13	Site 1	Pass
§15.247(a)(2)	6dB bandwidth	---	---	N/A
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	14	Site 1	Pass
§15.247(a)(1)	Carrier frequency separation	21	Site 1	Pass
§15.247(a)(1)(iii)	Number of hopping frequencies	24	Site 1	Pass
§15.247(a)(1)(iii)	Dwell Time	26	Site 1	Pass
§15.247(e)	Power spectral density*	---	---	N/A
§15.247(d)	Spurious RF conducted emissions	29	Site 1	Pass
§15.247(d)	Band edge	33	Site 1	Pass
§15.247(d) & §15.209 &	Spurious radiated emissions for transmitter and receiver	38	Site 1	Pass
§15.203	Antenna requirement	See note 2		Pass

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a permanently Internal antenna, which gain is 0dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2AE79-MJ771BT, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C.

SE-MJ771BT-K is identical with SE-MJ771BT-W, the difference between them only lies in the model name and colour, so full test was applied on SE-MJ771BT-W, another model deemed to fulfill the requirement of the standard without further testing.

### SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: May 15, 2015

Testing Start Date: May 18, 2015

Testing End Date: Jun 04, 2015

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

Prepared by:

Tested by:



Phoebe Hu  
EMC Project Manager




Calvin Weng  
EMC Project Engineer




Leon Zhang  
EMC Test Engineer

## 7 Test Setups


### 7.1 AC Power Line Conducted Emission test setups



### 7.2 Radiated test setups



### 7.3 Conducted RF test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
NoteBook	LENOVO	X240	---

Test software: Bluetest3.exe, which used to control the EUT in continues transmitting mode

The system was configured to hopping mode and non-hopping mode.

Hopping mode: typical working mode (normal hopping status)

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power

## 9 Technical Requirement

### 9.1 Conducted Emission on AC power port

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


#### Limit

According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50


Decreasing linearly with logarithm of the frequency

Product Type : Wireless Stereo Headphones  
 M/N : SE-MJ771BT-W  
 Operating Condition : Charging + BT transmitting  
 Test Specification : Line  
 Comment : AC 120V/60Hz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.193500	---	34.21	53.88	19.67	L1	9.7
0.193500	50.35	---	63.88	13.53	L1	9.7
3.914500	---	15.62	46.00	30.38	L1	9.9
3.914500	27.95	---	56.00	28.05	L1	9.9
12.473500	---	27.37	50.00	22.63	L1	10.0
12.473500	35.32	---	60.00	24.68	L1	10.0

Product Type : Wireless Stereo Headphones  
 M/N : SE-MJ771BT-W  
 Operating Condition : Charging + BT transmitting  
 Test Specification : Neutral  
 Comment : AC 120V/60Hz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.177500	---	36.43	54.60	18.17	N	9.7
0.177500	51.35	---	64.60	13.25	N	9.7
3.965500	---	13.05	46.00	32.95	N	9.8
3.965500	21.91	---	56.00	34.09	N	9.8
15.405500	---	26.08	50.00	23.92	N	10.0
15.405500	33.19	---	60.00	26.81	N	10.0

## 9.2 Conducted peak output power

### Test Method

1. Use the following spectrum analyzer settings:  
Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW,  
Sweep = auto, Detector function = peak, Trace = max hold
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power

### Limits

According to §15.247 (b) (1) , conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test result as below table

#### Bluetooth Mode GFSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	-4.27	Pass
Middle channel 2441MHz	-2.30	Pass
High channel 2480MHz	-0.77	Pass

#### Bluetooth Mode π/4-DQPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	-6.73	Pass
Middle channel 2441MHz	-4.52	Pass
High channel 2480MHz	-3.13	Pass

#### Bluetooth Mode 8DPSK modulation Test Result

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	-6.36	Pass
Middle channel 2441MHz	-4.18	Pass
High channel 2480MHz	-2.70	Pass

### 9.3 20 dB bandwidth and 99% Occupied Bandwidth

#### Test Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

#### Limit

Limit [kHz]


---

N/A

**20 dB bandwidth and 99% Occupied Bandwidth**


Bluetooth Mode GFSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	946.5	872.6	--	Pass
2440	946.5	868.3	--	Pass
2480	946.5	863.9	--	Pass




2402MHz

### 20 dB bandwidth and 99% Occupied Bandwidth



Date: 20.MAY.2015 17:16:48

### 2441MHz



Date: 20.MAY.2015 17:15:57


### 2480MHz



**20 dB bandwidth and 99% Occupied Bandwidth**


Bluetooth Mode  $\pi/4$ -DQPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1267.7	1172.2	--	Pass
2440	1272.1	1176.5	--	Pass
2480	1263.4	1176.5	--	Pass




Date: 20.MAY.2015 17:13:19

2402MHz



Date: 20.MAY.2015 17:14:11

### 2441MHz




Date: 20.MAY.2015 17:14:57

### 2480MHz

**20 dB bandwidth and 99% Occupied Bandwidth**


Bluetooth Mode 8DPSK Modulation test result

Frequency MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz	Result
2402	1263.4	1163.5	--	Pass
2440	1267.7	1163.5	--	Pass
2480	1259.0	1176.5	--	Pass




Date: 20.MAY.2015 17:12:12

2402MHz



Date: 20.MAY.2015 17:11:20

### 2441MHz



Date: 20.MAY.2015 17:10:12

### 2480MHz

## 9.4 Carrier Frequency Separation

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels, RBW  $\geq$  1% of the span, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak
2. By using the Max-Hold function record the separation of two adjacent channels.
3. Measure the frequency difference of these two adjacent channels by spectrum analyzer marker function.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

$$\frac{\text{Limit}}{\text{kHz}} \geq 25\text{kHz or } 2/3 \text{ of the } 20 \text{ dB bandwidth which is greater}$$

### GFSK Modulation Limit


Frequency MHz	2/3 of 20 dB Bandwidth kHz
2402	631
2441	631
2480	631

## Carrier Frequency Separation

Test result: The measurement was performed with the typical configuration (normal hopping status), here GFSK modulation mode was used to show compliance.


### GFSK Modulation test result

Frequency MHz	Carrier Frequency Separation kHz	Result
2402	998.6	Pass
2441	998.6	Pass
2480	1002.9	Pass




Date: 20.MAY.2015 17:35:40

2402MHz



### 2440MHz



### 2480MHz

## 9.5 Number of hopping frequencies

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels,  $RBW \geq 1\%$  of the span,  $VBW \geq RBW$ , Sweep = auto, Detector function = peak
2. Set the spectrum analyzer on Max-Hold Mode, and then keep the EUT in hopping mode.
3. Record all the signals from each channel until each one has been recorded.
4. Repeat above procedures until all frequencies measured were complete.

### Limit

**Limit  
number**

---


$\geq 15$



## Number of hopping frequencies

Test result: The measurement was performed with the typical configuration (normal hopping status), and the total hopping channels is constant for the all modulation mode according with the Bluetooth Core Specification. Here GFSK modulation mode was used to show compliance.

Number of hopping frequencies	Result
79	Pass



Date: 20.MAY.2015 17:54:41

## 9.6 Dwell Time

### Test Method

1. Connect EUT antenna terminal to the spectrum analyzer with a low loss cable.  
Equipment mode: Spectrum analyzer
2. RBW: 1MHz; VBW: 1MHz; SPAN: Zero Span
3. Adjust the center frequency of spectrum analyzer on any frequency be measured.
4. Measure the Dwell Time by spectrum analyzer Marker function.
5. Repeat above procedures until all frequencies measured were complete.

### Limit

According to §15.247(a)(1)(iii) . The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

## Dwell Time

### Dwell time

The maximum dwell time shall be 0,4 s.

According to the Bluetooth Core Specification, the worse result (DH5 mode) was reported to show compliance.

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation: 0.4 [s] \* hopping number = 0.4 [s] \* 79 [ch] = 31.6 [s\*ch];


The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 31.6s for DH5=1600 / 6 / 79 \*31.6=106.67

### Test Result

Modulation	Mode	Reading (µs)	Total Hops	Test Result (ms)	Limit (ms)	Result
GFSK	DH5	2971	106.67	316.92	< 400	Pass
π/4-DQPSK	2DH5	2971	106.67	316.92	< 400	Pass
8-DPSK	3DH5	2971	106.67	316.92	< 400	Pass


### GFSK Modulation



Date: 20.MAY.2015 17:38:37

DH5


### $\pi/4$ -DQPSK Modulation



Date: 20.MAY.2015 17:40:46

2DH5

### 8-DPSK Modulation



Date: 20.MAY.2015 17:41:44

3DH5

## 9.7 Spurious RF conducted emissions

### Test Method

1. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.  
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.


### Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


### Spurious RF conducted emissions

Only the worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

2402MHz




Date: 20.MAY.2015 18:40:48




Date: 20.MAY.2015 18:40:32

## Spurious RF conducted emissions

2441MHz




Date: 20.MAY.2015 18:48:26




Date: 20.MAY.2015 18:47:59

### Spurious RF conducted emissions

2480MHz



Date: 20.MAY.2015 18:50:11



Date: 20.MAY.2015 18:49:55



## 9.8 Band edge testing

### Test Method


- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

### Limit:


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

## Band edge testing

GFSK Modulation Test Result:  
Hopping on mode:




Date: 20.MAY.2015 17:25:58




Date: 20.MAY.2015 17:27:03

## Band edge testing

Hopping off mode:




Date: 20.MAY.2015 17:19:45




Date: 20.MAY.2015 17:28:12

## Band edge testing

8DPSK Modulation Test Result:  
Hopping on mode:




Date: 20.MAY.2015 17:23:17




Date: 20.MAY.2015 17:32:20

## Band edge testing

Hopping off mode:



Date: 20.MAY.2015 17:22:23



Date: 20.MAY.2015 17:31:43

## 9.9 Spurious radiated emissions for transmitter

### Test Method

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
3. Use the following spectrum analyzer settings:  
Span = wide enough to fully capture the emission being measured, RBW = 1 MHz for  $f \geq 1$ GHz, 100 kHz for  $f < 1$  GHz, VBW  $\geq$  RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Follow the guidelines in ANSI C63.4-2009 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{duty cycle}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

### Limit

According to part 15.247(d), the radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dB $\mu$ V/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

## Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP, GFSK mode) test result is listed in the report.

### Transmitting spurious emission test result as below:

#### Bluetooth Mode GFSK Modulation 2402MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBuV/m		
59	17.16	Horizontal	40	QP	Pass
213	17.60	Vertical	43.5	QP	Pass
*4804	55.84	Horizontal	74	PK	Pass
*4804	46.24	Horizontal	54	AV	Pass
*4804	57.91	Vertical	74	PK	Pass
*4804	48.31	Vertical	54	AV	Pass

#### Bluetooth Mode GFSK Modulation 2441MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBuV/m		
*4882	58.57	Horizontal	74	PK	Pass
*4882	48.97	Horizontal	54	AV	Pass
*4882	56.35	Vertical	74	PK	Pass
*4882	46.75	Vertical	54	AV	Pass

#### Bluetooth Mode GFSK Modulation 2480MHz Test Result

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBuV/m		
*4960	53.45	Horizontal	74	PK	Pass
*4960	43.85	Horizontal	54	AV	Pass
*4960	56.46	Vertical	74	PK	Pass
*4960	46.86	Vertical	54	AV	Pass

#### Remark:

- (1) AV Emission Level= PK Emission Level+20log(dutycycle)=PK Emission Level-9.6
- (2) Data of measurement within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (3) "\*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

## 10 Test Equipment List

### List of Test Instruments

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE	
CE	EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2015-8-17	<input checked="" type="checkbox"/>
	LISN	Rohde & Schwarz	ENV4200	100249	2015-8-17	<input checked="" type="checkbox"/>
	LISN	Rohde & Schwarz	ENV216	100326	2015-8-17	<input type="checkbox"/>
	ISN	Rohde & Schwarz	ENY81	100177	2015-8-17	<input type="checkbox"/>
	ISN	Rohde & Schwarz	ENY81-CAT6	101664	2015-8-17	<input type="checkbox"/>
	High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-58	2015-8-17	<input type="checkbox"/>
	RF Current probe	Rohde & Schwarz	EZ-17	100816	2015-8-17	<input type="checkbox"/>
C	Signal Analyzer	Rohde & Schwarz	FSV40	101030	2015-8-17	<input checked="" type="checkbox"/>
RE	EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2015-8-17	<input checked="" type="checkbox"/>
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2017-8-17	<input checked="" type="checkbox"/>
	Horn Antenna	Rohde & Schwarz	HF907	102294	2017-8-17	<input checked="" type="checkbox"/>
	Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2015-8-17	<input checked="" type="checkbox"/>
	Pre-amplifier	Rohde & Schwarz	SCU 40A	100432	2015-8-17	<input checked="" type="checkbox"/>
	3m Semi-anechoic chamber	TDK	9X6X6	----	2019-5-29	<input checked="" type="checkbox"/>

#### C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth\*
- 20dB bandwidth and 99% Occupied Bandwidth
- Carrier frequency separation
- Number of hopping frequencies
- Dwell Time
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge

Note: '\*' means the test item doesn't applied.



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

### System Measurement Uncertainty

Items	Extended Uncertainty
Radiated spurious emission	4.32dB (30MHz-1GHz) 2.27dB (1GHz -25GHz)
Conducted spurious emission	2.10dB(30MHz-25GHz)
Bandwidth test	$1*10^{-9}$