

FCC Test Report

Report No.: AGC10232230101FE04

FCC ID : 2AEAN-M2GO

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Wireless Handheld Condenser Microphone

BRAND NAME : RØDE

MODEL NAME : M2-G0

APPLICANT: Rode Microphones

DATE OF ISSUE : Jan. 11, 2023

STANDARD(S) : FCC Part 15.247

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 60

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 11, 2023	Valid	Initial Release



Page 3 of 60

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	7
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF TESTED SYSTEM	10
5.2. EQUIPMENT USED IN TESTED SYSTEM	10
5.3. SUMMARY OF TEST RESULTS	10
6. TEST FACILITY	11
7. PEAK OUTPUT POWER	12
7.1. MEASUREMENT PROCEDURE	12
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
7.3. LIMITS AND MEASUREMENT RESULT	
8. BANDWIDTH	17
8.1. MEASUREMENT PROCEDURE	17
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	17
8.3. LIMITS AND MEASUREMENT RESULTS	17
9. CONDUCTED SPURIOUS EMISSION	24
9.1. MEASUREMENT PROCEDURE	24
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	24
9.3. MEASUREMENT EQUIPMENT USED	24
9.4. LIMITS AND MEASUREMENT RESULT	24
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	36
10.1. MEASUREMENT PROCEDURE	36
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
10.3. MEASUREMENT EQUIPMENT USED	36
10.4. LIMITS AND MEASUREMENT RESULT	36
11. RADIATED EMISSION	40



Page 4 of 60

11.1. MEASUREMENT PROCEDURE	40
11.2. TEST SETUP	41
11.3. LIMITS AND MEASUREMENT RESULT	42
11.4. TEST RESULT	42
12. LINE CONDUCTED EMISSION TEST	56
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	56
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	56
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	57
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	57
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	58
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	60
APPENDIX B: PHOTOGRAPHS OF EUT	60



Page 5 of 60

1. VERIFICATION OF COMPLIANCE

Applicant	Rode Microphones			
Address	107 Carnarvon Street, Silverwater 2128, Australia			
Manufacturer	Rode Microphones			
Address	107 Carnarvon Street, Silverwater 2128, Australia			
Factory	Rode Microphones			
Address	107 Carnarvon Street, Silverwater 2128, Australia			
Product Designation	Wireless Handheld Condenser Microphone			
Brand Name	RØDE			
Test Model	M2-GO			
Date of receipt of test item	Jan. 04, 2023			
Date of test	Jan. 04, 2023 to Jan. 11, 2023			
Deviation	No any deviation from the test method			
Condition of Test Sample	Normal			
Test Result	Pass			
Report Template	AGCRT-ER-FCC/RF			

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Prepared By	Alan Duan	
	Alan Duan (Project Engineer)	Jan. 11, 2023
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Jan. 11, 2023
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Jan. 11, 2023



Page 6 of 60

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Wireless Handheld Condenser Microphone". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402GHz to 2.480GHz
RF Output Power	Antenna 1: -1.024dBm (Max) Antenna 2: -0.244dBm (Max)
Modulation	GFSK
Number of channels	40 Channels
Antenna Designation	Antenna 1: PCB Antenna (Comply with requirements of the FCC part 15.203) Antenna 2: PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	Antenna 1: -3.18dBi Antenna 2: 3.45dBi
Hardware Version	V1.0
Software Version	V1.0
Power Supply	DC 3.8V by battery or DC 5V by adapter

2.2. TABLE OF CARRIER FREQUENCYS

Channels	Frequency (GHz)	Channels	Frequency (GHz)
00	2.402	20	2.442
01	2.404	21	2.444
02	2.406	22	2.446
03	2.408	23	2.448
04	2.410	24	2.450
05	2.412	25	2.452
06	2.414	26	2.454
07	2.416	27	2.456
08	2.418	28	2.458
09	2.420	29	2.460
10	2.422	30	2.462
11	2.424	31	2.464
12	2.426	32	2.466
13	2.428	33	2.468
14	2.430	34	2.470
15	2.432	35	2.472
16	2.434	36	2.474
17	2.436	37	2.476
18	2.438	38	2.478
19	2.440	39	2.480



Page 7 of 60

2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AEAN-M2GO** filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.




Page 8 of 60

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty	
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$	
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$	
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$	
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$	
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$	
Uncertainty of spurious emissions, conducted	$U_c = \pm 2.7 \%$	
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$	





4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX_2402MHz_GFSK_1Mbps
2	Middle channel TX_2440MHz_GFSK_1Mbps
3	High channel TX_2480MHz_GFSK_1Mbps

Note: 1. Only the result of the worst case was recorded in the report, if no other cases.

- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting ☑ \\192.168.30.100\电气程额\FR\hat{m}\lambda{m}\lambda{1}_{\overline{m}}\lambda{



Page 10 of 60

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Wireless Handheld Condenser Microphone	M2-GO	2AEAN-M2GO	EUT
2	Adapter	TPA-23A050200CU01	DC 5V	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



Page 11 of 60

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	FARA	EZ-EMC	Ver. AGC-CON03A1	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 01, 2022	Sep. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	Apr. 28, 2021	Apr. 27, 2023
Test Software	FARA	EZ-EMC	Ver.RA-03A	N/A	N/A



Page 12 of 60

7. PEAK OUTPUT POWER


7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW ≥ DTS bandwidth.
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP





Page 13 of 60


7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power (Antenna 1)						
Test Mode Test Channel (MHz) Peak Power Limits (dBm) Pass or Fail						
	2402	-1.864	≤30	Pass		
GFSK	2440	-2.052	≤30	Pass		
	2480	-1.024	≤30	Pass		

Test Data of Conducted Output Power (Antenna 2)					
Test Mode Test Channel (MHz) Peak Power (dBm) Limits (dBm) Pass or Fail					
	2402	-0.244	≤30	Pass	
GFSK	2440	-1.658	≤30	Pass	
	2480	-2.861	≤30	Pass	

Test Graphs of Conducted Output Power (Antenna 1)


















Test Graphs of Conducted Output Power (Antenna 2)











Page 17 of 60

8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.


8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth (Antenna 1)						
Test Mode Test Channel 99% Occupied -6dB Limits (MHz) Bandwidth (MHz) Bandwidth (MHz) Pass or Fail						
	2402	1.057	0.709	≥0.5	Pass	
GFSK	2440	1.059	0.708	≥0.5	Pass	
	2480	1.064	0.714	≥0.5	Pass	


Test Data of Occupied Bandwidth and DTS Bandwidth (Antenna 2)						
Test Mode Test Channel 99% Occupied -6dB Limits (MHz) Pass or Fail						
	2402	1.057	0.709	≥0.5	Pass	
GFSK	2440	1.052	0.706	≥0.5	Pass	
	2480	1.059	0.714	≥0.5	Pass	










Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/























Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/








Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/









Test_Graph_2.4G_ANT2_2480_1Mbps_OBW



Web: http://www.agccert.com/









Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 24 of 60

9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT					
Annii abla Linia	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS			






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands (Antenna 1)




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_2.4G_ANT1_2402_1Mbps_Lower Band Emissions








































Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands (Antenna 2)















































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands (Antenna 1)




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_2.4G_ANT1_2480_1Mbps_Higher Band Edge Emissions







Test_Graph_2.4G_ANT2_2480_1Mbps_Higher Band Edge Emissions



Page 36 of 60

10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.


10.3. MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4. LIMITS AND MEASUREMENT RESULT


Test Data of Conducted Output Power Spectral Density (Antenna 1)					
Test Mode Test Channel (MHz) Power density Limit (dBm/3kHz) Pass or Fail					
	2402	-14.206	≤8	Pass	
GFSK	2440	-13.945	≤8	Pass	
	2480	-13.667	≤8	Pass	


Test Data of Conducted Output Power Spectral Density (Antenna 2)					
Test Mode Test Channel Power density Limit (MHz) (dBm/3kHz) Pass or Fair					
	2402	-12.409	≪8	Pass	
GFSK	2440	-14.311	≤8	Pass	
	2480	-14.627	≪8	Pass	





Test Graphs of Conducted Output Power Spectral Density (Antenna 1)












Test Graphs of Conducted Output Power Spectral Density (Antenna 2)














Page 40 of 60

11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE


- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.






11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 42 of 60

11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed


Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT

Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.





Radiated emission from 30MHz to 1000MHz

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		123.2655	5.63	21.13	26.76	43.50	-16.74	peak
2		324.4560	5.27	25.74	31.01	46.00	-14.99	peak
3		444.8514	6.66	26.17	32.83	46.00	-13.17	peak
4		468.8761	8.35	24.80	33.15	46.00	-12.85	peak
5		627.2738	4.82	26.51	31.33	46.00	-14.67	peak
6	*	881.4067	4.93	32.19	37.12	46.00	-8.88	peak

RESULT: PASS



Page 44 of 60

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		33.2111	5.52	16.02	21.54	40.00	-18.46	peak
2		55.2207	7.18	17.05	24.23	40.00	-15.77	peak
3	,	130.8369	6.01	16.43	22.44	43.50	-21.06	peak
4	3	360.4476	6.48	21.20	27.68	46.00	-18.32	peak
5	į	549.0193	6.27	24.65	30.92	46.00	-15.08	peak
6	*	721.7259	5.21	28.64	33.85	46.00	-12.15	peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

2. All test modes had been tested. The antenna 2 mode 1 is the worst case and recorded in the report.



Page 45 of 60

Radiated emission above 1GHz

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	47.25	0.08	47.33	74	-26.67	peak
4804.000	35.64	0.08	35.72	54	-18.28	AVG
7206.000	43.77	2.21	45.98	74	-28.02	peak
7206.000	31.88	2.21	34.09	54	-19.91	AVG
		·				
Remark:						

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	45.79	0.08	45.87	74	-28.13	peak
4804.000	35.23	0.08	35.31	54	-18.69	AVG
7206.000	40.55	2.21	42.76	74	-31.24	peak
7206.000	30.94	2.21	33.15	54	-20.85	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 46 of 60

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	48.32	0.14	48.46	74	-25.54	peak
4880.000	37.28	0.14	37.42	54	-16.58	AVG
7320.000	44.75	2.36	47.11	74	-26.89	peak
7320.000	33.96	2.36	36.32	54	-17.68	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	47.51	0.14	47.65	74	-26.35	peak
4880.000	36.73	0.14	36.87	54	-17.13	AVG
7320.000	42.61	2.36	44.97	74	-29.03	peak
7320.000	32.46	2.36	34.82	54	-19.18	AVG
Remark:						_

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 47 of 60

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	47.61	0.22	47.83	74	-26.17	peak
4960.000	38.63	0.22	38.85	54	-15.15	AVG
7440.000	42.11	2.64	44.75	74	-29.25	peak
7440.000	34.98	2.64	37.62	54	-16.38	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	47.29	0.22	47.51	74	-26.49	peak
4960.000	36.91	0.22	37.13	54	-16.87	AVG
7440.000	43.07	2.64	45.71	74	-28.29	peak
7440.000	32.53	2.64	35.17	54	-18.83	AVG

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS


Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been tested. The antenna 2 is the worst case and recorded in the report.







Test result for band edge emission at restricted bands (Antenna 1)

EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal


Test Graph for Peak Measurement








RESULT: PASS






Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone 20° C **Temperature Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Vertical Mode 1 **Antenna**

Test Graph for Peak Measurement Frequency Center Freq 2.387750000 GHz Avg Type: Log-Pw AvalHold: 100/100 Trig: Free Run Auto Tun Ref 126.99 dBµV/m Center Free 2.387750000 GH Start Fre 2.370000000 GH Stop Fre CF Ste 3.550000 MH Ma #VBW 3.0 MHz 2.401 80 GHz 89.049 dBµV/m 2.390 00 GHz 39.689 dBµV/m Freq Offse




RESULT: PASS






Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone 20° C **Temperature Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Horizontal Mode 3 **Antenna**




RESULT: PASS






Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone **Temperature** 20° C **Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Vertical Mode 3 **Antenna**



RESULT: PASS


Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.







Test result for band edge emission at restricted bands (Antenna 2)


EUT	Wireless Handheld Condenser Microphone	Model Name	M2-GO
Temperature	20° C	Relative Humidity	52%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal









RESULT: PASS






Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone 20° C **Temperature Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Vertical Mode 1 **Antenna**






RESULT: PASS






Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone 20° C **Temperature Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Horizontal Mode 3 **Antenna**

Test Graph for Peak Measurement Frequency Center Freq 2.488250000 GHz Avg Type: Log-Pwi Avg|Hold: 100/100 Trig: Free Run Auto Tun Mkr2 2.483 500 GH 56.370 dBµV/r Ref 126.99 dBμV/m Center Free Start Fre 2.476500000 GH Stop Fre CF Ste 2.350000 MH Ma #VBW 3.0 MHz 2.479 723 GHz 92.098 dBµV/m 2.483 500 GHz 56.370 dBµV/m Freq Offse




RESULT: PASS





Wireless Handheld Condenser **EUT** M2-GO **Model Name** Microphone **Temperature** 20° C **Relative Humidity** 52% **Pressure** 985hPa **Test Voltage** Normal Voltage **Test Mode** Vertical Mode 3 **Antenna**



RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 56 of 60

12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francis		Maximum RF Line Voltage					
Frequen	СУ	Q.P.(dBuV) Average					
150kHz~50	OkHz	66-56	56-46				
500kHz~5N	ИНz	56	46				
5MHz~30N	ИНz	60	50				

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 57 of 60

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST-L1



MEASUREMENT RESULT: "agc_fin"

2023/1/8 16:2	5					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	44.40	6.9	66	21.6	QP	L1
0.318000	32.10	6.0	60	27.7	QP	L1
0.342000	31.20	5.9	59	28.0	QP	L1
0.510000	38.70	5.4	56	17.3	QP	L1
0.530000	37.10	5.4	56	18.9	QP	L1
1.154000	30.50	5.6	56	25.5	QP	L1


MEASUREMENT RESULT: "agc fin2"

20	23/1/8 16:24 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.190000	28.70	6.6	54	25.3	AV	L1
	0.438000	26.40	5.6	47	20.7	AV	L1
	0.462000	26.00	5.5	47	20.7	AV	L1
	0.510000	35.70	5.4	46	10.3	AV	L1
	0.534000	33.70	5.4	46	12.3	AV	L1
	1.138000	23.20	5.6	46	22.8	AV	L1

RESULT: PASS



LINE CONDUCTED EMISSION TEST-N



MEASUREMENT RESULT: "agc_fin"

2023/1/8	16:21					
-	cy Level Hz dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.1540	00 44.70	6.9	66	21.1	QP	N
0.3420	00 32.00	5.9	59	27.2	QP	N
0.5060	00 37.10	5.4	56	18.9	QP	N
0.6060	00 25.90	5.4	56	30.1	QP	N
0.8020	00 25.50	5.4	56	30.5	QP	N
1.1340	00 26.50	5.6	56	29.5	QP	N

MEASUREMENT RESULT: "agc_fin2"

2023/1/8 16:21 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.190000 0.438000 0.510000 0.530000 0.854000 1.138000	29.50 26.60 35.50 33.80 23.60 22.90	6.6 5.6 5.4 5.4 5.4 5.6	54 47 46 46 46	12.2 22.4	AV AV AV	N N N N N

RESULT: PASS

Note: All the test modes had been tested, The antenna 2 Mode 1 was the worst case. Only the data of the worst case would be record in this test report.



Page 60 of 60

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC10232230101AP03

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC10232230101AP04

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.