

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

-- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

--Power and distance are rounded to the nearest mW and mm before calculation

--The result is rounded to one decimal place for comparison

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{Exd})^2/30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{(\text{dBuV/m})/20}/10^6$

d = measurement distance in meters (m) ---3m

So $\text{pt} = (\text{Exd})^2/30 \times \text{gt}$

Field strength = 95.29dBuV/m @3m

Ant gain 1dBi; so Ant numeric gain=1.26

So $\text{pt} = [10^{(95.29/20)/10^6} \times 3]^2 / (30 \times 1.26) \times 1000 \text{ mW} = 0.806 \text{ mW}$

So $(0.806 \text{ mW} / 5\text{mm}) \times \sqrt{2.441} = 0.252 < 3$

Then SAR evaluation is not required