



RF TEST REPORT

Report No.: SET2021-00469

Product Name: DV601

IC: 25914-DV601

FCC ID: 2AEDLDV601

Model No. : DV601

Applicant: ROSCO,INC

Address: 90-21 144TH PLACE JAMAICA, NY 11435.

Dates of Testing: 01/01/2021 —01/15/2021

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 48 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name DV601

Brand Name DV6

Trade Name DV6

Applicant ROSCO,INC

Applicant Address 90-21 144TH PLACE JAMAICA, NY 11435.

Manufacturer ROSCO,INC

Manufacturer Address 90-21 144TH PLACE JAMAICA, NY 11435.

Test Standards : 47 CFR FCC Part 2/22/24/27
RSS-Gen Issue 5
RSS-132 Issue 3
RSS-133 Issue 6
RSS-139 Issue 3

Test Result : PASS

Tested by : *Vincent*

2021.02.23

Vincent, Test Engineer

Reviewed by :

Chris You

2021.02.23

Chris You, Senior Engineer

Approved by :

Shuangwen Zhang

2021.02.23

Shuangwen Zhang, Manager

Table of Contents

1. GENERAL INFORMATION	5
1.1 EUT Description	5
1.2 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.3 Test Standards and Results	7
1.4 Test Configuration of Equipment under Test.....	8
1.5 Measurement Results Explanation Example	9
1.6 Facilities and Accreditations.....	9
2. TEST REQUIREMENTS	10
2.1 Conducted RF Output Power	10
2.2 Peak to Average Radio.....	12
2.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement	14
2.4 Frequency Stability.....	19
2.5 Conducted Out of Band Emissions	22
2.6 Bandedge	31
2.7 Transmitter Radiated Power (EIRP/ERP)	35
2.8 Radiated Spurious Emissions	39
2.9 Transmit antenna.....	46
3. LIST OF MEASURING EQUIPMENT	47
4. UNCERTAINTY OF EVALUATION	48



Change History		
Issue	Date	Reason for change
1.0	2021.02.23	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Type	DV601
EUT supports Radios application	WCDMA/HSPA
Hardware Version	REV A
Software Version	2.1.0
Frequency Range	WCDMA 850MHz Tx: 826.4 - 846.6MHz (at intervals of 200kHz); Rx: 871.4 - 891.6MHz (at intervals of 200kHz) WCDMA 1900MHz Tx: 1852.4 - 1907.6MHz (at intervals of 200kHz); Rx: 1932.4 - 1987.6MHz (at intervals of 200kHz) WCDMA 1700MHz Tx: 1712.4 - 1752.6MHz (at intervals of 200kHz); Rx: 2112.4 - 2152.6MHz (at intervals of 200kHz)
Maximum Output Power to Antenna	WCDMA 850: 22.46dBm WCDMA 1900: 23.65dBm WCDMA 1700: 23.64dBm
Type of Modulation	WCDMA: QPSK(Uplink) HSDPA:QPSK(Uplink) HSUPA:QPSK(Uplink)
Antenna Type	PIFA Antenna

1.2 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

System	Type of Modulation	Emission Designator	Frequency Tolerance (ppm)	Maximum ERP/EIRP(W)
WCDMA 850 RMC 12.2Kbps	QPSK	4M17F9W	0.0063	0.218
WCDMA 1900 RMC 12.2Kbps	QPSK	4M13F9W	0.0074	0.262
WCDMA 1700 RMC 12.2Kbps	QPSK	4M13F9W	0.0089	0.256

1.3 Test Standards and Results

1. 47 CFR Part 2, 22(H), 24(E), 27(L)
2. ANSI C63.26:2015
3. FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
4. RSS-GEN Issue 5
5. RSS-132 Issue 3
6. RSS-133 Issue 6
7. RSS-139 Issue 3

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Test detailed items/section required by FCC/IC rules and results are as below:

No.	Section		Description	Limit	Result
	FCC	IC			
1	2.1046	N/A	Conducted Output Power	Reporting Only	PASS
2	24.232(d) 27.50(d)	RSS-132,5.4 RSS-133,6.4 RSS-139,6.5	Peak to Average Radio	<13dBm	PASS
3	2.1049 22.917(b) 24.238(b) 27.53(g)	RSS-GEN,6.7 RSS-132, 5.5 RSS-133, 6.5 RSS-139, 3.1	Occupied Bandwidth	Reporting Only	PASS
4	2.1055 22.355 24.235 27.54	RSS-GEN, 6.11 RSS-132, 5.3 RSS-133, 6.3 RSS-139, 6.4	Frequency Stability	$\leq \pm 2.5\text{ppm}$	PASS
5	2.1051 22.917 24.238 27.53	RSS-GEN,6.13 RSS-132,5.5 RSS-133,6.5 RSS-139,6.6	Conducted Out of Band Emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS
6	22.913	RSS-132,5.4	Effective Radiated Power	<7Watts	PASS

	24.232	RSS-133,6.4	Equivalent Isotropic Radiated Power	<2Watts	PASS
	27.50d	RSS-139,6.5	Effective Radiated Power	<1Watts	PASS
7	2.1053	RSS-GEN,6.13	Radiated Spurious Emissions	< 43+10log10 (P[Watts])	PASS
	22.917	RSS-132,5.5			
	24.238	RSS-133,6.5			
	27.53	RSS-139,6.6			
8	/	RSS-GEN,6.8	Transmit antenna	Refer to RSS-GEN,6.8	PASS

1.4 Test Configuration of Equipment under Test

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for WCDMA Band V.
2. 30 MHz to 20000 MHz for WCDMA Band II.
3. 30 MHz to 18000 MHz for WCDMA Band IV.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDMA Band II	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDMA Band IV	RMC 12.2Kbps Link	RMC 12.2Kbps Link

Note: The maximum power levels are chosen to test as the worst case configuration as follows:

RMC 12.2Kbps mode for WCDMA band V,

RMC 12.2Kbps mode for WCDMA band II,

RMC 12.2Kbps mode for WCDMA band IV, only these modes were used for all tests.

1.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6B and 10dB attenuator.

Example:

Offset (dB) = RF cable loss(dB) + attenuator factor(dB).
= 7.5 + 10 = 17.5(dB)

1.6 Facilities and Accreditations

1.6.1 Test Facilities

CNAS-Lab Code: L1659

CCIC-SET is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until June 30th, 2021.

ISED Registration: 11185A-1

CAB identifier: CN0064

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until June 30th, 2021

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.6.2 Test Environment Conditions

Temperature (°C):	15 °C- 35 °C
Relative Humidity (%):	30% -60%
Atmospheric Pressure (kPa):	86KPa-106KPa

During the measurement, the environmental conditions were within the listed ranges:

2. TEST REQUIREMENTS

2.1 Conducted RF Output Power

2.1.1 Definition

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


2.1.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

2.1.4 Test Setup



2.1.5 Test Results of Conducted Output Power

WCDMA Model Test Verdict:

UMTS1900 (Band II)		Average Power (dBm)		
		9262CH	9400CH	9538cH
WCDMA	12.2kbps RMC	23.24	23.25	22.79
HSDPA	Subtest 1	23.22	23.21	22.65
	Subtest 2	23.22	23.18	22.57
	Subtest 3	23.18	23.06	22.42
	Subtest 4	23.09	23.20	22.39
	Subtest 5	23.15	23.20	22.68
HSUPA	Subtest 1	23.01	23.08	22.41
	Subtest 2	22.95	22.95	22.19
	Subtest 3	22.84	22.87	22.13
	Subtest 4	22.63	22.63	22.35
	Subtest 5	22.63	22.63	22.35
UMTS1700 (Band IV)		Average Power (dBm)		
		1313CH	1413CH	1513CH
WCDMA	12.2kbps RMC	23.38	22.63	23.58
HSDPA	Subtest 1	23.26	22.63	23.58
	Subtest 2	23.27	22.63	23.58
	Subtest 3	23.33	22.63	23.58
	Subtest 4	23.32	22.63	23.58
	Subtest 5	23.28	22.45	23.15
HSUPA	Subtest 1	23.31	22.35	23.01
	Subtest 2	23.33	22.10	22.85
	Subtest 3	23.19	22.03	22.74
	Subtest 4	23.15	22.00	22.64
	Subtest 5	23.21	22.00	22.64
UMTS850 (Band V)		Average Power (dBm)		
		4132CH	4183CH	4233CH
WCDMA	12.2kbps RMC	22.76	22.46	22.27
HSDPA	Subtest 1	22.41	22.33	22.16
	Subtest 2	22.35	22.15	22.10
	Subtest 3	22.15	22.21	22.02
	Subtest 4	22.06	22.17	21.95
	Subtest 5	22.35	22.32	22.12
HSUPA	Subtest 1	22.21	22.20	22.00
	Subtest 2	22.06	22.15	21.99
	Subtest 3	21.85	22.06	21.75
	Subtest 4	21.75	21.95	21.65
	Subtest 5	21.75	21.95	21.65

2.2 Peak to Average Radio

2.2.1 Definition and limit

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB. For IC rule: RSS-132,5.4、RSS-133, 6.4 and RSS-139,6.5: the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.,


2.2.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For WCDMA operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
5. Record the deviation as Peak to Average Ratio.

2.2.4 Test Setup



2.2.5 Test Results of Peak-to-Average Ratio

Band	Channel	Frequency (MHz)	Peak to Average radio	Limit	Verdict
			dB	dB	
WCDMA 1900MHz	9262	1852.4	2.94	13	PASS
	9400	1880.0	3.13		PASS
	9538	1907.6	3.03		PASS
WCDMA 1700MHz	1312	1712.4	2.73	13	PASS
	1412	1732.4	3.15		PASS
	1513	1752.6	2.75		PASS
WCDMA 850MHz	4132	826.4	2.68	13	PASS
	4183	836.6	2.94		PASS
	4233	846.6	3.07		PASS

2.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement

2.3.1 Definition

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For IC rule: The Occupied Bandwidth should meet the requirement of RSS-GEN,6.7、RSS-132, 5.5、RSS-133, 6.5、RSS-139, 3.1.


2.3.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03r01 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

2.3.4 Test Setup



2.3.5 Test Results of 99% Occupied Bandwidth and 26dB Bandwidth

Band	Channel	Frequency (MHz)	26dB bandwidth (KHz)	99% Occupied Bandwidth (KHz)	Refer to Plot
WCDMA 850MHz	4132	826.4	4731	4154.1	Plot A1
	4183	836.6	4727	4147.7	Plot A2
	4233	846.6	4731	4172.5	Plot A3
WCDMA 1900MHz	9262	1852.4	4707	4132.9	Plot B1
	9400	1880	4697	4129.4	Plot B2
	9538	1907.6	4693	4129.7	Plot B3
WCDMA 1700MHz	1312	1712.4	4700	4123.7	Plot C1
	1412	1732.4	4682	4128.6	Plot C2
	1513	1752.6	4695	4124.5	Plot C3

2.3.6 Test Results (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth




(Plot A1: WCDMA 850MHz Channel = 4132 Occupied bandwidth)



(Plot A2: WCDMA 850MHz Channel = 4183 Occupied bandwidth)



(Plot A3: WCDMA 850MHz Channel = 4233 Occupied bandwidth)



(Plot B1: WCDMA 1900MHz Channel = 9262 Occupied bandwidth)



(Plot B2: WCDMA 1900MHz Channel = 9400 Occupied bandwidth)



(Plot B3: WCDMA 1900MHz Channel = 9538 Occupied bandwidth)



(Plot C1: WCDMA 1700MHz Channel = 1312 bandwidth)



(Plot C2: WCDMA 1700 MHz Channel = 1412 bandwidth)



(Plot C3: WCDMA 1700 MHz Channel = 1513 bandwidth)

2.4 Frequency Stability

2.4.1 Requirement

For FCC/IC Rule: The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

2.4.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.


2.4.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to $-30\text{ }^{\circ}\text{C}$ and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in $10\text{ }^{\circ}\text{C}$ steps up to $50\text{ }^{\circ}\text{C}$. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

2.4.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25 \pm 5\text{ }^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

2.4.5 Test Setup



2.4.6 Test Results of Frequency Stability

WCDMA 850MHz Band

Band:	WCDMA Band V	Channel:	4183
Limit(ppm):	2.5	Frequency:	836.6MHz

Power (VDC)	Temperature (°C)	RMC 12.2Kbps	Result
		Deviation (ppm)	
12	-30	0.0036	PASS
	-20	0.0020	
	-10	0.0021	
	0	0.0043	
	+10	0.0063	
	+20	0.0038	
	+30	0.0054	
	+40	0.0042	
	+50	0.0033	
	9	0.0029	
36	+25	0.0057	

WCDMA 1900MHz Band

Band:	WCDMA Band II	Channel:	9400
Limit(ppm):	2.5	Frequency:	1880.0MHz

Power (VDC)	Temperature (°C)	RMC 12.2Kbps	Result
		Deviation (ppm)	
12	-30	0.0042	PASS
	-20	0.0029	
	-10	0.0032	
	0	0.0055	
	+10	0.0055	
	+20	0.0057	
	+30	0.0063	
	+40	0.0074	
	+50	0.0018	
	9	+25	
36	+25	0.0033	

WCDMA 1700MHz Band

Band:	WCDMA Band IV	Channel:	1412
Limit(ppm):	2.5	Frequency:	1732.4MHz

Power (VDC)	Temperature (°C)	RMC 12.2Kbps	Result
		Deviation (ppm)	
12	-30	0.0089	PASS
	-20	0.0087	
	-10	0.0074	
	0	0.0042	
	+10	0.0039	
	+20	0.0052	
	+30	0.0037	
	+40	0.0029	
	+50	0.0057	
	9	+25	
36	+25	0.0038	

Note 1. Normal Voltage = 12V. ; Low Voltage =9V.;Maximum Voltage =36 V

2.The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

2.5 Conducted Out of Band Emissions

2.5.1 Requirement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


2.5.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3 Test Procedures


1. The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$
8. For 9KHz to 30MHz: the amplitude of spurious emissions are attenuated by more than 20dB below the permissible value has no need to be reported.

2.5.4 Test Setup




2.5.5 Test Result (Plots) of Conducted Spurious Emission


Note: For 9 KHz to 30MHz: the amplitude of spurious emissions is attenuated by more than 20dB below the permissible value, so we not provide the test result here.




WCDMA850MHz Channel = 4132, 30MHz to 1GHz




WCDMA850MHz Channel = 4132, 1GHz to 9GHz




WCDMA850MHz Channel = 4183, 30MHz to 1GHz




WCDMA850MHz Channel = 4183, 1GHz to 9GHz




WCDMA850MHz Channel = 4233, 30MHz to 1GHz




WCDMA850MHz Channel = 4233, 1GHz to 9GHz




WCDMA1900MHz Channel = 9262, 30MHz to 1GHz




WCDMA1900MHz Channel = 9262, 1GHz to 20GHz




WCDMA1900MHz Channel = 9400, 30MHz to 1GHz




WCDMA1900MHz Channel = 9400, 1GHz to 20GHz




WCDMA1900MHz Channel = 9538, 30MHz to 1GHz




WCDMA1900MHz Channel = 9538 1GHz to 20GHz




WCDMA1700MHz Channel = 1312, 30MHz to 1GHz




WCDMA1700MHz Channel = 1312, 1GHz to 18GHz




WCDMA1700MHz Channel = 1414, 30MHz to 1GHz



WCDMA1700MHz Channel = 1414, 1GHz to 18GHz



WCDMA1700MHz Channel = 1513, 30MHz to 1GHz



WCDMA1700MHz Channel = 1513, 1GHz to 18GHz

2.6 Bandedge

2.6.1 Requirement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


2.6.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.6.3 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band GPRSs of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.

2.6.4 Test Setup



2.6.5 Test Result of Conducted Bandedge



(Plot A: WCDMA 850 Channel = 4132)



(Plot B: WCDMA 850 Channel = 4233)



(Plot C: WCDMA 1900 Channel = 9262)



(Plot D: WCDMA 1900 Channel = 9538)



(Plot E: WCDMA 1700 Channel = 1312)



(Plot F: WCDMA 1700 Channel = 1513)

2.7 Transmitter Radiated Power (EIRP/ERP)

2.7.1 Requirement

The substitution method, in ANSI C63.26:2015, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v03r01. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

2.7.2 Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GSM/GPRS) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a turntable 1.5 meters high in a fully anechoic chamber.
3. The EUT was placed 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst; UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01 v03r01.
5. The table was rotated 360 degrees to determine the position of the highest radiated power.
6. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
7. Taking the record of maximum ERP/EIRP.
8. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
9. The conducted power at the terminal of the dipole antenna is measured.

10. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.

$$11. \text{ERP/EIRP} = Ps + Et - Es + Gs = Ps + Rt - Rs + Gs$$

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.


$$Et = Rt + AF \quad Es = Rs + AF$$

AF (dB/m): Receive antenna factor

Rt : The highest received signal in spectrum analyzer for EUT.

Rs : The highest received signal in spectrum analyzer for substitution antenna.

2.7.4 Test Setup



2.7.5 Test Result of Transmitter Radiated Power

Test Notes:

1. This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, HSUPA capabilities. All configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2Kbps.
3. This unit was tested with its standard battery.
4. The worst case test configuration was found in the vertical positioning where the EUT is laying on its side. The data reported in the tables below were measured in this test setup.

Band	Channel	Frequency (MHz)	Antenna Pol (H/V)	Measured ERP dBm	Limit dBm	Verdict
WCDMA 850MHz	4132	826.4	H	23.35	38.5	PASS
			V	22.74		PASS
	4175	835	H	23.14		PASS
			V	22.62		PASS
	4233	846.6	H	23.39		PASS
			V	22.57		

Band	Channel	Frequency (MHz)	Antenna Pol (H/V)	Measured EIRP dBm	Limit dBm	Verdict
WCDMA 1900MHz	9262	1852.4	H	24.18	33	PASS
			V	23.54		PASS
	9400	1880	H	24.17		PASS
			V	23.46		PASS
	9538	1907.6	H	23.89		PASS
			V	23.24		

Band	Channel	Frequency (MHz)	Antenna Pol (H/V)	Measured EIRP dBm	Limit dBm	Verdict
WCDMA 1700MHz	1312	1712.4	H	24.09	30	PASS
			V	23.48		PASS
	1413	1732.4	H	23.57		PASS
			V	23.29		PASS
	1513	1752.6	H	23.84		PASS
			V	23.22		

2.8 Radiated Spurious Emissions

2.8.1 Requirement


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

2.8.2 Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.8.3 Test Setup


For radiated emissions from 9 kHz to 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.8.4 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8.
2. The EUT was placed on a rotatable wooden table 0.8/1.5 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
12. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13$ dBm.
13. This device employs GMSK technology with GSM and GPRS capabilities. All configurations were investigated and the worst case emissions were found in GSM mode.
14. This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, HSUPA capabilities. All configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2Kbps.
15. This unit was tested with its standard battery.
16. All Spurious Emission tests were performed in X, Y, Z axis direction and low, middle, high channel. And only the worst axis test condition was recorded in this test report.
17. The spectrum is measured from 9 KHz to the 10th harmonic of the fundamental frequency

of the transmitter using CISPR quasi peak detector below 1GHz. The worst case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.

18. For 9KHz to 30MHz: the amplitude of spurious emissions are attenuated by more than 20dB below the permissible value has no need to be reported.

2.8.5 Test Results of Radiated Spurious Emissions

Note: 1. (Absolute)Level=Reading Level + Factor

Worst-Case test data provide as below:

WCDMA 850 Middle Channel

30MHz~10GHz:

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	47.4775	-92.31	-72.49	-13.00	59.49	19.82	Horizontal
2	364.985	-102.00	-73.56	-13.00	60.56	28.44	Horizontal
3	667.927	-104.28	-69.56	-13.00	56.56	34.72	Horizontal
4	2322.66	-56.71	-53.77	-13.00	40.77	2.94	Horizontal
5	3244.12	-57.41	-48.24	-13.00	35.24	9.17	Horizontal
6	3722.36	-58.54	-48.15	-13.00	35.15	10.39	Horizontal

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	36.7968	-88.61	-68.02	-13.00	55.02	20.59	Vertical
2	63.9840	-92.40	-71.88	-13.00	58.88	20.52	Vertical
3	774.734	-104.08	-68.08	-13.00	55.08	36.00	Vertical
4	1829.41	-56.18	-56.86	-13.00	43.86	-0.68	Vertical
5	2679.83	-56.97	-51.69	-13.00	38.69	5.28	Vertical
6	3660.33	-57.55	-47.68	-13.00	34.68	9.87	Vertical

Worst-Case test data provide as below:

WCDMA 1900 Middle Channel

30MHz~20GHz:

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	34.8549	-90.71	-67.89	-13.00	54.89	22.82	Horizontal
2	660.160	-103.93	-69.11	-13.00	56.11	34.82	Horizontal
3	851.441	-104.17	-67.04	-13.00	54.04	37.13	Horizontal
4	3008.00	-58.33	-48.93	-13.00	35.93	9.40	Horizontal
5	3728.72	-58.75	-48.35	-13.00	35.35	10.40	Horizontal
6	5454.45	-59.60	-44.89	-13.00	31.89	14.71	Horizontal

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	63.9840	-91.42	-70.90	-13.00	57.90	20.52	Vertical
2	596.076	-103.22	-70.34	-13.00	57.34	32.88	Vertical
3	972.812	-103.38	-65.61	-13.00	52.61	37.77	Vertical
4	3948.94	-57.68	-48.29	-13.00	35.29	9.39	Vertical
5	5066.06	-58.56	-44.51	-13.00	31.51	14.05	Vertical
6	6243.24	-59.57	-41.75	-13.00	28.75	17.82	Vertical

Worst-Case test data provide as below:

WCDMA 1700 Middle Channel

30MHz~20GHz:

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	545.888	-87.64	-55.98	-36.00	19.98	31.66	Horizontal
2	660.063	-89.35	-54.53	-36.00	18.53	34.82	Horizontal
3	860.920	-88.07	-51.02	-36.00	15.02	37.05	Horizontal
4	1997.79	-56.75	-53.49	-30.00	23.49	3.26	Horizontal
5	3290.60	-57.16	-48.36	-30.00	18.36	8.80	Horizontal
6	3809.41	-58.80	-48.35	-30.00	18.35	10.45	Horizontal

Suspected List							
NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	37.4391	-85.02	-64.52	-36.00	28.52	20.50	Vertical
2	602.814	-87.98	-55.04	-36.00	19.04	32.94	Vertical
3	922.374	-87.89	-50.30	-36.00	14.30	37.59	Vertical
4	2224.24	-57.93	-54.05	-30.00	24.05	3.88	Vertical
5	3216.49	-59.03	-49.46	-30.00	19.46	9.57	Vertical
6	4977.69	-59.44	-45.32	-30.00	15.32	14.12	Vertical

2.9 Transmit antenna

2.9.1 Applicable Standard

According to RSS GEN issue5 6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

2.9.2 Antenna Information

Antenna Category: Internal Antenna

A internal Antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Operating frequency range	Ant. Type	Ant. Gain (Max)
1	DV601	WCDMA Band2: 1852.4-1907.6 MHz WCDMA Band4: 1712.4-1752.6 MHz WCDMA Band5: 826.4-846.4 MHz	PIFA	3.5dBi

2.9.3 Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.



3. LIST OF MEASURING EQUIPMENT

Description	Manufacturer	Model	Serial No.	Cal. Date	Due Date	Remark
EMI Test Receiver	R&S	ESU8	A0805559	2020.04.03	2021.04.02	Radiation
Loop Antenna	Schwarz beck	HFH2-Z2	100047	2019.04.26	2022.04.25	Radiation
Broadband antenna (30MHz~1GHz)	Schwarbeck	BBHA 9120 J	A190503537	2019.01.07	2021.01.06	Radiation
Broadband antenna (30MHz~1GHz)	R&S	HK116	A130701424	2018.01.19	2021.01.18	Radiation
Double ridge horn antenna (1GHz~18GHz)	R&S	HF906	100150	2019.04.27	2022.04.26	Radiation
Double ridge horn antenna (1GHz~18GHz)	R&S	HF906	100149	2019.04.17	2022.04.16	Radiation
Horn antenna (18GHz~26.5GHz)	AR	AT4510	A0804450	2020.06.19	2023.06.18	Radiation
Horn antenna (18GHz~26.5GHz)	AR	AT4003A	0329293	2020.09.17	2021.09.16	Radiation
Amplifier 30M~1GHz	MILMEGA	80RF1000-10004	A140101634	2020.03.24	2021.03.23	Radiation
Amplifier 1G~18GHz	MILMEGA	AS0104R-800/400	A160302517	2020.03.24	2021.03.23	Radiation
Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2020.05.18	2021.05.17	Conducted
Test Receiver	R&S	ESIB26	A0304218	2020.04.29	2021.04.28	Conducted
Temperature chamber	XSM	DNF810C	A0501375	2020.05.26	2021.05.25	Conducted
Wideband Radio Communication tester	R&S	CMW500	A130101034	2019.07.30	2021.07.29	Conducted
Power Supply	R&S	WYJ-60100	A141102031	2020.01.16	2023.01.15	Conducted
EMI Test Receiver	R&S	ESU8	A0805559	2020.04.03	2021.04.02	Radiation

4. UNCERTAINTY OF EVALUATION

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150KHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_{c(y)}$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_{c(y)}$)	2.4dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_{c(y)}$)	2.8dB
---	-------

** END OF REPORT **