

FCC Part 22H & 24E & 27 Measurement and Test Report

For

DBJ Technologies (Zhuhai) Co., Ltd.

First Floor, Block 1, Manufacture Center, No. 1 Software Road, Zhuhai,

Guangdong, China

FCC ID: 2AEIXZJ700

FCC Rules: FCC Part 22H, FCC Part 24E, FCC Part 27

Product Description: GPS Tracker

Tested Model: ZJ700

Report No.: STRD1804035E-1

Sample Receipt Date: 2018-04-08

Tested Date: 2018-04-09 to 2018-05-03

Issued Date: 2018-05-04

Tested By: Mike Shi / Engineer

Mike Shi

Reviewed By: Silin Chen / EMC Manager

Silin Chen

Approved & Authorized By: Jandy So / PSQ Manager

Jandy So

Prepared By:

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	6
1.7 TEST EQUIPMENT LIST AND DETAILS.....	7
2. SUMMARY OF TEST RESULTS.....	8
3. RF EXPOSURE.....	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. RF OUTPUT POWER.....	10
4.1 STANDARD APPLICABLE.....	10
4.2 TEST PROCEDURE.....	10
4.3 ENVIRONMENTAL CONDITIONS.....	10
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
5. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER.....	17
5.1 STANDARD APPLICABLE.....	17
5.2 TEST PROCEDURE.....	17
5.3 ENVIRONMENTAL CONDITIONS.....	17
5.4 SUMMARY OF TEST RESULTS.....	18
6. EMISSION BANDWIDTH.....	19
6.1 STANDARD APPLICABLE.....	19
6.2 TEST PROCEDURE.....	19
6.3 ENVIRONMENTAL CONDITIONS.....	19
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	20
7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL.....	36
7.1 STANDARD APPLICABLE.....	36
7.2 TEST PROCEDURE.....	36
7.3 ENVIRONMENTAL CONDITIONS.....	36
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	37
8. SPURIOUS RADIATED EMISSIONS.....	82
8.1 STANDARD APPLICABLE.....	82
8.2 TEST PROCEDURE.....	82
8.3 ENVIRONMENTAL CONDITIONS.....	82
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	82
<i>For Band 4 Mode.....</i>	90
9. FREQUENCY STABILITY.....	91
9.1 STANDARD APPLICABLE.....	91
9.2 TEST PROCEDURE.....	91
9.3 ENVIRONMENTAL CONDITIONS.....	91
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	92

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: DBJ Technologies (Zhuhai) Co., Ltd.
Address of applicant: First Floor, Block 1, Manufacture Center, No. 1 Software Road, Zhuhai, Guangdong, China

Manufacturer: DBJ Technologies (Zhuhai) Co., Ltd.
Address of manufacturer: First Floor, Block 1, Manufacture Center, No. 1 Software Road, Zhuhai, Guangdong, China

General Description of EUT:	
Product Name:	GPS Tracker
Model No.:	ZJ700
Rated Voltage:	Power Port:DC6-40V Battery:DC3.7V
Battery:	750mAh
Software Version:	TG107105
Hardware Version:	ZJ700_T_REV0_CR01
Device Category:	Mobile Device
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT:	
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 4, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 4: 1710-1755 MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 4: 2110-2155 MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 23.25dBm, \ WCDMA Band 4: 23.38 dBm WCDMA Band 5: 24.35dBm
Type of Emission:	WCDMA Band 2: 4M17F9W WCDMA Band 4: 4M17F9W WCDMA Band 5: 4M14F9W
Type of Modulation:	QPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: 1.11dBi, WCDMA Band 4: 1.08dBi WCDMA Band 5: -0.21dBi

1.2 Test Standards

The following report is prepared on behalf of the DBJ Technologies (Zhuhai) Co., Ltd.. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 971168 D01 Power Meas License Digital Systems v03 shall be performed also.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	WCDMA Band 5	Low, Middle, High Channels
TM2	HSDPA Band 5	Low, Middle, High Channels
TM3	HSUPA Band 5	Low, Middle, High Channels
TM4	WCDMA Band 4	Low, Middle, High Channels
TM5	HSDPA Band 4	Low, Middle, High Channels
TM6	HSUPA Band 4	Low, Middle, High Channels
TM7	WCDMA Band 2	Low, Middle, High Channels
TM8	HSDPA Band 2	Low, Middle, High Channels
TM9	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 4	WCDMA/HSDPA/HSUPA	1712.4MHz	1312
		1732.6MHz	1413
		1752.6MHz	1513
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538

Note: the transmitter has been tested on the communications mode of WCDMA, HSDPA, HSUPA compliance test and record the worst case.

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
DC Cable	1.0	Unshielded	Without Core

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Frequency Stability	Conducted	2.3%
Transmitter Spurious Emissions	Conducted	$\pm 0.42\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2017-06-12	2018-06-11
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2017-06-12	2018-06-11
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-12	2018-06-11
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2017-06-12	2018-06-11
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2017-06-12	2018-06-11
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2017-06-12	2018-06-11
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2017-06-12	2018-06-11
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2017-06-12	2018-06-11
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-12	2018-06-11
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-12	2018-06-11
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2017-06-12	2018-06-11
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2017-06-12	2018-06-11
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2017-08-15	2018-08-14
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2017-08-15	2018-08-14
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2017-06-12	2018-06-11
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1091	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c) , §27.50	RF Output Power	Compliant
§ 24.51, § 27.50	Peak-to-average Ratio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 24.238 (b) , § 27.53	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a) , § 27.53	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a) , § 27.53	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a) , § 27.53	Out of Band Emissions	Compliant
§ 22.355, § 24.235, § 27.54	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1091, the mobile transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF exposure report.

4. RF Output Power

4.1 Standard Applicable


According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

- 1.The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.4 Summary of Test Results/Plots

Max. Radiated Power

ERP For WCDMA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	23.11	1.5	0	H	1.5	0	21.61	38.45
826.4	21.07	1.5	0	V	1.5	0	19.57	38.45
Middle Channel								
836.6	23.33	1.5	0	H	1.5	0	21.83	38.45
836.6	21.18	1.5	0	V	1.5	0	19.68	38.45
High Channel								
846.6	23.12	1.5	0	H	1.5	0	21.62	38.45
846.6	21.26	1.5	0	V	1.5	0	19.76	38.45

ERP For HSDPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	22.31	1.5	0	H	1.5	0	20.81	38.45
826.4	20.46	1.5	0	V	1.5	0	18.96	38.45
Middle Channel								
836.6	22.29	1.5	0	H	1.5	0	20.79	38.45
836.6	20.51	1.5	0	V	1.5	0	19.01	38.45
High Channel								
846.6	22.27	1.5	0	H	1.5	0	20.77	38.45
846.6	20.81	1.5	0	V	1.5	0	19.31	38.45

ERP For HSUPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	22.05	1.5	0	H	1.5	0	20.55	38.45
826.4	20.32	1.5	0	V	1.5	0	18.82	38.45
Middle Channel								
836.6	21.92	1.5	0	H	1.5	0	20.42	38.45
836.6	20.40	1.5	0	V	1.5	0	18.90	38.45
High Channel								
846.6	22.12	1.5	0	H	1.5	0	20.62	38.45
846.6	20.24	1.5	0	V	1.5	0	18.74	38.45

EIRP For WCDMA Mode Band 4

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 27 Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
1712.4	13.97	1.5	0	H	1.8	7.7	19.87	30.00
1712.4	14.80	1.5	0	V	1.8	7.7	20.70	30.00
Middle Channel								
1732.6	14.62	1.5	0	H	1.8	7.7	20.52	30.00
1732.6	15.88	1.5	0	V	1.8	7.7	21.78	30.00
High Channel								
1752.6	14.03	1.5	0	H	1.8	7.7	19.93	30.00
1752.6	15.63	1.5	0	V	1.8	7.7	21.53	30.00

EIRP For HSDPA Mode Band 4

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 27 Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
1712.4	13.34	1.5	0	H	1.8	7.7	19.24	30.00
1712.4	15.96	1.5	0	V	1.8	7.7	21.86	30.00
Middle Channel								
1732.6	14.29	1.5	0	H	1.8	7.7	20.19	30.00
1732.6	15.28	1.5	0	V	1.8	7.7	21.18	30.00
High Channel								
1752.6	14.47	1.5	0	H	1.8	7.7	20.37	30.00
1752.6	15.84	1.5	0	V	1.8	7.7	21.74	30.00

EIRP For HSUPA Mode Band 4

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 27 Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
1712.4	13.18	1.5	0	H	1.8	7.7	19.08	30.00
1712.4	14.13	1.5	0	V	1.8	7.7	20.03	30.00
Middle Channel								
1732.6	14.93	1.5	0	H	1.8	7.7	20.83	30.00
1732.6	15.79	1.5	0	V	1.8	7.7	21.69	30.00
High Channel								
1752.6	14.51	1.5	0	H	1.8	7.7	20.41	30.00
1752.6	15.83	1.5	0	V	1.8	7.7	21.73	30.00

EIRP For WCDMA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	14.70	1.5	0	H	1.9	7.7	20.50	33
1852.4	15.73	1.5	0	V	1.9	7.7	21.53	33
Middle Channel								
1880.0	16.20	1.5	0	H	1.9	7.7	22.00	33
1880.0	15.19	1.5	0	V	1.9	7.7	20.99	33
High Channel								
1907.6	15.76	1.5	0	H	1.9	7.7	21.56	33
1907.6	14.80	1.5	0	V	1.9	7.7	20.60	33

EIRP For HSDPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	13.84	1.5	0	H	1.9	7.7	19.64	33
1852.4	12.23	1.5	0	V	1.9	7.7	18.03	33
Middle Channel								
1880.0	13.74	1.5	0	H	1.9	7.7	19.54	33
1880.0	13.98	1.5	0	V	1.9	7.7	19.78	33
High Channel								
1907.6	12.81	1.5	0	H	1.9	7.7	18.61	33
1907.6	13.21	1.5	0	V	1.9	7.7	19.01	33

EIRP For HSUPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
1852.4	13.03	1.5	0	H	1.9	7.7	18.83	33
1852.4	12.08	1.5	0	V	1.9	7.7	17.88	33
Middle Channel								
1880.0	13.36	1.5	0	H	1.9	7.7	19.16	33
1880.0	12.53	1.5	0	V	1.9	7.7	18.33	33
High Channel								
1907.6	12.99	1.5	0	H	1.9	7.7	18.79	33
1907.6	13.31	1.5	0	V	1.9	7.7	19.11	33

Note: Result = Substitute - Cable loss + Antenna Gain

Max. Conducted Output Power

For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	24.12	38.45
	Middle Channel	836.6	24.28	38.45
	High Channel	846.6	24.35	38.45
HSDPA	Low Channel	826.4	23.32	38.45
	Middle Channel	836.6	23.33	38.45
	High Channel	846.6	23.34	38.45
HSUPA	Low Channel	826.4	23.53	38.45
	Middle Channel	836.6	23.47	38.45
	High Channel	846.6	23.40	38.45

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	23.25	33.00
	Middle Channel	1880.0	22.53	33.00
	High Channel	1907.6	23.06	33.00
HSDPA	Low Channel	1852.4	21.73	33.00
	Middle Channel	1880.0	21.15	33.00
	High Channel	1907.6	21.75	33.00
HSUPA	Low Channel	1852.4	21.56	33.00
	Middle Channel	1880.0	21.41	33.00
	High Channel	1907.6	21.52	33.00

For WCDMA Band 4

Test Mode	Channel	Frequency (MHz)	Output Power (dBm)	FCC Part 27.50 Limit (dBm)
WCDMA	Low Channel	1712.4	23.29	30.0
	Middle Channel	1732.6	23.38	30.0
	High Channel	1752.6	23.09	30.0
HSUPA	Low Channel	1712.4	22.25	30.0
	Middle Channel	1732.6	22.18	30.0
	High Channel	1752.6	22.18	30.0
HSDPA	Low Channel	1712.4	21.94	30.0
	Middle Channel	1732.6	21.81	30.0
	High Channel	1752.6	21.57	30.0

5. Peak-to-average Ratio (PAR) of Transmitter

5.1 Standard Applicable


According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded. Record the maximum PAPR level associated with a probability of 0.1%.

Test Configuration for the emission bandwidth testing:



5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results

Only the worst case was selected to record

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
WCDMA	9400	1880	6.85	13
HSDPA	9400	1880	6.52	13
HSUPA	9400	1880	5.69	13

For WCDMA Band 4

Test Mode	Channel	Frequency (MHz)	PAR (dB)	Limit (dB)
WCDMA	1413	1732.6	7.35	13
HSDPA	1413	1732.6	4.06	13
HSUPA	1413	1732.6	5.44	13

6. Emission Bandwidth

6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

For Band 5

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.1572	4.720
	4183	836.6	4.1335	4.716
	4233	846.6	4.1251	4.713
HSDPA	4132	826.4	4.1704	4.729
	4183	836.6	4.1551	4.713
	4233	846.6	4.1297	4.713
HSUPA	4132	826.4	4.1624	4.721
	4183	836.6	4.1513	4.739
	4233	846.6	4.1404	4.707


For Band 2

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9262	1852.4	4.2124	4.860
	9400	1880.0	4.1238	4.706
	9538	1907.6	4.1533	4.717
HSDPA	9262	1852.4	4.1798	4.777
	9400	1880.0	4.1336	4.716
	9538	1907.6	4.1447	4.702
HSUPA	9262	1852.4	4.1841	4.814
	9400	1880.0	4.1382	4.724
	9538	1907.6	4.1493	4.714


For Band 4

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	1312	1712.4	4.1434	4.721
	1412	1732.6	4.1470	4.729
	1513	1752.6	4.1479	4.741
HSDPA	1312	1712.4	4.1371	4.722
	1412	1732.6	4.1387	4.729
	1513	1752.6	4.1295	4.719
HSUPA	1312	1712.4	4.1386	4.713
	1412	1732.6	4.1403	4.718
	1513	1752.6	4.1389	4.706


For Band V
WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel




For Band II
WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel




For Band IV
WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:



7.3 Environmental Conditions



Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.4 Summary of Test Results/Plots



Please refer to the following test plots For Cellular Band

For Band V



WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel





WCDMA Low Band Spurious Emission





WCDMA High Band Spurious Emission





HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel





HSDPA Low Band Spurious Emission





HSDPA High Band Spurious Emission





HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel



HSUPA Low Band Spurious Emission






HSUPA High Band Spurious Emission




For Band II



WCDMA Low Channel








WCDMA Middle Channel






WCDMA High Channel







WCDMA Low Band Spurious Emission





WCDMA High Band Spurious Emission






HSDPA Low Channel








HSDPA Middle Channel






HSDPA High Channel








HSDPA Low Band Spurious Emission




HSDPA High Band Spurious Emission






HSUPA Low Channel








HSUPA Middle Channel






HSUPA High Channel






HSUPA Low Band Spurious Emission






HSUPA High Band Spurious Emission





For Band IV


WCDMA Low Channel








WCDMA Middle Channel






WCDMA High Channel








WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission






HSDPA Low Channel








HSDPA Middle Channel






HSDPA High Channel







HSDPA Low Band Spurious Emission





HSDPA High Band Spurious Emission






HSUPA Low Channel








HSUPA Middle Channel






HSUPA High Channel






HSUPA Low Band Spurious Emission



HSUPA High Band Spurious Emission



8. Spurious Radiated Emissions

8.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

8.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


8.4 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


For band 5 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	34.7602	-68.40	-5.56	-73.96	-13.00	-60.96	ERP
2	63.3132	-69.04	-5.41	-74.45	-13.00	-61.45	ERP
3	208.5803	-70.34	-4.53	-74.87	-13.00	-61.87	ERP
4	382.5879	-68.98	3.08	-65.90	-13.00	-52.90	ERP
5	638.3686	-69.44	10.74	-58.70	-13.00	-45.70	ERP
6	785.0935	-68.41	9.85	-58.56	-13.00	-45.56	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	62.2128	-67.89	-5.17	-73.06	-13.00	-60.06	ERP
2	96.0986	-68.87	-5.34	-74.21	-13.00	-61.21	ERP
3	181.2834	-67.69	-7.22	-74.91	-13.00	-61.91	ERP
4	279.0436	-70.27	1.37	-68.90	-13.00	-55.90	ERP
5	413.2706	-69.62	3.64	-65.98	-13.00	-52.98	ERP
6	763.3757	-69.63	11.02	-58.61	-13.00	-45.61	ERP


For band 2 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	33.0950	-68.17	-5.84	-74.01	-13.00	-61.01	ERP
2	56.7917	-69.54	-4.73	-74.27	-13.00	-61.27	ERP
3	99.1797	-69.79	-4.88	-74.67	-13.00	-61.67	ERP
4	302.4812	-68.35	2.24	-66.11	-13.00	-53.11	ERP
5	768.7482	-68.68	10.70	-57.98	-13.00	-44.98	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	60.4919	-68.38	-4.81	-73.19	-13.00	-60.19	ERP
2	121.1231	-69.24	-4.97	-74.21	-13.00	-61.21	ERP
3	300.3673	-69.16	2.21	-66.95	-13.00	-53.95	ERP
4	614.2142	-69.60	10.53	-59.07	-13.00	-46.07	ERP
5	830.4002	-69.32	9.19	-60.13	-13.00	-47.13	ERP


For band 4 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	56.3948	-69.01	-4.73	-73.74	-13.00	-60.74	ERP
2	95.7622	-66.38	-5.39	-71.77	-13.00	-58.77	ERP
3	144.8418	-70.03	-6.72	-76.75	-13.00	-63.75	ERP
4	355.4273	-69.57	2.71	-66.86	-13.00	-53.86	ERP
5	631.6884	-69.34	10.51	-58.83	-13.00	-45.83	ERP
6	747.4826	-69.31	11.67	-57.64	-13.00	-44.64	ERP

Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	62.6507	-68.58	-5.27	-73.85	-13.00	-60.85	ERP
2	118.6014	-69.81	-4.87	-74.68	-13.00	-61.68	ERP
3	309.9977	-70.12	2.34	-67.78	-13.00	-54.78	ERP
4	434.0651	-70.02	4.06	-65.96	-13.00	-52.96	ERP
5	731.9203	-70.75	11.45	-59.30	-13.00	-46.30	ERP

Note: $Margin = (Reading + Correct) - Limit$

Spurious Emissions Above 1GHz
For Band 5 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (826.4MHz)						
1652.8	-31.84	4.94	-26.90	-13.00	-13.90	H
2479.2	-37.60	8.46	-29.14	-13.00	-16.14	H
1652.8	-36.94	4.94	-32.00	-13.00	-19.00	V
2479.2	-38.71	8.46	-30.25	-13.00	-17.25	V
Middle Channel (836.6MHz)						
1672.8	-36.81	5.11	-31.70	-13.00	-18.70	H
2509.2	-41.37	8.54	-32.83	-13.00	-19.83	H
1672.8	-31.93	5.11	-26.82	-13.00	-13.82	V
2509.2	-41.62	8.54	-33.08	-13.00	-20.08	V
High Channel (846.6MHz)						
1693.2	-41.43	5.25	-36.18	-13.00	-23.18	H
2539.8	-35.30	8.57	-26.73	-13.00	-13.73	H
1693.2	-37.83	5.25	-32.58	-13.00	-19.58	V
2539.8	-35.94	8.57	-27.37	-13.00	-14.37	V

For Band 2 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1852.4MHz)						
3704.8	-35.63	14.69	-20.94	-13.00	-7.94	H
5557.2	-37.44	10.17	-27.27	-13.00	-14.27	H
3704.8	-37.20	14.69	-22.51	-13.00	-9.51	V
5557.2	-40.29	14.69	-25.60	-13.00	-12.60	V
Middle Channel (1880MHz)						
3760.8	-38.56	10.08	-28.48	-13.00	-15.48	H
5640.0	-42.68	13.53	-29.15	-13.00	-16.15	H
3760.8	-37.41	10.08	-27.33	-13.00	-14.33	V
5640.0	-41.11	13.53	-27.58	-13.00	-14.58	V
High Channel (1907.6MHz)						
3815.2	-39.33	10.59	-28.74	-13.00	-15.74	H
5722.8	-40.84	15.03	-25.81	-13.00	-12.81	H
3815.2	-32.42	10.59	-21.83	-13.00	-8.83	V
5722.8	-43.71	15.03	-28.68	-13.00	-15.68	H

For Band 4 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1712.4MHz)						
3424.8	-48.05	9.87	-38.18	-13.00	-25.18	H
5137.2	-54.24	13.02	-41.22	-13.00	-28.22	H
3424.8	-50.64	9.87	-40.77	-13.00	-27.77	V
5137.2	-49.78	13.02	-36.76	-13.00	-23.76	V
Middle Channel (1732.6MHz)						
3465.2	-50.96	5.11	-45.85	-13.00	-32.85	H
5197.8	-51.08	8.54	-42.54	-13.00	-29.54	H
3465.2	-51.66	5.11	-46.55	-13.00	-33.55	V
5197.8	-53.40	8.54	-44.86	-13.00	-31.86	V
High Channel (1752.6MHz)						
3505.2	-54.81	10.03	-44.78	-13.00	-31.78	H
5257.8	-54.87	14.03	-40.84	-13.00	-27.84	H
3505.2	-54.18	10.03	-44.15	-13.00	-31.15	V
5257.8	-52.42	14.03	-38.39	-13.00	-25.39	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	DC 3.5-4.2V declared by manufacturer
-30°C to +50°C	Normal

9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

For WCDMA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	60	0.0717
40	3.7	52	0.0622
30	3.7	43	0.0514
20	3.7	35	0.0418
10	3.7	32	0.0383
0	3.7	25	0.0299
-10	3.7	30	0.0359
-20	3.7	34	0.0406
-30	3.7	38	0.0454

For WCDMA Band 4 Mode

Reference Frequency(Middle Channel): 1732.6MHz MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	69	0.0398
40	3.7	63	0.0364
30	3.7	54	0.0312
20	3.7	48	0.0277
10	3.7	45	0.0260
0	3.7	37	0.0214
-10	3.7	42	0.0242
-20	3.7	48	0.0277
-30	3.7	55	0.0317

For WCDMA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	62	0.0330
40	3.7	55	0.0293
30	3.7	45	0.0239
20	3.7	37	0.0197
10	3.7	32	0.0170
0	3.7	25	0.0133
-10	3.7	29	0.0154
-20	3.7	36	0.0191
-30	3.7	42	0.0223

For HSDPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	69	0.0825
40	3.7	54	0.0645
30	3.7	43	0.0514
20	3.7	38	0.0454
10	3.7	31	0.0371
0	3.7	26	0.0311
-10	3.7	32	0.0383
-20	3.7	35	0.0418
-30	3.7	43	0.0514

For HSDPA Band 4 Mode

Reference Frequency(Middle Channel): 1732.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	59	0.0341
40	3.8	54	0.0312
30	3.8	43	0.0248
20	3.8	37	0.0214
10	3.8	31	0.0179
0	3.8	25	0.0144
-10	3.8	32	0.0185
-20	3.8	35	0.0202
-30	3.8	42	0.0242

For HSDPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	60	0.0319
40	3.7	52	0.0277
30	3.7	46	0.0245
20	3.7	38	0.0202
10	3.7	35	0.0186
0	3.7	31	0.0165
-10	3.7	38	0.0202
-20	3.7	45	0.0239
-30	3.7	52	0.0277

For HSUPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	70	0.0837
40	3.7	58	0.0693
30	3.7	47	0.0562
20	3.7	43	0.0514
10	3.7	37	0.0442
0	3.7	32	0.0383
-10	3.7	36	0.0430
-20	3.7	42	0.0502
-30	3.7	48	0.0574

For HSUPA Band 4 Mode

Reference Frequency(Middle Channel): 1732.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	55	0.0317
40	3.8	50	0.0289
30	3.8	38	0.0219
20	3.8	32	0.0185
10	3.8	26	0.0150
0	3.8	22	0.0127
-10	3.8	28	0.0162
-20	3.8	32	0.0185
-30	3.8	38	0.0219

For HSUPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	68	0.0362
40	3.7	58	0.0309
30	3.7	51	0.0271
20	3.7	43	0.0229
10	3.7	35	0.0186
0	3.7	29	0.0154
-10	3.7	37	0.0197
-20	3.7	44	0.0234
-30	3.7	50	0.0266

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): WCDMA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	35	0.0418
	3.7	35	0.0418
	4.2	41	0.0490
Reference Frequency(Middle Channel): WCDMA 1732.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	49	0.0283
	3.7	48	0.0277
	4.2	42	0.0242
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	39	0.0207
	3.7	37	0.0197
	4.2	40	0.0213
Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	38	0.0454
	3.7	38	0.0454
	4.2	33	0.0394

Reference Frequency(Middle Channel): HSDPA 1732.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	38	0.0219
	3.7	37	0.0214
	4.2	33	0.0190
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	38	0.0202
	3.7	38	0.0202
	4.2	37	0.0197
Reference Frequency(Middle Channel): HSUPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	37	0.0442
	3.7	43	0.0514
	4.2	45	0.0538
Reference Frequency(Middle Channel): HSUPA 1732.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	37	0.0214
	3.7	32	0.0185
	4.2	35	0.0202
Reference Frequency(Middle Channel): HSUPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.5	39	0.0207
	3.7	43	0.0229
	4.2	38	0.0202

***** END OF REPORT *****