



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
 Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
 Fax: +86 (0) 755 2671 0594
 Email: ee.shenzhen@sgs.com

Report No.: SZEM170600640802

Page: 1 of 7

RF Exposure Evaluation Report

Application No.: SZEM1706006408CR
Applicant: Sunwave Communications Co., Ltd
Manufacturer: Sunwave Communications Co., Ltd
Factory: Sunwave Communications Co., Ltd
Product Name: Remote Unit
Product Description: The RU conducts digital-analog conversion and power amplification of the input signals.
Model No.(EUT): iDAS-R211
Trade Mark: CROSSFIRE,SUNWAVE
FCC ID: 2AEJ4R2110505
Standards: 47 CFR Part 1.1307 (2016)
 47 CFR Part 1.1310 (2016)
Date of Receipt: 2017-05-15
Date of Test: 2017-05-15 to 2017-06-25
Date of Issue: 2017-06-26

| | |
|----------------------|--------------|
| Test Result : | PASS* |
|----------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
 EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2017-06-25 | | Original |
| | | | | |
| | | | | |

| | | | | |
|--------------------------|--|-----------------------------|--|------------|
| Authorized for issue by: | | | | |
| Tested By | | <i>Edison Li</i> | | 2017-06-25 |
| | | Edison Li /Project Engineer | | Date |
| Checked By | | <i>Eric Fu</i> | | 2017-06-26 |
| | | Eric Fu /Reviewer | | Date |



3 Contents

| | Page |
|---|------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION | 2 |
| 3 CONTENTS..... | 3 |
| 4 GENERAL INFORMATION..... | 4 |
| 4.1 CLIENT INFORMATION..... | 4 |
| 4.2 GENERAL DESCRIPTION OF EUT | 4 |
| 4.3 TEST LOCATION | 4 |
| 4.4 TEST FACILITY | 5 |
| 4.5 DEVIATION FROM STANDARDS..... | 5 |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS | 5 |
| 4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 5 |
| 5 RF EXPOSURE EVALUATION..... | 6 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5.1.1 Limits | 6 |
| 5.1.2 Test Procedure..... | 6 |
| 4.1.3 EUT RF EXPOSURE EVALUATION..... | 7 |



4 General Information

4.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Sunwave Communications Co., Ltd. |
| Address of Applicant: | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |
| Manufacturer: | Sunwave Communications Co., Ltd. |
| Address of Manufacturer: | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |
| Factory: | Sunwave Communications Co., Ltd. |
| Address of Factory: | Sunwave Building 581 Huoju Avenue, Binjiang District, Hangzhou, P.R.China Zip: 310053 |

4.2 General Description of EUT

| | |
|---------------------|--|
| Product Name: | Remote Unit |
| Model No.: | iDAS-R211 |
| Trade Mark: | CROSSFIRE,SUNWAVE |
| Sample Type: | Fixed production |
| Antenna Gain: | 12.5dBi |
| Power Supply: | AC120V 60Hz |
| Optical Fiber: | 100cm (unshielded) |
| DC Cable: | 120cm (unshielded) |
| Type of Modulation: | LTE, CDMA, WCDMA |
| Frequency Band: | Downlink 869MHz to 894MHz include the Modulation: LTE, CDMA, WCDMA |

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.



4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout * G) / (4 * Pi * R^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm² . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 12.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 17.8 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

| LTE | | 869~894MHz | | | | |
|-----------------|----------------------------|--------------------------------|-------------------------|------------------------|-------------------------------------|------------------------------------|
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (m) |
| 871.5 | 12.5 | 17.8 | 44 | 25118.86 | 2.91 | 3.50 |
| 881.5 | 12.5 | 17.8 | 44 | 25118.86 | 2.94 | 3.48 |
| 891.5 | 12.5 | 17.8 | 44 | 25118.86 | 2.97 | 3.46 |
| WCDMA | | 869~894MHz | | | | |
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (m) |
| 871.4 | 12.5 | 17.8 | 44 | 25118.86 | 2.90 | 3.50 |
| 881.5 | 12.5 | 17.8 | 44 | 25118.86 | 2.94 | 3.48 |
| 891.6 | 12.5 | 17.8 | 44 | 25118.86 | 2.97 | 3.46 |
| CDMA | | 869~894MHz | | | | |
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (m) |
| 860.25 | 12.5 | 17.8 | 44 | 25118.86 | 2.87 | 3.52 |
| 881.5 | 12.5 | 17.8 | 44 | 25118.86 | 2.94 | 3.48 |
| 892.75 | 12.5 | 17.8 | 44 | 25118.86 | 2.98 | 3.46 |

25118.86W is the turn-up tolerance procedure power.

Conclusion:

So the recommend use distance away from EUT external antenna is larger than 3.52 meter.