

SAR TEST REPORT

For

GSM GLOBE.COM INC

2G mobile phone

Test Model: S1 Barcelona

List Model No.: S1 Barcelona plus, S1 Barcelona pro

Prepared for : GSM GLOBE.COM INC
Address : 134 N.E 1 Street, Miami, Florida, United States 33132

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an
Avenue, Bao'an District, Shenzhen, Guangdong, China

Tel : (86)755-82591330
Fax : (86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 16, 2018
Number of tested samples : 1
Serial number : Prototype
Date of Test : November 16, 2018~ November 23, 2018
Date of Report : December 18, 2018

SAR TEST REPORT**Report Reference No. : LCS181108063AEB**

Date Of Issue : December 18, 2018

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure : Full application of Harmonised standards
Partial application of Harmonised standards
Other standard testing method **Applicant's Name..... : GSM GLOBE.COM INC**

Address : 134 N.E 1 Street, Miami, Florida, United States 33132

Test Specification:Standard : IEEE Std C95.1, 2005&IEEE Std 1528™-2013&& FCC Part
2.1093

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2014-09

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. : 2G mobile phone

Trade Mark : GOL


Model/Type Reference : S1 Barcelona

Operation Frequency..... : GSM 850MHz/PCS1900MHz, Bluetooth2.1+EDR


Modulation Type..... : GSM(GMSK), Bluetooth(GFSK,8DPSK, $\pi/4$ -DQPSK)

Ratings : DC 3.7V by Rechargeable Li-ion Battery(600mAh)


Recharged by DC 5V/500mA AC/DC ADAPTOR

Result : Positive**Compiled by:**

Vera Deng/ File administrators

Supervised by:

Calvin Weng/ Technique principal

Approved by:

Gavin Liang/ Manager

SAR -- TEST REPORT**Test Report No. : LCS181108063AEB**December 18, 2018
Date of issue

Type / Model..... : S1 Barcelona

EUT..... : 2G mobile phone

Applicant..... : GSM GLOBE.COM INC

Address..... : 134 N.E 1 Street, Miami, Florida, United States 33132

Telephone..... : /

Fax..... : /

Manufacturer..... : Shenzhen Goldstone Science and Technology Co., LtdAddress..... : RM 03, 10/F NEW HENNESSY TOWER 263 HENNESSY
RD WANCHAI HK

Telephone..... : /

Fax..... : /

Factory..... : Shenzhen Goldstone Science and Technology Co., LtdAddress..... : RM 03, 10/F NEW HENNESSY TOWER 263 HENNESSY
RD WANCHAI HK

Telephone..... : /

Fax..... : /

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|-------------------|---------------|-------------|
| 000 | December 18, 2018 | Initial Issue | Gavin Liang |
| | | | |
| | | | |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. TEST STANDARDS AND TEST DESCRIPTION..... | 6 |
| 1.1. TEST STANDARDS | 6 |
| 1.2. TEST DESCRIPTION | 6 |
| 1.3. GENERAL REMARKS | 6 |
| 1.4. PRODUCT DESCRIPTION | 6 |
| 1.5. STATEMENT OF COMPLIANCE | 8 |
| 2. TEST ENVIRONMENT | 9 |
| 2.1. TEST FACILITY | 9 |
| 2.2. ENVIRONMENTAL CONDITIONS | 9 |
| 2.3. SAR LIMITS | 9 |
| 2.4. EQUIPMENTS USED DURING THE TEST | 10 |
| 3. SAR MEASUREMENTS SYSTEM CONFIGURATION | 11 |
| 3.1. SAR MEASUREMENT SET-UP | 11 |
| 3.2. OPENSAR E-FIELD PROBE SYSTEM..... | 12 |
| 3.3. PHANTOMS..... | 13 |
| 3.4. DEVICE HOLDER | 13 |
| 3.5. SCANNING PROCEDURE | 14 |
| 3.6. DATA STORAGE AND EVALUATION..... | 15 |
| 3.7. POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM..... | 16 |
| 3.8. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS | 18 |
| 3.9. TISSUE EQUIVALENT LIQUID PROPERTIES | 18 |
| 3.10. SYSTEM CHECK | 19 |
| 3.11. SAR MEASUREMENT PROCEDURE | 21 |
| 3.12. POWER REDUCTION | 21 |
| 3.13. POWER DRIFT | 21 |
| 4. TEST CONDITIONS AND RESULTS..... | 22 |
| 4.1. CONDUCTED POWER RESULTS | 22 |
| 4.2. MANUFACTURING TOLERANCE | 24 |
| 4.3. TRANSMIT ANTENNAS AND SAR MEASUREMENT POSITION..... | 26 |
| 4.4. SAR MEASUREMENT RESULTS | 27 |
| 4.5. SIMULTANEOUS TX SAR CONSIDERATIONS..... | 28 |
| 4.6. SAR MEASUREMENT VARIABILITY | 30 |
| 4.7. GENERAL DESCRIPTION OF TEST PROCEDURES | 31 |
| 4.8. MEASUREMENT UNCERTAINTY (450MHZ-6GHZ)..... | 31 |
| 4.9. SYSTEM CHECK RESULTS | 32 |
| 4.10 SAR TEST GRAPH RESULTS | 36 |
| 5. CALIBRATION CERTIFICATES | 40 |
| 5.1 PROBE-EPGO324 CALIBRATION CERTIFICATE..... | 40 |
| 5.2 SID835DIPOLE CALIBRATION CERITCATE..... | 50 |
| 5.3 SID1900 DIPOLE CALIBRATION CERTIFICATE | 62 |
| 6. EUT TEST PHOTOGRAPHS | 73 |
| 6.1 PHOTOGRAPH OF LIQUIDDEPTH | 73 |
| 6.2 PHOTOGRAPH OF THE TEST..... | 75 |
| 7. EUT PHOTOGRAPHS | 78 |

1. TEST STANDARDS AND TEST DESCRIPTION

1.1. Test Standards

[IEEE Std C95.1, 2005](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 KHz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

[IEEE Std 1528™-2013](#): IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

[FCC Part 2.1093](#): Radiofrequency Radiation Exposure Evaluation: Portable Devices

[KDB447498 D01 General RF Exposure Guidance](#): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

[KDB648474 D04 Handset SAR v01r03](#): SAR Evaluation Considerations for Wireless Handsets

[KDB865664 D01 SAR Measurement 100 MHz to 6 GHz](#): SAR Measurement Requirements for 100 MHz to 6 GHz

[KDB865664 D02 RF Exposure Reporting](#): RF Exposure Compliance Reporting and Documentation Considerations

[KDB 941225 D06 Hotspot Mode](#): SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES

1.2. Test Description

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power . And Test device is identical prototype.

1.3. General Remarks

| | | |
|--------------------------------|---|-------------------|
| Date of receipt of test sample | : | November 16, 2018 |
| Testing commenced on | : | November 16, 2018 |
| Testing concluded on | : | November 23, 2018 |

1.4. Product Description

The **GSM GLOBE.COM INC.'s** Model: **S1 Barcelona** or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

| General Description | |
|---|--|
| Product Name: | 2G mobile phone |
| Model/Type reference: | S1 Barcelona |
| List Model No.: | S1 Barcelona plus, S1 Barcelona pro |
| Model Declaration: | PCB board, structure and internal of these model(s) are the same, only model name and shell colors is different for these models. |
| Modulation Type: | GMSK for GSM/GPRS |
| Device category: | Portable Device |
| Exposure category: | General population/uncontrolled environment |
| EUT Type: | Production Unit |
| Hardware Version | SE039_MB_V2.0 |
| Software Version: | SE0397_MDTX_F009_GOL_S1_Barcelona_F4_V01_T01_20181113 |
| Power supply: | DC 3.7V by Rechargeable Li-ion Battery(600mAh) Recharged by DC 5V/500mA AC/DC ADAPTOR |
| Antenna Gain: | 1.8dBi (max.) for GSM 850; 1.9dBi (max.) for GSM 900; 1.6dBi (max.) for DCS 1800; 1.5dBi (max.) for PCS 1900; 1.0dBi (max.) for BT |
| Antenna Type: | Integral Antenna |
| <i>The EUT is GSM mobile phone. the mobile phone is intended for speech and Multimedia Message Service (MMS) transmission. It is equipped with GPRS class 12 for GSM850, PCS1900, and Bluetooth, For more information see the following datasheet</i> | |
| Technical Characteristics | |
| GSM | |

| | |
|-----------------------|---|
| Support Networks | GSM, GPRS |
| Support Band | GSM850/PCS1900/GPRS850/GPRS1900 |
| Frequency | GSM850: 824.2~848.8MHz GSM1900: 1850.2~1909.8MHz |
| Power Class: | GSM850:Power Class 4 PCS1900:Power Class 1 |
| GSM Release Version | R99 |
| GPRS Multislot Class | 12 |
| EGPRS Multislot Class | Not Supported |
| DTM Mode | Not Supported |
| Modulation Type: | GMSK for GSM/GPRS |
| Bluetooth | |
| Bluetooth Version: | 2.1+EDR |
| Modulation: | GFSK, $\pi/4$ -DQPSK, 8-DPSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 79 |
| Channel separation: | 1MHz |

1.5. Statement of Compliance

The maximum of results of SAR found during testing for S1 Barcelona are follows:

<Highest Reported standalone SAR Summary>

| Classment Class | Frequency Band | Head (Report SAR _{1-g} (W/kg)) | Body-worn (Report SAR _{1-g} (W/kg)) |
|-----------------|----------------|---|--|
| PCE | GSM 850 | 0.934 | 1.138 |
| | GSM1900 | 0.520 | 0.684 |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

<Highest Reported simultaneous SAR Summary>

| Exposure Position | Frequency Band | Reported SAR _{1-g} (W/kg) | Classment Class | Highest Reported Simultaneous Transmission SAR _{1-g} (W/kg) |
|-------------------|----------------|------------------------------------|-----------------|--|
| Body-worn | GSM 850 | 1.138 | PCE | 1.190 |
| | BT | 0.052 | DSS | |

2. TEST ENVIRONMENT

2.1. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Site Description
EMC Lab. : FCC Registration Number. is 254912
Industry Canada Registration Number. is 9642A-1.
ESMD Registration Number. is ARCB0108.
UL Registration Number. is 100571-492.
TUV SUD Registration Number. is SCN1081.
TUV RH Registration Number. is UA 50296516-001
NVLAP Registration Code is 600167-0.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|--------------|
| Temperature: | 18-25 ° C |
| Humidity: | 40-65 % |
| Atmospheric pressure: | 950-1050mbar |

2.3. SAR Limits

| EXPOSURE LIMITS | FCC Limit (1g Tissue) | |
|--|--|--|
| | SAR (W/kg) | |
| | (General Population / Uncontrolled Exposure Environment) | (Occupational / Controlled Exposure Environment) |
| Spatial Average(averaged over the whole body) | 0.08 | 0.4 |
| Spatial Peak(averaged over any 1 g of tissue) | 1.6 | 8.0 |
| Spatial Peak(hands/wrists/ feet/anklesaveraged over 10 g) | 4.0 | 20.0 |

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

2.4. Equipments Used during the Test

| Test Equipment | Manufacturer | Type/Model | Serial Number | Calibration | |
|-------------------------------------|--------------|-----------------|---------------------------|------------------|-----------------|
| | | | | Calibration Date | Calibration Due |
| PC | Lenovo | G5005 | MY42081102 | N/A | N/A |
| SAR Measurement system | SATIMO | 4014_01 | SAR_4014_01 | N/A | N/A |
| Signal Generator | Agilent | E4438C | MY42081396 | 06/16/2018 | 06/15/2019 |
| Multimeter | Keithley | Multimeter 2000 | 4059164 | 06/16/2018 | 06/15/2019 |
| S-parameter Network Analyzer | Agilent | 8753ES | US38432944 | 11/15/2018 | 11/14/2019 |
| Wideband Radia Communication Tester | R&S | CMW500 | 1201.0002K50 | 11/15/2018 | 11/14/2019 |
| E-Field PROBE | SATIMO | SSE2 | SN 31/17 EPO324 | 10/08/2018 | 10/07/2019 |
| DIPOLE 835 | SATIMO | SID 835 | SN 07/14 DIP 0G835-303 | 10/01/2018 | 09/30/2021 |
| DIPOLE 1900 | SATIMO | SID 1900 | SN 38/18 DIP 1G900-466 | 09/24/2018 | 09/23/2021 |
| Power meter | Agilent | E4419B | MY45104493 | 06/16/2018 | 06/15/2019 |
| Power meter | Agilent | E4418B | GB4331256 | 06/16/2018 | 06/15/2019 |
| Power sensor | Agilent | E9301H | MY41497725 | 06/16/2018 | 06/15/2019 |
| Power sensor | Agilent | E9301H | MY41495234 | 06/16/2018 | 06/15/2019 |
| Directional Coupler | MCLI/USA | 4426-20 | 0D2L51502 | 06/16/2018 | 06/15/2019 |
| Mobile Phone POSITIONING DEVICE | SATIMO | MSH98 | SN 40/14 MSH98 | N/A | N/A |
| SAM PHANTOM | SATIMO | SAM117 | SN 40/14 SAM117 | N/A | N/A |
| COMOSAR OPEN Coaxial Probe | SATIMO | OCPG 68 | SN 40/14 OCPG68 | N/A | N/A |
| Liquid measurement Kit | HP | 85033D | 3423A03482 | N/A | N/A |

Note:

- 1) Per KDB865664D01 requirements for dipole calibration, the test laboratory has adopted three year extended calibration interval. Each measured dipole is expected to evaluate with following criteria at least on annual interval.
 - a) There is no physical damage on the dipole;
 - b) System check with specific dipole is within 10% of calibrated values;
 - c) The most recent return-loss results, measured at least annually, deviates by no more than 20% from the previous measurement;
 - d) The most recent measurement of the real or imaginary parts of the impedance, measured at least annually is within 5Ω from the previous measurement.
- 2) Network analyzer probe calibration against air, distilled water and a shorting block performed before measuring liquid parameters.

3.SAR MEASUREMENTS SYSTEM CONFIGURATION

3.1. SAR Measurement Set-up

The OPENSAR system for performing compliance tests consist of the following items:

A standard high precision 6-axis robot (KUKA) with controller and software.

KUKA Control Panel (KCP)

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with a Video Positioning System(VPS).

The stress sensor is composed with mechanical and electronic when the electronic part detects a change on the electro-mechanical switch,It sends an "Emergency signal" to the robot controller that to stop robot's moves

A computer operating Windows XP.

OPENSAR software


Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.

The SAM phantom enabling testing left-hand right-hand and body usage.

The Position device for handheld EUT

Tissue simulating liquid mixed according to the given recipes .

System validation dipoles to validate the proper functioning of the system.



3.2. OPENSAR E-field Probe System

The SAR measurements were conducted with the dosimetric probe EPGO324(manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

Probe Specification

Construction Symmetrical design with triangular core
 Interleaved sensors
 Built-in shielding against static charges
 PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

Calibration ISO/IEC 17025 calibration service available.


| | |
|---------------|--|
| Frequency | 450 MHz to 6 GHz; Linearity:0.25dB(450 MHz to 6 GHz) |
| Directivity | 0.25 dB in HSL (rotation around probe axis) 0.5 dB in tissue material (rotation normal to probe axis) |
| Dynamic Range | 0.01W/kg to > 100 W/kg; Linearity: 0.25 dB |
| Dimensions | Overall length: 330 mm (Tip: 16mm) Tip diameter: 5 mm (Body: 8 mm) Distance from probe tip to sensor centers: 2.5 mm |
| Application | General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones |



Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.


The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



3.3. Phantoms

The SAM Phantom SAM117 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1, EN62209-2:2010. The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.



SAM Twin Phantom

3.4. Device Holder

In combination with the Generic Twin Phantom SAM117, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).



Device holder supplied by SATIMO

3.5. Scanning Procedure

The procedure for assessing the peak spatial-average SAR value consists of the following steps

Power Reference Measurement

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

| | ≤ 3 GHz | > 3 GHz |
|--|---|---|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | 5 mm ± 1 mm | $\frac{1}{2} \cdot \delta \cdot \ln(2)$ mm ± 0.5 mm |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location | 30° ± 1° | 20° ± 1° |
| Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area} | ≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm | 3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm |
| | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device. | |

Zoom Scan

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

| Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom} | | ≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm* | 3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm* | |
|---|------------------------------------|--|--|---|
| Maximum zoom scan spatial resolution, normal to phantom surface | uniform grid: $\Delta z_{Zoom}(n)$ | ≤ 5 mm | 3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm | |
| | graded grid | $\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface | ≤ 4 mm | 3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm |
| | | $\Delta z_{Zoom}(n>1)$: between subsequent points | ≤ 1.5 · $\Delta z_{Zoom}(n-1)$ mm | |
| Minimum zoom scan volume | x, y, z | ≥ 30 mm | 3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm | |
| Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details. | | | | |
| * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. | | | | |

Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

3.6. Data Storage and Evaluation

Data Storage

The OPENSAR software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The OPENSAR software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

| | | |
|--------------------|---------------------------|----------------------|
| Probe parameters: | - Sensitivity | Normi, ai0, ai1, ai2 |
| | - Conversion factor | ConvFi |
| | - Diode compression point | Dcpi |
| Device parameters: | - Frequency | f |
| | - Crest factor | cf |
| Media parameters: | - Conductivity | σ |
| | - Density | ρ |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the OPENSAR components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With V_i = compensated signal of channel i (i = x, y, z)
 U_i = input signal of channel i (i = x, y, z)
 cf = crest factor of exciting field
 dcp_i = diode compression point

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes} : E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$H - \text{fieldprobes} : H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

With V_i = compensated signal of channel i (i = x, y, z)
 $Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
 [mV/(V/m)²] for E-field Probes
 $ConvF$ = sensitivity enhancement in solution

- aij = sensor sensitivity factors for H-field probes
- f = carrier frequency [GHz]
- Ei = electric field strength of channel i in V/m
- Hi = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

- with SAR = local specific absorption rate in mW/g
- Etot = total field strength in V/m
- σ = conductivity in [mho/m] or [Siemens/m]
- ρ = equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

3.7. Position of the wireless device in relation to the phantom

General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.


The power flow density is calculated assuming the excitation field as a free space field

$$P_{(pwe)} = \frac{E_{tot}^2}{3770} \text{ or } P_{(pwe)} = H_{tot}^2 \cdot 37.7$$

Where P_{pwe}=Equivalent power density of a plane wave in mW/cm²


E_{tot}=total electric field strength in V/m

H_{tot}=total magnetic field strength in A/m




- W_t Width of the handset at the level of the acoustic
- W_b Width of the bottom of the handset
- A Midpoint of the width w_r of the handset at the level of the acoustic output
- B Midpoint of the width w_b of the bottom of the handset

Picture 1-a Typical “fixed” case handset Picture 1-b Typical “clam-shell” case handset



Picture 2 Cheek position of the wireless device on the left side of SAM



Picture 3 Tilt position of the wireless device on the left side of SAM

For body SAR test we applied to FCC KDB941225, KDB447498, KDB248227, KDB648654;

3.8. Tissue Dielectric Parameters for Head and Body Phantoms

The liquid is consisted of water,salt,Glycol,Sugar,Preventol and Cellulose.The liquid has previously been proven to be suited for worst-case.It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB865664.

The composition of the tissue simulating liquid

| Ingredient (% Weight) | 750MHz | | 835MHz | | 1800 MHz | | 1900 MHz | | 2450MHz | | 2600MHz | | 5000MHz | |
|-----------------------------|--------|------|--------|------|----------|-------|----------|-------|---------|-------|---------|-------|---------|------|
| | Head | Body | Head | Body | Head | Body | Head | Body | Head | Body | Head | Body | Head | Body |
| Water | 39.28 | 51.3 | 41.45 | 52.5 | 54.5 | 40.2 | 54.9 | 40.4 | 62.7 | 73.2 | 60.3 | 71.4 | 65.5 | 78.6 |
| Preventol | 0.10 | 0.10 | 0.10 | 0.10 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| HEC | 1.00 | 1.00 | 1.00 | 1.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| DGBE | 0.00 | 0.00 | 0.00 | 0.00 | 45.33 | 59.31 | 44.92 | 59.10 | 36.80 | 26.70 | 39.10 | 28.40 | 0.00 | 0.00 |
| Triton X-100 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 17.2 | 10.7 |

| Target Frequency (MHz) | Head | | Body | |
|---------------------------|--------------|---------------|--------------|---------------|
| | ϵ_r | $\sigma(S/m)$ | ϵ_r | $\sigma(S/m)$ |
| 150 | 52.3 | 0.76 | 61.9 | 0.80 |
| 300 | 45.3 | 0.87 | 58.2 | 0.92 |
| 450 | 43.5 | 0.87 | 56.7 | 0.94 |
| 835 | 41.5 | 0.90 | 55.2 | 0.97 |
| 900 | 41.5 | 0.97 | 55.0 | 1.05 |
| 915 | 41.5 | 0.98 | 55.0 | 1.06 |
| 1450 | 40.5 | 1.20 | 54.0 | 1.30 |
| 1610 | 40.3 | 1.29 | 53.8 | 1.40 |
| 1800-2000 | 40.0 | 1.40 | 53.3 | 1.52 |
| 2450 | 39.2 | 1.80 | 52.7 | 1.95 |
| 3000 | 38.5 | 2.40 | 52.0 | 2.73 |
| 5800 | 35.3 | 5.27 | 48.2 | 6.00 |

3.9. Tissue equivalent liquid properties


Dielectric Performance of Head and Body Tissue Simulating Liquid

| Tissue Type | Measured Frequency (MHz) | Target Tissue | | Measured Tissue | | | | Liquid Temp. | Test Data |
|-------------|--------------------------|---------------|--------------|-----------------|--------|--------------|--------|--------------|------------|
| | | σ | ϵ_r | σ | Dev. | ϵ_r | Dev. | | |
| 835H | 835 | 0.90 | 41.50 | 0.88 | -2.22% | 41.94 | -1.06% | 20.5 | 11/16/2018 |
| 1900H | 1800 | 1.40 | 40.00 | 1.43 | 2.14% | 39.57 | -1.08% | 21.3 | 11/22/2018 |
| 835B | 835 | 0.97 | 55.20 | 0.95 | -2.06% | 55.01 | -0.34% | 20.8 | 11/19/2018 |
| 1900B | 1800 | 1.52 | 53.30 | 1.49 | -1.97% | 53.97 | 1.26% | 20.7 | 11/23/2018 |

3.10. System Check

The purpose of the system check is to verify that the system operates within its specifications at the device test frequency. The system check is simple check of repeatability to make sure that the system works correctly at the time of the compliance test;

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).



The output power on dipole port must be calibrated to 20 dBm (100mW) before dipole is connected.



Photo of Dipole Setup

Justification for Extended SAR Dipole Calibrations

Referring to KDB 865664D01V01r04, if dipoles are verified in return loss (<-20dB, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended. While calibration intervals not exceed 3 years.

SID835SN 07/14 DIP 0G835-303 Extend Dipole Calibrations

| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
|---------------------|------------------|-----------|----------------------|-------------|---------------------------|-------------|
| 2018-10-01 | -24.49 | | 55.9 | | 2.8 | |

SID1900 SN 38/18 DIP 1G900-466 Extend Dipole Calibrations

| Date of Measurement | Return-Loss (dB) | Delta (%) | Real Impedance (ohm) | Delta (ohm) | Imaginary Impedance (ohm) | Delta (ohm) |
|---------------------|------------------|-----------|----------------------|-------------|---------------------------|-------------|
| 2018-09-24 | -26.43 | | 50.5 | | 4.7 | |

| Mixture Type | Frequency (MHz) | Power | SAR _{1g} (W/Kg) | SAR _{10g} (W/Kg) | Drift (%) | 1W Target | | Difference percentage | | Liquid Temp | Date |
|--------------|-----------------|---------------------|--------------------------|---------------------------|-----------|--------------------------|---------------------------|-----------------------|--------|-------------|------------|
| | | | | | | SAR _{1g} (W/Kg) | SAR _{10g} (W/Kg) | 1g | 10g | | |
| Head | 835 | 100 mW | 0.985 | 0.635 | 2.04 | 9.60 | 6.20 | 2.60% | 2.42% | 20.5 | 11/16/2018 |
| | | Normalize to 1 Watt | 9.85 | 6.35 | | | | | | | |
| Body | 835 | 100 mW | 0.978 | 0.636 | 1.95 | 9.90 | 6.39 | -1.21% | -0.47% | 20.8 | 11/19/2018 |
| | | Normalize to 1 Watt | 9.78 | 6.36 | | | | | | | |
| Head | 1900 | 100 mW | 3.927 | 2.008 | -1.65 | 39.84 | 20.20 | -1.43% | -0.59% | 21.3 | 11/22/2018 |
| | | Normalize to 1 Watt | 39.27 | 20.08 | | | | | | | |
| Body | 1900 | 100 mW | 4.117 | 2.059 | -0.97 | 43.33 | 21.59 | -4.98% | -4.63% | 20.7 | 11/23/2018 |
| | | Normalize to 1 Watt | 41.17 | 20.59 | | | | | | | |

3.11. SAR measurement procedure

The measurement procedures are as follows:

3.11.1 Conducted power measurement

- a. For WWAN power measurement, use base station simulator connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- b. Read the WWAN RF power level from the base station simulator.
- c. For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously Transmission, at maximum RF power in each supported wireless interface and frequency band.
- d. Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power.

3.11.2 GSM Test Configuration

SAR tests for GSM 850 and GSM 1900, a communication link is set up with a System Simulator (SS) by air link. Using CMU200 the power level is set to "5" for GSM 850, set to "0" for GSM 1900. Since the GPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5. the EGPRS class is 12 for this EUT, it has at most 4 timeslots in uplink and at most 4 timeslots in downlink, the maximum total timeslots is 5.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. GSM voice and GPRS data use GMSK, which is a constant amplitude modulation with minimal peak to average power difference within the time-slot burst. For EDGE, GMSK is used for MCS 1 – MCS 4 and 8-PSK is used for MCS 5 – MCS 9; where 8-PSK has an inherently higher peak-to-average power ratio. The GMSK and 8-PSK EDGE configurations are considered separately for SAR compliance. The GMSK EDGE configurations are grouped with GPRS and considered with respect to time-averaged maximum output power to determine compliance. The 3G SAR test reduction procedure is applied to 8-PSK EDGE with GMSK GPRS/EDGE as the primary mode.

3.12. Power Reduction

The product without any power reduction.

3.13. Power Drift

To control the output power stability during the SAR test, SAR system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. This ensures that the power drift during one measurement is within 5%.

4. TEST CONDITIONS AND RESULTS

4.1. Conducted Power Results

According KDB 447498D01 General RF Exposure Guidance v06 Section 4.1 2) states that "Unless it is specified differently in the published RF exposure KDB procedures, these requirements also apply to test reduction and test exclusion considerations. Time-averaged maximum conducted output power applies to SAR and, as required by § 2.1091(c), time-averaged ERP applies to MPE. When an antenna port is not available on the device to support conducted power measurement, such as FRS and certain Part 15 transmitters with built-in integral antennas, the maximum output power allowed for production units should be used to determine RF exposure test exclusion and compliance."

<GSM Conducted Power>

General Note:

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. According to October 2013TCB Workshop, for GSM / GPRS / EGPRS, the number of time slots to test for SAR should correspond to the highest frame-average maximum output power configuration, considering the possibility of e.g. 3rd party VoIP operation for head and body-worn SAR testing, the EUT was set in GPRS (2Tx slot) for GSM850/GSM1900 band due to their highest frame-average power.
3. For body-worn mode SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS (4Tx slots) for GSM850/GSM1900 band due to its highest frame-average power.

Conducted power measurement results for GSM850/PCS1900

<SIM1>

| GSM 850 | Tune-up | Burst Conducted power (dBm) | | | Division Factors | Tune-up | Average power (dBm) | | | |
|-------------|-----------------|-----------------------------|--------------|--------------|------------------|----------------|------------------------|--------------|--------------|--------------|
| | | Channel/Frequency(MHz) | | | | | Channel/Frequency(MHz) | | | |
| | Max | 128/824.2 | 190/836.6 | 251/848.8 | | Max | 128/824.2 | 190/836.6 | 251/848.8 | |
| GSM | 33.00 | 32.69 | 32.70 | 32.67 | -9.03dB | 23.97 | 23.66 | 23.67 | 23.64 | |
| GPRS (GMSK) | 1TX slot | 33.00 | 32.56 | 32.58 | 32.57 | -9.03dB | 23.97 | 23.53 | 23.55 | 23.54 |
| | 2TX slot | 31.00 | 30.97 | 30.99 | 30.98 | -6.02dB | 24.98 | 24.95 | 24.97 | 24.96 |
| | 3TX slot | 30.00 | 29.48 | 29.51 | 29.46 | -4.26dB | 25.74 | 25.22 | 25.25 | 25.20 |
| | 4TX slot | 28.50 | 28.02 | 28.05 | 28.00 | -3.01dB | 25.49 | 25.01 | 25.04 | 24.99 |
| GSM 1900 | Tune-up | Burst Conducted power (dBm) | | | Division Factors | Tune-up | Average power (dBm) | | | |
| | | Channel/Frequency(MHz) | | | | | Channel/Frequency(MHz) | | | |
| | Max | 512/1850.2 | 661/1880 | 810/1909.8 | | Max. | 512/1850.2 | 661/1880 | 810/1909.8 | |
| GSM | 30.00 | 29.68 | 29.72 | 29.70 | -9.03dB | 20.97 | 20.65 | 20.69 | 20.67 | |
| GPRS (GMSK) | 1TX slot | 30.00 | 29.51 | 29.53 | 29.47 | -9.03dB | 20.97 | 20.48 | 20.50 | 20.44 |
| | 2TX slot | 28.50 | 27.97 | 28.02 | 27.99 | -6.02dB | 22.48 | 21.95 | 22.00 | 21.97 |
| | 3TX slot | 27.00 | 26.52 | 26.55 | 26.48 | -4.26dB | 22.74 | 22.26 | 22.29 | 22.22 |
| | 4TX slot | 25.00 | 24.96 | 24.98 | 24.93 | -3.01dB | 21.99 | 21.95 | 21.97 | 21.92 |

Notes:

1. Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.00dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.00dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.00dB

2. According to the conducted power as above, the GPRS measurements are performed with 3Txslot for GPRS850 and 3Txslot GPRS1900.

3. This EUT owns two SIM cards , we found the SIM 1 is the worst case ,so its result is recorded in this report.

<SIM2>

| GSM 850 | | Burst Average Conducted power (dBm) | | |
|----------------|----------|-------------------------------------|-----------|------------|
| | | Channel/Frequency(MHz) | | |
| | | 128/824.2 | 190/836.6 | 251/848.8 |
| GSM | | 32.66 | 32.69 | 32.61 |
| GPRS (GMSK) | 1TX slot | 32.53 | 32.57 | 32.50 |
| | 2TX slot | 30.93 | 30.95 | 30.90 |
| | 3TX slot | 29.45 | 29.48 | 29.43 |
| | 4TX slot | 27.88 | 27.94 | 27.91 |
| GSM 1900 | | Burst Average Conducted power (dBm) | | |
| | | Channel/Frequency(MHz) | | |
| | | 512/1850.2 | 661/1880 | 810/1909.8 |
| GSM | | 29.63 | 29.66 | 29.60 |
| GPRS (GMSK) | 1TX slot | 29.47 | 29.51 | 29.43 |
| | 2TX slot | 27.96 | 28.01 | 27.99 |
| | 3TX slot | 26.49 | 26.51 | 26.46 |
| | 4TX slot | 24.91 | 24.93 | 24.87 |

<BT Conducted Power>

| Mode | channel | Frequency (MHz) | Conducted AVG output power (dBm) |
|-----------|---------|-----------------|----------------------------------|
| GFSK | 0 | 2402 | 3.195 |
| | 39 | 2441 | 3.139 |
| | 78 | 2480 | 2.706 |
| π/4-DQPSK | 0 | 2402 | 2.496 |
| | 39 | 2441 | 2.426 |
| | 78 | 2480 | 1.944 |
| 8DPSK | 0 | 2402 | 2.656 |
| | 39 | 2441 | 2.556 |
| | 78 | 2480 | 2.125 |

Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

| Bluetooth Turn up Power (dBm) | Separation Distance (mm) | Frequency (GHz) | Exclusion Thresholds |
|-------------------------------|--------------------------|-----------------|----------------------|
| 4.0 | 5 | 2.45 | 0.8 |

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.8 < 3.0, SAR testing is not required.

4.2. Manufacturing tolerance

GSM Speech <SIM1>

| GSM 850 (GMSK) (Burst Average Power) | | | |
|---------------------------------------|-------------|-------------|-------------|
| Channel | Channel 128 | Channel 190 | Channel 251 |
| Target (dBm) | 32.0 | 32.0 | 32.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| GSM 1900 (GMSK) (Burst Average Power) | | | |
| Channel | Channel 512 | Channel 661 | Channel 810 |
| Target (dBm) | 29.0 | 29.0 | 29.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

<SIM1>

| GSM 850 GPRS (GMSK) (Burst Average Power) | | | | |
|--|----------------------|------|------|------|
| Channel | | 128 | 190 | 251 |
| 1 Txslot | Target (dBm) | 32.0 | 32.0 | 32.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 2 Txslot | Target (dBm) | 30.0 | 30.0 | 30.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 3 Txslot | Target (dBm) | 29.0 | 29.0 | 29.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 4 Txslot | Target (dBm) | 27.5 | 27.5 | 27.5 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| GSM 1900 GPRS (GMSK) (Burst Average Power) | | | | |
| Channel | | 512 | 661 | 810 |
| 1 Txslot | Target (dBm) | 29.0 | 29.0 | 29.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 2 Txslot | Target (dBm) | 27.5 | 27.5 | 27.5 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 3 Txslot | Target (dBm) | 26.0 | 26.0 | 26.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 4 Txslot | Target (dBm) | 24.0 | 24.0 | 24.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

GSM Speech <SIM2>

| GSM 850 (GMSK) (Burst Average Power) | | | |
|---------------------------------------|-------------|-------------|-------------|
| Channel | Channel 128 | Channel 190 | Channel 251 |
| Target (dBm) | 32.0 | 32.0 | 32.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| GSM 1900 (GMSK) (Burst Average Power) | | | |
| Channel | Channel 512 | Channel 661 | Channel 810 |
| Target (dBm) | 29.0 | 29.0 | 29.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

<SIM2>

| GSM 850 GPRS (GMSK) (Burst Average Power) | | | | |
|--|----------------------|------|------|------|
| Channel | | 128 | 190 | 251 |
| 1 Txslot | Target (dBm) | 32.0 | 32.0 | 32.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 2 Txslot | Target (dBm) | 30.0 | 30.0 | 30.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 3 Txslot | Target (dBm) | 28.5 | 28.5 | 28.5 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 4 Txslot | Target (dBm) | 27.0 | 27.0 | 27.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| GSM 1900 GPRS (GMSK) (Burst Average Power) | | | | |
| Channel | | 512 | 661 | 810 |
| 1 Txslot | Target (dBm) | 29.0 | 29.0 | 29.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 2 Txslot | Target (dBm) | 27.5 | 27.5 | 27.5 |

| | | | | |
|----------|----------------------|------|------|------|
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 3 Txslot | Target (dBm) | 26.0 | 26.0 | 26.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 4 Txslot | Target (dBm) | 24.0 | 24.0 | 24.0 |
| | Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

Bluetooth V2.1+EDR**GFSK (Average)**

| Channel | Channel 0 | Channel 39 | Channel 78 |
|----------------------|-----------|------------|------------|
| Target (dBm) | 3.0 | 3.0 | 2.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |


 π /4DQPSK (Average)

| Channel | Channel 0 | Channel 39 | Channel 78 |
|----------------------|-----------|------------|------------|
| Target (dBm) | 2.0 | 2.0 | 1.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

8DPSK (Average)

| Channel | Channel 0 | Channel 39 | Channel 78 |
|----------------------|-----------|------------|------------|
| Target (dBm) | 2.0 | 2.0 | 2.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

4.3. Transmit Antennas and SAR Measurement Position



Antenna information:

| | |
|-------------------|-----------|
| WWAN Main Antenna | GSM TX/RX |
| BT Antenna | BT TX/RX |

Note:

- 1). Per KDB648474 D04, because the overall diagonal distance of this devices is 115mm<160mm, it is considered as "Phablet" device.
- 2). Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR < 1.2 W/kg.

4.4. SAR Measurement Results

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} * 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Scaling factor} = 10^{(P_{\text{target}} - P_{\text{measured}})/10}$$

$$\text{Reported SAR} = \text{Measured SAR} * \text{Scaling factor}$$

Where

P_{target} is the power of manufacturing upper limit;

P_{measured} is the measured power;

Measured SAR is measured SAR at measured power which including power drift)

Reported SAR which including Power Drift and Scaling factor

Duty Cycle

| Test Mode | Duty Cycle |
|------------------------|------------|
| Speech for GSM850/1900 | 1:8 |
| GPRS850 | 1:2.67 |
| GPRS1900 | 1:2.67 |

4.4.1 SAR Results

SAR Values [GSM 850]

| Ch. | Freq. (MHz) | Time slots | Test Position | Conducted Power (dBm) | Maximum Allowed Power (dBm) | Power Drift (%) | Scaling Factor | SAR _{1-g} results(W/kg) | | Graph Results |
|---|-------------|------------|---------------|-----------------------|-----------------------------|-----------------|----------------|----------------------------------|--------------|---------------|
| | | | | | | | | Measured | Reported | |
| <i>measured / reported SAR numbers –Head<SIM1></i> | | | | | | | | | | |
| 190 | 836.6 | Voice | Left Cheek | 32.70 | 33.00 | 3.48 | 1.072 | 0.872 | 0.934 | Plot 1 |
| 128 | 824.2 | Voice | Left Cheek | 32.69 | 33.00 | 1.02 | 1.074 | 0.637 | 0.684 | |
| 251 | 848.8 | Voice | Left Cheek | 32.67 | 33.00 | -3.54 | 1.079 | 0.710 | 0.766 | |
| 190 | 836.6 | Voice | Left Tilt | 32.70 | 33.00 | -1.24 | 1.072 | 0.510 | 0.546 | |
| 190 | 836.6 | Voice | Right Cheek | 32.70 | 33.00 | -2.81 | 1.072 | 0.632 | 0.677 | |
| 190 | 836.6 | Voice | Right Tilt | 32.70 | 33.00 | -0.75 | 1.072 | 0.400 | 0.429 | |
| <i>measured / reported SAR numbers - Body (distance 10mm)<SIM1></i> | | | | | | | | | | |
| 190 | 836.6 | 3Txslots | Front | 29.51 | 30.00 | 2.75 | 1.119 | 0.578 | 0.647 | |
| 190 | 836.6 | 3Txslots | Rear | 29.51 | 30.00 | 2.38 | 1.119 | 1.017 | 1.138 | Plot 2 |
| 128 | 824.2 | 3Txslots | Rear | 29.48 | 30.00 | 2.75 | 1.127 | 0.796 | 0.897 | |
| 251 | 848.8 | 3Txslots | Rear | 29.46 | 30.00 | -2.77 | 1.132 | 0.942 | 1.067 | |

Remark:

1. The value with black color is the maximum SAR Value of each test band.
2. The frame average of GPRS (3Tx slots) higher than GSM and sample can support VoIP function, tested at GPRS (3Tx slots) mode for head.
3. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).

SAR Values [GSM 1900]

| Ch. | Freq. (MHz) | time slots | Test Position | Conducted Power (dBm) | Maximum Allowed Power (dBm) | Power Drift (%) | Scaling Factor | SAR _{1-g} results(W/kg) | | Graph Results |
|---|-------------|------------|---------------|-----------------------|-----------------------------|-----------------|----------------|----------------------------------|--------------|---------------|
| | | | | | | | | Measured | Reported | |
| <i>measured / reported SAR numbers –Head<SIM1></i> | | | | | | | | | | |
| 661 | 1880.0 | Voice | Left Cheek | 29.72 | 30.00 | -2.60 | 1.067 | 0.360 | 0.384 | |
| 661 | 1880.0 | Voice | Left Tilt | 29.72 | 30.00 | 1.56 | 1.067 | 0.185 | 0.197 | |
| 661 | 1880.0 | Voice | Right Cheek | 29.72 | 30.00 | -0.60 | 1.067 | 0.488 | 0.520 | Plot 3 |
| 661 | 1880.0 | Voice | Right Tilt | 29.72 | 30.00 | 2.71 | 1.067 | 0.217 | 0.231 | |
| <i>measured / reported SAR numbers – Body (distance 10mm)</i> | | | | | | | | | | |
| 661 | 1880.0 | 3Txslots | Front | 26.55 | 27.00 | 1.54 | 1.109 | 0.366 | 0.406 | |
| 661 | 1880.0 | 3Txslots | Rear | 26.55 | 27.00 | -0.42 | 1.109 | 0.617 | 0.684 | Plot 4 |

Remark:

1. The value with black color is the maximum SAR Value of each test band.
2. The frame average of GPRS (3Tx slots) higher than GSM and sample can support VoIP function, tested at GPRS (3Tx slots) mode for head.
3. Per FCC KDB Publication 447498 D01, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is optional for such test configuration(s).

4.4.2 Standalone SAR Test Exclusion Considerations and Estimated SAR

Per KDB447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion;

• (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [$\sqrt{f(\text{GHz})}$]/x
W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

• 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Per FCC KD B447498 D01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the transmitting antenna in a specific a physical test configuration is ≤ 1.6 W/Kg. When the sum is greater than the SAR limit, SAR test exclusion is determined by the SAR to peak location separation ratio.

$$\text{Ratio} = \frac{(\text{SAR}_1 + \text{SAR}_2)^{1.5}}{(\text{peak location separation, mm})} < 0.04$$

| Estimated stand alone SAR | | | | | |
|---------------------------|-----------------|---------------|---------------------|--------------------------|-------------------------------------|
| Communication system | Frequency (MHz) | Configuration | Maximum Power (dBm) | Separation Distance (mm) | Estimated SAR _{1-g} (W/kg) |
| Bluetooth* | 2450 | Head | 4.00 | 5 | 0.105 |
| Bluetooth* | 2450 | Body-worn | 4.00 | 10 | 0.052 |

Remark:

1. Bluetooth*- Including Lower power Bluetooth
2. Maximum average power including tune-up tolerance;
3. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion
4. Body as body use distance is 10mm from manufacturer declaration of user manual

4.5. Simultaneous TX SAR Considerations

4.5.1 Introduction

The following procedures adopted from "FCC SAR Considerations for Cell Phones with Multiple Transmitters" are applicable to handsets with built-in unlicensed transmitters such as Bluetooth devices which may simultaneously transmit with the licensed transmitter.

For the DUT, the BT modules sharing same antenna, GSM modules sharing a single antenna; BT and GSM can simultaneous transmit;

Application Simultaneous Transmission information:

| Air-Interface | Band (MHz) | Type | Simultaneous Transmissions | Voice over Digital Transport(Data) |
|---------------|------------|------|----------------------------|------------------------------------|
| GSM | 850 | VO | Yes, BT | N/A |
| | 1900 | VO | | |
| | GPRS | DT | Yes, BT | N/A |
| BT | 2450 | DT | Yes, GSM, GPRS | N/A |

Note: VO-Voice Service only; DT-Digital Transport

Note:

BT- Classical Bluetooth;

4.5.2 Evaluation of Simultaneous SAR

Head Exposure Conditions

Simultaneous transmission SAR for BT and GSM

| Test Position | GSM850 Reported SAR _{1-g} (W/kg) | GSM1900 Reported SAR _{1-g} (W/kg) | BT Estimated SAR _{1-g} (W/kg) | MAX. Σ SAR _{1-g} (W/kg) | SAR _{1-g} Limit (W/kg) | Peak location separation ratio | Simut Meas. Required |
|---------------|---|--|--|---|---------------------------------|--------------------------------|----------------------|
| Left Cheek | 0.934 | 0.384 | 0.105 | 1.039 | 1.6 | no | no |
| LeftTilt | 0.677 | 0.197 | 0.105 | 0.782 | 1.6 | no | no |
| Right Cheek | 0.429 | 0.520 | 0.105 | 0.625 | 1.6 | no | no |
| Right Tilt | 0.429 | 0.231 | 0.105 | 0.534 | 1.6 | no | no |

Body-worn Exposure Conditions

Simultaneous transmission SAR for BT and GSM

| Test Position | GSM850 Reported SAR _{1-g} (W/kg) | GSM1900 Reported SAR _{1-g} (W/kg) | BT Estimated SAR _{1-g} (W/kg) | MAX. Σ SAR _{1-g} (W/kg) | SAR _{1-g} Limit (W/kg) | Peak location separation ratio | Simut Meas. Required |
|---------------|---|--|--|---|---------------------------------|--------------------------------|----------------------|
| Front | 0.647 | 0.406 | 0.052 | 0.699 | 1.6 | no | no |
| Rear | 1.138 | 0.684 | 0.052 | 1.190 | 1.6 | no | no |

Note:

1. The value with **black** color is the maximum values of standalone
2. The value with blue color is the maximum values of Σ SAR_{1-g}

4.6. SAR Measurement Variability

According to KDB865664, Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR value of the initial repeated measurement is < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. A second repeated measurement is required only if the measured result for the initial repeated measurement is within 10% of the SAR limit and vary by more than 20%, which are often related to device and measurement setup difficulties. The following procedures are applied to determine if repeated measurements are required. The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.19 The repeated measurement results must be clearly identified in the SAR report. All measured SAR, including the repeated results, must be considered to determine compliance and for reporting according to KDB 690783. Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

| Frequency Band (MHz) | Air Interface | RF Exposure Configuration | Test Position | Repeated SAR (yes/no) | Highest Measured SAR _{1-g} (W/Kg) | First Repeated | |
|----------------------|---------------|---------------------------|---------------|-----------------------|--|------------------------------------|-------------------------------|
| | | | | | | Measured SAR _{1-g} (W/Kg) | Largest to Smallest SAR Ratio |
| 850 | GSM850 | Standalone | Body-Rear | no | 1.017 | 0.813 | 0.865 |
| 1900 | GSM1900 | Standalone | Body-Rear | no | 0.617 | n/a | n/a |

Remark:

1. *Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 or 3 (1-g or 10-g respectively)*

4.7. General description of test procedures

1. The DUT is tested using CMU 200 communications testers as controller unit to set test channels and maximum output power to the DUT, as well as for measuring the conducted peak power.
2. Test positions as described in the tables above are in accordance with the specified test standard.
3. Tests in body position were performed in that configuration, which generates the highest time based averaged output power (see conducted power results).
4. Tests in head position with GSM were performed in voice mode with 1 timeslot unless GPRS/EGPRS/DTM function allows parallel voice and data traffic on 2 or more timeslots.
5. UMTS was tested in RMC mode with 12.2 kbit/s and TPC bits set to 'all 1'.
6. WiFi was tested in 802.11b/g/n mode with 1 Mbit/s and 6 Mbit/s. According to KDB 248227 the SAR testing for 802.11g/n is not required since When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
7. Required WiFi test channels were selected according to KDB 248227
8. According to FCC KDB pub 248227 D01, When there are multiple test channels with the same measured maximum output power, the channel closest to mid-band frequency is selected for SAR measurement and when there are multiple test channels with the same measured maximum output power and equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.
9. According to FCC KDB pub 941225 D06 this device has been tested with 10 mm distance to the phantom for operation in WiFi hot spot mode.
10. Per FCC KDB pub 941225 D06 the edges with antennas within 2.5 cm are required to be evaluated for SAR to cover WiFi hot spot function.
11. According to IEEE 1528 the SAR test shall be performed at middle channel. Testing of top and bottom channel is optional.
12. According to KDB 447498 D01 testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
13. IEEE 1528-2003 require the middle channel to be tested first. This generally applies to wireless devices that are designed to operate in technologies with tight tolerances for maximum output power variations across channels in the band.
14. Per KDB648474 D04 require when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is < 1.2 W/kg.
15. Per KDB648474 D04 require when the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, using the same wireless mode test configuration for voice and data, such as UMTS, LTE and Wi-Fi, and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface)




4.8. Measurement Uncertainty (450MHz-6GHz)

Not required as SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is ≥ 1.5 W/kg for 1-g SAR according to KDB865664D01.

4.9. System Check Results

Test mode:835MHz(Head)
 Product Description:Validation
 Model:Dipole SID835
 E-Field Probe:SSE2(SN 31/17 EPGO324)
 Test Date:November 16, 2018

| | |
|-----------------------------------|-------------------|
| Medium(liquid type) | HSL_850 |
| Frequency (MHz) | 835.0000 |
| Relative permittivity (real part) | 41.94 |
| Conductivity (S/m) | 0.88 |
| Input power | 100mW |
| Crest Factor | 1.0 |
| Conversion Factor | 1.55 |
| Variation (%) | 2.040000 |
| SAR 10g (W/Kg) | 0.634632 |
| SAR 1g (W/Kg) | 0.985201 |
| SURFACE SAR | VOLUME SAR |






Test mode:835MHz(Body)
 Product Description:Validation
 Model:Dipole SID835
 E-Field Probe:SSE2(SN 31/17 EPGO324)
 Test Date:November 19, 2018

| | |
|-----------------------------------|-----------|
| Medium(liquid type) | MSL_850 |
| Frequency (MHz) | 835.0000 |
| Relative permittivity (real part) | 55.01 |
| Conductivity (S/m) | 0.95 |
| Input power | 100mW |
| Crest Factor | 1.0 |
| Conversion Factor | 1.59 |
| Variation (%) | -3.720000 |
| SAR 10g (W/Kg) | 0.636394 |
| SAR 1g (W/Kg) | 0.978316 |

SURFACE SAR

VOLUME SAR






Test mode:1900MHz(Head)
 Product Description:Validation
 Model :Dipole SID1900
 E-Field Probe:SSE2(SN 31/17 EPGO324)
 Test Date: November 22, 2018

| | |
|-----------------------------------|-----------|
| Medium(liquid type) | HSL_1900 |
| Frequency (MHz) | 1900.0000 |
| Relative permittivity (real part) | 39.57 |
| Conductivity (S/m) | 1.43 |
| Input power | 100mW |
| Crest Factor | 1.0 |
| Conversion Factor | 1.86 |
| Variation (%) | -0.400000 |
| SAR 10g (W/Kg) | 2.008320 |
| SAR 1g (W/Kg) | 3.927201 |

SURFACE SAR

VOLUME SAR






Test mode:1900MHz(Body)
 Product Description:Validation
 Model :Dipole SID1900
 E-Field Probe:SSE2(SN 31/17 EPGO324)
 Test Date: November 23, 2018

| | |
|-----------------------------------|-----------|
| Medium(liquid type) | MSL_1900 |
| Frequency (MHz) | 1900.0000 |
| Relative permittivity (real part) | 53.97 |
| Conductivity (S/m) | 1.49 |
| Input power | 100mW |
| Crest Factor | 1.0 |
| Conversion Factor | 1.93 |
| Variation (%) | 1.330000 |
| SAR 10g (W/Kg) | 2.058632 |
| SAR 1g (W/Kg) | 4.116921 |

SURFACE SAR

VOLUME SAR



4.10 SAR Test Graph Results

SAR plots for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination according to FCC KDB 865664 D02;

#1





Test Mode:GSM 850MHz,Middle channel(Head Left Cheek)

Product Description:2G mobile phone

Model:S1 Barcelona

Test Date:November 16, 2018





| | |
|-----------------------------------|----------------------------|
| Medium(liquid type) | HSL_850 |
| Frequency (MHz) | 836.6000 |
| Relative permittivity (real part) | 41.94 |
| Conductivity (S/m) | 0.88 |
| E-Field Probe | SN 31/17 EPG0324 |
| Crest Factor | 8 |
| Conversion Factor | 1.55 |
| Sensor | 4mm |
| Area Scan | dx=8mm dy=8mm |
| Zoom Scan | 5x5x7,dx=8mm dy=8mm dz=5mm |
| Variation (%) | 3.480000 |
| SAR 10g (W/Kg) | 0.563422 |
| SAR 1g (W/Kg) | 0.871861 |
| SURFACE SAR | VOLUME SAR |



#2

Test Mode: GPPS850MHz,Middle channel(Body Rear Side)
 Product Description:2G mobile phone
 Model:S1 Barcelona
 Test Date:November 19, 2018

| | |
|-----------------------------------|----------------------------|
| Medium(liquid type) | MSL_850 |
| Frequency (MHz) | 836.6000 |
| Relative permittivity (real part) | 55.01 |
| Conductivity (S/m) | 0.95 |
| E-Field Probe | SN 31/17 EPG0324 |
| Crest Factor | 2.67 |
| Conversion Factor | 1.59 |
| Sensor | 4mm |
| Area Scan | dx=8mm dy=8mm |
| Zoom Scan | 5x5x7,dx=8mm dy=8mm dz=5mm |
| Variation (%) | 2.380000 |
| SAR 10g (W/Kg) | 0.696977 |
| SAR 1g (W/Kg) | 1.017480 |
| SURFACE SAR | VOLUME SAR |



#3

Test Mode:GSM 1900MHz,Middle channel(Head Right Cheek)

Product Description:2G mobile phone





Model:S1 Barcelona

Test Date:November 22, 2018

| | |
|-----------------------------------|----------------------------|
| Medium(liquid type) | HSL_1900 |
| Frequency (MHz) | 1880.0000 |
| Relative permittivity (real part) | 39.57 |
| Conductivity (S/m) | 1.43 |
| E-Field Probe | SN 31/17 EPGO324 |
| Crest Factor | 8 |
| Conversion Factor | 1.86 |
| Sensor | 4mm |
| Area Scan | dx=8mm dy=8mm |
| Zoom Scan | 5x5x7,dx=8mm dy=8mm dz=5mm |
| Variation (%) | -0.600000 |
| SAR 10g (W/Kg) | 0.294059 |
| SAR 1g (W/Kg) | 0.487704 |

SURFACE SAR

VOLUME SAR



#4

Test Mode: GPRS1900MHz,Middle channel(Body Rear Side)

Product Description:2G mobile phone

Model:S1 Barcelona

Test Date:November 23, 2018

| | |
|-----------------------------------|----------------------------|
| Medium(liquid type) | MSL_1900 |
| Frequency (MHz) | 1880.0000 |
| Relative permittivity (real part) | 53.97 |
| Conductivity (S/m) | 1.49 |
| E-Field Probe | SN 31/17 EPGO324 |
| Crest Factor | 2.67 |
| Conversion Factor | 1.93 |
| Sensor | 4mm |
| Area Scan | dx=8mm dy=8mm |
| Zoom Scan | 5x5x7,dx=8mm dy=8mm dz=5mm |
| Variation (%) | -0.420000 |
| SAR 10g (W/Kg) | 0.362941 |
| SAR 1g (W/Kg) | 0.617422 |
| SURFACE SAR | VOLUME SAR |

