



RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Test Result of RF Exposure Evaluation

BT mode

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK	1.344	1.36	0.000586	1.0	PASS
$\pi/4$ -DQPSK	-1.368	0.73	0.000314	1.0	PASS
8-DPSK	-2.359	0.58	0.000250	1.0	PASS

Remark: antenna gain=3.35dBi

2.4G WIFI mode

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	14.091	25.65	0.011036	1.0	PASS
802.11g	17.522	56.52	0.024318	1.0	PASS
802.11n20	17.852	60.98	0.026237	1.0	PASS
802.11n40	17.411	55.09	0.023704	1.0	PASS

Remark: 802.11b/g/n antenna gain=3.35dBi

5.2G WIFI mode

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a	8.078	6.42	0.002267	1.0	PASS
802.11n20	7.931	6.21	0.002192	1.0	PASS
802.11n40	9.343	8.60	0.003034	1.0	PASS
802.11ac20	7.846	6.09	0.002149	1.0	PASS
802.11ac40	9.318	8.55	0.003017	1.0	PASS

Remark: 802.11a/n/ac antenna gain=2.49dBi



5.8G WIFI mode

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a	10.355	10.85	0.003830	1.0	PASS
802.11n20	10.381	10.92	0.003853	1.0	PASS
802.11n40	10.689	11.72	0.004137	1.0	PASS
802.11ac20	10.396	10.95	0.003867	1.0	PASS
802.11ac40	10.659	11.64	0.004108	1.0	PASS

Remark: 802.11a/n/ac antenna gain=2.49dBi

Note:5G&2.4G antenna does not support simultaneous operation, 5G antenna does not work when 2.4G antenna is working, 5G antenna does not work when 2.4G antenna is working.