

RF EXPOSURE REPORT



Report No.: 15070226-FCC-H1

Supersede Report No.: N/A

Applicant	KINGTA TECHNOLOGY CO.,LIMITED	
Product Name	Bluetooth Speaker	
Model No.	8034423	
Serial No.	SPBW1035 B18 20510 , 20511, 20512,Extreme Pump H2O ,Escape, UB-SPB15, BT- 018MW,KB102H,B1,B3D,B6H,B9H,B25,B26,B28 ,B30, B38,B39, B55,B52,B58,B68 ,YA3300,WS-4014,Blunote 2.0,NU-024, 3134	
Test Standard	FCC 2.1093	
Test Date	April 8 to April 14, 2015	
Issue Date	April 15, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
<i>Wiky.Jam</i>	<i>Chris You</i>	
Wiky Jam Test Engineer	Chris You Checked By	
<p>This test report may be reproduced in full only</p> <p>Test result presented in this test report is applicable to the tested sample only</p>		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070226-FCC-H1
Page	3 of 8

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1093 - MAXIMUM PERMISSIBLE EXPOSURE.....	7
5.1 RF EXPOSURE.....	7
5.2 TEST RESULT	8

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070226-FCC-H1	NONE	Original	April 15, 2015

2. Customer information

Applicant Name	KINGTA TECHNOLOGY CO.,LIMITED
Applicant Add	FLOOR 4,BUILDING 9,FUTING INDUSTRIAL ZONE,ZHUCUN,GUANLAN,BAO' AN ,SHENZHEN
Manufacturer	KINGTA TECHNOLOGY CO.,LIMITED
Manufacturer Add	FLOOR 4,BUILDING 9,FUTING INDUSTRIAL ZONE,ZHUCUN,GUANLAN,BAO' AN ,SHENZHEN

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Speaker
Main Model:	8034423
Serial Model:	SPBW1035 B18 20510 , 20511, 20512,Extreme Pump H2O ,Escape, UB-SPB15, BT-018MW,KB102H,B1,B3D,B6H,B9H,B25,B26,B28 ,B30, B38,B39, B55,B52,B58,B68 ,YA3300,WS-4014,Blunote 2.0,NU-024, 3134
Date EUT received:	April 7, 2015
Test Date(s):	April 8 to April 14, 2015
Antenna Gain:	Bluetooth: 0 dBi
Type of Modulation:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
RF Operating Frequency (ies):	Bluetooth: 2402-2480 MHz
Number of Channels:	Bluetooth: 79CH
Port:	Power Port, Earphone Port, USB Port
Input Power:	Battery: Model: ZKH523450AR Spec: 3.7V 1000mAh Limited charger voltage: 4.2V
Trade Name :	NA
GPRS/EGPRS Multi-slot class	N/A
FCC ID:	2AEKUB29

5. FCC §2.1093 - Maximum Permissible exposure

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-7.976	-8±1	-7	0.20	0.06	3
	Mid	2441	-10.0	-10±1	-9	0.126	0.04	3
	High	2480	-9.793	-10±1	-9	0.126	0.04	3
π /4 DQPSK	Low	2402	-8.249	-8±1	-7	0.20	0.06	3
	Mid	2441	-10.11	-10±1	-9	0.126	0.04	3
	High	2480	-10.08	-10±1	-9	0.126	0.04	3
8-DPSK	Low	2402	-8.23	-8±1	-7	0.20	0.06	3
	Mid	2441	-10.16	-10±1	-9	0.126	0.04	3
	High	2480	-10.04	-10±1	-9	0.126	0.04	3

Result: Compliance

No SAR measurement is required.