

NOTES:

1. DIMENSIONING AND TOLERANCING UNLESS OTHERWISE SPECIFIED:  
A. THE CORRESPONDING 3-D DATABASE IS BASIC  
B. SURFACE PROFILE UNLESS OTHERWISE SPECIFIED  
DIMENSIONS 0.0 UP TO 3.000" 

	.005	A	B	C
--	------	---	---	---

  
DIMENSIONS 3.001 TO 5.000": 

	.007	A	B	C
--	------	---	---	---

  
DIMENSIONS OVER 5.000": 

	.010	A	B	C
--	------	---	---	---

  
C. ALL UNTOLERANCED DIMENSIONS ARE BASIC  
D. ALL CORNER RADII NOT INDICATED IN 3D DATABASE ARE TO BE R0.005in MAX
2. MATERIAL: PC+ABS; COLOR: BLACK  
SmallHD APPROVED EQUIVALENT SIMILAR TO:  
SABIC CYCOLOY C1200HF -OR- CHIMEI WONDERLOY PC-385  
PAINT EXTERNAL SURFACES USING CLEAR RUBBERIZED PAINT.
3. ALL MATERIALS MUST COMPLY WITH EU DIRECTIVE 2011/65/EU -  
REDUCTION OF HAZARDOUS SUBSTANCES (RoHS2).
4. SURFACE APPEARANCE  
A. GENERAL SURFACE FINISH WHERE NOT OTHERWISE SPECIFIED  
SHALL BE SUFFICIENT TO FACILITATE PART EJECTION.  
B. SPECIAL SURFACE FINISH REQUIREMENTS AS INDICATED  

[ X ]

FINISH A \_\_ VDI-24 \_\_\_\_  

[ ]

FINISH B \_\_\_\_  

[ ]

FINISH C \_\_\_\_
5. IDENTIFICATION MARKINGS  
A. TEXT: DEPTH < 0.010", MUST BE SUB-FLUSH (MAY NOT PROTRUDE)  
B. MARKINGS  

[ ]

PART NUMBER  

[ X ]

REVISION (IN ACCORDANCE WITH THIS DOCUMENT)  

[ ]

DATE CODE (YYWW)  

[ X ]

CAVITY NUMBER (I, II, III, IV, etc)  

[ ]

MATERIAL AND RECYCLE SYMBOL

C. THE LOCATION OF THE CAVITY MARK SHALL NOT BE ON ANY  
COSMETIC SURFACES  
AND WILL BE SPECIFIED IF CRITICAL.

D. LOCATION OF MARKINGS TO BE APPROVED PRIOR TO  
MANUFACTURE.

E. IF A CAVITY IS REPLACED, THE REPLACEMENT SHALL BEAR A  
MARKING DIFFERENT FROM ANY OTHER, INCLUDING THE  
ORIGINAL.
6. PARTING LINE MISMATCH NOT TO EXCEED .005in
7. LOCATION OF GATES AND EJECTOR PINS TO BE APPROVED BY SMALLHD
8. EJECTOR PIN MARKS AND EJECTOR FLASH (UNLESS OTHERWISE SPECIFIED) MARKS  
ACCEPTABLE TO 0.05MM RAISED TO 0.20MM DEPRESSED
9. GATE VESTIGE FLUSH TO BELOW SURFACE
10. FLASH PERMITTED TO .002in MAX/SIDE
11. CLEANLINESS: PARTS ARE TO BE FREE OF OIL, DUST, WAX, ETC
12. PART TO BE FREE OF BURRS AND SHARP EDGES FOR SAFE HANDLING
13. QUALIFICATION  
A. ( S T ) INDICATES DIMENSIONS AND/OR CRITERIA WHICH MUST BE CONTROLLED  
THROUGH S.P.C. METHODS AND MAINTAIN A Cpk VALUE OF 1.33
14. PACKING AND SHIPPING, UNLESS OTHERWISE SPECIFIED  
A. PARTS SHALL BE FREE AND CLEAN OF ALL FOREIGN MATTER  
B. PARTS MUST BE ADEQUATELY PACKAGED TO PREVENT DAMAGE DURING SHIPPING AND  
HANDLING  
C. PART NUMBER, REVISION LETTER, SUPPLIER CODE, AND DATE CODE TO BE MARKED ON  
EACH PACKAGE

ALL CAVITY-SIDE SURFACES ARE  
COSMETIC , EXCEPT AS NOTED  
(SEE NOTES 2 & 4)

PERMITTED GATE AREA

PART MARKING  
SEE NOTE-5

REVISIONS			
REV.	DATE	DESCRIPTION	APPROVED
P1A	4/10/2019	INITIAL 3D PRINT RELEASE FOR TRADE SHOW	SPL
P2B	7/2/2019	INITIAL TOOLING RELEASE	SPL
P3A	9/27/2019	INCREASE RIB WALL THICKNESS TO IMPROVE MOLD FLOW ADDED BATTERY CONTACT + & -	SPL
P4A	11/13/2019	ADDED FCC MARKING AND UPDATED PAINT MASK DETAIL	SPL

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Small HD, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IN OF Small HD, LLC IS PROHIBITED.		MATERIAL SEE NOTES 2		DESCRIPTION CINE7 REMOTE COVER	
THIRD ANGLE PROJECTION				DRAWN BY S.LYNCH	
TOLERANCES: UNLESS OTHERWISE SPECIFIED		X.XXX: ± .005 X.XX: ± .010		DESIGNED BY S.LYNCH	
UNITS: in		GEOMETRIC TOLERANCING PER ASME Y14.5m-2009		DOCUMENT NUMBER DRW-CINE7-REMOTE-COVER_P4A	
SCALE 3:1 P4A		SIZE D SHEET 1 of 4			

MODEL INFORMATION MUST BE LEGIBLE AFTER PAINTING  
NO POOLING OF PAINT PERMITTED

PAINT MASK THIS AREA

MODEL: ACC-REMOTE-C7T  
FCC ID: 2AELXC7RMT IC: 20120-C7RMT

**GRAPHICS VIEW**