



# FCC RADIO TEST REPORT

**FCC ID** : 2AEM4-5170111  
**Equipment** : Wireless Router  
**Brand Name** : eero  
**Model Name** : SN10001  
**Applicant** : eero LLC  
660 3rd Street, 4th Floor, San Francisco, CA, USA  
**Manufacturer** : eero LLC  
660 3rd Street, 4th Floor, San Francisco, CA, USA  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Apr. 29, 2024 and testing was performed from May 09, 2024 to Jun. 13, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**Sporton International Inc. Wensan Laboratory**

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>History of this test report.....</b>                          | <b>3</b>  |
| <b>Summary of Test Result.....</b>                               | <b>4</b>  |
| <b>1 General Description .....</b>                               | <b>5</b>  |
| 1.1 Product Feature of Equipment Under Test.....                 | 5         |
| 1.2 Modification of EUT .....                                    | 6         |
| 1.3 Testing Location .....                                       | 6         |
| 1.4 Applicable Standards.....                                    | 6         |
| <b>2 Test Configuration of Equipment Under Test .....</b>        | <b>7</b>  |
| 2.1 Carrier Frequency and Channel .....                          | 7         |
| 2.2 Test Mode.....                                               | 8         |
| 2.3 Connection Diagram of Test System.....                       | 10        |
| 2.4 Support Unit used in test configuration and system .....     | 10        |
| 2.5 EUT Operation Test Setup .....                               | 11        |
| 2.6 Measurement Results Explanation Example.....                 | 11        |
| <b>3 Test Result .....</b>                                       | <b>12</b> |
| 3.1 6dB and 99% Bandwidth Measurement .....                      | 12        |
| 3.2 Output Power Measurement.....                                | 13        |
| 3.3 Power Spectral Density Measurement .....                     | 14        |
| 3.4 Conducted Band Edges and Spurious Emission Measurement ..... | 16        |
| 3.5 Radiated Band Edges and Spurious Emission Measurement .....  | 17        |
| 3.6 AC Conducted Emission Measurement.....                       | 22        |
| 3.7 Antenna Requirements .....                                   | 24        |
| <b>4 List of Measuring Equipment.....</b>                        | <b>25</b> |
| <b>5 Measurement Uncertainty .....</b>                           | <b>26</b> |
| <b>Appendix A. Conducted Test Results</b>                        |           |
| <b>Appendix B. AC Conducted Emission Test Result</b>             |           |
| <b>Appendix C. Radiated Spurious Emission Test Data</b>          |           |
| <b>Appendix D. Duty Cycle Plots</b>                              |           |



## History of this test report

| Report No. | Version | Description                                                                                          | Issue Date    |
|------------|---------|------------------------------------------------------------------------------------------------------|---------------|
| FR422010B  | 01      | Initial issue of report                                                                              | Jun. 25, 2024 |
| FR422010B  | 02      | Revise Equipment<br>This report is an updated version, replacing the report issued on Jun. 25, 2024. | Aug. 21, 2024 |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |
|            |         |                                                                                                      |               |

## Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items                                         | Result (PASS/FAIL) | Remark                                 |
|---------------|-----------------|----------------------------------------------------|--------------------|----------------------------------------|
| 3.1           | 15.247(a)(2)    | 6dB Bandwidth                                      | Pass               | -                                      |
| 3.1           | 2.1049          | 99% Occupied Bandwidth                             | Reporting only     | -                                      |
| 3.2           | 15.247(b)       | Power Output Measurement                           | Pass               | -                                      |
| 3.3           | 15.247(e)       | Power Spectral Density                             | Pass               | -                                      |
| 3.4           | 15.247(d)       | Conducted Band Edges                               | Pass               | -                                      |
|               |                 | Conducted Spurious Emission                        | Pass               | -                                      |
| 3.5           | 15.247(d)       | Radiated Band Edges and Radiated Spurious Emission | Pass               | 0.36 dB under the limit at 2483.81 MHz |
| 3.6           | 15.207          | AC Conducted Emission                              | Pass               | 11.90 dB under the limit at 0.80 MHz   |
| 3.7           | 15.203          | Antenna Requirement                                | Pass               | -                                      |

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Yun Huang**

**Report Producer: Ming Chen**



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

| Product Feature                                                                                                                                                                                               |                 |                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------|
| <b>General Specs</b><br>Bluetooth-LE, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax/be, Wi-Fi 5GHz 802.11a/n/ac/ax/be, and IEEE 802.15.4.                                                                                    |                 |                                                                   |
| <b>Antenna Type</b><br>WLAN:<br><5G_Ant. 0>: Dipole Antenna<br><2.4G_Ant. 0 and 5G_Ant. 1>: Dipole Antenna<br><2.4G_Ant. 1 >: Dipole Antenna<br>Bluetooth-LE: Dipole Antenna<br>IEEE 802.15.4: Dipole Antenna |                 |                                                                   |
| Antenna information                                                                                                                                                                                           |                 |                                                                   |
| 2400 MHz ~ 2483.5 MHz                                                                                                                                                                                         | Peak Gain (dBi) | <2.4G_Ant0>: 2.13<br><2.4G_Ant1>: 3.14                            |
| Antenna information for Directional Gain                                                                                                                                                                      |                 |                                                                   |
| 2400 MHz ~ 2483.5 MHz                                                                                                                                                                                         | Peak Gain (dBi) | <2.4G_Ant0 + 2.4G_Ant1 ><br>Correlated:4.21<br>Uncorrelated: 1.30 |

**Remark:** The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.



## 1.2 Modification of EUT

No modifications made to the EUT during the testing.

## 1.3 Testing Location

|                    |                                                                                                                           |
|--------------------|---------------------------------------------------------------------------------------------------------------------------|
| Test Site          | Sporton International Inc. EMC & Wireless Communications Laboratory                                                       |
| Test Site Location | No.52, Huaya 1st Rd., Guishan Dist.,<br>Taoyuan City 333, Taiwan (R.O.C.)<br>TEL: +886-3-327-3456<br>FAX: +886-3-328-4978 |
| Test Site No.      | <b>Sporton Site No.</b><br>CO05-HY (TAF Code:1190)                                                                        |
| Remark             | The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory. |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

|                    |                                                                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site          | Sporton International Inc. Wensan Laboratory                                                                                                     |
| Test Site Location | No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist.,<br>Taoyuan City 333010, Taiwan (R.O.C.)<br>TEL: +886-3-327-0868<br>FAX: +886-3-327-0855 |
| Test Site No.      | <b>Sporton Site No.</b><br>TH05-HY, 03CH22-HY                                                                                                    |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

## 1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

### Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

| Frequency Band  | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) |
|-----------------|---------|----------------|---------|----------------|
| 2400-2483.5 MHz | 1       | 2412           | 7       | 2442           |
|                 | 2       | 2417           | 8       | 2447           |
|                 | 3       | 2422           | 9       | 2452           |
|                 | 4       | 2427           | 10      | 2457           |
|                 | 5       | 2432           | 11      | 2462           |
|                 | 6       | 2437           |         |                |



## 2.2 Test Mode

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n is smaller than 802.11ac mode, so all other conducted and radiated test is covered by 802.11ac mode.

The power for 802.11ax mode is smaller than 802.11be mode, so all other conducted and radiated test is covered by 802.11be mode.

**The final test modes include the worst data rates for each modulation shown in the table below.**

### MIMO Mode

| Modulation                            | Data Rate |
|---------------------------------------|-----------|
| 802.11b                               | 1 Mbps    |
| 802.11g                               | 6 Mbps    |
| 802.11n HT20 (Covered by VHT20)       | MCS0      |
| 802.11n HT40 (Covered by VHT40)       | MCS0      |
| 802.11ac VHT20                        | MCS0      |
| 802.11ac VHT40                        | MCS0      |
| 802.11ax HE20 (Covered by EHT20 Mode) | MCS0      |
| 802.11ax HE40 (Covered by EHT40 Mode) | MCS0      |
| 802.11be EHT20                        | MCS0      |
| 802.11be EHT40                        | MCS0      |


| Test Cases                           |                                                            |
|--------------------------------------|------------------------------------------------------------|
| <b>AC<br/>Conducted<br/>Emission</b> | Mode 1 : WLAN (2.4GHz) Link + PoE Power Injector (C510011) |

| Ch. #  | 2400-2483.5 MHz |         |                |                |
|--------|-----------------|---------|----------------|----------------|
|        | 802.11b         | 802.11g | 802.11ac VHT20 | 802.11ac VHT40 |
| Low    | 01              | 01      | 01             | 03             |
|        | -               | 02      | 02             | -              |
| Middle | 06              | 06      | 06             | 06             |
| High   | 11              | 09      | -              | 09             |
|        | -               | 10      | 10             | -              |
|        | -               | 11      | 11             | -              |

| Ch. #  | 2400-2483.5 MHz |                |
|--------|-----------------|----------------|
|        | 802.11be EHT20  | 802.11be EHT40 |
| Low    | 01              | 03             |
|        | 02              | -              |
|        | 03              | -              |
| Middle | 06              | 06             |
| High   | 09              | 09             |
|        | 10              | -              |
|        | 11              | -              |

**Remark:** For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

| Item | Equipment    | Brand Name  | Model Name              | FCC ID             | Data Cable | Power Cord                                                 |
|------|--------------|-------------|-------------------------|--------------------|------------|------------------------------------------------------------|
| 1.   | Notebook     | DELL        | Latitude 3420           | FCC DoC            | N/A        | AC I/P:<br>Unshielded, 1.2 m<br>DC O/P:<br>Shielded, 1.8 m |
| 2.   | Notebook     | Lenovo      | IdeaPad Gaming 3 15IHU6 | FCC DoC            | N/A        | AC I/P:<br>Unshielded, 1.2 m<br>DC O/P:<br>Shielded, 1.8 m |
| 3.   | PoE INJECTOR | eero        | POE-PTTI-3055NDN        | FCC DOC            | N/A        | N/A                                                        |
| 4.   | Mobile Phone | Apple       | A1586                   | BCG-E2816A         | N/A        | N/A                                                        |
| 5.   | Button       | SmartThings | IM6001-BTP01            | 2AF4S-IM6001-BTP01 | N/A        | N/A                                                        |



## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT Version 4.0.95.1” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


### 3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.



### **3.3 Power Spectral Density Measurement**

#### **3.3.1 Limit of Power Spectral Density**

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

#### **3.3.2 Measuring Instruments**

Please refer to the measuring equipment list in this test report.


#### **3.3.3 Test Procedures**

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add  $10 \log(N_{\text{ANT}})$  dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity  $10 \log(N_{\text{ANT}})$  dB is added to each spectrum value before comparing to the emission limit. The addition of  $10 \log(N_{\text{ANT}})$  dB serves to apportion the emission limit among the  $N_{\text{ANT}}$  outputs so that each output is permitted to contribute no more than  $1/N_{\text{ANT}}^{\text{th}}$  of the PSD limit .

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


### 3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

### 3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup



### 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490      | 2400/F(kHz)                          | 300                              |
| 0.490 – 1.705      | 24000/F(kHz)                         | 30                               |
| 1.705 – 30.0       | 30                                   | 30                               |
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

#### 3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

#### 3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.



7. Use the following spectrum analyzer settings:


For average measurement:

The procedure for method trace averaging is as follows:


- a) RBW = 1 MHz.
- b) VBW  $\geq [3 \times \text{RBW}]$ .
- c) Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq \text{RBW} / 2$ . Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging).
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of  $1 / D$ , where  $D$  is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - i. If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where  $D$  is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
  - ii. If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

### 3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





### **3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

### **3.5.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C.

### **3.5.7 Duty Cycle**

Please refer to Appendix D.

### **3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix C.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of Emission<br>(MHz) | Conducted Limit (dB $\mu$ V) |           |
|--------------------------------|------------------------------|-----------|
|                                | Quasi-Peak                   | Average   |
| 0.15-0.5                       | 66 to 56*                    | 56 to 46* |
| 0.5-5                          | 56                           | 46        |
| 5-30                           | 60                           | 50        |

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

#### 3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.



## 4 List of Measuring Equipment

| Instrument                       | Brand Name      | Model No.               | Serial No.                 | Characteristics               | Calibration Date | Test Date                   | Due Date      | Remark                |
|----------------------------------|-----------------|-------------------------|----------------------------|-------------------------------|------------------|-----------------------------|---------------|-----------------------|
| AC Power Source                  | ChainTek        | APC-1000W               | N/A                        | N/A                           | N/A              | May 09, 2024                | N/A           | Conduction (CO05-HY)  |
| EMI Test Receiver                | Rohde & Schwarz | ESR3                    | 102388                     | 9kHz~3.6GHz                   | Dec. 06, 2023    | May 09, 2024                | Dec. 05, 2024 | Conduction (CO05-HY)  |
| Hygrometer                       | Testo           | 608-H1                  | 34913912                   | N/A                           | Oct. 26, 2023    | May 09, 2024                | Oct. 25, 2024 | Conduction (CO05-HY)  |
| LISN                             | Rohde & Schwarz | ENV216                  | 100081                     | 9kHz~30MHz                    | Nov. 22, 2023    | May 09, 2024                | Nov. 21, 2024 | Conduction (CO05-HY)  |
| Software                         | Rohde & Schwarz | EMC32                   | N/A                        | N/A                           | N/A              | May 09, 2024                | N/A           | Conduction (CO05-HY)  |
| Pulse Limiter                    | SCHWARZBECK     | VTSD 9561-FN            | 00691                      | N/A                           | Jul. 28, 2023    | May 09, 2024                | Jul. 27, 2024 | Conduction (CO05-HY)  |
| LISN Cable                       | MVE             | RG-400                  | 260260                     | N/A                           | Dec. 28, 2023    | May 09, 2024                | Dec. 27, 2024 | Conduction (CO05-HY)  |
| Hygrometer                       | TECPEL          | DTM-303A                | TP201996                   | N/A                           | Nov. 07, 2023    | May 29, 2024~Jun. 12, 2024  | Nov. 06, 2024 | Conducted (TH05-HY)   |
| Power Sensor                     | DARE            | RPR3006W                | 15I00041SNO10 (NO:248)     | 10MHz~6GHz                    | Jan. 10, 2024    | May 29, 2024~Jun. 12, 2024  | Jan. 09, 2025 | Conducted (TH05-HY)   |
| Signal Analyzer                  | Rohde & Schwarz | FSV40                   | 101566                     | 10Hz~40GHz                    | Aug. 23, 2023    | May 29, 2024~Jun. 12, 2024  | Aug. 22, 2024 | Conducted (TH05-HY)   |
| Loop Antenna                     | Rohde & Schwarz | HFH2-Z2                 | 100488                     | 9kHz~30MHz                    | Sep. 12, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Sep. 11, 2024 | Radiation (03CH22-HY) |
| Bilog Antenna with 6dB           | TESEQ & WOKEN   | CBL 6111D & 00802N1D-06 | 63304 & 002                | 30MHz~1GHz                    | Oct. 15, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Oct. 14, 2024 | Radiation (03CH22-HY) |
| Amplifier                        | SONOMA          | 310N                    | 421581                     | N/A                           | Jul. 15, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Jul. 14, 2024 | Radiation (03CH22-HY) |
| Double Ridged Guide Horn Antenna | RFSPIN          | DRH18-E                 | LE2C04A18EN                | 1GHz~18GHz                    | Jul. 12, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Jul. 11, 2024 | Radiation (03CH22-HY) |
| SHF-EHF Horn Antenna             | SCHWARZBECK     | BBHA 9170               | 1224                       | 18GHz~40GHz                   | Jul. 10, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Jul. 09, 2024 | Radiation (03CH22-HY) |
| Amplifier                        | EMEC            | EM01G18GA               | 060877                     | N/A                           | Sep. 28, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Sep. 27, 2024 | Radiation (03CH22-HY) |
| Preamplifier                     | EMEC            | EM18G40G                | 060872                     | 18-40GHz                      | Sep. 06, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Sep. 05, 2024 | Radiation (03CH22-HY) |
| Signal Analyzer                  | Keysight        | N9010B                  | MY60241058                 | 10Hz~44GHz                    | Jul. 06, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Jul. 05, 2024 | Radiation (03CH22-HY) |
| Hygrometer                       | TECPEL          | DTM-303A                | TP211469                   | N/A                           | Jan. 03, 2024    | Jun. 08, 2024~Jun. 13, 2024 | Jan. 02, 2025 | Radiation (03CH22-HY) |
| Controller                       | EMEC            | EM1000                  | N/A                        | Control Turn table & Ant Mast | N/A              | Jun. 08, 2024~Jun. 13, 2024 | N/A           | Radiation (03CH22-HY) |
| Antenna Mast                     | ChainTek        | MBS-520-1               | N/A                        | 1m~4m                         | N/A              | Jun. 08, 2024~Jun. 13, 2024 | N/A           | Radiation (03CH22-HY) |
| Turn Table                       | ChainTek        | T-200-S-1               | N/A                        | 0~360 Degree                  | N/A              | Jun. 08, 2024~Jun. 13, 2024 | N/A           | Radiation (03CH22-HY) |
| Software                         | Audix           | E3 6.09824_2019122      | RK-002347                  | N/A                           | N/A              | Jun. 08, 2024~Jun. 13, 2024 | N/A           | Radiation (03CH22-HY) |
| RF Cable                         | HUBER + SUHNER  | SUCOFLEX 102            | 803951/2                   | 9kHz~30MHz                    | Mar. 06, 2024    | Jun. 08, 2024~Jun. 13, 2024 | Mar. 05, 2025 | Radiation (03CH22-HY) |
| RF Cable                         | HUBER + SUHNER  | SUCOFLEX 102            | 804390/2,804611/2,804615/2 | N/A                           | Oct. 24, 2023    | Jun. 08, 2024~Jun. 13, 2024 | Oct. 23, 2024 | Radiation (03CH22-HY) |



## 5 Measurement Uncertainty

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 3.5 dB |
|----------------------------------------------------------------------------|--------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 6.5 dB |
|----------------------------------------------------------------------------|--------|

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 4.5 dB |
|----------------------------------------------------------------------------|--------|

### Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 4.5 dB |
|----------------------------------------------------------------------------|--------|

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 5.4 dB |
|----------------------------------------------------------------------------|--------|

**Appendix A. Test Result of Conducted Test Items**

|                |                      |                    |       |    |
|----------------|----------------------|--------------------|-------|----|
| Test Engineer: | Eason Huang          | Temperature:       | 21~25 | °C |
| Test Date:     | 2024/5/29~2024/06/12 | Relative Humidity: | 51~54 | %  |

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

| 2.4GHz Band MIMO |           |     |     |             |                       |       |              |       |                    |           |
|------------------|-----------|-----|-----|-------------|-----------------------|-------|--------------|-------|--------------------|-----------|
| Mod.             | Data Rate | NTX | CH. | Freq. (MHz) | 99% Occupied BW (MHz) |       | 6dB BW (MHz) |       | 6dB BW Limit (MHz) | Pass/Fail |
|                  |           |     |     |             | Ant0                  | Ant1  | Ant0         | Ant1  |                    |           |
| 11b              | 1Mbps     | 2   | 1   | 2412        | 13.14                 | 13.19 | 7.52         | 8.07  | 0.50               | Pass      |
| 11b              | 1Mbps     | 2   | 6   | 2437        | 13.19                 | 13.09 | 8.02         | 8.07  | 0.50               | Pass      |
| 11b              | 1Mbps     | 2   | 11  | 2462        | 13.14                 | 13.04 | 7.57         | 8.01  | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 1   | 2412        | 17.13                 | 17.18 | 15.07        | 15.65 | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 2   | 2417        | 17.08                 | 16.98 | 15.04        | 15.07 | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 6   | 2437        | 16.93                 | 17.03 | 15.08        | 15.07 | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 9   | 2452        | 17.13                 | 17.03 | 15.11        | 15.10 | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 10  | 2457        | 16.98                 | 16.83 | 15.08        | 15.07 | 0.50               | Pass      |
| 11g              | 6Mbps     | 2   | 11  | 2462        | 17.03                 | 17.23 | 15.09        | 15.09 | 0.50               | Pass      |
| VHT20            | MCS0      | 2   | 1   | 2412        | 18.08                 | 18.03 | 15.86        | 15.59 | 0.50               | Pass      |
| VHT20            | MCS0      | 2   | 2   | 2417        | 18.08                 | 17.83 | 15.10        | 15.08 | 0.50               | Pass      |
| VHT20            | MCS0      | 2   | 6   | 2437        | 18.03                 | 18.13 | 18.82        | 15.84 | 0.50               | Pass      |
| VHT20            | MCS0      | 2   | 10  | 2457        | 18.08                 | 17.83 | 15.10        | 15.08 | 0.50               | Pass      |
| VHT20            | MCS0      | 2   | 11  | 2462        | 17.93                 | 18.18 | 15.07        | 16.02 | 0.50               | Pass      |
| VHT40            | MCS0      | 2   | 3   | 2422        | 36.76                 | 36.76 | 35.05        | 35.06 | 0.50               | Pass      |
| VHT40            | MCS0      | 2   | 6   | 2437        | 36.86                 | 37.26 | 35.08        | 35.86 | 0.50               | Pass      |
| VHT40            | MCS0      | 2   | 9   | 2452        | 36.96                 | 36.96 | 35.11        | 35.08 | 0.50               | Pass      |

**TEST RESULTS DATA**  
**Average Output Power**

| 2.4GHz Band MIMO |           |     |     |             |                               |       |       |                             |      |          |      |                  |      |                        |      |            |
|------------------|-----------|-----|-----|-------------|-------------------------------|-------|-------|-----------------------------|------|----------|------|------------------|------|------------------------|------|------------|
| Mod.             | Data Rate | NTX | CH. | Freq. (MHz) | Average Conducted Power (dBm) |       |       | Conducted Power Limit (dBm) |      | DG (dBi) |      | EIRP Power (dBm) |      | EIRP Power Limit (dBm) |      | Pass /Fail |
|                  |           |     |     |             | Ant0                          | Ant1  | SUM   | Ant0                        | Ant1 | Ant0     | Ant1 | Ant0             | Ant1 | Ant0                   | Ant1 |            |
| 11b              | 1Mbps     | 2   | 1   | 2412        | 20.90                         | 21.10 | 24.01 | 30.00                       |      | 1.30     |      | 25.31            |      | 36.00                  |      | Pass       |
| 11b              | 1Mbps     | 2   | 6   | 2437        | 21.70                         | 22.20 | 24.97 | 30.00                       |      | 1.30     |      | 26.27            |      | 36.00                  |      | Pass       |
| 11b              | 1Mbps     | 2   | 11  | 2462        | 21.00                         | 21.00 | 24.01 | 30.00                       |      | 1.30     |      | 25.31            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 1   | 2412        | 17.80                         | 18.00 | 20.91 | 30.00                       |      | 1.30     |      | 22.21            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 2   | 2417        | 19.20                         | 19.20 | 22.21 | 30.00                       |      | 1.30     |      | 23.51            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 6   | 2437        | 21.60                         | 22.20 | 24.92 | 30.00                       |      | 1.30     |      | 26.22            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 9   | 2452        | 19.60                         | 19.70 | 22.66 | 30.00                       |      | 1.30     |      | 23.96            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 10  | 2457        | 18.20                         | 18.50 | 21.36 | 30.00                       |      | 1.30     |      | 22.66            |      | 36.00                  |      | Pass       |
| 11g              | 6Mbps     | 2   | 11  | 2462        | 18.10                         | 18.10 | 21.11 | 30.00                       |      | 1.30     |      | 22.41            |      | 36.00                  |      | Pass       |
| HT20             | MCS0      | 2   | 1   | 2412        | 17.40                         | 18.20 | 20.83 | 30.00                       |      | 1.30     |      | 22.13            |      | 36.00                  |      | Pass       |
| HT20             | MCS0      | 2   | 2   | 2417        | 19.00                         | 19.20 | 22.11 | 30.00                       |      | 1.30     |      | 23.41            |      | 36.00                  |      | Pass       |
| HT20             | MCS0      | 2   | 6   | 2437        | 21.40                         | 22.20 | 24.83 | 30.00                       |      | 1.30     |      | 26.13            |      | 36.00                  |      | Pass       |
| HT20             | MCS0      | 2   | 10  | 2457        | 18.80                         | 19.00 | 21.91 | 30.00                       |      | 1.30     |      | 23.21            |      | 36.00                  |      | Pass       |
| HT20             | MCS0      | 2   | 11  | 2462        | 17.60                         | 17.20 | 20.41 | 30.00                       |      | 1.30     |      | 21.71            |      | 36.00                  |      | Pass       |
| HT40             | MCS0      | 2   | 3   | 2422        | 16.40                         | 16.60 | 19.51 | 30.00                       |      | 1.30     |      | 20.81            |      | 36.00                  |      | Pass       |
| HT40             | MCS0      | 2   | 6   | 2437        | 16.50                         | 17.10 | 19.82 | 30.00                       |      | 1.30     |      | 21.12            |      | 36.00                  |      | Pass       |
| HT40             | MCS0      | 2   | 9   | 2452        | 16.10                         | 16.30 | 19.21 | 30.00                       |      | 1.30     |      | 20.51            |      | 36.00                  |      | Pass       |
| VHT20            | MCS0      | 2   | 1   | 2412        | 17.50                         | 18.30 | 20.93 | 30.00                       |      | 1.30     |      | 22.23            |      | 36.00                  |      | Pass       |
| VHT20            | MCS0      | 2   | 2   | 2417        | 19.10                         | 19.30 | 22.21 | 30.00                       |      | 1.30     |      | 23.51            |      | 36.00                  |      | Pass       |
| VHT20            | MCS0      | 2   | 6   | 2437        | 21.50                         | 22.30 | 24.93 | 30.00                       |      | 1.30     |      | 26.23            |      | 36.00                  |      | Pass       |
| VHT20            | MCS0      | 2   | 10  | 2457        | 18.90                         | 19.10 | 22.01 | 30.00                       |      | 1.30     |      | 23.31            |      | 36.00                  |      | Pass       |
| VHT20            | MCS0      | 2   | 11  | 2462        | 17.70                         | 17.30 | 20.51 | 30.00                       |      | 1.30     |      | 21.81            |      | 36.00                  |      | Pass       |
| VHT40            | MCS0      | 2   | 3   | 2422        | 16.50                         | 16.70 | 19.61 | 30.00                       |      | 1.30     |      | 20.91            |      | 36.00                  |      | Pass       |
| VHT40            | MCS0      | 2   | 6   | 2437        | 16.60                         | 17.20 | 19.92 | 30.00                       |      | 1.30     |      | 21.22            |      | 36.00                  |      | Pass       |
| VHT40            | MCS0      | 2   | 9   | 2452        | 16.20                         | 16.40 | 19.31 | 30.00                       |      | 1.30     |      | 20.61            |      | 36.00                  |      | Pass       |

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Peak Power Spectral Density**

| 2.4GHz Band MIMO |           |     |     |             |                     |        |              |          |      |                           |      |           |
|------------------|-----------|-----|-----|-------------|---------------------|--------|--------------|----------|------|---------------------------|------|-----------|
| Mod.             | Data Rate | NTX | CH. | Freq. (MHz) | Peak PSD (dBm/3kHz) |        |              | DG (dBi) |      | Peak PSD Limit (dBm/3kHz) |      | Pass/Fail |
|                  |           |     |     |             | Ant0                | Ant1   | Worse + 3.01 | Ant0     | Ant1 | Ant0                      | Ant1 |           |
| 11b              | 1Mbps     | 2   | 1   | 2412        | -1.53               | -1.99  | 1.48         | 4.21     |      | 8.00                      |      | Pass      |
| 11b              | 1Mbps     | 2   | 6   | 2437        | 0.27                | 0.94   | 3.95         | 4.21     |      | 8.00                      |      | Pass      |
| 11b              | 1Mbps     | 2   | 11  | 2462        | -1.40               | -1.35  | 1.66         | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 1   | 2412        | -4.11               | -4.59  | -1.10        | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 2   | 2417        | -3.44               | -3.85  | -0.43        | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 6   | 2437        | 0.39                | 0.48   | 3.49         | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 9   | 2452        | -1.59               | -1.48  | 1.53         | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 10  | 2457        | -3.19               | -3.45  | -0.18        | 4.21     |      | 8.00                      |      | Pass      |
| 11g              | 6Mbps     | 2   | 11  | 2462        | -4.74               | -4.75  | -1.73        | 4.21     |      | 8.00                      |      | Pass      |
| VHT20            | MCS0      | 2   | 1   | 2412        | -6.53               | -6.10  | -3.09        | 4.21     |      | 8.00                      |      | Pass      |
| VHT20            | MCS0      | 2   | 2   | 2417        | -3.72               | -3.95  | -0.71        | 4.21     |      | 8.00                      |      | Pass      |
| VHT20            | MCS0      | 2   | 6   | 2437        | -2.59               | -1.71  | 1.30         | 4.21     |      | 8.00                      |      | Pass      |
| VHT20            | MCS0      | 2   | 10  | 2457        | -4.69               | -4.32  | -1.31        | 4.21     |      | 8.00                      |      | Pass      |
| VHT20            | MCS0      | 2   | 11  | 2462        | -5.39               | -5.19  | -2.18        | 4.21     |      | 8.00                      |      | Pass      |
| VHT40            | MCS0      | 2   | 3   | 2422        | -10.07              | -9.93  | -6.92        | 4.21     |      | 8.00                      |      | Pass      |
| VHT40            | MCS0      | 2   | 6   | 2437        | -11.19              | -10.94 | -7.93        | 4.21     |      | 8.00                      |      | Pass      |
| VHT40            | MCS0      | 2   | 9   | 2452        | -11.27              | -10.91 | -7.90        | 4.21     |      | 8.00                      |      | Pass      |

Measured power density (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Average Output Power**

| 2.4GHz Band MIMO |           |     |     |             |           |                               |       |       |                             |      |          |      |                  |      |                        |      |            |
|------------------|-----------|-----|-----|-------------|-----------|-------------------------------|-------|-------|-----------------------------|------|----------|------|------------------|------|------------------------|------|------------|
| Mod.             | Data Rate | NTx | CH. | Freq. (MHz) | RU Config | Average Conducted Power (dBm) |       |       | Conducted Power Limit (dBm) |      | DG (dBi) |      | EIRP Power (dBm) |      | EIRP Power Limit (dBm) |      | Pass /Fail |
|                  |           |     |     |             |           | Ant0                          | Ant1  | SUM   | Ant0                        | Ant1 | Ant0     | Ant1 | Ant0             | Ant1 | Ant0                   | Ant1 |            |
| HE20             | MCS0      | 2   | 1   | 2412        | Full      | 17.00                         | 16.80 | 19.91 | 30.00                       |      | 1.30     |      | 21.21            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 2   | 2417        | Full      | 17.40                         | 17.60 | 20.51 | 30.00                       |      | 1.30     |      | 21.81            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 3   | 2422        | Full      | 19.10                         | 19.00 | 22.06 | 30.00                       |      | 1.30     |      | 23.36            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 6   | 2437        | Full      | 21.00                         | 21.80 | 24.43 | 30.00                       |      | 1.30     |      | 25.73            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 9   | 2452        | Full      | 18.50                         | 18.60 | 21.56 | 30.00                       |      | 1.30     |      | 22.86            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 10  | 2457        | Full      | 17.40                         | 17.40 | 20.41 | 30.00                       |      | 1.30     |      | 21.71            |      | 36.00                  |      | Pass       |
| HE20             | MCS0      | 2   | 11  | 2462        | Full      | 16.80                         | 16.50 | 19.66 | 30.00                       |      | 1.30     |      | 20.96            |      | 36.00                  |      | Pass       |
| HE40             | MCS0      | 2   | 3   | 2422        | Full      | 17.00                         | 17.30 | 20.16 | 30.00                       |      | 1.30     |      | 21.46            |      | 36.00                  |      | Pass       |
| HE40             | MCS0      | 2   | 6   | 2437        | Full      | 17.40                         | 17.90 | 20.67 | 30.00                       |      | 1.30     |      | 21.97            |      | 36.00                  |      | Pass       |
| HE40             | MCS0      | 2   | 9   | 2452        | Full      | 15.10                         | 14.90 | 18.01 | 30.00                       |      | 1.30     |      | 19.31            |      | 36.00                  |      | Pass       |

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

| 2.4GHz Band MIMO |           |                 |     |             |           |                       |       |              |       |                    |           |
|------------------|-----------|-----------------|-----|-------------|-----------|-----------------------|-------|--------------|-------|--------------------|-----------|
| Mod.             | Data Rate | N <sub>TX</sub> | CH. | Freq. (MHz) | RU Config | 99% Occupied BW (MHz) |       | 6dB BW (MHz) |       | 6dB BW Limit (MHz) | Pass/Fail |
|                  |           |                 |     |             |           | Ant0                  | Ant1  | Ant0         | Ant1  |                    |           |
| EHT20            | MCS0      | 2               | 1   | 2412        | Full      | 18.98                 | 19.18 | 15.23        | 16.75 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 2   | 2417        | Full      | 18.93                 | 19.03 | 15.07        | 15.87 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 3   | 2422        | Full      | 18.93                 | 19.03 | 15.05        | 15.84 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 6   | 2437        | Full      | 19.08                 | 19.08 | 16.08        | 17.18 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 9   | 2452        | Full      | 18.98                 | 18.98 | 15.97        | 16.51 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 10  | 2457        | Full      | 18.98                 | 19.03 | 15.80        | 16.53 | 0.50               | Pass      |
| EHT20            | MCS0      | 2               | 11  | 2462        | Full      | 18.93                 | 19.13 | 16.11        | 16.66 | 0.50               | Pass      |
| EHT40            | MCS0      | 2               | 3   | 2422        | Full      | 38.06                 | 38.06 | 35.07        | 35.08 | 0.50               | Pass      |
| EHT40            | MCS0      | 2               | 6   | 2437        | Full      | 38.26                 | 38.26 | 35.45        | 36.34 | 0.50               | Pass      |
| EHT40            | MCS0      | 2               | 9   | 2452        | Full      | 38.16                 | 37.96 | 36.27        | 35.08 | 0.50               | Pass      |

**TEST RESULTS DATA**  
**Average Output Power**

| 2.4GHz Band MIMO |           |     |     |             |           |                               |       |       |                             |      |          |      |                  |      |                        |      |            |
|------------------|-----------|-----|-----|-------------|-----------|-------------------------------|-------|-------|-----------------------------|------|----------|------|------------------|------|------------------------|------|------------|
| Mod.             | Data Rate | Ntx | CH. | Freq. (MHz) | RU Config | Average Conducted Power (dBm) |       |       | Conducted Power Limit (dBm) |      | DG (dBi) |      | EIRP Power (dBm) |      | EIRP Power Limit (dBm) |      | Pass /Fail |
|                  |           |     |     |             |           | Ant0                          | Ant1  | SUM   | Ant0                        | Ant1 | Ant0     | Ant1 | Ant0             | Ant1 | Ant0                   | Ant1 |            |
| EHT20            | MCS0      | 2   | 1   | 2412        | Full      | 17.10                         | 16.90 | 20.01 | 30.00                       |      | 1.30     |      | 21.31            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 2   | 2417        | Full      | 17.50                         | 17.70 | 20.61 | 30.00                       |      | 1.30     |      | 21.91            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 3   | 2422        | Full      | 19.20                         | 19.10 | 22.16 | 30.00                       |      | 1.30     |      | 23.46            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 6   | 2437        | Full      | 21.10                         | 21.90 | 24.53 | 30.00                       |      | 1.30     |      | 25.83            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 9   | 2452        | Full      | 18.60                         | 18.70 | 21.66 | 30.00                       |      | 1.30     |      | 22.96            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 10  | 2457        | Full      | 17.50                         | 17.50 | 20.51 | 30.00                       |      | 1.30     |      | 21.81            |      | 36.00                  |      | Pass       |
| EHT20            | MCS0      | 2   | 11  | 2462        | Full      | 16.90                         | 16.60 | 19.76 | 30.00                       |      | 1.30     |      | 21.06            |      | 36.00                  |      | Pass       |
| EHT40            | MCS0      | 2   | 3   | 2422        | Full      | 17.10                         | 17.40 | 20.26 | 30.00                       |      | 1.30     |      | 21.56            |      | 36.00                  |      | Pass       |
| EHT40            | MCS0      | 2   | 6   | 2437        | Full      | 17.50                         | 18.00 | 20.77 | 30.00                       |      | 1.30     |      | 22.07            |      | 36.00                  |      | Pass       |
| EHT40            | MCS0      | 2   | 9   | 2452        | Full      | 15.20                         | 15.00 | 18.11 | 30.00                       |      | 1.30     |      | 19.41            |      | 36.00                  |      | Pass       |

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Peak Power Spectral Density**


| 2.4GHz Band MIMO |           |                 |     |             |           |                     |        |              |          |      |                           |      |           |
|------------------|-----------|-----------------|-----|-------------|-----------|---------------------|--------|--------------|----------|------|---------------------------|------|-----------|
| Mod.             | Data Rate | N <sub>TX</sub> | CH. | Freq. (MHz) | RU Config | Peak PSD (dBm/3kHz) |        |              | DG (dBi) |      | Peak PSD Limit (dBm/3kHz) |      | Pass/Fail |
|                  |           |                 |     |             |           | Ant0                | Ant1   | Worse + 3.01 | Ant0     | Ant1 | Ant0                      | Ant1 |           |
| EHT20            | MCS0      | 2               | 1   | 2412        | Full      | -6.88               | -7.18  | -3.87        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 2   | 2417        | Full      | -7.36               | -7.31  | -4.30        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 3   | 2422        | Full      | -4.64               | -4.90  | -1.63        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 6   | 2437        | Full      | -3.48               | -3.06  | -0.05        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 9   | 2452        | Full      | -4.81               | -4.58  | -1.57        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 10  | 2457        | Full      | -6.89               | -7.27  | -3.88        | 4.21     |      | 8.00                      |      | Pass      |
| EHT20            | MCS0      | 2               | 11  | 2462        | Full      | -6.36               | -6.54  | -3.35        | 4.21     |      | 8.00                      |      | Pass      |
| EHT40            | MCS0      | 2               | 3   | 2422        | Full      | -9.15               | -8.79  | -5.78        | 4.21     |      | 8.00                      |      | Pass      |
| EHT40            | MCS0      | 2               | 6   | 2437        | Full      | -8.85               | -9.21  | -5.84        | 4.21     |      | 8.00                      |      | Pass      |
| EHT40            | MCS0      | 2               | 9   | 2452        | Full      | -11.65              | -11.91 | -8.64        | 4.21     |      | 8.00                      |      | Pass      |

Measured power density (dBm) has offset with cable loss.

**6dB and 99% Occupied Bandwidth**


MIMIO &lt;Ant. 0+1&gt;

&lt;802.11b&gt;



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


&lt;802.11g&gt;



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




## &lt;802.11ac VHT20&gt;



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


## &lt;802.11ac VHT40&gt;



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




## &lt;802.11be EHT20&gt;



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


## &lt;802.11be EHT40&gt;




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

**Power Spectral Density(dBm/3kHz)**

&lt;802.11b&gt;



&lt;802.11g&gt;







## &lt;802.11ac VHT20&gt;

## Maximum Power Density Plot (dBm/3kHz)

## MIMO Ant 0




## MIMO Ant 1




## &lt;802.11ac VHT40&gt;



## Maximum Power Density Plot (dBm/3kHz)

## MIMO Ant 0



## MIMO Ant 1







**<802.11be EHT20>**

**<802.11be EHT40>**


**Band Edges and Spurious Emission**

Number of TX = 2, Ant. 0 (Measured)

Test Mode : 802.11b

Test Channel : 01


**100kHz PSD reference Level****Low Channel Plot****Spurious Emission 30MHz~1GHz****Spurious Emission 1GHz~26.5GHz**



Test Mode : 802.11b


Test Channel : 06

## 100kHz PSD reference Level




## Middle Channel Plot

## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


## 100kHz PSD reference Level




## High Channel Plot



## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 02

## 100kHz PSD reference Level




Date: 12 JUN 2024 10:26:15

## Middle Channel Plot




Date: 12 JUN 2024 10:27:27

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 10:26:33

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 10:27:00



Test Mode : 802.11g


Test Channel : 06

## 100kHz PSD reference Level




## High Channel Plot

## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 09

## 100kHz PSD reference Level




Date: 12 JUN 2024 10:45:58

## Low Channel Plot




Date: 12 JUN 2024 10:48:46

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 10:47:46

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 10:48:13




Test Mode : 802.11g

Test Channel : 10


## 100kHz PSD reference Level




## Middle Channel Plot



## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 11

## 100kHz PSD reference Level




Date: 12 JUN 2024 11:41:41

## High Channel Plot




Date: 12 JUN 2024 11:43:03

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 11:42:05

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 11:42:30



Test Mode : 802.11ac VHT20


Test Channel : 01

## 100kHz PSD reference Level




Date: 12 JUN 2024 13:54:16

## Low Channel Plot




Date: 12 JUN 2024 13:55:51

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 13:54:43

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 13:55:17



Test Mode : 802.11ac VHT20


Test Channel : 02

## 100kHz PSD reference Level




Date: 12 JUN 2024 14:09:10

## Middle Channel Plot




Date: 12 JUN 2024 14:10:58

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 14:10:11

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 14:10:36



Test Mode : 802.11ac VHT20

Test Channel : 06


## 100kHz PSD reference Level



Date: 12 JUN 2024 14:22:44


## High Channel Plot

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 14:23:12

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 14:23:32



Test Mode : 802.11ac VHT20


Test Channel : 10

## 100kHz PSD reference Level




Date: 12 JUN 2024 14:32:02

## Low Channel Plot




Date: 12 JUN 2024 14:33:47

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 14:32:40

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 14:33:10



Test Mode : 802.11ac VHT20


Test Channel : 11

## 100kHz PSD reference Level




Date: 12 JUN 2024 14:42:04

## Middle Channel Plot




Date: 12 JUN 2024 14:43:23

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 14:42:28

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 14:42:45



Test Mode : 802.11ac VHT40


Test Channel : 03

## 100kHz PSD reference Level




Date: 12 JUN 2024 15:07:40

## Low Channel Plot




Date: 12 JUN 2024 15:09:07

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 15:08:05

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 15:08:24



Test Mode : 802.11ac VHT40


Test Channel : 06

## 100kHz PSD reference Level




## Middle Channel Plot

## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11ac VHT40


Test Channel : 09

## 100kHz PSD reference Level




Date: 12 JUN 2024 15:48:51

## High Channel Plot




Date: 12 JUN 2024 15:50:04

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 15:49:13

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 15:49:31




Test Mode : 802.11be EHT20\_FullIRU

Test Channel : 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11be EHT20\_FullIRU


Test Channel : 02

## 100kHz PSD reference Level




Date: 12 JUN 2024 16:18:26

## Middle Channel Plot




Date: 12 JUN 2024 16:19:36

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 16:19:00

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 16:19:20



Test Mode : 802.11be EHT20\_FullIRU


Test Channel : 03

## 100kHz PSD reference Level




Date: 12 JUN 2024 18:59:30

## High Channel Plot




Date: 12 JUN 2024 19:01:14

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 18:59:58

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 19:00:28



Test Mode : 802.11be EHT20\_FullIRU


Test Channel : 06

## 100kHz PSD reference Level




## Low Channel Plot

## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11be EHT20\_FullIRU


Test Channel : 09

## 100kHz PSD reference Level




Date: 12 JUN 2024 16:37:05

## Middle Channel Plot




Date: 12 JUN 2024 16:38:09

## Spurious Emission 30MHz~1GHz



Date: 12 JUN 2024 16:37:25

## Spurious Emission 1GHz~26.5GHz




Date: 12 JUN 2024 16:37:42




Test Mode : 802.11be EHT20\_FullIRU

Test Channel : 10


## 100kHz PSD reference Level



## High Channel Plot



## Spurious Emission 30MHz~1GHz



## Spurious Emission 1GHz~26.5GHz

