

# RF EXPOSURE EVALUATION REPORT

FCC ID : 2AEM4-71213573  
Equipment : Wireless router/access point  
Brand Name : eero  
Model Name : S010001  
Applicant : eero LLC  
660 3rd Street, 4th Floor, San Francisco, CA 94107  
Manufacturer : eero LLC  
660 3rd Street, 4th Floor, San Francisco, CA 94107  
Standard : 47 CFR Part 1.1307

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 1.1307 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

<b>1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>2. MAXIMUM RF AVERAGE OUTPUT POWER .....</b>	<b>4</b>
<b>3. RF EXPOSURE LIMIT INTRODUCTION .....</b>	<b>5</b>
<b>4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....</b>	<b>6</b>
4.1. Standalone Power Density Calculation .....	6



### History of this test report

Report No.	Version	Description	Issued Date
FA210727001-01	Rev. 01	Initial issue of report	Jan. 12, 2022



### 1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Wireless router/access point
Brand Name	eero
Model Name	S010001
FCC ID	2AEM4-71213573
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.5GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8GHz Band: 5725 MHz ~ 5885 MHz WLAN UNII-4: 5885 MHz ~5925 MHz WLAN 6E: 6115 MHz ~ 6425 MHz, 6425 MHz ~ 6525 MHz, 6525 MHz ~ 6875 MHz, 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz Zigbee: 2405 MHz ~ 2475 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth LE Zigbee: BPSK
SW Version	eeroOS v.6.8
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

**Reviewed by:** Jason Wang

**Report Producer:** Daisy Peng

### 2. Maximum RF average output power

Band / Channel / Frequency (MHz)	Maximum Average Power (dBm)
Bluetooth	18.70
2.4GHz WLAN	29.96
5.2GHz WLAN	27.75
5.3GHz WLAN	22.25
5.5GHz WLAN	23.88
5.8GHz WLAN	29.97
WLAN UNII-4	28.19
6GHz WLAN	16.57
Zigbee	17.50



3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Table with 5 columns: Frequency range (MHz), Electric field strength (V/m), Magnetic field strength (A/m), Power density (mW/cm²), Averaging time (minutes). It is divided into two sections: (A) Limits for Occupational/Controlled Exposures and (B) Limits for General Population/Uncontrolled Exposure.

The MPE was calculated at 22 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

S = PG / (4πR²)

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



**4. Radio Frequency Radiation Exposure Evaluation**

**4.1. Standalone Power Density Calculation**

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 22cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
WLAN2.4GHz Band	4.85	29.96	34.8	3.03	3026.91	0.498	1.000
WLAN5.2GHz Band	5.71	27.75	33.5	2.22	2218.20	0.365	1.000
WLAN5.3GHz Band	5.71	22.25	28.0	0.63	625.17	0.103	1.000
WLAN5.5GHz Band	5.71	23.88	29.6	0.91	909.91	0.150	1.000
WLAN5.8GHz Band	5.71	29.97	35.7	3.70	3698.28	0.608	1.000
WLANUNII-4	5.40	28.19	33.6	2.29	2285.60	0.376	1.000
WLAN6GHz	4.18	16.57	20.8	0.12	118.85	0.020	1.000
Bluetooth	3.24	18.70	21.9	0.16	156.31	0.026	1.000
Zigbee	3.24	17.50	20.7	0.12	118.58	0.020	1.000

**Conclusion:**

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.