



Test Report No.: FM180920N037



RF EXPOSURE REPORT

Applicant	Particle Industries, Inc
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA

Manufacturer or Supplier	Particle Industries, Inc
Address	126 Post St, 4th floor, San Francisco, CA 94108 USA
Product	Boron LTE
Brand Name	Particle Industries, Inc
Model	BRN402
Additional Model & Model Difference	N/A
Date of tests	Sep. 03, 2018 ~ Nov. 08, 2018

- FCC Part 2 (Section 2.1091)
- KDB 447498 D01
- IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	
	Date: Nov. 16, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: FM180920N037

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. TARGET POWER AND TOLERANCE	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6
7. CONCLUSION OF SIMULTANEOUS TRANSMITTER.....	6



BUREAU
VERITAS

Test Report No.: FM180920N037

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM180920N037	Original release	Nov. 16, 2018

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



1. CERTIFICATION

FCC ID:	2AEMI-BRN402
PRODUCT:	Boron LTE
BRAND NAME:	Particle Industries, Inc
MODEL NO.:	BRN402
ADDITIONAL NO.:	N/A
TEST SAMPLE:	Engineering Sample
APPLICANT:	Particle Industries, Inc
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. TARGET POWER AND TOLERANCE

<u>Technology/Band</u>	<u>Mode</u>	<u>Target Power and Tolerance (dBm)</u>
LTE BAND 2	QPSK/16QAM	23.8±1.0 dBm
LTE BAND 4	QPSK/16QAM	24±1.0 dBm
LTE BAND 5	QPSK/16QAM	24±1.0 dBm
LTE BAND 12	QPSK/16QAM	24±1.0 dBm
LTE BAND 13	QPSK/16QAM	24±1.0 dBm
DSSS(802.15.4)	OQPSK	-1±1.0 dBm

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
LTE Band 12	1.0	25.0	26.000	0.398	398.107	0.079	0.466	0.170
LTE Band 13	1.0	25.0	26.000	0.398	398.107	0.079	0.520	0.152
LTE Band 5	1.0	25.0	26.000	0.398	398.107	0.079	0.550	0.144
LTE Band 4	3.5	25.0	28.500	0.708	707.946	0.141	1.000	0.141
LTE Band 2	3.5	24.8	28.300	0.676	676.083	0.135	1.000	0.135
DSSS(802.15.4)	0	0	0	0.001	-	0.000199	1.000	0.000199

7. CONCLUSION OF SIMULTANEOUS TRANSMITTER

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1+CPD2/LPD2+.....etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is $0.170+0.000199 = 0.170199$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---