

# RF Exposure Evaluation

## FCC ID: 2AEMJSB5-SLAVE

### 1. Client Information

**Applicant** : SW Technology Limited  
**Address** : Room A206 2nd Floor, Building 24, Science and Technology Park Industrial Estate, Keyuan Road #5, Nanshan, Shenzhen, China  
**Manufacturer** : SW Technology Limited  
**Address** : Room A206 2nd Floor, Building 24, Science and Technology Park Industrial Estate, Keyuan Road #5, Nanshan, Shenzhen, China

### 2. General Description of EUT

<b>EUT Name</b>	:	Baby Safety-slave unit	
<b>Models No.</b>	:	SB5	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency: Bluetooth:2402~2480MHz	
		Number of Channel:	BLE:40 Channels
		Max Peak Output Power:	GFSK:4.26 dBm
		Antenna Gain:	1 dBi Integral Antenna
		Modulation Type:	1Mbps(GFSK)
<b>Power Supply</b>	:	DC power by battery	
<b>Power Rating</b>	:	DC 3V by 2*1.5V AAA Battery.	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

#### Note:

More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})]^* [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})]^* [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0$  for 10-g SAR

## 2.

**Calculation:**

Test separation: 5mm						
BLE Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Ant Gain (dBi)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	4.26	1.0	±0.5	2.99	0.93	3.0
2.442	4.09	1.0	±0.5	2.88	0.90	3.0
2.480	4.10	1.0	±0.5	2.88	0.91	3.0

**So standalone SAR measurements are not required.**