

## Letter of Declaration

Fast Wireless Charger

FCC ID: 2AEMN-P8

**a) Power transfer frequency is less than 1 MHz.**

- ✓ The power transfer frequency of DUT (Device under Test) is between 110 KHz and 205 KHz.

**b) Output power from each primary coil is less than 15 watts**

- ✓ Output power from each coils are less than 10 watts. When the DUT is in charging mode,

**c) The transfer system includes only single primary and second coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.**

- ✓ The EUT Conforms to the above requirements. Pls refer to the EUT internal photos for more details.

**d) Client device is inserted in or placed directly in contact with transmitter**

- ✓ When the client device is placed directly in contact with transmitter, then charging is able to start.


**e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).**

- ✓ The EUT Conforms to the above requirements.

**f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.**

- ✓ The highest leakage field is less than 50 % of the MPE limit.

Name: Dan Yao



Position: Product Manager

DESAY INFOR TECHNOLOGY CO., LTD

Date: 20 Aug., 2018