

FCC PART 22H, PART 24E
FCC PART 27
MEASUREMENT AND TEST REPORT
For
MAXWEST INTERNATIONAL LIMITED.

No.1,Longgang Road,Buji, Longgang, Shenzhen,China

FCC ID: 2AEN3ASTRO5NLTE

Report Type: Original Report	Product Type: Mobile Phone
Report Number:	RDG171020005-00D
Report Date:	2017-11-16
Reviewed By:	Jerry Zhang EMC Manager <i>Jerry Zhang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) & § 27.50 - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA	17
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	33
FCC §2.1051, §22.917(A) & §24.238(A) & §27.53 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS ..	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS.....	59
TEST DATA	59
FCC §2.1053, §22.917 & §24.238 & §27.53 - SPURIOUS RADIATED EMISSIONS	93
APPLICABLE STANDARD	93
TEST PROCEDURE	93
TEST EQUIPMENT LIST AND DETAILS.....	93
TEST DATA	94
FCC §22.917(A) & §24.238(A) & §27.53 - BAND EDGES.....	98
APPLICABLE STANDARD	98
TEST PROCEDURE	98
TEST EQUIPMENT LIST AND DETAILS.....	98
TEST DATA	99

FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY.....	148
APPLICABLE STANDARD	148
TEST PROCEDURE	148
TEST EQUIPMENT LIST AND DETAILS.....	149
TEST DATA	149

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **MAXWEST INTERNATIONAL LIMITED.**'s product, model number: **Astro 5N LTE (FCC ID: 2AEN3ASTRO5NLTE)** (the "EUT") in this report was a **Mobile Phone**, which was measured approximately: 14.4 cm (L) x 7.4 cm (W) x 1.1 cm (H), rated input voltage:DC 3.8V from battery or DC 5.0V from adapter.

Adapter Information:

Model:AsTro 5N LTE

Input: AC100-240V 50/60Hz 0.2A

Output: 5.0V, 1A

**All measurement and test data in this report was gathered from production sample serial number: 171020005 (Assigned by BACL,Dongguan). The EUT was received on 2017-10-10.*

Objective

This report is prepared on behalf of **MAXWEST INTERNATIONAL LIMITED.** in accordance with: Part 2-Subpart J, Part 22-Subpart H, and Part 24-Subpart E of the Federal Communications Commission's rules. Part 2, Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Rules for output power, modulation characteristic, occupied bandwidth, spurious emissions at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AEN3ASTRO5NLTE.

FCC Part 15C DSS submissions with FCC ID: 2AEN3ASTRO5NLTE.

FCC Part 15B JBP submissions with FCC ID: 2AEN3ASTRO5NLTE.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D-2010.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp.(Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Unwanted Emissions, radiated	30MHz ~ 1GHz: 5.85 dB 1G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

Bay Area Compliance Laboratories Corp. (Dongguan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L5662). And accredited to ISO/IEC 17025 by NVLAP(Test Laboratory Accreditation Certificate Number 500069-0), the FCC Designation No. CN5002 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Dongguan) was registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D 2010.

The test items were performed with the EUT operating at testing mode.


Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R&S	Universal Radio Communication Tester	CMU200	106891
R&S	Wideband Radio Communication Tester	CMW500	147473
N/A	ANTENNA	N/A	N/A

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310, §2.1093	RF Exposure	Compliance
§2.1046; § 22.913 (a); § 24.232 (c); §27.50	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a); §27.53	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a); §27.53	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235; §27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

FCC §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG171020005-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E, Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) & § 27.50 - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §24.232 (d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c) (10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d), (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h),(2) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

Test Procedure

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
 Press Connection control to choose the different menus
 Press RESET > choose all the reset all settings
 Connection Press Signal Off to turn off the signal and change settings
 Network Support > GSM + GPRS or GSM + EGSM
 Main Service > Packet Data
 Service selection > Test Mode A – Auto Slot Config. off
 MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
 > Slot configuration > Uplink/Gamma
 > 33 dBm for GPRS 850
 > 30 dBm for GPRS 1900
 > 27 dBm for EGPRS 850
 > 26 dBm for EGPRS 1900
 BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
 Frequency Offset > + 0 Hz
 Mode > BCCH and TCH
 BCCH Level > -85 dBm (May need to adjust if link is not stable)
 BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

 Channel Type > Off
 P0 > 4 dB
 Slot Config > Unchanged (if already set under MS signal)
 TCH > choose desired test channel
 Hopping > Off
 Main Timeslot > 3
 Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

 Bit Stream > 2E9-1 PSR Bit Stream
 AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
 Connection Press Signal on to turn on the signal and change settings

WCDMA-Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	βc / βd	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
MPR(dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	

HSPA+

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105

- Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.
- Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).
- Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default.
- Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.
- Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
<p>Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.</p> <p>Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.</p>		

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N _{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
NS_04	6.6.2.2.2	41	20	>10	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

Radiated method:

ANSI/TIA-603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-09-01	2018-09-01
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
R&S	Spectrum Analyzer	FSP 38	100478	2016-12-08	2017-12-08
ETS LINDGREN	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
HP	Signal Generator	1026	320408	2016-12-08	2017-12-08
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2016-01-05	2019-01-04
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
Unknown	Coaxial Cable	0.1m	C-1	Each Time	/
R&S	Universal Radio Communication Tester	CMU200	106 891	2017-10-18	2018-10-18
R&S	Wideband Radio Communication Tester	CMW500	147473	2017-08-31	2018-08-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3~25.8°C
Relative Humidity:	27~45 %
ATM Pressure:	101~101.6 kPa

* The testing was performed by Sunny Cen & George Pang & Swim Lv from 2017-10-23 to 2017-11-04.

Conducted Output Power

Cellular Band & PCS Band

Band	Channel No.	Conducted Peak Output Power (dBm)				
		GSM	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot
Cellular	128	31.40	31.42	29.63	28.14	26.28
	190	31.50	31.57	29.66	28.16	26.50
	251	31.60	31.58	29.67	28.18	26.37
PCS	512	28.90	28.90	27.16	25.77	23.98
	661	28.90	28.88	27.17	25.81	24.02
	810	28.80	28.79	27.14	25.74	23.89

WCDMA Band II

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.54	3.16	22.34	3.00	22.37	2.92
HSDPA	1	22.57	3.14	21.86	3.03	21.26	2.93
	2	22.34	3.25	21.69	2.91	21.39	2.99
	3	22.25	3.11	21.47	2.95	21.48	2.85
	4	22.75	3.19	21.58	2.99	21.02	2.83
HSUPA	1	21.49	3.12	21.28	3.10	21.44	2.76
	2	21.65	3.15	21.64	3.06	21.58	2.98
	3	21.32	3.23	22.03	3.04	21.63	3.01
	4	21.14	3.18	21.89	2.93	21.33	2.86
	5	21.28	3.06	21.74	2.95	21.05	2.96
DC-HSDPA	1	21.36	3.24	21.56	3.02	21.64	2.84
	2	21.44	3.26	21.33	3.06	21.96	2.89
	3	21.59	3.11	21.25	2.96	21.78	2.95
	4	21.31	3.16	21.75	2.99	21.54	2.98
HSPA+	1	21.69	3.28	21.89	3.08	21.62	2.97

WCDMA Band V

Mode	3GPP Sub Test	Low Channel		Middle Channel		High Channel	
		Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)	Ave. Power (dBm)	PAR (dB)
Rel 99	1	22.12	3.16	21.99	3.08	21.96	2.84
HSDPA	1	21.71	3.26	21.64	3.02	21.47	21.89
	2	21.89	3.09	21.36	3.05	21.36	21.93
	3	21.66	3.25	21.58	3.12	21.58	21.42
	4	21.53	3.21	21.47	3.13	21.22	21.52
HSUPA	1	21.87	3.22	21.62	3.15	21.64	21.35
	2	21.46	3.15	21.89	3.09	21.69	21.68
	3	21.96	3.18	21.45	3.19	21.42	21.53
	4	21.84	3.13	21.32	3.14	21.79	21.69
	5	21.47	3.19	21.14	3.02	21.34	21.99
DC-HSDPA	1	21.36	3.24	21.52	3.06	21.54	21.59
	2	21.25	3.16	21.79	3.19	21.03	21.74
	3	21.14	3.17	21.13	3.02	21.59	21.82
	4	21.59	3.23	20.96	3.09	21.49	21.37
HSPA+	1	21.43	3.17	21.44	3.07	21.41	21.59

LTE Band 2 (PART 24)

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	1#0	21.93	22.41	22.61
		1#3	22.70	22.68	23.20
		1#5	21.90	21.71	22.76
		3#0	22.60	2.76	23.02
		3#3	22.57	22.76	23.06
		6#0	21.96	21.79	22.24
	16QAM	1#0	21.67	22.03	21.79
		1#3	22.74	22.23	22.58
		1#5	22.71	22.10	22.48
		3#0	22.10	22.23	22.30
		3#3	22.02	22.19	22.38
		6#0	20.31	20.42	20.57
3MHz	QPSK	1#0	21.91	21.87	22.47
		1#8	22.64	22.32	23.02
		1#14	22.56	23.03	23.40
		10#0	22.05	21.88	22.14
		10#5	21.80	21.65	22.53
		15#0	22.16	21.89	22.33
	16QAM	1#0	22.61	21.45	23.13
		1#8	22.59	22.08	22.36
		1#14	22.47	22.01	22.67
		10#0	21.23	21.36	21.35
		10#5	21.33	21.39	21.46
		15#0	20.52	20.53	20.78
5MHz	QPSK	1#0	22.47	22.52	22.18
		1#13	22.84	22.86	23.14
		1#24	22.50	22.55	22.90
		10#0	22.02	21.85	22.10
		10#15	21.76	21.61	22.36
		25#0	22.05	21.78	22.18
	16QAM	1#0	21.75	21.51	22.03
		1#13	22.12	22.77	22.72
		1#24	21.99	22.67	22.50
		10#0	21.09	21.32	21.18
		10#15	20.83	21.32	21.37
		25#0	20.42	20.33	20.48

10MHz	QPSK	1#0	22.30	22.45	22.23
		1#25	22.40	22.95	22.88
		1#49	22.02	22.58	22.83
		25#0	22.03	21.81	21.78
		25#25	21.96	22.42	22.35
	50#0	22.01	21.79	21.83	
	16QAM	1#0	21.95	22.32	21.29
		1#25	21.81	22.17	22.95
		1#49	21.66	21.88	22.50
		25#0	21.88	21.42	21.79
25#25		22.08	21.39	21.80	
50#0	20.36	20.64	20.63		
15MHz	QPSK	1#0	22.31	22.53	21.98
		1#38	22.52	22.44	23.15
		1#74	22.58	22.06	22.72
		36#0	21.98	21.81	22.16
		36#39	22.05	21.71	22.23
	75#0	21.97	21.73	21.67	
	16QAM	1#0	22.15	23.30	22.33
		1#38	22.75	23.26	23.03
		1#74	23.12	22.21	22.76
		36#0	21.95	21.85	21.56
36#39		22.07	21.67	21.78	
75#0	22.05	20.45	20.81		
20MHz	QPSK	1#0	22.42	22.42	22.59
		1#50	22.54	22.31	22.62
		1#99	22.52	22.18	22.30
		50#0	21.96	21.76	21.49
		50#50	22.05	21.75	22.28
	100#0	22.03	21.72	22.24	
	16QAM	1#0	22.33	22.30	22.34
		1#50	22.23	21.75	22.24
		1#99	23.04	21.96	22.94
		50#0	21.85	21.77	21.53
50#50		21.90	21.78	22.26	
100#0	21.87	21.74	22.24		

LTE Band 4 (PART 27)

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4MHz	QPSK	1#0	22.99	23.11	23.03
		1#3	23.27	22.95	22.91
		1#5	23.11	22.84	22.89
		3#0	23.19	22.54	22.52
		3#3	23.20	22.53	22.46
		6#0	22.54	22.52	22.45
	16QAM	1#0	23.15	22.51	22.05
		1#3	23.26	21.96	21.91
		1#5	23.14	21.99	21.88
		3#0	23.25	23.02	22.45
		3#3	23.23	22.48	22.47
		6#0	21.57	21.58	21.31
3MHz	QPSK	1#0	23.18	22.92	22.94
		1#8	23.24	22.91	23.01
		1#14	23.51	23.12	23.32
		10#0	22.79	21.95	21.94
		10#5	22.79	22.03	21.93
		15#0	22.45	22.48	22.37
	16QAM	1#0	22.32	22.51	22.76
		1#8	22.73	22.70	22.69
		1#14	23.06	23.17	22.66
		10#0	22.88	22.01	21.85
		10#5	22.87	22.07	21.84
		15#0	21.38	21.59	21.50
5MHz	QPSK	1#0	23.04	23.01	22.88
		1#13	23.44	22.57	22.27
		1#24	23.06	22.53	22.18
		10#0	22.63	21.94	21.85
		10#15	22.64	21.94	21.81
		25#0	22.36	21.39	21.20
	16QAM	1#0	22.89	22.47	21.84
		1#13	22.03	23.06	21.96
		1#24	22.08	23.12	22.03
		10#0	21.95	21.94	21.85
		10#15	21.96	22.04	21.91
		25#0	21.11	21.15	21.07

10MHz	QPSK	1#0	22.98	22.61	22.66
		1#25	23.10	22.52	22.44
		1#49	22.71	22.39	22.42
		25#0	21.94	21.95	21.81
		25#25	21.98	21.88	21.93
	16QAM	50#0	21.31	21.41	21.62
		1#0	21.96	22.03	22.36
		1#25	21.33	22.01	21.51
		1#49	21.28	22.06	21.40
		25#0	21.92	22.04	21.86
15MHz	QPSK	25#25	21.95	21.95	21.76
		50#0	21.17	21.21	21.45
		1#0	22.93	22.84	22.89
		1#38	22.45	22.52	22.41
		1#74	22.51	22.57	22.39
	16QAM	36#0	21.94	21.94	21.96
		36#39	21.94	22.01	21.93
		75#0	21.67	21.86	21.55
		1#0	22.34	22.72	22.66
		1#38	21.62	22.99	22.92
20MHz	QPSK	1#74	21.92	23.01	23.03
		36#0	21.85	21.95	21.95
		36#39	21.83	22.01	21.93
		75#0	21.13	21.25	21.21
		1#0	22.51	22.81	22.79
	16QAM	1#50	22.87	22.86	23.14
		1#99	22.39	22.63	22.23
		50#0	21.94	21.83	21.91
		50#50	21.88	21.96	21.82
		100#0	21.54	21.72	21.61
16QAM	1#0	23.03	22.50	23.28	
	1#50	22.28	22.69	23.30	
	1#99	22.26	22.40	23.39	
	50#0	21.92	21.72	21.91	
	50#50	21.95	21.90	21.82	
		100#0	21.32	21.17	21.23

LTE Band 5 (PART 22)

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)		
1.4MHz	QPSK	1#0	22.93	22.49	22.81		
		1#3	22.95	22.67	22.83		
		1#5	22.89	22.65	22.90		
		3#0	22.59	22.45	22.65		
		3#3	22.57	22.39	22.69		
		6#0	22.07	21.98	22.32		
	16QAM	1#0	22.08	21.24	21.70		
		1#3	22.18	21.34	22.27		
		1#5	22.26	21.25	22.28		
		3#0	22.64	22.50	22.63		
3MHz	QPSK	1#0	22.68	22.54	22.78		
		1#8	22.74	22.56	22.66		
		1#14	22.79	22.45	22.61		
		10#0	22.18	22.04	22.11		
		10#5	22.14	22.02	22.19		
		15#0	22.19	22.05	22.24		
	16QAM	1#0	22.15	22.09	22.28		
		1#8	22.21	22.08	22.35		
		1#14	22.29	22.03	22.41		
		10#0	22.10	22.07	22.14		
		10#5	22.08	22.06	22.09		
		15#0	21.06	21.32	21.38		
		5MHz	QPSK	1#0	22.78	22.72	22.80
				1#13	22.83	22.63	22.88
1#24	22.77			22.69	22.81		
10#0	22.21			21.93	22.19		
10#15	22.22			22.00	22.21		
16QAM	25#0		22.25	22.06	22.13		
	1#0		22.86	22.05	22.43		
	1#13		22.88	22.08	22.45		
	1#24		22.82	22.11	22.41		
	10#0		22.24	21.98	22.23		
10MHz	QPSK	10#15	22.27	22.04	22.24		
		25#0	20.84	21.17	21.26		
		1#0	22.91	22.68	22.58		
		1#25	22.85	22.57	22.78		
		1#49	22.83	22.77	22.80		
		25#0	22.13	22.06	22.06		
		25#25	22.09	22.06	22.17		
	16QAM	50#0	22.07	22.05	22.12		
		1#0	23.11	21.41	21.28		
		1#25	22.55	21.37	21.54		
		1#49	22.56	21.52	22.52		
		25#0	22.16	22.08	22.10		
		25#25	22.12	22.10	22.23		
		50#0	21.18	21.23	21.45		

LTE Band 7 (PART 27)

Channel Bandwidth	Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5MHz	QPSK	1#0	21.84	21.70	21.85
		1#13	21.94	21.85	22.22
		1#24	21.81	21.52	21.92
		10#0	22.02	21.70	21.88
		10#15	21.72	21.59	21.96
	25#0	22.17	21.76	21.95	
	16QAM	1#0	21.95	22.08	21.74
		1#13	21.87	22.23	22.12
		1#24	21.75	21.93	21.85
		10#0	22.03	21.79	21.88
10#15		21.71	21.69	21.96	
25#0	21.13	20.83	21.02		
10MHz	QPSK	1#0	21.80	21.65	21.65
		1#25	22.11	21.94	22.11
		1#49	21.82	21.78	21.87
		25#0	21.84	22.03	21.77
		25#25	22.12	21.82	22.11
	50#0	21.97	21.90	21.95	
	16QAM	1#0	22.32	21.80	21.70
		1#25	22.54	22.01	22.09
		1#49	22.25	21.81	21.86
		25#0	21.81	21.97	21.81
25#25		22.10	21.77	22.13	
50#0	20.96	20.87	21.14		
15MHz	QPSK	1#0	21.30	20.97	21.02
		1#38	22.01	21.80	21.92
		1#74	21.17	21.15	21.36
		36#0	21.67	21.74	21.68
		36#39	21.92	21.77	21.84
	75#0	21.76	21.66	21.58	
	16QAM	1#0	21.25	21.85	21.40
		1#38	21.99	22.33	22.24
		1#74	21.47	21.55	21.70
		36#0	21.59	21.70	21.69
36#39		21.86	21.78	21.85	
75#0	20.68	20.66	20.76		
20MHz	QPSK	1#0	21.89	21.64	21.77
		1#50	22.00	21.87	21.91
		1#99	21.66	22.02	21.95
		50#0	21.63	21.71	21.48
		50#50	21.79	21.67	21.65
	100#0	21.90	21.79	21.79	
	16QAM	1#0	22.10	22.42	22.03
		1#50	22.19	22.32	22.06
		1#99	22.24	22.46	22.39
		50#0	21.59	21.62	21.48
50#50		21.76	21.67	21.68	
100#0	20.71	20.58	20.98		

PAR, Band 2

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	5.20	4.12	4.32	13
	100 RB		6.48	6.36	6.44	13
16QAM	1 RB	20 MHz	5.60	4.88	4.96	13
	100 RB		7.12	7.00	7.20	13

PAR, Band 4

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	4.64	4.00	5.80	13
	100 RB		6.52	7.88	6.40	13
16QAM	1 RB	20 MHz	5.08	5.08	6.36	13
	100 RB		7.16	7.12	7.20	13

PAR, Band 5

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	10 MHz	4.28	5.04	4.52	13
	50 RB		5.20	5.32	5.20	13
16QAM	1 RB	10 MHz	4.96	5.56	3.96	13
	50 RB		6.16	6.24	6.24	13

PAR, Band 7

Test Modulation		Channel Bandwidth	Low Channel PAR (dB)	Middle Channel PAR (dB)	High Channel PAR (dB)	Limit (dB)
QPSK	1 RB	20 MHz	5.64	4.96	5.12	13
	100 RB		6.44	6.36	6.48	13
16QAM	1 RB	20 MHz	5.68	5.56	4.96	13
	100 RB		7.16	7.04	7.16	13

Note: peak-to-average ratio (PAR) <13 dB.

ERP & EIRP

Part 22H

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Middle Channel								
836.600	H	91.73	16.8	0.0	1	15.8	38.5	22.7
836.600	V	101.29	29.5	0.0	1	28.5	38.5	10.0
WCDMA Band V Middle Channel								
836.600	H	85.50	10.6	0.0	1	9.6	38.5	28.9
836.600	V	90.80	19	0.0	1	18.0	38.5	20.5

Part 24E

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
PCS 1900 Middle Channel								
1880.000	H	92.87	19.9	11.1	1.6	29.4	33.0	3.6
1880.000	V	91.30	18.1	11.1	1.6	27.6	33.0	5.4
WCDMA Band II Middle Channel								
1880.000	H	86.25	13.3	11.1	1.6	22.8	33.0	10.2
1880.000	V	82.94	9.8	11.1	1.6	19.3	33.0	13.7

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit - Absolute Level

LTE Band 2

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK 1.4 MHz Middle Channel								
1880.000	H	86.05	13.1	11.1	1.6	22.6	33.0	10.4
1880.000	V	82.32	9.2	11.1	1.6	18.7	33.0	14.3
QPSK 3 MHz Middle Channel								
1880.000	H	86.71	13.8	11.1	1.6	23.3	33.0	9.7
1880.000	V	84.53	11.4	11.1	1.6	20.9	33.0	12.1
QPSK 5 MHz Middle Channel								
1880.000	H	86.66	13.7	11.1	1.6	23.2	33.0	9.8
1880.000	V	84.14	11	11.1	1.6	20.5	33.0	12.5
QPSK 10 MHz Middle Channel								
1880.000	H	85.42	12.5	11.1	1.6	22.0	33.0	11.0
1880.000	V	83.34	10.2	11.1	1.6	19.7	33.0	13.3
QPSK 15 MHz Middle Channel								
1880.000	H	84.95	12	11.1	1.6	21.5	33.0	11.5
1880.000	V	82.57	9.4	11.1	1.6	18.9	33.0	14.1
QPSK 20 MHz Middle Channel								
1880.000	H	84.35	11.4	11.1	1.6	20.9	33.0	12.1
1880.000	V	82.11	9	11.1	1.6	18.5	33.0	14.5
16QAM 1.4 MHz Middle Channel								
1880.000	H	86.64	13.7	11.1	1.6	23.2	33.0	9.8
1880.000	V	83.18	10	11.1	1.6	19.5	33.0	13.5
16QAM 3 MHz Middle Channel								
1880.000	H	87.31	14.4	11.1	1.6	23.9	33.0	9.1
1880.000	V	84.32	11.2	11.1	1.6	20.7	33.0	12.3
16QAM 5 MHz Middle Channel								
1880.000	H	85.72	12.8	11.1	1.6	22.3	33.0	10.7
1880.000	V	83.67	10.5	11.1	1.6	20.0	33.0	13.0
16QAM 10 MHz Middle Channel								
1880.000	H	85.22	12.3	11.1	1.6	21.8	33.0	11.2
1880.000	V	83.17	10	11.1	1.6	19.5	33.0	13.5
16QAM 15 MHz Middle Channel								
1880.000	H	84.65	11.7	11.1	1.6	21.2	33.0	11.8
1880.000	V	82.38	9.2	11.1	1.6	18.7	33.0	14.3
16QAM 20 MHz Middle Channel								
1880.000	H	84.13	11.2	11.1	1.6	20.7	33.0	12.3
1880.000	V	81.72	8.6	11.1	1.6	18.1	33.0	14.9

LTE Band 4

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK 1.4 MHz Middle Channel								
1732.500	H	88.97	15.5	10.7	1.5	24.7	30.0	5.3
1732.500	V	85.15	11.4	10.7	1.5	20.6	30.0	9.4
QPSK 3 MHz Middle Channel								
1732.500	H	88.55	15.1	10.7	1.5	24.3	30.0	5.7
1732.500	V	84.44	10.7	10.7	1.5	19.9	30.0	10.1
QPSK 5 MHz Middle Channel								
1732.500	H	88.19	14.7	10.7	1.5	23.9	30.0	6.1
1732.500	V	83.80	10	10.7	1.5	19.2	30.0	10.8
QPSK 10 MHz Middle Channel								
1732.500	H	87.52	14	10.7	1.5	23.2	30.0	6.8
1732.500	V	83.53	9.7	10.7	1.5	18.9	30.0	11.1
QPSK 15 MHz Middle Channel								
1732.500	H	86.01	12.5	10.7	1.5	21.7	30.0	8.3
1732.500	V	83.24	9.5	10.7	1.5	18.7	30.0	11.3
QPSK 20 MHz Middle Channel								
1732.500	H	85.87	12.4	10.7	1.5	21.6	30.0	8.4
1732.500	V	83.05	9.3	10.7	1.5	18.5	30.0	11.5
16QAM 1.4 MHz Middle Channel								
1732.500	H	88.83	15.3	10.7	1.5	24.5	30.0	5.5
1732.500	V	84.71	10.9	10.7	1.5	20.1	30.0	9.9
16QAM 3 MHz Middle Channel								
1732.500	H	88.34	14.9	10.7	1.5	24.1	30.0	5.9
1732.500	V	84.19	10.4	10.7	1.5	19.6	30.0	10.4
16QAM 5 MHz Middle Channel								
1732.500	H	87.62	14.1	10.7	1.5	23.3	30.0	6.7
1732.500	V	83.77	10	10.7	1.5	19.2	30.0	10.8
16QAM 10 MHz Middle Channel								
1732.500	H	86.21	12.7	10.7	1.5	21.9	30.0	8.1
1732.500	V	83.35	9.6	10.7	1.5	18.8	30.0	11.2
16QAM 15 MHz Middle Channel								
1732.500	H	85.89	12.4	10.7	1.5	21.6	30.0	8.4
1732.500	V	83.18	9.4	10.7	1.5	18.6	30.0	11.4
16QAM 20 MHz Middle Channel								
1732.500	H	85.62	12.1	10.7	1.5	21.3	30.0	8.7
1732.500	V	82.80	9	10.7	1.5	18.2	30.0	11.8

LTE Band 5

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK 1.4 MHz Middle Channel								
836.500	H	87.50	12.6	0.0	1	11.6	38.5	26.9
836.500	V	93.80	22	0.0	1	21.0	38.5	17.5
QPSK 3 MHz Middle Channel								
836.500	H	86.60	11.7	0.0	1	10.7	38.5	27.8
836.500	V	92.90	21.1	0.0	1	20.1	38.5	18.4
QPSK 5 MHz Middle Channel								
836.500	H	83.70	8.8	0.0	1	7.8	38.5	30.7
836.500	V	92.60	20.8	0.0	1	19.8	38.5	18.7
QPSK 10 MHz Middle Channel								
836.500	H	83.90	9	0.0	1	8.0	38.5	30.5
836.500	V	92.60	20.8	0.0	1	19.8	38.5	18.7
16QAM 1.4 MHz Middle Channel								
836.500	H	87.20	12.3	0.0	1	11.3	38.5	27.2
836.500	V	93.40	21.6	0.0	1	20.6	38.5	17.9
16QAM 3 MHz Middle Channel								
836.500	H	86.10	11.2	0.0	1	10.2	38.5	28.3
836.500	V	92.50	20.7	0.0	1	19.7	38.5	18.8
16QAM 5 MHz Middle Channel								
836.500	H	82.90	8	0.0	1	7.0	38.5	31.5
836.500	V	92.10	20.3	0.0	1	19.3	38.5	19.2
16QAM 10 MHz Middle Channel								
836.500	H	81.50	6.6	0.0	1	5.6	38.5	32.9
836.500	V	92.20	20.4	0.0	1	19.4	38.5	19.1

LTE Band 7

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK 5 MHz Middle Channel								
2535.000	H	80.13	9.1	12.2	1.8	19.5	33.0	13.5
2535.000	V	77.08	5.7	12.2	1.8	16.1	33.0	16.9
QPSK 10 MHz Middle Channel								
2535.000	H	79.71	8.6	12.2	1.8	19.0	33.0	14.0
2535.000	V	76.76	5.4	12.2	1.8	15.8	33.0	17.2
QPSK 15 MHz Middle Channel								
2535.000	H	78.54	7.5	12.2	1.8	17.9	33.0	15.1
2535.000	V	76.21	4.9	12.2	1.8	15.3	33.0	17.7
QPSK 20 MHz Middle Channel								
2535.000	H	78.64	7.6	12.2	1.8	18.0	33.0	15.0
2535.000	V	76.44	5.1	12.2	1.8	15.5	33.0	17.5
16QAM 5 MHz Middle Channel								
2535.000	H	79.97	8.9	12.2	1.8	19.3	33.0	13.7
2535.000	V	76.95	5.6	12.2	1.8	16.0	33.0	17.0
16QAM 10 MHz Middle Channel								
2535.000	H	78.85	7.8	12.2	1.8	18.2	33.0	14.8
2535.000	V	76.46	5.1	12.2	1.8	15.5	33.0	17.5
16QAM 15 MHz Middle Channel								
2535.000	H	78.34	7.3	12.2	1.8	17.7	33.0	15.3
2535.000	V	75.84	4.5	12.2	1.8	14.9	33.0	18.1
16QAM 20 MHz Middle Channel								
2535.000	H	78.15	7.1	12.2	1.8	17.5	33.0	15.5
2535.000	V	76.07	4.7	12.2	1.8	15.1	33.0	17.9

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53- OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-12-08	2017-12-08
R&S	Universal Radio Communication Tester	CMU200	106 891	2017-10-18	2018-10-18
R&S	Wideband Radio Communication Tester	CMW500	147473	2017-08-31	2018-08-31
Unknown	Coaxial Cable	0.1m	C-1	Each Time	/
Pasternack	RF Coaxial Cable	0.5m	C-5	Each Time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.8~27.8°C
Relative Humidity:	44~45 %
ATM Pressure:	101~101.6 kPa

The testing was performed by George Pang & Swim Lv from 2017-10-27 to 2017-11-04.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Band	Test Channel	Mode	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
Cellular	M	GSM	0.246	0.316
PCS		PCS	0.244	0.318
WCDMA Band II		Rel 99	4.120	4.680
		HSDPA	4.120	4.700
		HSUPA	4.120	4.680
WCDMA Band V		Rel 99	4.100	4.660
		HSDPA	4.100	4.700
		HSUPA	4.100	4.680

Band	Test Modulation	Test Bandwidth (MHz)	Test Channel	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
LTE Band 2	QPSK	1.4	M	1.116	1.500
		3		2.700	3.072
		5		4.540	5.180
		10		9.000	9.840
		15		13.560	15.480
		20		18.080	20.080
	16QAM	1.4	M	1.110	1.476
		3		2.700	3.036
		5		4.540	5.440
		10		8.960	9.840
		15		13.560	15.180
		20		18.080	20.160


Band	Test Modulation	Test Bandwidth (MHz)	Test Channel	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
LTE Band 4	QPSK	1.4	M	1.116	1.476
		3		2.700	3.060
		5		4.560	5.160
		10		8.960	9.840
		15		13.560	15.498
		20		18.080	19.958
	16QAM	1.4	M	1.128	1.476
		3		2.700	3.048
		5		4.540	5.420
		10		8.960	9.920
		15		13.560	15.258
		20		18.080	20.118
LTE Band 5	QPSK	1.4	M	1.116	1.470
		3		2.700	3.042
		5		4.560	5.200
		10		9.000	9.780
	16QAM	1.4	M	1.134	1.458
		3		2.700	3.042
		5		4.540	5.420
		10		8.960	9.860
LTE Band 7	QPSK	5	M	4.540	5.220
		10		8.960	9.800
		15		13.560	15.480
		20		18.000	20.180
	16QAM	5	M	4.540	5.480
		10		9.000	9.880
		15		13.560	15.180
		20		18.080	20.080

GSM 850 Cellular Band




Date: 27.OCT.2017 13:09:13

GSM PCS1900 Cellular Band




Date: 27.OCT.2017 13:27:01

REL99 Band II




Date: 27.OCT.2017 15:04:09

HSDPA Band II




Date: 27.OCT.2017 14:58:07

HSUPA Band II




Date: 27.OCT.2017 15:01:02

REL99 Band V




Date: 27.OCT.2017 15:10:47

HSDPA Band V



Date: 27.OCT.2017 15:16:10


HSUPA Band V



Date: 27.OCT.2017 15:13:53


LTE Band 2

QPSK_1.4 MHz




Date: 4.NOV.2017 14:36:40

QPSK_3 MHz




Date: 4.NOV.2017 16:07:24

QPSK_5 MHz




Date: 4.NOV.2017 14:55:58

QPSK_10 MHz




Date: 4.NOV.2017 15:00:02

16QAM_1.4 MHz




Date: 4.NOV.2017 14:34:49

16QAM_3 MHz




Date: 4.NOV.2017 16:02:46

16QAM_5 MHz




Date: 4.NOV.2017 14:53:58

16QAM_10 MHz




Date: 4.NOV.2017 15:01:30

16QAM_15 MHz



Date: 4.NOV.2017 15:57:34


16QAM_20 MHz



Date: 4.NOV.2017 15:52:13


LTE Band 4:

QPSK_1.4 MHz




Date: 4.NOV.2017 15:41:00

QPSK_3 MHz




Date: 4.NOV.2017 15:39:27

QPSK_5 MHz




Date: 4.NOV.2017 15:33:16

QPSK_10 MHz




Date: 4.NOV.2017 15:25:29

QPSK_15 MHz




Date: 4.NOV.2017 15:44:29

QPSK_20 MHz




Date: 4.NOV.2017 15:47:33

16QAM_1.4 MHz




Date: 4.NOV.2017 15:42:18

16QAM_3 MHz




Date: 4.NOV.2017 15:38:19

16QAM_5 MHz




Date: 4.NOV.2017 15:35:29

16QAM_10 MHz




Date: 4.NOV.2017 15:27:02

16QAM_15 MHz



Date: 4.NOV.2017 15:45:38


16QAM_20 MHz



Date: 4.NOV.2017 15:49:46


LTE Band 5:

QPSK_1.4 MHz




Date: 4.NOV.2017 16:12:29

QPSK_3 MHz




Date: 4.NOV.2017 16:17:01

QPSK_5 MHz




Date: 4.NOV.2017 16:22:49

QPSK_10 MHz




Date: 4.NOV.2017 16:24:52

16QAM_1.4 MHz




Date: 4.NOV.2017 16:10:18

16QAM_3 MHz




Date: 4.NOV.2017 16:18:18

16QAM_5 MHz



Date: 4.NOV.2017 16:20:51


16QAM_10 MHz



Date: 4.NOV.2017 16:25:54


LTE Band 7:

QPSK_5 MHz




Date: 4.NOV.2017 16:31:37

QPSK_10 MHz




Date: 4.NOV.2017 16:33:49

QPSK_15 MHz




Date: 4.NOV.2017 16:40:04

QPSK_20 MHz




Date: 4.NOV.2017 16:41:22

16QAM_5 MHz




Date: 4.NOV.2017 16:29:27

16QAM_10 MHz




Date: 4.NOV.2017 16:36:05

16QAM_15 MHz



Date: 4.NOV.2017 16:38:29

16QAM_20 MHz



Date: 4.NOV.2017 16:44:24

FCC §2.1051, §22.917(a) & §24.238(a) & §27.53 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) , §24.238(a) and §27.53.

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Universal Radio Communication Tester	CMU200	106 891	2017-10-18	2018-10-18
R&S	Wideband Radio Communication Tester	CMW500	147473	2017-08-31	2018-08-31
Unknown	Coaxial Cable	0.1m	C-1	Each Time	/
Pasternack	RF Coaxial Cable	0.5m	C-5	Each Time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each Time	/
R&S	Spectrum Analyzer	FSP 38	100478	2016-12-08	2017-12-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.6~26.3°C
Relative Humidity:	45~60 %
ATM Pressure:	101.3~101.4 kPa


The testing was performed by George Pang & Swim Lv from 2017-10-26 to 2017-11-15.

Please refer to the following plots.

GSM850_Middle Channel




Date: 26.OCT.2017 23:46:19




Date: 26.OCT.2017 23:47:07


PCS 1900_ Middle Channel



Date: 26.OCT.2017 23:50:07




Date: 26.OCT.2017 23:51:25




Date: 26.OCT.2017 23:51:55


REL99 Band II_Middle Channel



Date: 26.OCT.2017 23:12:38




Date: 26.OCT.2017 22:43:24




Date: 26.OCT.2017 22:42:47

Rel 99 Band V_ Middle Channel




Date: 26.OCT.2017 23:02:46




Date: 26.OCT.2017 23:04:03

LTE Band 2 (Middle Channel)


QPSK_1.4 MHz



Date: 26.OCT.2017 21:14:50




Date: 26.OCT.2017 21:36:42




Date: 26.OCT.2017 21:18:39


QPSK_3 MHz



Date: 26.OCT.2017 21:23:36




Date: 26.OCT.2017 21:37:44




Date: 26.OCT.2017 21:24:12


QPSK_5 MHz



Date: 26.OCT.2017 21:26:30




Date: 26.OCT.2017 21:25:48




Date: 26.OCT.2017 21:24:59


QPSK_10 MHz



Date: 26.OCT.2017 21:28:25




Date: 26.OCT.2017 21:38:24




Date: 26.OCT.2017 21:30:47


QPSK_15 MHz



Date: 26.OCT.2017 21:33:50




Date: 26.OCT.2017 21:33:07




Date: 26.OCT.2017 21:32:14


QPSK_20 MHz



Date: 26.OCT.2017 21:42:10




Date: 26.OCT.2017 21:39:47




Date: 26.OCT.2017 21:40:37

LTE Band 4 (Middle Channel)


QPSK_1.4 MHz



Date: 26.OCT.2017 21:43:10




Date: 26.OCT.2017 21:45:19




Date: 26.OCT.2017 21:45:46


QPSK_3 MHz



Date: 26.OCT.2017 21:56:16




Date: 26.OCT.2017 21:48:47




Date: 26.OCT.2017 21:47:39


QPSK_5 MHz



Date: 26.OCT.2017 21:50:31




Date: 26.OCT.2017 21:52:08




Date: 15.NOV.2017 18:13:23

QPSK_10 MHz




Date: 26.OCT.2017 21:55:23


QPSK_15 MHz



Date: 26.OCT.2017 21:57:38




Date: 26.OCT.2017 21:58:23




Date: 26.OCT.2017 21:59:13


QPSK_20 MHz



Date: 26.OCT.2017 22:02:49




Date: 26.OCT.2017 22:01:34




Date: 26.OCT.2017 22:00:22

LTE Band 5 (Middle Channel)

QPSK_1.4 MHz




Date: 26.OCT.2017 22:04:28




Date: 26.OCT.2017 22:08:06

QPSK_3 MHz




Date: 26.OCT.2017 22:09:42




Date: 26.OCT.2017 22:08:57

QPSK_5 MHz




Date: 26.OCT.2017 22:10:44




Date: 26.OCT.2017 22:11:19

QPSK_10 MHz




Date: 26.OCT.2017 22:12:58




Date: 26.OCT.2017 22:12:20

LTE Band 7 (Middle Channel)


QPSK_5 MHz



Date: 26.OCT.2017 22:28:37




Date: 26.OCT.2017 22:28:06




Date: 26.OCT.2017 22:27:04


QPSK_10 MHz



Date: 26.OCT.2017 22:24:26




Date: 26.OCT.2017 22:25:45




Date: 26.OCT.2017 22:26:23


QPSK_15 MHz



Date: 26.OCT.2017 22:24:55




Date: 26.OCT.2017 22:22:37




Date: 26.OCT.2017 22:22:10


QPSK_20 MHz



Date: 26.OCT.2017 22:20:06



Date: 26.OCT.2017 22:20:54



Date: 26.OCT.2017 22:21:35

FCC §2.1053, §22.917 & §24.238 & §27.53 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917, § 24.238 and § 27.53.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017-09-01	2018-09-01
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2016-12-08	2017-12-08
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-05
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
HP	Signal Generator	1026	320408	2016-12-08	2017-12-08
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
TDK RF	Horn Antenna	HRN-0118	130 084	2016-01-05	2019-01-04
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2017-06-16	2020-06-15
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.3°C
Relative Humidity:	27~38 %
ATM Pressure:	101~101.4 kPa

* The testing was performed by Sunny Cen&Blake Yang from 2017-10-23 to 2017-10-26.

EUT Operation Mode: Transmitting

Cellular Band (PART 22H)

30 MHz-10 GHz:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM850, Frequency:836.600 MHz								
1673.200	H	47.64	-55.1	10.5	1.5	-46.1	-13.0	33.1
1673.200	V	43.18	-59.4	10.5	1.5	-50.4	-13.0	37.4
2509.800	H	46.95	-53.8	12.2	1.8	-43.4	-13.0	30.4
2509.800	V	45.71	-56.4	12.2	1.8	-46.0	-13.0	33.0
214.000	H	44.80	-64	0.0	0.5	-64.5	-13.0	51.5
464.000	V	45.20	-62.4	0.0	0.7	-63.1	-13.0	50.1
WCDMA Band V R99, Frequency:836.600 MHz								
1673.200	H	48.63	-54.1	10.5	1.5	-45.1	-13.0	32.1
1673.200	V	42.91	-59.7	10.5	1.5	-50.7	-13.0	37.7
2509.800	H	47.24	-53.5	12.2	1.8	-43.1	-13.0	30.1
2509.800	V	43.08	-59.1	12.2	1.8	-48.7	-13.0	35.7
531.000	H	45.10	-58.5	0.0	0.7	-59.2	-13.0	46.2
197.000	V	46.50	-64.2	0.0	0.5	-64.7	-13.0	51.7

PCS Band (PART 24E)

30 MHz-20 GHz:

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBµV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM1900, Frequency:1880.000 MHz								
3760.000	H	47.66	-50.1	12.3	2.1	-39.9	-13.0	26.9
3760.000	V	42.24	-55.2	12.3	2.1	-45.0	-13.0	32.0
5640.000	H	46.27	-46.1	13.0	2.4	-35.5	-13.0	22.5
5640.000	V	41.82	-50.9	13.0	2.4	-40.3	-13.0	27.3
332.000	H	44.50	-62.9	0.0	0.5	-63.4	-13.0	50.4
94.000	V	45.60	-67.3	0.0	0.3	-67.6	-13.0	54.6
WCDMA Band II, R99, Frequency:1880.000 MHz								
3760.000	H	48.72	-49	12.3	2.1	-38.8	-13.0	25.8
3760.000	V	45.22	-52.2	12.3	2.1	-42.0	-13.0	29.0
5640.000	H	46.72	-45.7	13.0	2.4	-35.1	-13.0	22.1
5640.000	V	43.24	-49.5	13.0	2.4	-38.9	-13.0	25.9
249.000	H	44.20	-65	0.0	0.5	-65.5	-13.0	52.5
418.000	V	45.60	-62.4	0.0	0.6	-63.0	-13.0	50.0

LTE Band 2 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1880.000 MHz								
3760.000	H	47.30	-50.4	12.3	1.5	-39.6	-13.0	26.6
3760.000	V	43.59	-53.8	12.3	1.5	-43.0	-13.0	30.0
5640.000	H	44.28	-48.1	13.0	1.3	-36.4	-13.0	23.4
5640.000	V	42.24	-50.5	13.0	1.3	-38.8	-13.0	25.8
449.000	H	45.60	-58.9	0.0	0.7	-59.6	-13.0	46.6
449.000	V	46.20	-61.5	0.0	0.7	-62.2	-13.0	49.2

LTE Band 4 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 1732.500 MHz								
3465.000	H	49.62	-49.1	12.2	1.6	-38.5	-13.0	25.5
3465.000	V	43.22	-54.1	12.2	1.6	-43.5	-13.0	30.5
5197.500	H	47.31	-45.9	12.9	1.4	-34.4	-13.0	21.4
5197.500	V	42.62	-50.5	12.9	1.4	-39.0	-13.0	26.0
148.000	H	46.20	-60.2	0.0	0.4	-60.6	-13.0	47.6
148.000	V	47.10	-65.5	0.0	0.4	-65.9	-13.0	52.9

LTE Band 5 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 836.500 MHz								
1673.000	H	48.32	-54.4	10.5	1.3	-45.2	-13.0	32.2
1673.000	V	42.67	-60	10.5	1.3	-50.8	-13.0	37.8
2509.500	H	49.36	-51.4	12.2	1.2	-40.4	-13.0	27.4
2509.500	V	43.62	-58.5	12.2	1.2	-47.5	-13.0	34.5
3346.000	H	48.22	-50.7	12.3	1.6	-40.0	-13.0	27.0
3346.000	V	42.22	-55.7	12.3	1.6	-45.0	-13.0	32.0
152.000	H	45.40	-61.2	0.0	0.4	-61.6	-13.0	48.6
152.000	V	47.20	-65.3	0.0	0.4	-65.7	-13.0	52.7

LTE Band 7 (30MHz-26GHz)

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 2535.000 MHz								
5070.000	H	48.62	-44.7	13.0	1.4	-33.1	-25	8.1
5070.000	V	42.67	-50.4	13.0	1.4	-38.8	-25	13.8
7605.000	H	49.44	-38.6	12.8	1.4	-27.2	-25	2.2
7605.000	V	41.17	-47.5	12.8	1.4	-36.1	-25	11.1
401.000	H	45.70	-59.1	0.0	0.6	-59.7	-25	34.7
401.000	V	46.50	-61.7	0.0	0.6	-62.3	-25	37.3

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit - Absolute Level

FCC §22.917(a) & §24.238(a) & §27.53 - BAND EDGES


Applicable Standard

FCC § 2.1053, §22.917, § 24.238 and § 27.53.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Universal Radio Communication Tester	CMU200	106 891	2017-10-18	2018-10-18
R&S	Wideband Radio Communication Tester	CMW500	147473	2017-08-31	2018-08-31
Unknown	Coaxial Cable	0.1m	C-1	Each Time	/
Pasternack	RF Coaxial Cable	0.5m	C-5	Each Time	/
E-Microwave	Two-way Splitter	ODP-1-6-2S	OE0120142	Each Time	/
R&S	Spectrum Analyzer	FSP 38	100478	2016-12-08	2017-12-08

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25.8~27.8°C
Relative Humidity:	44~45 %
ATM Pressure:	101~101.6 kPa

The testing was performed by George Pang & Swim Lv from 2017-10-27 to 2017-11-04.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following plots.

GSM 850, Left Band Edge




Date: 30.OCT.2017 16:19:31

GSM 850, Right Band Edge




Date: 27.OCT.2017 14:04:09

GSM 1900, Left Band Edge



Date: 27.OCT.2017 13:49:42


GSM 1900, Right Band Edge



Date: 30.OCT.2017 16:02:25


WCDMA Band II:

REL99 Band II, Left Band Edge




Date: 27.OCT.2017 15:54:19

REL99 Band II, Right Band Edge




Date: 27.OCT.2017 15:52:22

HSDPA Band II, Left Band Edge




Date: 27.OCT.2017 15:59:18

HSDPA Band II, Right Band Edge




Date: 27.OCT.2017 15:58:13

HSUPA Band II, Left Band Edge



Date: 27.OCT.2017 15:56:00


HSUPA Band II, Right Band Edge



Date: 27.OCT.2017 15:57:07


WCDMA Band V

REL99 Band V, Left Band Edge




Date: 27.OCT.2017 15:48:53

REL99 Band V Right Band Edge




Date: 27.OCT.2017 15:50:24

HSDPA Band V, Left Band Edge




Date: 27.OCT.2017 15:40:50

HSDPA Band V, Right Band Edge




Date: 27.OCT.2017 15:41:54

HSUPA Band V, Left Band Edge



Date: 27.OCT.2017 15:46:20


HSUPA Band V, Right Band Edge



Date: 27.OCT.2017 15:43:57


LTE Band II

QPSK_1.4MHz_6 RB_Left




Date: 4.NOV.2017 14:24:01

QPSK_1.4MHz_6 RB_Right




Date: 4.NOV.2017 14:25:36

QPSK_3MHz_15 RB_Left




Date: 4.NOV.2017 14:22:38

QPSK_3MHz_15 RB_Right




Date: 4.NOV.2017 14:20:07

QPSK_5MHz_25 RB_Left




Date: 4.NOV.2017 14:12:15

QPSK_5MHz_25 RB_Right




Date: 4.NOV.2017 14:10:17

QPSK_10MHz_50 RB_Left




Date: 15.NOV.2017 18:08:31

QPSK_10MHz_50 RB_Right




Date: 4.NOV.2017 14:09:05

QPSK_15MHz_75 RB_Left




Date: 4.NOV.2017 14:00:22

QPSK_15MHz_75 RB_Right




Date: 4.NOV.2017 14:01:29

QPSK_20MHz_FULL RB_Left




Date: 4.NOV.2017 13:54:12

QPSK_20MHz_FULL RB_Right




Date: 4.NOV.2017 13:55:46

16QAM_1.4MHz_6 RB_ Left




Date: 4.NOV.2017 14:27:23

16QAM_1.4MHz_6 RB_ Right




Date: 4.NOV.2017 14:26:46

16QAM_3MHz_15 RB_Left




Date: 4.NOV.2017 14:18:23

16QAM_3MHz_15 RB_Right




Date: 4.NOV.2017 14:17:05

16QAM_5MHz_25 RB_Left




Date: 4.NOV.2017 14:14:11

16QAM_5MHz_25 RB_Right




Date: 4.NOV.2017 14:14:48

16QAM_10MHz_50 RB_Left




Date: 4.NOV.2017 14:06:24

16QAM_10MHz_50 RB_Right




Date: 4.NOV.2017 14:07:46

16QAM_15MHz_75 RB_Left




Date: 4.NOV.2017 13:59:42

16QAM_15MHz_75 RB_Right




Date: 4.NOV.2017 13:58:46

16QAM_20MHz_FULL RB_Left



Date: 4.NOV.2017 13:57:10


16QAM_20MHz_FULL RB_Right



Date: 4.NOV.2017 13:55:22


LTE Band IV

QPSK_1.4MHz_6 RB_Left




Date: 4.NOV.2017 13:31:00

QPSK_1.4MHz_6 RB_Right




Date: 4.NOV.2017 13:29:56

QPSK_3MHz_15 RB_Left




Date: 4.NOV.2017 13:35:29

QPSK_3MHz_15 RB_Right




Date: 4.NOV.2017 13:34:31

QPSK_5MHz_25 RB_Left




Date: 4.NOV.2017 13:38:45

QPSK_5MHz_25 RB_Right




Date: 4.NOV.2017 13:37:46

QPSK_10MHz_50 RB_Left




Date: 4.NOV.2017 13:40:13

QPSK_10MHz_50 RB_Right




Date: 4.NOV.2017 13:41:10

QPSK_15MHz_75 RB_Left




Date: 4.NOV.2017 13:47:02

QPSK_15MHz_75 RB_Right




Date: 4.NOV.2017 13:46:24

QPSK_20MHz_FULL RB_Left




Date: 4.NOV.2017 13:50:15

QPSK_20MHz_FULL RB_Right




Date: 4.NOV.2017 13:50:56

16QAM_1.4MHz_6 RB_ Left




Date: 4.NOV.2017 13:25:37

16QAM_1.4MHz_6 RB_ Right




Date: 4.NOV.2017 13:28:23

16QAM_3MHz_15 RB_Left




Date: 4.NOV.2017 13:32:45

16QAM_3MHz_15 RB_Right




Date: 4.NOV.2017 13:33:36

16QAM_5MHz_25 RB_Left




Date: 4.NOV.2017 13:36:32

16QAM_5MHz_25 RB_Right




Date: 4.NOV.2017 13:36:59

16QAM_10MHz_50 RB_Left




Date: 4.NOV.2017 13:43:21

16QAM_10MHz_50 RB_Right




Date: 4.NOV.2017 13:41:53

16QAM_15MHz_75 RB_Left




Date: 4.NOV.2017 13:47:42

16QAM_15MHz_75 RB_Right




Date: 4.NOV.2017 13:48:43

16QAM_20MHz_FULL RB_Left



Date: 4.NOV.2017 13:52:10


16QAM_20MHz_FULL RB_Right



Date: 4.NOV.2017 13:51:45


LTE Band V

QPSK_1.4MHz_6 RB_Left




Date: 4.NOV.2017 13:18:06

QPSK_1.4MHz_6 RB_Right




Date: 4.NOV.2017 13:19:37

QPSK_3MHz_15 RB_Left




Date: 4.NOV.2017 13:10:44

QPSK_3MHz_15 RB_Right




Date: 4.NOV.2017 13:11:40

QPSK_5MHz_25 RB_Left




Date: 4.NOV.2017 13:01:54

QPSK_5MHz_25 RB_Right




Date: 4.NOV.2017 13:02:38

QPSK_10MHz_50 RB_Left




Date: 4.NOV.2017 13:00:21

QPSK_10MHz_50 RB_Right




Date: 4.NOV.2017 12:58:44

16QAM_1.4MHz_6 RB_ Left




Date: 4.NOV.2017 13:22:32

16QAM_1.4MHz_6 RB_ Right




Date: 4.NOV.2017 13:20:27

16QAM_3MHz_15 RB_Left




Date: 4.NOV.2017 13:14:36

16QAM_3MHz_15 RB_Right




Date: 4.NOV.2017 13:12:52

16QAM_5MHz_25 RB_Left




Date: 4.NOV.2017 13:04:36

16QAM_5MHz_25 RB_Right




Date: 4.NOV.2017 13:03:52

16QAM_10MHz_50 RB_Left



Date: 4.NOV.2017 12:56:18


16QAM_10MHz_50 RB_Right



Date: 4.NOV.2017 12:57:51


LTE Band VII

QPSK_5MHz_25 RB_Left




Date: 4.NOV.2017 11:09:43

QPSK_5MHz_25 RB_Right




Date: 4.NOV.2017 11:08:47

QPSK_10MHz_50 RB_Left




Date: 4.NOV.2017 11:15:57

QPSK_10MHz_50 RB_Right




Date: 4.NOV.2017 11:14:45

QPSK_15MHz_75 RB_Left




Date: 4.NOV.2017 11:44:40

QPSK_15MHz_75 RB_Right




Date: 4.NOV.2017 11:43:21

QPSK_20MHz_FULL RB_Left




Date: 4.NOV.2017 12:06:08

QPSK_20MHz_FULL RB_Right




Date: 4.NOV.2017 12:05:36

16QAM_5MHz_25 RB_Left




Date: 4.NOV.2017 11:07:20

16QAM_5MHz_25 RB_Right




Date: 4.NOV.2017 11:08:08

16QAM_10MHz_50 RB_Left




Date: 4.NOV.2017 11:52:02

16QAM_10MHz_50 RB_Right




Date: 4.NOV.2017 11:50:51

16QAM_15MHz_75 RB_Left




Date: 4.NOV.2017 11:46:31

16QAM_15MHz_75 RB_Right




Date: 4.NOV.2017 11:48:37

16QAM_20MHz_FULL RB_Left



Date: 4.NOV.2017 12:04:11

16QAM_20MHz_FULL RB_Right



Date: 4.NOV.2017 12:04:56

FCC §2.1055, §22.355 & §24.235 & §27.54 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235, §27.54

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set from 85% to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-4	2017-09-10	2018-09-09
R&S	Universal Radio Communication Tester	CMU200	106 891	2017-10-18	2018-10-18
R&S	Wideband Radio Communication Tester	CMW500	147473	2017-08-31	2018-08-31
UNI-T	Multimeter	UT39A	M130199938	2017-04-02	2018-04-02
Unknown	Coaxial Cable	0.1m	C-1	Each Time	/
Pro instrument	DC Power Supply	pps3300	N/A	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25.8~27 °C
Relative Humidity:	42~45 %
ATM Pressure:	101.4~101.6 kPa

The testing was performed by George Pang & Swim Lv on 2017-10-25&2017-11-04.

Cellular Band (Part 22H)

GMSK, Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limit
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	-6	-0.007	2.5
-20		-7	-0.008	
-10		-6	-0.007	
0		-6	-0.007	
10		-5	-0.006	
20		-8	-0.010	
30		-8	-0.010	
40		-6	-0.007	
50		-5	-0.006	
25		3.6	-7	
25	4.35	-6	-0.007	

PCS Band (Part 24E)

GMSK, Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V _{DC}	Hz	ppm	
-30	3.8	-5	-0.003	Pass
-20		-4	-0.002	
-10		-6	-0.003	
0		-4	-0.002	
10		-4	-0.002	
20		-7	-0.004	
30		-6	-0.003	
40		-4	-0.002	
50		-5	-0.003	
25		3.6	-4	
25	4.35	-5	-0.003	

WCDMA Band II: R99

Middle Channel, $f_c = 1880.0$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V _{DC}	Hz	ppm	
-30	3.8	4	0.002	Pass
-20		5	0.003	
-10		3	0.002	
0		5	0.003	
10		3	0.002	
20		6	0.003	
30		4	0.002	
40		6	0.003	
50		7	0.004	
25		3.6	5	
25	4.35	5	0.003	

WCDMA Band V: R99

Middle Channel, $f_c = 836.6$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Results
°C	V _{DC}	Hz	ppm	
-30	3.8	1	0.001	Pass
-20		2	0.002	
-10		1	0.001	
0		1	0.001	
10		-1	-0.001	
20		0	0.000	
30		2	0.002	
40		2	0.002	
50		0	0.000	
25		3.6	1	
25	4.35	-1	-0.001	

LTE Band 2:

QPSK, Channel Bandwidth:10MHz Middle Channel, $f_c = 1880$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V_{DC}	Hz	ppm	
-30	3.8	-4.63	-0.0025	Pass
-20		-5.60	-0.0030	
-10		-2.63	-0.0014	
0		-5.60	-0.0030	
10		5.28	0.0028	
20		3.82	0.0020	
30		6.05	0.0032	
50		-3.58	-0.0019	
25	3.6	5.90	0.0031	
25	4.35	1.21	0.0006	

16QAM, Channel Bandwidth:10MHz Middle Channel, $f_c = 1880$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V_{DC}	Hz	ppm	
-30	3.8	-9.79	-0.0052	Pass
-20		-8.34	-0.0044	
-10		-10.96	-0.0058	
0		-8.34	-0.0044	
10		-13.88	-0.0074	
20		-7.58	-0.0040	
30		-6.27	-0.0033	
55		-9.00	-0.0048	
25	3.6	-11.75	-0.0063	
25	4.35	-10.32	-0.0055	

LTE Band 4:

QPSK, Channel Bandwidth:10MHz Middle Channel, $f_c = 1732.5$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	-11.08	-0.0064	Pass
-20		-12.17	-0.0070	
-10		-7.31	-0.0042	
0		-12.17	-0.0070	
10		-7.71	-0.0045	
20		-5.52	-0.0032	
30		-13.45	-0.0078	
55		-13.17	-0.0076	
25	3.6	-11.11	-0.0064	
25	4.35	-14.30	-0.0083	

16QAM, Channel Bandwidth:10MHz Middle Channel, $f_c = 1732.5$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	-5.09	-0.0029	Pass
-20				
-10		-1.27	-0.0007	
0		-5.40	-0.0031	
10		-1.35	-0.0008	
20		-3.35	-0.0019	
30		-9.36	-0.0054	
55		-7.12	-0.0041	
25	3.6	-4.43	-0.0026	
25	4.35	-10.91	-0.0063	

LTE Band 5:

QPSK, Channel Bandwidth:10MHz Middle Channel, $f_c = 836.5$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Limits
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	-7.98	-0.0095	2.5
-20		-6.34	-0.0076	
-10		-7.95	-0.0095	
0		-6.34	-0.0076	
10		-7.40	-0.0088	
20		-1.33	-0.0016	
30		-1.02	-0.0012	
55	-5.11	-0.0061		
25	3.6	-1.09	-0.0013	
25	4.35	-8.52	-0.0102	

16QAM, Channel Bandwidth:10MHz Middle Channel, $f_c = 836.5$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	ppm
-30	3.8	-2.05	-0.0025	2.5
-20		-1.71	-0.0020	
-10		-1.71	-0.0020	
0		0.32	0.0004	
10		-4.68	-0.0056	
20		-1.06	-0.0013	
30		0.48	0.0006	
55	-8.36	-0.0100		
25	3.6	-8.28	-0.0099	
25	4.35	-6.06	-0.0072	

LTE Band 7:

QPSK, Channel Bandwidth:10MHz Middle Channel, $f_c = 2535$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	1.40	0.0006	Pass
-20		-0.91	-0.0004	
-10		1.77	0.0007	
0		-0.91	-0.0004	
10		5.80	0.0023	
20		5.72	0.0023	
30		6.32	0.0025	
55		1.64	0.0006	
25	3.6	6.92	0.0027	
25	4.35	7.13	0.0028	

16QAM, Channel Bandwidth:10MHz Middle Channel, $f_c = 2535$ MHz				
Temperature	Voltage	Frequency Error	Frequency Error	Result
°C	V _{DC}	Hz	ppm	
-30	3.8	0.44	0.0002	Pass
-20		3.58	0.0014	
-10		3.58	0.0014	
0		0.00	0.0000	
10		6.98	0.0028	
20		2.62	0.0010	
30		6.62	0.0026	
55		0.69	0.0003	
25	3.6	6.81	0.0027	
25	4.35	6.09	0.0024	

Note: The fundamental emissions stay within the authorized bands of operation based on the frequency deviation measured is small, the extreme voltage was declared by applicant.

******* END OF REPORT *******